GGG-T-00570a(GSA-FSS)
October 20, 1965
Revision of
Int. Fed. Spec. GGG-T-00570(GM-FSS)
June 24, 1964

INTERIM FEDERAL SPECIFICATION

TORCH KIT, SOLDERING (PROPANE GAS)

This Interim Federal Specification was developed by the Standardization Division, Federal Supply Service, General Services Administration, Washington, D. D. 20406 based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

1. SCOPE AND CLASIFICATION.

1.1 scope. - This specification covers a soldering torch kit used for soldering, heating and brazing operations.

1.1.1 Federal spacification coverage. - Federal specifications do not include all varieties of the commodity as indicated by the title of the specification, or which are commercially available, but are intended to cover only those generally used by the Federal Government

1.2 Classification.

1.2.1 Type. - The soldering torch kit covered by this specification shall be furnished In one type as hereinafter specified.

2. APPLICABLE DOCUMENTS

2.1 Specifications and standards. The following specifications and standards, of the issues In effect on date of invitation for bids, form a part of this specification.

Federal Specifications:

PPP-B-566 - Boxes, Folding, Paperboard.
PPP-585 - Boxes, Wood, Wirebound.
PPP-B-591 - Boxes, Fiberboard, Wood-Cleated.
PPP-B-601 - Boxes, Wood, Cleated-Plywood.
PPP-B-621 - Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636 - Box, Fiberboard.
PPP-B-640 - Boxes, Fiberboard, Corrugated, Triple, Wall.
PPP-B-665 - Boxes, Paperboard, Metal Stayed (Including Stay Material).
PPP-B-676 - Boxes, Set-Up, Paperboard.

Federal Standards:

Fed. Std. No. 102 - Preservation, packaging, and Packing Levels.
Fed. Std. No. 123 - Marking for Domestic Shipment (Civilian Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal specifications and Standards and at the prices indicated In the Index. The Index, which included cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government renting Office, Washington, D. C., 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D. C., Atlanta, Chicago, Kanasa City, Mo., Dallas, Denver, San Francisco, Los Angeles, and Seattle, Wash.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:40Z
Check the source to verify that this is the current version before use.

Military Specification:

MIL-P-116 - Preservation, Methods of.

Military standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD- 129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractor in Connection with specific procurement functions should be obtained from the procuring activity or as directed by the contacting officer.)

2.2 other publications. - The following documents form a part of this specification. Unless otherwise indicated, the issue in effect on date of invitation for bids shall-apply.

National Bureau of Standards Handbook:

H28 - Screw-Thread Standards for Federal Service.

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, D. C. 20402)

Code of Federal Regulations:

49 CFR 71-90- Interstate Commerce Commission (ICC) Rules and Regulations for the Transportation of Explosives and Other Dangerous Articles.

(The Interstate Commerce Commission Regulations are now a part of the Code of Federal Regulations available from the Superintendent of Documents, Government Printing Office, Washington, D. c. 20402. Orders should cite "49-CFR-71-909".)

3. REQUIREMENTS

3.1 Materials.- Materials used in the construction of the soldering torch kits shall be as specified herein. When materials are not definitely specified, they shall be of good quality normally used for the purpose in commercial practice. All materials shall be new and unused, and free from any defects or imperfections which might affect the appearance or serviceability of the soldering torch kits.

3.2 Design and construction. - The torch kits shall be so designed and constructed as to be convenient to operate and entirely adequate for the purpose intended. All parts subject to wear shall be readily accessible for adjustment or repair. Construction shall be free from any defects or characteristics that may render the torch kits unsuitable or inefficient for the purposed Intended.

3.3 Interchangeability. - All replaceable parts shall be manufactured to definite standards, tolerances, and clearances in order that any such part may be replaced without requiring modification.

3.4 Identification marking. - 'Me torch kit unit and carrying case shall be marked in a plain and permanent manner with the manufacturer's name or trademark of such known character that the source of' manufacture can be readily determined.

3.5 coating and plating. - All major components hating corrosive metal surfaces shall be provided with a protective coating or plating.

3.6 painting. - The torch kit carrying case and propane gas cylinder shall be properly cleaned and one coat of good grade of enamel or lacquer shall be applied as a finish coat. The color of the paint shall be the manufacturer's standard shade.

3.7 Soldering torch kit. - The soldering torch kit shall consist essentially of l disposable fuel cylinder (fully loaded), burner unit, pencil burner head, utility burner head, soldering tip, flame spreader, flint lighter and carrying case.

3.7.1 Cylinder. - The fuel cylinder shall be of the disposable type (nonrefillable). The cylinder shall conform to 49-CFR-71-90 Interstate Commerce Commission Rules and Regulations for the Transportation of Explosives and Other Dangerous Articles, or shall be made in accordance with special permit issued by Interstate Commerce Commission for use with liquefied petroleum gas. The cylinder shall be furnished with a sufficient quantity of propane gas to last up to 14 hours on pencil-flame and up to 4 hours on blow-torch flare?. The neck of the cylinder shall be provided with a l-inch diameter by 20 NEF threads per Inch for connecting the burner unit.

Source: https://assist.dla.mil - Downloaded: 2026-10-26T12:40Z
Check the source to verify that this is the current version before use.

3.7.1.1 Cylinder safety relief valve. - A suitable spring loaded relief valve shall be located in the fuel reservoir. This valve shall be set to open at a pressure of not more than 375 p.s.i.

3.7.1.2 Cylinder sealing valve. - Cylinders shall be equipped with an internal self-sealing valve to prevent leakage of fuel when burner unit is not attached.

3.7.1.3 Dirt Cover. - The fitting to which the burner unit is attached during operation shall be provided with a suitable cover, threadad or snap-on type, to keep dirt out of the cylinder head when burner unit is not attached.

3.7.2 Burner unit. - The burner unit shall be of brass or copper. the burner unit shall be provided with a regulating control valve for adjusting the flame to the desired height. The adjustment needle in the control valve may be made of steel. A length of copper or brass tubing at least 3 inches long by approximately 5/16 inch outside diameter by 3/16 inch inside diameter shall be attached to the burner unit by means of a compression nut. The burner end of the tubing shall be externally threaded for attaching the utility burner or the pencil burner heed.

3.7.3 pencil burner head. - the pencil burner head shall be of brain or copper. It shall contain a small orifice to produce a pencil point flame. The lower end of the pencil burner head shall be internally threaded for connecting to the end of the burner head tubing. ,

3.7.4 Utility burner heed. - The utility burner head shall be similar to the pencil burner head described above except that the head shall be provided with l large orifice to produce a flame suitable for work requiring a greater volume of heat. The lower end of the utility burner head shall be internally threaded for connecting to the end of the burner head tubing.

3.7.5 Soldering tip. - The soldering tip shall have a housing of brass or copper, with a replaceable copper tip. Means shall be provided for securing the soldering tip to the pencil burner bead.

3.7.6 Flame spreader. - The flame spreader shall be fan shaped to produce a wide flame to cover a wide area. Means shall be provided for securing the flame spreader to the utility burner bead.

3.7.7 Flint lighter. - The flint lighter shall be of metal containing l replaceable flint. It shall be capable of producing an Ignition spark to light the torch.

3.7.8 Carrying case. - The carrying case shall be of sheet metal, finished with a good grade of enamel or lacquer. The carting case shall be of such size to hold the fuel cylinder and all component parts of the kit. The case shall be equipped with a hinged cover, means for holding the cover in a closed position, and a carrying handle.

3.8 Threads, - All threaded parts shall be in the inch system and shall conform to National Bureau of Standards Handbook H28.

3.9 Workmanship. Workmanship of the soldering torch kits shall be of the quality prevailing among manufacturers normally producing soldering torch kits of the type specified herein.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. - Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and service conform to prescribed requirements.

4.2 Sampling for lot acceptance.

4.2.1 Inspection lot. - All soldering torch kits offered for delivery at one time shall be considered a lot for the purpose of acceptance, inspection and tests.

4.2.2 sampling for visual and dimensional inspection. - A sample of soldering torch kits shall be taken by the inspector from each inspection lot of material offered for Government Inspection of visual and dimensional characteristics in accordance with MIL-STD- 105. The inspection level shall be II and the AQL 1.5 percent defective.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:40Z
Check the source to verify that this is the current version before use.

4.2.3 Sampling for tests. - One soldering torch kit shall be taken from each lot for the test specified in 4.4.

4.3 Visual and dimensional examination. - Each of the sample soldering torch kits shall be examined for material, dimensions, protective coating, marking,workmanship, and general compliance with this specification. Any torch kit in the sample containing one or more defects shall be rejected, and if the number of defective torch kits in any sample exceeds the acceptance number for that sample, the lot represented by the sample shall be rejected.

4.4 Test.

4.4.1 Operational test. - The torch shall operate satisfactorily on the fuel for which it is designed. Lighting shall be instantaneous and without preheating, pumping or priming. Burning shall be steady and without pulsation; in normal position, upside down or any angle. The regular burner flame shall not be easily extinguishable by wind. All tips shall operate satisfactorily with the torch. The soldering tip shall provide sufficient heat to melt 50/50 solder.

4.5 Rejected lots. - Rejected lots may be resubmitted for examination and tests provided the contractor has removed or repaired all nonconforming torch kits. Samples shall again be selected and Inspected from such resubmitted lots to verify compliance with this specification. Rejected torch kits shall not be resubmitted for inspection without furnishing full particulars concerning previous rejections, and measures taken to overcome the defects.

4.6 Inspection of preparation for delivery requirements. - An inspection shall be made to determine that packaging, packing and marking requirements are in compliance with section 5 of this specification. Defects shall be scored in accordance with table I. For examination of contents, the sample unit shall be one shipping container fully prepared for delivery selected just prior to the closing operations. Defects of closure listed shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be II and the AQL shall be 4.0 defects per hundred units.

Table I. - Classification of preparation for delivery defects.

Examine	Defect
Markings (exterior and interior)	Omitted; incorrect; illegible; or improper size, location, sequence, or method of application.
Materials	Any component missing, or damaged.
workmanship	Inadequate application of components, such as incomplete closure of container flaps, loose strapping, inadequate stapling. Bulging or distortion of container.

5. PREPARATION FOR DELIVERY.

(For civil agency procurement, the definitions and application of levels of packaging and packing shall be in accordance with Fed. Std. No. 102.)

5.1 Packaging. - Packaging shall be level A, B, or C, as specified (see 6.2).

5.1.1 Level A. - The kits shall be packaged method IC-2 in accordance with MIL-P-116.

5.1.2 Level B. - Each kit shall repackaged In a close-fitting box conforming to PPP-B-566, PPP-B-665, or PP-B-676. The box shall be closed in accordance with the appendix to the box specification.

5.1.3 Level C. - The kits shall be packaged in accordance with the suppliers commercial practice.

-.2 Packing. - Packing shall be level A, B, or C, as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:40Z
Check the source to verify that this is the current version before use.

5.2.1 Level A. - The kits shall be packed in closefitting boxes conforming to PPP-B-585, class 3; PPP-B-591, class 11; PPP-B-601, overseas type; PPP-B-621, class 2, PPP-B-636, class weather-resistant; or PPP-B-640, class 2, grade A, the boxes shall be closed and strapped in accordance with the applicable specification or appendix thereto. The gross weight of the triple wall fiberboard box and the wood boxes shall not exceed approximately 200 pounds. The gross weight of the PP-B-636 fiberboard box shall not exceed the weight limitations of the box specification.

5.2.2 Level B. - The kits shall be packaged in a close-fitting box conforming to PPP-B-636, class domestic, style RSC. Closure shall be In accordance with method I of the appendix to the box specification.

5.2.3 Level C. - The kits shall be packed to insure carrier acceptance and safe delivery to destination in containers complying with the rules and regulations applicable to the mode of transportation.

5.3 Marking.

5.3.1 Civil agencies. - In addition to special markings required by the contract or order (6.2), the packages and shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.3.2 Military activities. - In addition to special markings required by the contract or order (see 6.2), the packages and shipping containers shall be marked in accordance with MIL-STD- 129.

6. NOTES.

6.1 Intended use. - The soldering torch kits are intended for soldering electrical connections, sweating copper tubing, burning paint, etc.

6.2 Ordering data. - Purchasers should exercise any desired options offered herein and should specify the following applicable:

(a) Title, number and date of this specification.
(b) Level of packaging and packing required (see 5.1 and 5.2)
(c) Special marking, if required (see 5.3).

6.3 Transportation description. - Transportation descriptions and minimum weights applicable to this commodity are:

Rail:
Torches, blow, compressed gas.
Carload minimum weight 30,000 pounds.

Motor:
Torches, hand, with fuel, not over 1 quart capacity.
Truckload minimum weight 30,000 pounds, subject to Rule 115,
National Motor Freight Classification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:40Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:40Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:40Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:40Z
Check the source to verify that this is the current version before use.