MILITARY SPECIFICATION SHEET

HOSE ASSEMBLIES, POLYTETRAFLUOROETHYLENE, ARAMID FIBER REINFORCED, 5000 AND 8000 PSI, DESIGN STANDARD FOR STYLE STRAIGHT TO STRAIGHT

This specification is approved for use within the Naval Air Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the hose assemblies designed herein shall consist of this document and the latest issue in effect of specification MIL-H-85800.




FIGURE 1. Dimensions and configuration

AMSC N/A

FSC 4720

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:29Z
Check the source to verify that this is the current version before use.

TABLE I. HOSE DIMENSIONS AND DESIGN DATA

DASH NO	HOSE SIZE	THREAD T PER MIL-S-8879	A MAX	B DIA MIN	C HEX	D HEX	ID MIN	OD MAX	HOSE WT MAX LBS/IN
-03	.125	.3750-28UNJS-3B	1.580	.063	.438	.550	.125	.395	.005
-04	.250	.4375-24UNJS-3B	2.100	.109	.562	.690	.212	.490	.008
-06	.375	.5625-20UNJS-3B	2.290	.188	.688	.960	.298	.730	.019
-08	.500	.7188-20UNJS-3B	2.750	.313	.875	1.200	.391	.940	.028
-10	.625	.8438-18UNJS-3B	2.910	.375	1.000	1.300	.485	1.090	.036
-12	.750	1.0000-16UNJ-3B	3.270	.469	1.125	1.650	.602	1.405	.060
-14	.875	1.1250-16UNJS-3B	3.400	.595	1.250	1.750	.745	1.625	.075
-16	1.000	1.2500-14UNJS-3B	3.530	.719	1.375	1.900	.852	1.825	.104




FIGURE 2. Hose fitting detail

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:29Z
Check the source to verify that this is the current version before use.

NOTES:


1. Dimensions are in inches.
2. Unless otherwise specified, tolerance are decimals ±.010 inch; angles ±1 degree.
3. End fittings are to mate with male end per MIL-F-85720/1.
4. Length "L" is measured from outer corner of sealing surface to outer corner of sealing surface. See Table II for available length increment and tolerances.
5. A true circular cross section is not required through the end fittings. However, the ball diameter B listed in Table I shall pass through the hose assemblies.
6. Thread T shall conform with MIL-S-8879.

TABLE II. HOSE LENGTH INCREMENT

HOSE ASSEMBLY LENGTH	AVAILABLE INCREMENT	TOLERANCE
UNDER 18 INCHES	NOT LESS THAN 0.1 INCH	± 0.100 INCH
18 TO 36 INCHES	NOT LESS THAN 0.2 INCH	± 0.200 INCH
36 TO 50 INCHES	NOT LESS THAN 0.5 INCH	± 0.500 INCH
OVER 50 INCHES	NOT LESS THAN 1 INCH	± 1.000 INCH

7. The part number shall be designated to reflect the base assembly number, lockwire code, hose size and hose length.

Example of part number.



Preparing Activity
Navy - AS

(Project No. 4720-N002)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:29Z
Check the source to verify that this is the current version before use.