MIL-H-87028B(SH)
27 April 1987
SUPERSEDING
MIL- H-87028A(SH)
25 July 1978
(See 6.8)

MILITARY SPECIFICATION

HARNESS, DIVERS (MK-12)

This specification is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements for a divers harness, of one type and size, to be worn as a component of the MK-12 diving system.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbook. The following specifications, standards, and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDIISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

V-T-295	- Thread, Nylon.
QQ-N-290	- Nickel Plating (Electrodeposited).
PPP-B-636	- Boxes, Shipping, Fiberboard.

MILITARY

MIL-W-4088	- Webbing, Textile, Woven Nylon.
MIL-R-5632	- Rods and Wire, Steel Welding (for Aircraft Applications).
MIL-C-14538	- Chromium Plating, Black (Electrodepositcd).
MIL-B-17757	- Boxes, Shipping, Fiberboard (Modular Sizes).
MIL-F-21840	- Fastener Tapes, Hook and Pile, Synthetic.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to. Commander, Naval Sea Systems Command, SEA 55Z3. Department of the Navy, Washington, DC 20362-5101 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 4220
DISTRIBUTION STATEMENT A Approved for public release; distribution unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:36Z
Check the source to verify that this is the current version before use.

STANDARDS

FEDERAL

FED- STD-751 - Stitches, Seams, and Stitchings.

MILITARY

MIL_STD-105 - Sampling Procedures and Tables for inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-147 - Palletized Unit Loads.
MS2207 - Adjuster Assembly, Safety Shoulder Harness Belt.
MS22043 Snap Hook-Coiled Spring, Parachute, Quick Fit.
MS22044 - Snap Hook-Coiled Spring, Parachute.
MS22045 - Ring-Parachute Harness "V",

HANDBOOK

MILITARY

MIL-HDBK-53 Guide for Sampling Inspection.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

LAWS AND REGULATIONS

U.S. POSTAL SERVICE MANUAL

(Copies of the manual may be obtained from the Superintendent of Documents , U.S. Government Printing Office , Washington, DC 20402.)

DRAWINGS

AIR FORCE

44B26454 - Link-Safety Belt , Latch Fastener.

NAVAL SEA SYSTEMS COMMAND (NAVSEA)

592-4759180 - Harness, Divers, MK-12 [including drawings 592-4759181 through 592-4759185).
592-4759186 - Ring, Parachute Harness, Quick Fit, "V".
592-4759187 - Latch and Pin Assembly, Safety Belt (3 sheets and also including drawing 592-4759188).
592-4759189 - Ring, Parachute Harness, "V" Assembly.

(Copies of specifications, standards, handbooks, drawings, publications, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

Source: https://assist.dla.mil -- Downloaded: 202610-23T11:36Z
Check the source to verify that this is the current version before use.

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted shall be those listed in the issue of the DoDISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DoDISS shall be the issue **of the** nongovernment documents which is current on the date of the solicitation.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)
D 3951 - Standard Practice for Commercial Packaging.
(DoD adopted)

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

AMERICAN WELDING SOCIETY (AWS)
WH Volume 2 - Welding Handbook, Indexes.

(Application for copies should be addressed to the American Welding Society) inc. , 550 NW LeJeune Road, P.O. Box 351040, Miami, FL 33135.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT
National Motor Freight Classification

(Application for copies should be addressed to the National Motor Freight Traffic Association, Inc. , ATA TRAFFIC Dept. 2200 Mill Road, Alexandria,VA 22314.)

UNIFORM CLASSIFICATION COMMITTEE AGENT
Uniform Freight Classification Ratings, Rules and Regulations

(Application for copies should be addressed to the Uniform Classification Committee Agent, Tariff Publication Officer, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

(Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards),the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.3 and 6.3).

Source: https://assist.dla.mil -- Downloaded: 202610-23T11:36Z
Check the source to verify that this is the current version before use.

3.2 Materials.

3.2.1 Webbing. The webbing shall be 1-3/4 inches conforming to type XIII of MIL_W_4088. The color of t-he webbing shall be black.

3.2.2 Thread. The thread used for assembling the harness shall conform to type I or II, class B, size 3 of V-T-295.

3.2.3 Fastener tapes. The hook and pile fastener tape (2-inch width) shall conform to type II , class 4 of MIL-F-21840 with the exception that the pile tape be supplied unnapped. The color of the tape shall be black.

3.2.4 Adjuster waist belt. The adjusters for tile waist belts shall conform to MS22007. The adjuster shall be furnished without finish or plating except as specified in 3.3.

3.2.5 Adjuster, shoulder strap. The adjuster for t-he shoulder straps shall conform to United States Forgecraft Corporation part number 60D562 or- equal, [see 6.4). The adjuster shall be furnished without finish or plating except as specified in 3.3.

3.2.6 Link, waist belt. The link connector for the waist belts shall conform to Air Force Drawing 44B26454. The link shall be furnished without finish or plating except as specified in 3.3.

3.2.7 Latch , waist belt. The latch connector for the waist belts shall conform to Drawing 592-4759187. The latch shall be furnished without finish or plating except as specified in 3.3.

3.2.8 V-ring. The V-ring attached to the lower portion of the left shoulder strap shall conform to MS22045. The V-ring shall be furnished without finish or plating except as specified in 3.3.

3.2.9 Modified V-ring. The modified V-ring attached to the lower end of the front jocking strap shall conform to Drawing 592-4759189. The modified V-ring shall be furnished without finish or plating except as specified in 3.3.

3.2.10 Adjustable, modified V-ring. The modified adjustable V-ring attached to the loose end of the crotch strap shall conform to Drawing 592-4759186. The modified adjustable V-ring shall be furnished without finish or plating except as specified in 3.3.

3.2.11 Snap hook. The snap hooks attached to the upper end of the rear jocking straps shall conform to MS22044. The snap hook shall be furnished without finish or plating except as specified in 3.3.

3.2.12 Snap hook , adjustable. The adjustable snap hook attached to the upper end of the front jocking strap shall conform to MS22043. The adjustable snap hook shall be furnished without finish or plating except as specified in 3.3.

3.2.13 buckle. The buckle used for attaching the rear jocking straps to the main harness assembly shall conform to United States Forgecraft Corporation part number 2060A or equal, (see 6.4). The buckle shall be furnished with one tongue and roller, without finish or plating except as specified in 3.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:36Z
Check the source to verify that this is the current version before use.

3.2.14 Buckle, modified. The buckles used for attaching accessories to the jocking harness shall conform to United States Forgecraft Corporation] part number 2060A or equal, (see 6.4) . The buckle shall be furnished with roller and without tongue and without finish or plating except as specified. in 3.3.

3.2.15 Grommets and washers, The grommets and washers for the rear jocking straps' shall be stainless steel, size 1, plain. The grommets and washers are available from Stimpson Co. Inc. , or equal.

3.2.16 Locking pin. The locking pin for the waist belt latch, (see 3.2.7) shall be in accordance with Drawing 592-4759187, find no. 3.

3.2.17 Recovered materials. Unless otherwise specified herein, all equipment, material, and articles incorporated in the products covered by this specification shall be new and shall be fabricated using materials produced from recovered materials to the maximum extent practicable without jeopardizing the intended use. The term "recovered materials'! means materials which have been collected or recovered from solid waste and reprocessed to become a source of raw materials, as opposed to virgin raw materials. None of the above shall be interpreted to mean that the use of used or rebuilt products is allowed under this specification unless otherwise specifically specified.

3.3 Metal hardware.

3.3.1 Finish metal. Metal hardware items with the exception of the grommets and washers (see 3.2.15), the locking pin (see 3.2.16], the locking pin catch spring and the nut, bolt and washer-that retain the locking pin catch spring (see 3.2.7), shall be nickel and black chrome plated, after all basic metal heat treatments and mechanical operations have been completed.

3.3.2 Unfinished metal. Unfinished metal hardware items shall have a nickel plated finish applied over a copper underplaying of 0,0002 to 0.0004 inch thick. The nickel plating shall conform to class 1, grade C of QQ-N-290. After the nickel has been applied, a coating of black chrome shall be applied to the stainless steel grommets and washers. The black chrome plating shall be of a sufficient thickness to meet the finish requirements of MIL-C-14538. The stainless steel locking pin, locking pin catch spring and nut, bolt and washer that retain the locking pin catch spring, shall remain unplated. When specified in the contract *or* order a certificate of compliance shall be prepared for the metal finish (see 6.2.2).

3.4 Welding. The modified V-rings specified in 3.2.9 and 3.2.10 shall be welded in accordance with AWS WH Vol. 2. Use 4140 steel filler wire as specified in MIL-R-5632. Preheat and interpass temperatures shall be 500 degrees Fahrenheit (260 degrees Celsius). The heat treatment (quench and temper) to attain hardness should be done immediately after welding. Precaution should be taken to prevent hydrogen embrittlement of the weld. Each welded ring shall be inspected with a 1,000 pound tensile pull test to determine critical defects as specified in MIL-STD-105 and MIL-HDBK-53. No reworking of the welded rings is allowed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:36Z
Check the source to verify that this is the current version before use.

3.5 Design. The harness shall be of the "H" design with adjustable shoulder, waist, and chest straps. Three adjustable jocking straps shall be attached to the harness; two in the rear and one in the front. Four tongueless buckles shall be attached to the harness; two at the top and two on the front. The design of the harness shall conform in appearance to Drawing 592-4759180.

3.6 Construction. The construct ion shal1 be in accordance with the drawings specified herein.

3 .6.1 Stitches , seams, and stitchings. Stitches , seams , and stitchings , shall be performed using stitch type 301 with 5 to 7 stitches per inch, and shall conform Lo FED- STD- 751 .

3 .6.1.1 Type 301 stitching. Ends of all stitching shall be backstitched or overstitched not less than l/2-inch except where ends are held down by other stitching. Thread tensions shall be maintained so that there will be no loose stitching resulting in loose bobbin or top thread, or excessively tight stitching resultlng in puckering of the material sewn. The lock shall be embedded in the material sewn. The box stitching patterns shown on the detailed drawings are for dimensions and stitching patterns only and do not indicate starting and flnishing points for the stitching.

3 .6.1.1.1 Repairs of type 301 stitching. Repairs to type 301 stitching shall be as follows:

(a) When thread breaks or bobbin run-outs occur during sewing, the stitching shall be repaired by restarting the stitching not less than 1/2 inch in back of the end of the stitching. The ends of the stitching are not required to be backstitched.

(b) Thread breaks. two or more consecutive skipped stitches , or run-offs noted during inspection of the item [in-process or end item) shall be repaired by overstit-thing. The stitching shall start not less than l/2 inch in hack of the defective area, continue over the defective area and continue not less than 1/2 inch beyond the defective area onto the existing stitching. loose or excessively tight stitching shall be repaired by removing the defectlve stitching without damaging the materials, and restitching in the required manner . The ends of the stitchining are not required LO be backstitched.

3.6.1.2 Automatic stitching. Automatic stitching machines may be used to perform any of the stitch patterns provided the requirements for the stitch pattern, stitches per inch, and size and type of thread are met; and not less then three tying, overlapping or backstitches are used to secure the ends of the stitching

3.6.1.3 Thread ends. Thread ends shall be trimmed to 1/4-inch maximum length .

3.6.2 Fusing of nylon webbing Ends of webbing and grommet holes shall be fused smooth. Fusing of the webbing ends and grommet holes shall be accomplished prior to assembling for stitching. The apparatus used to fuse the webbing ends shall generate sufficient heat to provide a smooth edge with the cut ends of the webbing yarns all fused together.

Source: https://assist.dla.mil -- Downloaded: 202610-23T11:36Z
Check the source to verify that this is the current version before use.

3 .6.3 Repairs. Unless otherwise specified herein, repairs to the harness are not allowed.

3.6,4 Replacement of defective components. During the spreading, cutting, and manufacturing process, components having material defects or damages that are specified in 4.4.1.1 shall be removed from production and replaced with non-defective and properly matched components.

3.7 Workmanship. The finished harness shall conform to the quality and grade of product established by this specification. The occurrence of defects shall not exceed the applicable acceptable quality levels.

4. QUALITY ASSURANCE PROVISIONS

4,1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own **or** any other facilities suitable for the performance of the. inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

(a) First article inspection (see 4.3).
(b) Quality conformance inspection (see 4.4),

4.3 First article inspection. First article inspection shall consist of examinations specified in 4.4.1 through 4.4.1.3.

4.4 Quality conformance inspection. Sampling for inspection shall be performed in accordance with M1L-STD-105, except where otherwise indicated herein,

4,4,1 Examination of the end item. Examination of the end item shall be in accordance with 4.4,1.1 and 4.4.1.2. The applicable inspection levels and acceptable quality levels (AQL's) shall be as specified in 4.4.1.3. The sample unit shall be one finished harness assembly complete with front and rear jocking straps. The lot size shall be expressed in terms of the sample unit.

4,4.1.1 Visual examination. The finished harnesses shall be examined for the defects classified in accordance with table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:36Z
Check the source to verify that this is the current version before use.

TABLE 1. Visual defects

Defect	Classification	
	Major	Minor
Seams and stitching		
Stitching pattern not as specified.	x	
Any row of stitching missing.	x	
One stitch per inch under or over minimum and maximum specified.		x
Two or more stitches per inch under or over minimum and maximum specified.	x	
Ends of stitching not backstitched or secured as specified.		x
Open seam less than 1/2 inch.	x	
open seam 1/2 inch or more.	x	
Wrong seam or stitch type.	x	
Tension loose resulting in loose top or bottom thread, or tight tension causing puckering of material at stitch line.	x	
Needle chews or bunched stitching.	x	
Thread breaks not overstitched as specified.		x
Any stitching irregualr, unevenly gauged, or not uniform.		x
NOTE: A seam shall be classified as open when one or more stitches joining a seam are broken or when two or more consecutive skipped stitches or runoffs occur. On double stitched seams, a seam shall be considered open when either one or both sides or the scam are open.		
Webbing		
Wrong color.		x
Not specified type or class.	x	
Cut , tear, hole, abrasion or weak area.	x	
Metallic components		
Any surface rough, misaligned, distorted or contains corrosion, scale, pit, nick, sliver, burr, sharp edge , dent or crack,	x	
Any loose, detached, or otherwise not securely retained or incomplete assembly.	x	
Any malformed, fractured, broken, chipped or bent.	x	
Webbing adjusters that do not hold webbing or cause webbing to bind or fray.	x	
Protective finish omitted or not as specified.	x	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:36Z
Check the source to verify that this is the current version before use.

TABLE I. Visual defects. - Continued

Defect	Classification	
	Major	Minor
Thread		
Not type, class or size specified.	x	
Not specified color.		x
Construction and assembly		
Any component missing, not assembled *or* joined as specified.	x	
Any mend, darn, patch or splice.		x
Grommet holes not finished as specified.		x
Ends of webbing not finished as specified.		x
Cleanness		
Grease, oil, ink smears, dirt or other foreign matter clearly noticeable.		x
Thread ends not trimmed to 1/4-inch maximum length.		x

4.4.1.2 Examination for dimensions. The harness shall be examined for measurement defects, A defect shall be considered to exist if any measurement deviates from the measurements and tolerances specified on the applicable drawings.

4.4.1.3 Inspection levels and acceptable quality levels. The inspection levels and AQL's expressed in defects per 100 units for visual and dimensional examination in accordance with MIL-STD-105 shall be as follows:

	AQL's	Inspection level
For defects applicable to 4.4.1.1		
Major	2.5	I
Total (major and minor combined)	6.5	I
For defects applicable to 4.4.1.2		
One class	6.5	S-3

4,5 Inspection of packaging. Sample packages and packs, and the inspection of the preservation-packaging, packing and marking for shipment and storage shall be in accordance with the requirements of section 5 and the documents specified therein.

5. PACKAGING

(The packaging requirements specified herein apply only for direct Government acquisition. For the extent of applicability of the packaging requirements of referenced documents listed in section 2, see 6.6.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:36Z
Check the source to verify that this is the current version before use.

5.1 Preservation Preservation shall be level A or commercial as specified (see 6.2.1)

5 .1.1 Level A.

5.1.1.1 Each harness, with shoulder belts and waist belts properly attached, shall be neatly folded. The front and rear jocking straps need not be attached to the main harness assembly, they may be folded in half and laid on top of the folded main harness assembly. The folded harness and straps shall measure approximately 14-1/2 by 14-1/2 inches. Each folded harness and strap assembly shall be inserted in a snug-fitting, clear polyethylene film bag having a film thickness of not less than 0.0035 inch. The bag may be fabricated from polyethylene film tubing or sheeting. Seams and closures shall be formed by heat sealing. A 1/4-inch diameter hole shall be made at one corner of each bag to allow excess air to escape. As an alternate, the polyethylene bag may be of the tuck-in or reverse flap type, in which a heat seal closure and corner hole are not required. Each harness assembly shall be further packaged in a fiberboard box conforming to type CF, variety SW, style RSC, class domestic, grade 200 of PPP-B-636. Inside dimensions of the box shall be 14-3/4 inches in length and width and 3-5/8 inches in depth. Any void in the container shall be filled with crumpled commercial grade kraft paper.

5.1.2 Commercial. Harnesses shall be packaged in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B or commercial as specified (see 6.2.1).

5.2.1 Level A. Six harnesses, packaged as specified in 5.1, shall be packed in a fiberboard shipping contaainer-assembled, closed and reinforced conforming to type CF, class weather-resistant . grade V2s, size 3, style SW of MIL-B-1775. Level A packages shall be packed six in length along one side panel within a shipping container.

5.2.2 Level B. Six harnesses, packaged as specified in 5.1, shall be packed in a fiberboard shipping container assembled, closed and reinforced conforming to type CF, class domestic, grade 275, size 3, style SW as specified in MIL-B-17757. Level A packages shall be packed six in length along one side panel within a shipping container.

5 2 .2.1 When specified (see 6.2.1), the shipping container shall be a grade V3c, V3s or V4s fiberboard box fabricated in accordance with MIL-B-17757 and closed in accordance with the appendix of the box specification.

5.2.3 Commericial Harnesses preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951-

5 .3 Marking. In addition to ally special marking required (see 6.2. 1), Interior packages and exterior shipping containers shall be marked in accordance with MIL-STD-129. Marking for commercial shipments shall be in accordance with ASTM D 3951.

Source: https://assist.dla.mil -- Downloaded: 202610-23T11:36Z
Check the source to verify that this is the currentversion before use.

5.3.1 Special marking. Each interior package and shipping container shall be marked on the top, in black letters, not less than 1/2 inch in height. In addition, two sides of each shipping container shall be marked with the same legend. The label legend shall be as follows:

HARNESS , DIVERS (MK - 12)
CONTRACT NO: DLA-100-00-0-0000 (Example)
STOCK NO: 4220-00-000-0000 (Example)
NAME OF SUPPLIER:

5.4 Palletization. When specified (see 6.2.1), harnesses, packed as specified in 5.2, shall be palletized in accordance with load type I of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L. Pallet patterns shall be in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the pallet patterns specified in MIL-STD-147) the pallet pattern used shell first be approved by the contracting officer.

6. NOTES

6.1 Intended use. The harnesses are designed to be worn as a component of the MK-12 diving system. The harness along with the front and rear jocking strap is used to keep the divers neck ring snug on his shoulders- Also, the harness prevents the divers dress suit from expansion due to internal air pressure.

4.2 Ordering data.

6.2.1 Acquisition requirements. Acquisition documents should specify the following:

(a) Title, number, and date of this specification.
(b) When first article is required (see 3.1).
(c) Preservation and packing required (see 5.1 and 5.2).
(d) When weather- resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
(e) Special marking required (see 5.3).
(f) When palletization is required (see 5,4).

6.2.2 Data requirements. When this specification is used in an acquisition and data are required to be delivered, the data requirements identified below shall be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved Contract Data Requirements List (CDRL), incorporated into the contract. When the provisions of DoD FAR Supplement, Part 27, Sub-Part 27.410-6 (DD Form 1423) are invoked and the DD Form 1423 is not used, the data specified below shall be delivered by the contractor in accordance with the contract or purchase order requirements . Deliverable data required by this specification are cited in the following paragraphs.

Paragraph no.	Data requirement title	Applicable DID no.	Option
3.3.2	Certificate of compliance	DI-E-2[illegible]1	---

Source: https://assist.dla.mil -- Downloaded: 202610-23T11:36Z
Check the source to verify that this is the currentversion before use.

(Data item descriptions related to this specification, and identified in section 6 will be approved and listed as such in DoD 5010.12-L. , AMSDL. Copies of data item descriptions required by the contractors in connection with specific acquisition functions should be obtained from the Naval Publications and Forms Center or as directed by the contracting officer.)

6.2.2.1 The data requirements of 6.2.2and any task in sections 3, 4, or 5 of this specification required to be performed to meet a data requirement may be waived by the contracting/acquisition activity upon certification by the offeror that identical data were submitted by the offeror and accepted by the Government under a previous contract for identical item acquired to this specification. This does not apply to specific data which may be required for each contract regardless of whether an identiical item has been supplied previously (for example, test reports).

6.3 First article. When a first article inspection is required, the items should be a first article sample. The first article should consist of one unit. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, approval of first article test results and disposition of first articles. Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test-, must furnish evidence with, the bid that prior Government approval is presently appropriate for the pending contract.

6.4 Metal hardware, with the exception of the locking pin, the harness buckle spring, grommets and washers can be obtained from United States Forgecraft Corporation, P.O. Box 387, Fort Smith, AR 72902.

6.5 Parts list. The following parts list is included as a convenience only and the Government assumes no liability whatsoever for any inaccuracies :

Item	Quantity/harness	Reference
Webbing, 1-3/4 inch	363 inches (approximate)	MIL-W-4O88
Pile fastener tape, 2 inch	8 inches (approximate)	MIL-F-21840
Hook fastener tape, 2 inch	6-1/2 inches (approximate)	MIL-F-21840
Thread, nylon	as required	V-T-295
Buckle, strap bar		Part number 2060A (United States Forgecraft Corporation)
Buckle, strap bar (tongueless)		Part number 2060A (United States Forgecraft Corporation)

Source: https://assist.dla.mil -- Downloaded: 2026l0-23T11:36Z
Check the source to verify that this is the current version before use.

Item	Quantity/(harness	Reference
Link connector	2	Part number 60D562 (United States Forgecraft Corporation)
Snap hook, non-adjustable	2	Drawing MS22044
Snap hook, adjustable	1	Drawing MS22043
Adjuster, harness	2	Drawing MS22007-1
Ring "V"	1	Drawing MS22045
Lock fastener link	1	Drawing 44026454
Latch and locking pin assembly	1	Drawing - made from 44B26452 and 53501-4-05
Ring, parachute "V" type, assembly, non-adjustable	1	Drawing - made from MS22045 and 42B6034
Ring, parachute "V" type, assembly, adjustable	1	Drawing - made from MS70102 and 42B6034
Grommets and washers	34	Size 1, plain (Stimpson Co., Inc.)

6.6 Sub-contracted material and parts. The packaging requirements of referenced documents listed in section 2 do not apply when material and parts are acquired by the contractor for incorporation into the equipment and lose their separate identity when the equipment is shipped.

6.7 Subject term (key word) listing.

Divers
Diving system, MK 12
Harness

6.8 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Preparing activity:
Navy - SH
(Project 4220-N302)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:36Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:36Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE NAVY

COMMANDER
NAVAL SEA SYSTEMS COMMAND (SEA 55Z3)
DEPARTMENT OF THE NAVY
WASHINGTON, DC 20362-5101

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 12503 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

COMMANDER
NAVAL SEA SYSTEMS COMMAND (SEA 55Z3)
DEPARTMENT OF THE NAVY
WASHINGTON, DC 20362-5101

NO POSTAG
NECESSAR
IF MAILED
IN THE
UNITED STA

Source: https://assist.dla.mil -- Downloaded: 2026l0-23T11:36Z
Check the source to verify that this is the currentversion before use.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-H-87028B(SH)	HARNESS, DIVERS (MK-12)

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*:

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 202610-23T11:36Z
Check the source to verify that this is the current version before use.