MILITARY SPECIFICATION

JACKET, INSECT REPELLENT

This amendment forms a part of Military Specification MIL-J-87024, dated 31 August 1976, and is approved for use by all Departments and Agencies of the Department of Defense.

Page 3

3.3.2 - Line 3, Delete "36 and 20" and substitute "40 and 24"

3.3.3 - End of sentence, delete period "(.) and add ", Type II, Green Shade 3046.

Page 4

3.3.8 - Line 3, Delete "1-1/2 by 3 inches (3.8 by 7.6 cm)" and substitute "1-1/4 by 2-1/4 inches"

Page 5

3.3.11 - Under "Caution", line 1, delete "our" and substitute "out".

Page 8

3.8 - Table I, operation 4b, add "or as an alternate, stitch together interlining and bottom edge of the sleeve using 515 or 519 or 516 stitch types; an SSA-2 seam; 8 to 10 stitches per inch with a size B thread for the overedge stitch and size E for the chain stitch. The chain stitch shall be approximately 1/8 inch from the edge of the interlining."

Page 10

Table I, Operation 6d, line 2, delete "1/2 inch (12.7mm)" and substitute "1 inch".

Operation 6e, delete in its entirety and substitute "e. Staystitch two plaits in the hood bottom, as indicated by marks on the pattern, folding each outside edge towards the center seam of hood. I.E. with the bulk (on the inside of the hood) folded toward center".

FSC 8415

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:35Z
Check the source to verify that this is the current version before use.

Page 11

Table I, Operation 7a, add "or as an alternate, stitch a length of 1/2 inch wide tape along the inside bottom edge of the jacket using 515, 516, or 519 stitch types; an SSA-2 seam; 8 to 10 stitches per inch with a size B thread for the overedge stitch and size E for the chain stitch. The chain stitch shall be approximately 1/8 inch from the edge of the tape."

Operation 7c, line 2 - after "fronts" delete remainder of sentence and substitute "as indicated by marks on the interlining pattern and through all plies."

Operation 7d, line 3 - delete "1/2 inch (12.7mm)" and substitute "1 inch."

Page 12

Table I, Operation 9, delete in its entirety and substitute:

"a. Attach five male snap fasteners to the right front closure as indicated by marks on the interlining pattern and through all plies.

b. Attach five female snap fasteners to the left front closure as indicated by marks on the interlining pattern and through all plies.

c. Attach two male and one female snap fastener to each of the sleeve bottoms as indicated by marks on the interlining pattern and through all plies.

NOTE: The female snap fastener is secured on the sleeve bottom after folding as indicated by markings on the interlining pattern and through all plies".

3.9 Table II - Tolerance for sleeve, delete "plus or minus 1". Also, under "front length', delete "22 (55.9), 23-1/2 (59.7) and 25 (63.5)" and substitute "21-1/2, 23, and 24-1/2" respectively.

Custodian:
Navy - NU

Review Activities:
Navy - MS, CG
DLA-CT

User Activities:
Navy - MC, AS, YD

Preparing Activity:
Navy - NU

Project No. 8415-N391

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:35Z
Check the source to verify that this is the current version before use.