MILITARY SPECIFICATION SHEET

SLEEVING, FOR IDENTIFICATION MARKING, HEAT SHRINKABLE, POLYOLEFIN, FLEXIBLE

This amendment forms a part of Military Specification Sheet MIL-S-85848/1(AS), dated 1 May 1987, and is approved for use within the Naval Air Systems Command, Department of The Navy, and is available for use by all Departments and agencies of the Department of Defense.

Page 1

Under Continuous operating temperature range: Delete all temperature ratings for Type I and Type II and substitute: "-40° to +105°C (-40°F to +221°F) for both Types."

Page 4

Table III,

1. Under Requirements, Specific Gravity: Delete "1.35" and substitute "1.38"
2. Under Test Procedure and Conditions:
   a. Delete all conditions for 4.6.7 and substitute "121° ± 1°C (250° ± 2°F) for both types"
   b. Delete all conditions for 4.6.8 and substitute "105° ± 1°C (221° ± °F) for both types"
   c. Delete all conditions for 4.6.9 and substitute "-40° ± 1°C (-40° ± 2°F) for both types"

Restricted shrinkage: After 4.6.3, delete the remainder of the paragraph and substitute: "149° ± 2°C (300° ± 4°F) for 3 to 5 minutes until the sleeve is snug."

Unrestricted shrinkage: After 4.5.1, delete the remainder of the paragraph and substitute: "149° ± 2°C (300° ± 4°F) for 5 minutes."

Preparing Activity
Navy - AS
(Project No. 5970-N668)

AMSC N/A FSC 5970

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:30Z
Check the source to verify that this is the current version before use.