MIL-C-19179B
AMENDMENT 2
6 February 1984
SUPERSEDING
AMENDMENT 1
11 December 1981

# MILITARY SPECIFICATION

## COUPLING ASSEMBLY, QUICK-DISCONNECT, FUEL

This amendment forms a part of Military Specification MIL-C-19179B, dated 22 March 1963, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1, under "SPECIFICATIONS, FEDERAL": Delete reference to "P-S-661".

Under "SPECIFICATIONS, FEDERAL": Add:

"P-D-680 - Dry Cleaning Solvent.
QQ-C-390 - Copper Alloy Castings (Including Cast Bar).
QQ-N-286 - Nickel-Copper-Aluminum Alloy, Wrought.
TT-S-735 - Standard Test Fluids; Hydrocarbon."

PAGES 1 and 2

2.1, under "SPECIFICATIONS, MILITARY": Delete reference to "MIL-S-3136", "MIL-S-3950", MIL-J-5161", "MIL-P-6906", "MIL-S-7742", "MIL-P-7936", "MIL-B-16522", "MIL-S-21195", and "MIL-D-70327".

* 2.1, under "SPECIFICATIONS, MILITARY": Add:

"DOD-D-1000 - Drawings, Engineering and Associated Lists.
MIL-S-8879 - Screw Threads, Controlled Radius Root With Increased Minor Diameter; General Specification for.
MIL-S-83731 - Switches, Toggle, Unsealed and Sealed Toggle, General Specification for."

FSC 4730



Source: https://assist.dla.mil -- Downloaded: 202610-18T12:22Z
Check the source to verify that this is the current version before use.

* 2.1, under "STANDARDS, MILITARY": Delete and substitute:

"STANDARDS

MILITARY

MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-130 - Identification Marking of US Military Property.
MIL-STD-143 - Standards and Specifications, Order of Precedence for the Selection of.
MIL-STD-794 - Parts and Equipment, Procedures for Packaging of.
MIL-STD-889 - Dissimilar Metals.
MS16625 - Rings, Retaining, Internal, Basic (Tapered Section Type).
MS16656 - Switch, Toggle, Single Pole, Single Throw.
MS20995 - Wire, Safety or Lock.
MS26549 - Nipple, Quick Disconnect, 2-1/2 Inch, Pressure Fuel Servicing, Flange Type.
MS26550 - Coupling, Quick Disconnect, 2-1/2 Inch, Pressure Fuel Servicing, Nozzle to Hose.
MS26551 - Strainer, 2-1/2 Inch, Pressure Fuel Servicing.
MS26552 - Nipple, Quick Disconnect, 2-1/2 Inch, Pressure Fuel Servicing, Open Flow, Wrench Type.
MS26553 - Nipple, Quick Disconnect, 2-1/2 Inch, Pressure Fuel Servicing, With Check Valve, Wrench Type.
MS29512 - Packing, Preformed, Hydrocarbon Fuel Resistant, Tube Fitting, "O" Ring.
MS29513 - Packing, Preformed, Hydrocarbon Fuel Resistant, "O" Ring.
MS29520 - Envelope Dimensions, Nozzle, Pressure Fuel Servicing Locking, Aircraft, Type D-1.
MS33540 - Safety Wiring and Coiter Pinning, General Practices for.
MS33588 - Nuts, Self-Locking, Aircraft, Design and Usage; Limitations of.
MS35058 - Switch, Toggle One Pole, Sealed Toggle."

* 2.2: Delete in its entirety and substitute:

"2.2 Other publications. The following document forms a part of this specification to the extent specified herein. The issues of the documents which are indicated as DoD adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable.

SOCIETY OF AUTOMOTIVE ENGINEERS (SAE)
AMS 4631 - Aluminum Bronze Rods, Bars, and Forgings 90.5Cu-7.5Al-1.9S.

(Application for copies should be addressed to the Society of Automotive Engineers, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.)"



Source: https://assist.dla.mil -- Downloaded: 2026-10-18T12:22Z
Check the source to verify that this is the current version before use.

PAGE 3

3.3.1, lines 9 and 10: Delete "Standard MS33586" and substitute "MIL-STD-889".

Table I, column 1: Delete "NAS-669 (b)" and substitute "MS16625".

Under note (b), line 2: Delete "NAS-669" and substitute "MS16625".

Under note (c), line 1: Delete "NAS-669-225" and substitute "MS16625-1218".

3.3.2, lines 3 and 4: Delete "Specification MIL-J-5161".

Line 4: Delete "MIL-S-3136" and substitute "TT-S-735".

PAGE 4

Figure 1, under "Strainer Retaining Ring": Delete "NAS PART NO. 669-225" and substitute "MS16625-1218".

PAGE 5

* Table II, lines 1 through 11: Delete and substitute:

"TABLE II. Metal requirements for components.

| MS Part no. | Name | Material specification | | |
|---|---|---|---|---|
| | | | Alloy | Temper |
| MS26549-1 | Nipple | QQ-A-601<br>QQ-A-596<br>QQ-A-367 | 356<br>356<br>2014 | T6<br>T6<br>T6 |
| MS26549-2<br>MS26550-1<br><br>MS26550-2<br>MS26550-3 | Nipple<br>Coupling body<br>Other metal parts<br>Coupling<br>Coupling body<br>Ball<br>Spring<br>Cam<br><br>Other metal parts | QQ-C-390<br>Same as for MS26549-1<br>See 3.3.1<br>Same as for MS26550-1<br>QQ-C-390<br>QQ-N-286 NiCu<br>QQ-W-423 Cres, type 302<br>AMS 4631 Aluminum Bronze<br>QQ-C-390, alloy 958<br>Bronze or NiCu, as approved | | |

3.4: Delete sentences 3, 4 and 5 and substitute: "The coupling shall incorporate a primary and secondary lock. The secondary lock shall be visible in order to show that a positive lock has been attained. Both shall be easily operable by personnel wearing heavy winter gloves."



Source: https://assist.dla.mil -- Downloaded: 2026-10-18T12:22Z
Check the source to verify that this is the current version before use.

PAGE 6

3.6, lines 2 and 3: Delete "Specification MIL-S-7742" and substitute "MIL-S-8879".

* 3.8: Delete and substitute:

"3.8 Switches. For couplings containing electrical switches, the switch installation shall be explosion-proof, covered by a rubber boot and shielded by a protective guard. Switches shall be single pole single throw and shall be in accordance with MS16656 or MS35058 except that it shall be dimensioned so that the top of the switch toggle shall not extend above the switch guard to prevent abrasion of the rubber boot. The boot shall completely cover the switch lever to the mounting plate to prevent moisture from entering the mounting hole. A guard, similar to that shown on MS26550 shall protect the switch from external damage."

3.10, lines 7 and 8: Delete "Specification MIL-D-70327" and substitute "DOD-D-1000".

3.12 Delete and substitute:

"3.12 Identification of product."

3.12.1 Delete and substitute:

"3.12.1 Markings. Assemblies and parts shall be clearly and permanently identified by steel stamping or a permanently attached nameplate in accordance with MIL-STD-130. The following information shall be provided on each coupling and nipple.

Coupling (or nipple as applicable)
MS part no.
Manufacturers part no.
Manufacturers name or trademark
Serial no."

PAGE 8

4.2.1, line 16: Delete "Specification MIL-D-70327" and substitute "DOD-D-1000".

PAGE 9

4.4.2, line 3: Delete "MIL-S-3136" and substitute "TT-S-735".

Line 5: Delete "Specification P-S-661" and substitute "P-D-680".



Source: https://assist.dla.mil -- Downloaded: 202610-18T12:22Z
Check the source to verify that this is the currentversion before use.

5.1.1, line 5: Delete "Specification MIL-P-7936" and substitute "MIL-STD-794".

6.3: Delete and substitute:

"6.3 With respect to products requiring qualification, awards will be made only for products which are, at the time set for opening of bids, qualified for inclusion in Qualified Products List QPL-19179 whether or not such products have actually been so listed by that date. The attention of the contractors is called to these requirements, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or purchase orders for the products covered by this specification. The activity responsible for the Qualified Products List is the Naval Sea Systems Command, SEA 55Z3, Department of the Navy, Washington, DC 20362 and information pertaining to qualification of products may be obtained from that activity. Application for Qualification tests shall be made in accordance with "Provisions Governing Qualification SD-6" (see 6.3.1).

6.3.1 Copies of "Provisions Governing Qualification SD-6" may be obtained upon application to Commanding Officer, Naval Publications and Forms Center, 5801 Tabor Avenue, Philadelphia, PA 19120."

NOTE: The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Army - ME
Navy - SH
Air Force - 99

Review activity:
DLA - CS

Preparing activity:
Navy - SH
(Project 4730-0614)



Source: https://assist.dla.mil -- Downloaded: 2026-10-18T12:22Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T12:22Z
Check the source to verify that this is the current version before use.