MIL-B-43064C
12 November 1981
SUPERSEDING
MIL-B-43064B
6 September 1973

MILITARY SPECIFICATION

BINDER, LOOSE-LEAF (EQUIPMENT LOGBOOK)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one size loose-leaf binder (equipment logbook).

1.2 Classification. The loose leaf binder shall be of the following size:

Size 1 - Deleted
Size 2 - 1-1/2 inch capacity

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

L-P-375	-	Plastic Film, Flexible, Vinyl Chloride
UU-B-623	-	Book Cover Board
PPP-B-566	-	Boxes, Folding, Paperboard
PPP-B-636	-	Boxes, Shipping, Fiberboard
PPP-B-676	-	Boxes, Setup

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Natick Research and Development Laboratories, Natick, MA 01760 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:29Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-P-116 - Preservation, Methods Of
MIL-C-43006 - Cloth and Strip Laminated, Vinyl Nylon High Strength, Flexible

STANDARDS

FEDERAL

FED-STD-123 - Marking for Shipment (Civil Agencies)
FED-STD-595 - Colors

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-1188 - Commercial Packaging of Supplies and Equipment

(Copies of specifications, standards and publications required by contractors in connection with specific procurement functions, should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply:

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

E 18 - Rockwell Hardness and Rockwell Superficial Hardness of Metallic Materials

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Materials and components (see 6.3).

3.1.1 Backbone. The backbone shall be book cover board, No 17, with 1/8 inch rounded corners, and conform to UU-B-623. The thickness shall not be less than 0.120 inches.

3.1.2 Fillerboard (commercial). Commercial fillerboard thickness shall not be less than 0.050 inches with 1/8 inch rounded corners.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:29Z
Check the source to verify that this is the current version before use.

3.1.3 Ring protector reinforcement. The reinforcement shall be made from laminated open mesh woven nylon cloth conforming to the weight, breaking strength (initial only), stiffness, blocking, construction and laminating vinyl film requirements of type II, class 1 or 2 of MIL-C-43006.

3.1.4 Plastic.

3.1.4.1 Covering. The vinyl plastic covering thickness shall not be less than 0.015 inches and conform to type II, class 2 of L-P-375. The color shall approximate color No. 34108 of FED-STD-595 and shall have a French calf grain finish.

3.1.4.2 Pockets (clear window). The pockets shall be vinyl plastic film 0.008 inch minimum thickness conforming to type II, class 1 of L-P-375 except that the film shall be clear and transparent.

3.1.5 Steel.

3.1.5.1 Ring plates. Steel used for the ring plates shall be cold-rolled having a hardness of not less than Rockwell 80 B when tested in accordance with 4.2.1.

3.1.5.2 Spring or tension plate. Steel used for the spring or tension plate shall be cold-rolled having a hardness of not less than Rockwell 65 B when tested in accordance with 4.2.1.

3.1.5.3 Rings. Steel used for rings shall have a hardness of not less than Rockwell 65 B when tested in accordance with 4.2.1.

3.1.5.4 Metal finish. All metal parts which will be exposed upon completion of the fabrication of the binder shall have a corrosion resistant finish and shall show no evidence of corrosion when tested in accordance with 4.3.1.

3.2 Design and construction.

3.2.1 Binder. The binder shall be loose leaf and with three rings. The back of the cover shall have an inside pocket. The outside of the binder shall have two clear title slot pockets. The rings shall open and close by means of booster clips attached at one or both ends of the binding mechanism. The binding mechanism shall be fastened to the back of the binder with rivets. The inside diameters of the rings shall be 1-1/2 inches. The distance between adjacent ring centers shall be 3-1/2 inches. The distance between the outside ring centers shall be 7 inches. The ring capacities shall be 7-1/2 inches. Heat sealed seams shall meet the applicable requirements and tests in L-P-375.

3.2.1.1 Covering (plastic). The covering shall be as specified in 3.1.4.1 over fillerboard specified in 3.1.2 The covering shall overlap the fillerboard and shall be heat-sealed around the edges.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:29Z
Check the source to verify that this is the current version before use.

3.2.1.2 Pocket, plastic (inside back cover). A pocket made of the plastic film specified in 3.1.4.1 shall be located on the inside back cover along the 10 inch dimension. It shall be 3-1/2 inches ± 1/4 wide. Its edges shall be heat sealed and the corners at the opening of the inside back cover shall be reinforced by a heat weld. The weld shall be 1/4 inch square or round at the pocket seal points.

3.2.1.3 Pockets, plastic (clear window). The binder shall have two, clear plastic, title slot window pockets made of the material specified in 3.1.4.2. One pocket shall be located along the backbone, its upper edge 2 inches from the top of binder opening at the top. It shall be of dimensions capable of receiving a 1 by 3 inch card insert. The other pocket shall be centered on the front cover, with the lower edge 2 inches from the bottom of the front binder cover and shall be of dimensions capable of receiving a 3 by 5 inch card insert (see figure 1). Both pockets shall have a half-moon thumb cut centered at the top opened edge for easy removal of cards. All closure seams shall be heat sealed.

3.2.1.4 Ring plate. The ring plate shall be steel as specified in 3.1.5.1, not less than 0.040 inch thick, and not less than 0.770 inch wide.

3.2.1.5 Rings (oval). The rings shall be steel as specified in 3.1.5.3, securely fastend to the ring plate. The ring stock shall be not less than 0.125 by 0.180 inch. The rings shall fit snugly when closed.

3.2.1.6 Spring or tension plate. The spring or tension plate, within which the ring plates operate, shall be steel as specified in 3.1.5.2 and shall be not less than 0.015 inch thick.

3.2.1.7 Fillerboard. The fillerboard shall be of nominal dimensions 7-3/4 wide by 9-5/8 inches long conforming to 3.1.2. Tolerances shall be sufficient so as to provide a binder conforming to the dimensions specified in 3.2.1.9.

3.2.1.8 Ring protector strip. A ring protector strip of fiberboard conforming to 3.1.3, shall be attached 1/4 inch from the edge of the backbone adjacent to each side of the binding mechanism.

3.2.1.9 Size and capacity. The binders shall be 10 inches +1/4, -1/8 inches in length and 8 inches +1/4, -1/8 inches in width. The binder capacity shall not be less than 1-1/2 inches.

3.3 Marking.

3.3.1 Identification marking. The manufacturer's name or trademark, contract number, and date of manufacture shall be printed or stamped on the inside of one cover.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:29Z
Check the source to verify that this is the current version before use.

3.3.2 Special marking. Unless otherwise specified (see 6.2), the markings shown in figure 1 shall be blind embossed on the front cover of the binders.

3.4 Workmanship. The binders shall be well finished, clean, and all edges shall be smooth. All metal parts shall be free from burrs and rough edges. The binding mechanism shall be securely fastened to the backbone and constructed so that no parts will work loose in service. The protective envelope shall be well finished, clean, free from cuts, tears, creases, cracks or other imperfections, all edges shall be smooth.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.2.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document. In addition, components shall be tested for the characteristics listed in table I. For purposes of sampling, the lot for each component listed shall be expressed in units of the components required to manufacture one complete end item, as applicable. The sample unit shall be one complete component as designated in table I. The sample size for the designated lot shall be as shown below. There shall be no evidence of failure of any sample unit to meet the requirements as specified.

Lot size	Sample size
800 or less	2
801 up to and including 22,000	3
22,001 and more	5

All test reports shall contain the individual values utilized in expressing the final result.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:29Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS FOR TESTING Component tests — TABLE I

CHARACTERISTIC		Specification Reference		Requirements Applicable To		Number Determinations Per Unit	Results Reported As		Inspect Level	AQL
		Requirement	Test Method	Individ Unit	Lot Aver		Pass or Fail	Numerically to Nearest		
Backbone	Thickness	3.1.1	Standard		X	3		0.001 inch		
	Corner radius	3.1.1	Standard	X		Each corner	X			
Book cover fillerboard	Thickness	3.1.2	Standard		X	3		0.001 inch		
	Corner radius	3.1.2	Standard	X		2 corners	X			
Ring plate	Thickness	3.2.1.4	Standard		X	3		0.001 inch		
	Hardness	3.1.5.1	ASTM E 18	X		3		Scale reading		
Spring or tension plate	Thickness	3.2.1.6	Standard		X	3		0.001 inch		
	Hardness	3.1.5.2	ASTM E 18	X		3		Scale reading		
Rings (set of 3)										
	Hardness	3.1.5.3	ASTM E 18	X		3		Scale reading		
Heat seal strength: Flexible vinyl chloride		3.2.1	L-P-375	X		.1	X			

NATICK Form 598
1 Mar 77 EDITION OF 1 JUL 76 IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:29Z
Check the source to verify that this is the current version before use.

4.2.2 End item examination. The end item shall be examined in accordance with 4.2.2.1, 4.2.2.2 and 4.2.2.3. The lot size shall be expressed in units of one binder. The sample unit shall be one binder.

4.2.2.1 Visual examination. The end item shall be examined for defects listed below. The inspection level shall be S-4 and the acceptance quality level (AQL) shall be 2.5 defects per hundred units.

Examine	Defect
Design, construction and workmanship, general (applicable to all components and assemblies)	Not of loose-leaf, 3-ring binder style
	Inside pocket missing or not on inside of back cover
	Title pockets missing or not positioned as specified
	Binding mechanism not of type specified
	Binding mechanism not fastened to book cover as specified
	Any fiberboard strip missing or not positioned as specified
	Vinyl film covering does not overlap fillerboard
	Vinyl film covering not continuously heat-sealed around periphery of binder over fillerboard
	Inside pocket not heat-sealed or spot welded at corner openings as specified
	Binding mechanism not positioned as specified
	Any rivet used in fastening binding mechanism to binder cover missing, loose, or not properly rolled and peened
	Closure seams of exterior plastic pockets not heat-sealed
	Any opening in heat-sealed seams of exterior plastic pockets
	Half-moon thumb cut opening in exterior plastic pockets missing
	Not color specified
	Color not uniform
	Not French calf grain finish
	Any evidence of rust on any hardware
	Finish on visible hardware not smooth and bright
	Exterior plastic pockets not clear, transparent plastic
	Any cut, tear, crack, hole or scuffed area on inside or outside surface of binder covering
	Any loose or broken rivet
	Any tear, cut, hole, or crack in exterior plastic pockets
	Any broken, loose, or bent ring

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:29Z
Check the source to verify that this is the current version before use.

Examine	Defect
Design, construction and workmanship, general (applicable to all components and assemblies) (cont'd)	Any broken, loose, or bent booster clip Any dent in ring plate Any ring which does not fit snugly when closed, i.e., sprung so that ring closure is incomplete Any burr or rough edge on any exposed metal part Any spot or stain Any opening in any heat-sealed area
Identification marking	Missing, incomplete, not legible
Special marking	Not positioned on the inside of one cover Not in accordance with figure 1 Not blind embossed on the front cover

4.2.2.2 Dimensional examination. The end item shall be examined for the defects listed below. The inspection level shall be S-2 and the AQL shall be 6.5 defects per hundred units.

Examine	Defect
Binder (closed)	Length more than 10-1/4 inches Length less than 9-7/8 inches Width more than 8-1/4 inches Width less than 7-7/8 inches Dimensions of outside plastic pockets are such as to prevent insertion of required size inserts, or are such that inserts fall out when binder is inverted
Binder (open)	Rings less than 1-1/2 inches inside diameter Rings not spaced 3-1/2 inches between centers End rings not spaced 7 inches between centers Inside pocket less than 3-1/2 inches in width or not full length of binder Heat weld (square or round) at corners of inside pocket less than 1/4 inch

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:29Z
Check the source to verify that this is the current version before use.

4.2.2.3 Operational examination. The end item shall be examined for defects listed below. The inspection level shall be S-2 and the AQL shall be 2.5 defects per hundred units.

Examine	Defect
Binding mechanism- The binder shall be opened and the binding mechanism opened and closed in the normal manner of operation Repeat this operation five consecutive times	Booster clips do not properly function, rings do not open or close completely

4.2.3 End item testing. The exposed metal parts of the end item shall be tested for corrosion resistance as specified in 4.3.1. The lot size shall be expressed in units of one binder. The sample unit shall be one binder. The sample size for the applicable lot size shall be as shown below. There shall be no evidence of failure of any sample unit to meet the requirements as specified.

Lot size	Sample size
800 or less	2
801 up to and including 22,000	3
22,001 and more	5

4.2.4 Packaging inspection Packaging inspection shall be made to determine that preservation, packing, and marking comply with section 5 and the requirements shall be in accordance with the Group A, Group B and when required (see 6.2) the Group C (rough handling) requirements of MIL-P-116. Defects shall be scored as set forth below. The sample unit shall be one shipping container fully packaged except that it need not be closed. Defects of closure listed below shall be examined on shipping containers fully packaged. The lot shall be the number of shipping containers offered for inspection at one time. The inspection level shall be S-2 and the AQL shall be 2.5 defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:29Z
Check the source to verify that this is the current version before use.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Materials	Any component missing, damaged or not as specified
Workmanship	Inadequate application of components such as: incomplete closure of container flaps, loose strapping, improper taping, or inadequate stapling Bulging or distortion of container
Contents	Number of items per shipping container is more or less than required Number of items per unit packed is more or less than required 1/

1/ For this defect, one unit pack from each shipping container in the sample shall be examined.

4.3 Methods of inspection.

4.3.1 Corrosion resistance test, exposed metal parts. All exposed metal parts shall be tested for corrosion resistance by placing them in a boiling 10 percent (by weight) aqueous solution of sodium chloride for a period of 15 minutes. The fittings, upon being removed from this solution, shall be immediatley immersed in 10 percent (by weight) aqueous solution of sodium chloride at room temperature. They shall then be removed from this solution and, without having the adhering liquid wiped off, allowed to dry for 24 hours at room temperature. The metal parts shall then be rinsed in lukewarm water, allowed to dry, and examined for evidence of corrosion.

5. Packaging

5.1 Preservation. Preservation shall be level A, B or Commercial as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Binders. Four binders shall be unit packed in a snug-fitting paperboard folding or setup box conforming to variety 2, style III, type G, class i of PPP-B-566; or type I, variety 2, class A, style 3 or 4 of PPP-B-676. Binders shall be arranged in the box with the binding plate edges alternated. Each box shall be securely closed with 2 inch minimum width pressure-sensitive water-resistant tape as specified in the appendix of the applicable box specification.

5.1.1.2 Level B. Unit packing to be the same as level A.

5.1.2 Commercial. Binders shall be preserved in accordance with MIL-STD-1188.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:29Z
Check the source to verify that this is the current version before use.

5.2 Packing. Packing shall be level A, B, or Commercial as specified (see 6.2).

5.2.1 Level A packing. Thirty-six binders, preserved as specified in 5.1, shall be packed in a snug-fitting shipping container conforming to style RSC, grade V2s of PPP-B-636. Each shipping container shall be closed in accordance with method III, waterproofed in accordance with method V and reinforced as specified in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.2.4.

5.2.2 Level B packing. Thirty-six binders, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. Each shipping container shall be closed in accordance with method II as specified in the apppendix of PPP-B-636, except that the inspection shall be in accordance with 4.2.4.

5.2.2.1 Weather-resistant fiberboard container. When specified (see 6.2), the shipping container shall be a grade V3c, V3s or V4s fiberboard box, fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.2.4.

5.2.3 Commercial packing. Binders, preserved as specified in 5.1, shall be packed in accordance with MIL-STD-1188.

5.3 Marking. In addition to any special marking required by the contract, unit packs and shipping containers shall be marked in accordance with MIL-STD-129 or MIL-STD-1188, as applicable.

6. NOTES

6.1 Intended use. The binder is intended for use in military aircraft and vehicles for filing maintenance records and reports.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) Marking requirements, when applicable, (see 3.3.2).
(c) Selection of applicable levels of preservation and packing (see 5.1 and 5.2).
(d) When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
(e) When rough handling is required (see 4.2.4).

6.3 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the specification (see 3.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:29Z
Check the source to verify that this is the current version before use.

6.4 Deletion date. This specification deletes the size 1 binder shown in MIL-B-43064B, dated 6 September 1973.

6.5 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodian:

Army - GL

Review activities:

Army - AV, SM, MI

User activities:

Navy - SA, MC

Preparing activity:

Army - GL

Project No. 7510-0325

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:29Z
Check the source to verify that this is the current version before use.

U.S. ARMY

EQUIPMENT LOG BOOK



THIS RECORD IS A DEPARTMENT OF ARMY CONTROLLED ITEM AND MUST BE SAFEGUARDED AGAINST LOSS AND DAMAGE. IN THE EVENT OF LOSS, SEE TM 38-750.

PROPERTY OF THE U. S. GOVERNMENT

FIG. 1

☆U.S. GOVERNMENT PRINTING OFFICE: 1981—505-022/8866

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:29Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*:

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:29Z
Check the source to verify that this is the current version before use.