MIL-T-43047D
31 December 1985
SUPERSEDING
MIL-T-43047C
19 August 1971

MILITARY SPECIFICATION

TRUCKS, HAND, SHELF, 2 and 4 SHELVES

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers two types of four-shelf hand trucks and a two-shelf truck with a utensil rack.

* 1.2 Classification. The trucks shall be of the following types as specified (see 6.2):

Type I - 4 shelves (2 fixed and 2 adjustable), 800-pound capacity
Type II - 4 fixed shelves, 1400-pound capacity
Type III - 2 fixed shelves, with utensil rack, 900-pound capacity

2. APPLICABLE DOCUMENTS

* 2.1 Government documents. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this document to the extent specified herein.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to U.S. Army Natick Research and Development Center, Natick, MA 01760-5014, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A

FSC 3920

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:27Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

FF-C-77	- Casters, Rigid and Swivel (Institutional Duty)
PPP-B-601	- Boxes, Wood, Cleated-Plywood
PPP-B-636	- Boxes, Shipping, Fiberboard
PPP-C-843	- Cushion Material, Cellulosic

MILITARY

MIL-C-52950	- Crates, Wood, Open and Covered

STANDARDS

FEDERAL

FED-STD-601	- Rubber: Sampling and Testing

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	- Marking for Shipment and Storage
MIL-STD-130	- Identification Marking of US Military Property
MIL-STD-1186	- Cushioning, Anchoring, Bracing, Blocking and Waterproofing; with Appropriate Test Methods

(Copies of documents required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

* 2.2 Other publications. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this document to the extent specified herein.

NATIONAL SANITATION FOUNDATION (NSF)

Standard No. 2 - Food Service Equipment

Listing of Food Service Equipment

(Application for copies should be addressed to the National Sanitation Foundation, P.O. Box 1468, Ann Arbor, Michigan 48106.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:27Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

A 167 - Stainless and Heat-Resisting Chromium-Nickel Steel Plate, Sheet, and Strip
A 240 - Heat-Resisting Chromium and Chromium-Nickel Stainless Steel Plate, Sheet and Strip for Pressure Vessels
D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pennsylvania 19103.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence.

3. REQUIREMENTS

3.1 First article. When specified, a sample shall be subjected to first article inspection (see 4.3, 6.2, and 6.3).

3.2 Standard product. The trucks delivered under this document shall be the manufacturer's current commercial standard product except for any changes required to comply with document requirements.

3.3 Codes and standards. The trucks shall conform to the applicable requirements of NSF Standard No. 2.

3.3.1 Compliance. Prior to the approval of the first article, if one is submitted, or prior to the approval of the first shipment, the contractor shall submit to the contracting officer or his authorized representative satisfactory evidence that the trucks he proposes to furnish under this document meet the applicable requirements of NSF Standard No. 2 as follows:

a. A listing in the current edition of the NSF "Listing of Food Service Equipment" or display of the NSF Seal on the finished truck; or

b. A certification for the truck, issued by NSF under their special one-time contract evaluation/certification service; or

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:27Z
Check the source to verify that this is the current version before use.

c. A certified test report from a recognized independent testing laboratory acceptable to the medical department of the service for which the trucks are being acquired, indicating that the trucks have been tested and conform to NSF Standard No. 2.

* 3.4 Materials. The materials shall conform to the referenced documents and requirements specified herein. Recycled material may be used (see 6.4).

* 3.4.1 Stainless steel. Stainless steel sheet, plate and strip shall conform to the requirements of type 302 or 304 of ASTM A 167 or ASTM A 240.

* 3.5 Design and construction. The type I and II trucks shall consist of a frame, four shelves, four swivel-type casters, and four rubber corner bumpers. The type III truck shall consist of a frame, two shelves, four swivel type casters, four rubber corner bumpers, and a utensil rack. The type I truck shall be of the knockdown type with the second and third shelves adjustable. The shelves of the type II and III trucks shall be permanently fastened to the frame. The type III truck shall have a utensil rack permanently attached to the frame above the top shelf. The frame, shelves, utensil rack, and reinforcing for frame, rack, and shelves shall be fabricated of corrosion-resisting steel specified in 3.4.1. Casters shall be removable. The corner bumpers shall be of molded, gray, rubber compound that is nonmarking, when tested as specified in 4.4.1.1.1, and have a Shore A durometer hardness of 70 ± 5, when tested as specified in 4.4.1.1.2. The corner bumpers shall be attached to the corner uprights at the approximate height of the lowest shelf by corrosion-resisting steel inserts, nuts, bolts, and lockwashers or may be 5-inch diameter circular revolving type mounted on the caster stems. Capacities and dimensions of the trucks shall be as specified in table I. The truck, casters, and utensil rack shall show no evidence of breakage, parts separation, or permanent distortion when tested as specified in 4.5.1, 4.5.2, and 4.5.3. The trucks shall be towable with a force not exceeding 4 percent of the gross weight of the truck loaded to rated capacity when tested as specified in 4.5.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:27Z
Check the source to verify that this is the current version before use.

TABLE I. Shelf and truck capacities and dimensions

	Rated capacities (pounds minimum)		Shelf dimensions (inches ±1/2 inch)		Overall truck dimensions (inches ±1/2 inch)		
Type	Per truck	Per shelf	Length	Width	Length	Width	Height
I	800	200	59 1/2	29 1/2	60	30	62
II	1400	350	59 1/2	29 1/2	60	30	62
III	900	300	48	18	49	19	62

3.5.1 Type I truck.

3.5.1.1 Frame, type I. The type I truck frame shall be fabricated of four angles. The angles shall be assembled in an upright position to form the truck corners. The inside faces of the angles shall face inward.

* 3.5.1.2 Shelves, type I. The type I truck shall have four shelves. The second and third shelves shall be adjustable without the use of hand tools over a range of 38 equally spaced holes in the corner upright angles spaced over a total distance of 37 inches. Fillers or spacers may be used at the corners. The shelves shall be flat with the edges so formed as to comply with the sanitation and load requirements specified herein. The corner joints shall be welded. The top surface of each shelf shall have equally spaced slots, holes, or other type openings. The top surface may be corrugated or the openings may be dimpled to strengthen the shelf. The total range in area of the openings for each shelf shall be that represented by 5/8-inch diameter holes equally spaced on 2-inch centers over an area 24 by 54 inches (minimum space area) or by slots 28 inches long by 5/8 inch wide spaced laterally on 1 3/4-inch centers for a distance of 54 inches (maximum space area) except that the distance may be 46 inches minimum for the bottom shelf.

* 3.5.1.3 Casters, type I. Casters for the type I truck shall conform to type II, class B, wheel diameter 5 inches, style c, mounting P of FF-C-77. Casters shall have the necessary load rating to comply with the requirements and tests outlined herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:27Z
Check the source to verify that this is the current version before use.

3.5.2 Type II truck.

3.5.2.1 Frame, type II. The frame of the type II truck shall consist of four tubes in an upright position to form the truck corners and sixteen horizontally positioned tubes, with four tubes in the same plane for each shelf welded together to form the shelf supports.

3.5.2.2 Shelves, type II. The shelves for the type II truck shall be formed by welding tubes not more than 4 inches apart across and under the shelf supports. The top surface of the shelf supports shall be between 1/4 inch and 3/8 inch higher than the top surface of the shelf tubing. The lower shelf shall be 15 inches high as measured from the ground to the top surface of the shelf. The top surface of the upper shelf shall be a minimum of 60 inches as measured from the ground. The second and third shelves shall be equally spaced between the lower and upper shelves.

* 3.5.2.3 Casters, type II. Casters for the type II truck shall conform to type II, class C, wheel diameter 5 inches, style c, mounting N, P, or T of FF-C-77. Two casters on one long side of the truck shall be equipped with brakes. Casters shall have the necessary load rating to comply with the requirements and tests outlined herein.

3.5.3 Type III, truck.

3.5.3.1 Frame, type III. The frame for the type III truck shall be fabricated from tubing and shall consist of four corner uprights welded to the shelves specified in 3.5.3.2. Two of the corner uprights on one long side of the truck shall extend above the level of the top shelf a straight distance of 6 inches ± 1 inch and shall be bent toward the other long side of the truck at an angle of 45° ± 3° to form the end support of the utensil rack. The bent portion of the utensil rack shall be at a right angle to the long axis of the truck and shall be of sufficient length to extend over the top shelf to within one inch of the opposite side.

3.5.3.2 Shelves, type III. The type III truck shall have two shelves. Each shelf shall consist of four tubes welded between the corner uprights to support the shelf and hold the frame together. The top surface of each shelf shall be formed of not less than 9 strips, each not less than 2 inches in width, and equally spaced not more than 3 inches apart at right angles to the long axis of the truck. The ends of the strips shall be rounded over and welded to the two long shelf supports. The top surface of the bottom shelf shall be 8 inches ± 1 inch above the floor level. The top surface of the top shelf shall be 33 1/2 inches ± 1 inch above the floor level.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:27Z
Check the source to verify that this is the current version before use.

3.5.3.3 Utensil rack, type III. The utensil rack shall consist of two rods or flat bars welded between the utensil rack supports with ten utensil hooks fastened to each bar or rod in such a manner as to slide easily the full length of the bar or rod and not be removable. The utensil hooks shall be fabricated of rod and shall have a blunt point to accommodate utensils.

3.5.3.4 Casters, type III. Casters for type III trucks shall conform to type II, class B, wheel diameter 5 inch, mounting A, style c of FF-C-77. Two casters on diagonal corners shall have brakes. Casters shall have the necessary load rating to comply with the requirements and tests outlined herein.

3.6 Marking for identification. The trucks shall be marked on an external surface with the manufacturer's name, make/model, contract number and National Stock Number. Marking shall be applied in accordance with MIL-STD-130.

3.7 Finish. Finish shall comply with the applicable requirements of NSF Standard No. 2.

3.8 Workmanship. The trucks shall be manufactured in such a manner as to be uniform in quality and shall be complete, clean, and free of breaks, scratches, fabrication marks, sharp edges, sharp corners, burrs, slivers, deformities, and other defects that will adversely affect life, serviceability, or appearance. There shall be no visible evidence of rust or corrosion.

3.8.1 Welds. Welds shall be continuous, smooth, and free of pinholes, cracks, burnholes, incomplete fusion, and pits. All scale or flux shall be removed and all welds shall be ground to blend with adjoining surface.

3.8.2 Threaded fasteners. All threaded fasteners shall be drawn tight and shall be free of crossed or stripped threads. There shall be no missing nuts, bolts, or lockwashers.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the document where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:27Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 6.2), it shall be inspected in accordance with the quality assurance provisions of this document. Any failure to conform to the quality assurance provisions of this document shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, all inspections shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.4.1.1 In-process testing. The rubber bumper shall be tested for nonmarking in accordance with 4.4.1.1.1 and hardness in accordance with 4.4.1.1.2 to determine compliance with the hardness and nonmarking requirements of 3.5. The lot shall consist of all rubber bumpers offered for acceptance at one time. The sample unit shall be one rubber bumper. The inspection level shall be S-1 and the acceptable quality level (AQL) shall be 4.0, expressed in terms of defects per hundred units.

4.4.1.1.1 Nonmarking. The rubber bumper shall be drawn across a sheet of white bond paper with moderate pressure. The paper shall than be visibly examined for rubber marks. Marks that can be removed by rubbing with dry fingers shall not be considered as nonconformance.

4.4.1.1.2 Hardness. The rubber bumper shall be tested for hardness in accordance with method 3021 of FED-STD-601.

4.4.2 End item inspection. The lot shall consist of all trucks of one type offered for inspection at one time. The sample unit shall be one completely assembled truck.

* 4.4.2.1 Visual inspection. Inspection of the trucks shall be made for the defects listed in table II. The inspection level shall be II, and the AQL shall be 2.5 for major defects and 6.5 for total defects, expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:27Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of visual defects

Examine	Defect	Classification	
		Major	Minor
Finish	Dirty, scratches, fabrication marks not removed		201
	Rust, corrosion	101	
Construction and workmanship (general)	Not specified type	102	
	Part missing or not as specified	103	
	Burrs, sharp edges, sharp corners, slivers		202
	Deformities, breaks	104	
Casters	Not swivel type	105	
	Not removable	106	
Type I truck	Frame not fabricated of angles	107	
	Shelves not adjustable, not flat	108	
	Shelf edges not turned down and in	109	
	Shelves not fabricated of sheet steel	110	
	Shelves not perforated or slotted as specified	111	
	Corner joints of shelves not welded	112	
Type II truck	Frame not fabricated of tube	113	
	Shelves not fabricated of tube	114	
	Frame and shelves not welded into a single unit	115	
	Shelves not flat with outer tubes raised over shelf level		203
Type III truck	Frame not fabricated of tube	116	
	Shelf supports not fabricated of tube	117	
	Frame and shelves not welded together	118	
	Top surfaces of shelves not as specified	119	
	Shelf strips not bent over shelf supports or not welded to shelf supports	120	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:27Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of visual defects - Continued

Examine	Defect	Classification	
		Major	Minor
Type III truck (continued)	Utensil rack not as specified	121	
	Less than 10 hooks on each utensil rack rod or bar	122	
	Utensil hooks do not slide full length of the bar or rod or can be removed	123	
	Utensil hooks do not have blunt points		204
	Two casters on diagonal corners not equipped with brakes	124	
Welds	Not continuous, cracks, incomplete fusion, missing	125	
	Scale or flux not removed		205
	Pinholes, burnholes, pits		206
	Welds not ground to blend with adjoining surfaces	126	
Threaded fasteners	Missing	127	
	Incomplete (lockwasher or nut missing)		207
	Threads crossed or stripped		208
	Loose		209
Marking for identification	Missing, illegible, incomplete, incorrect		210

4.4.2.2 Dimensional inspection. Examination of the trucks shall be made for compliance with specified dimensions. Any dimension that is not within the specified tolerance shall be classified as a defect. The inspection level shall be S-2, and the AQL shall be 4.0, expressed in terms of defects per hundred units.

4.4.2.3 End item testing. When a first article is not required, the initial production item shall be tested as specified in 4.5.1 through 4.5.4. Any noncompliance with specified requirements shall be cause for rejection of the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:27Z
Check the source to verify that this is the current version before use.

4.4.3 Standards compliance. Proof of compliance with the requirements of 3.3 shall be submitted to the Government representative.

4.4.4 Packaging inspection. An examination shall be made for the defects in table III to determine that preservation, packing, and marking comply with the requirements of section 5. The lot shall be the number of containers offered for inspection at one time. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-3, and the AQL shall be 6.5, expressed in terms of defects per hundred units.

TABLE III. Packaging inspection

Examine	Defect
Markings (exterior container)	Omitted, incorrect, illegible, or of improper size, location, sequence, or method of application
Materials	Any component missing, damaged, or not as specified

4.5 Tests.

* 4.5.1 Static overload. While positioned on a hard level surface, the truck shall be loaded with a static load of not less than 1600 pounds for the type I truck, not less than 2800 pounds for the type II truck, and not less than 1600 pounds for the type III truck. The load shall be distributed equally on all four shelves and over the entire top surface of each shelf of the type I and II trucks. A load of 300 pounds shall be distributed over each shelf and 15 pounds suspended from each utensil hook of the type III truck. The load shall remain on the truck for a period of not less than 10 minutes. The load shall then be removed and the truck examined to determine compliance with 3.5. Any nonconformance with specified requirements shall constitute failure of this test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:27Z
Check the source to verify that this is the current version before use.

* 4.5.2 Obstacle test. The trucks shall be uniformly loaded with 800 pounds for type I, 1000 pounds for type II, and 900 pounds for type III. The loaded truck shall be made to pass over a 1/8-inch obstacle at a speed of not less than 3 feet per second a total of 5 times. The obstacle shall be 12 inches wide, have vertical faces, and be long enough to permit both casters to strike the obstacle at the same time. At the conclusion of the test, the load shall be removed and the truck and casters examined to determine compliance with 3.5. Any nonconformance with specified requirements shall constitute failure of this test.

4.5.3 Impact load. The truck loaded as in 4.5.2 shall be propelled into a hard rigid wall at a speed of not less than 2 miles per hour (mph) 6 times. Four collisions shall involve the wall and each corner bumper. Two collisions shall involve the wall and two corner bumpers at each end of the truck. The load shall then be removed and the truck and rubber bumpers examined to determine compliance with 3.5. Any nonconformance with specified requirements shall constitute failure of this test.

4.5.4 Rolling resistance. The trucks, after testing as specified in 4.5.1, 4.5.2, and 4.5.3, shall be loaded to the capacities shown in table I and towed, utilizing a tension dynamometer, over a smooth level surface at a speed of not less than 2 mph. After the truck has attained a speed of 2 mph, the tension dynamometer shall be observed over distance of not less than 100 feet. The maximum reading on the tension dynamometer registered over the 100-foot distance shall then be used to determine the force required to move the truck to determine compliance with the towing requirement of 3.5. Any nonconformance with specified requirements shall constitute failure of this test.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial, as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Type I.

5.1.1.1.1 Disassembly. Each type I truck shall be completely disassembled.

5.1.1.1.2 Assembly hardware and casters. Assembly hardware, such as nuts and bolts, shall be placed in a cotton cloth drawstring bag. Four casters and the bagged hardware shall be unit packed in the most compact manner in a

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:27Z
Check the source to verify that this is the current version before use.

snug-fitting fiberboard box conforming to style RSC, grade W6c or W6s of PPP-B-636. Closure and waterproofing shall be in accordance with the appendix of PPP-B-636. The maximum outside height of the box shall not exceed 3 1/2 inches.

5.1.1.1.3 Connecting and supporting components. Connecting and supporting components for one truck, such as gussets, angle fillers, and shelf support angles, shall be wire-tied by item in a compact bundle with minimum 0.072-inch diameter annealed wire.

5.1.1.2 Type II and type III. The casters shall be disassembled from each type II or type III truck and unit packed in a snug-fitting fiberboard box conforming to style RSC, grades W6c or W6s of PPP-B-636. Closure and waterproofing shall be in accordance with the appendix of PPP-B-636.

* 5.1.2 Commercial. Trucks shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or Commercial as specified (see 6.2).

5.2.1 Level A packing.

5.2.1.1 Type I trucks. Components of each type I truck, preserved as specified in 5.1, shall be compactly nested in a snug-fitting, cleated-plywood shipping container conforming to overseas type, style A or B of PPP-B-601. One shelf shall be placed in the crate with flanges down; another shelf, with flanges up, shall be placed on the first shelf. The casters, hardware, and connecting and supporting components shall be packed within the shelf, then blocked, braced, wired, and cushioned to prevent movement or damage while in transit. Cushioning material shall conform to type II, class B of PPP-C-843. The third shelf shall be placed with flanges down on the second shelf, and the fourth shelf shall be placed in the crate with the flanges up. The contents shall be anchored in accordance with MIL-STD-1186. Each shipping container shall be closed and strapped in accordance with the appendix of PPP-B-601.

* 5.2.1.2 Type II and type III trucks. Each type II or type III truck, preserved as specified in 5.1, shall be packed in a cleated-plywood shipping container as specified in 5.2.1.1. The unit packed casters shall be placed in an unused portion of the container. Contents shall be anchored as specified in 5.2.1.1. The container shall be closed and strapped as specified in 5.2.1.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:27Z
Check the source to verify that this is the current version before use.

5.2.2 Level B packing.

* 5.2.2.1 Type I trucks. Components of each type I truck, preserved as specified in 5.1, shall be packed as specified in 5.2.1.1, except that the container shall conform to type II, style B of MIL-C-52950 and cushioning material shall conform to type I or II, class B of PPP-C-843.

* 5.2.2.2 Type II and type III trucks. Each type II or type III truck, preserved as specified in 5.1, shall be packed as specified in 5.2.1.2, except that the container shall conform to type IV, style A of MIL-C-52950.

* 5.2.3 Commercial packing. Trucks, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Marking. In addition to any special marking required by the contract or purchase order, shipping containers shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

6. NOTES

6.1 Intended use. The trucks are intended for use in military hospitals and troop messes for transporting and storing clean and dry pots and pans.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. Type of truck required (see 1.2).
c. When a first article is required (see 3.1, 4.3, and 6.3).
d. Selection of the applicable levels of preservation and packing (see 5.1 and 5.2).

* 6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in all acquisition instruments regarding arrangements for inspection and approval of the first article.

* 6.4 Recycled material. The contractor is encouraged to use recycled material when practical, provided that it meets the requirements of this document (see 3.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:27Z
Check the source to verify that this is the current version before use.

6.5 Changes from previous issue. The margins of this document are marked with an asterisk (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this doucment based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Army - GL
Air Force - 99

Review activities:

Army - MD, ME, TS
Air Force - 84
DSA-GS

Preparing activity:

Army - GL

Project No. 3920-0168

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:27Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY
US Army Natick Research and Development Center
Natick, Massachusetts 01760

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300
STRNC-ES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research and Development Center
ATTN: STRNC-ES
Natick, MA 01760

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:27Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-T-43047D	TRUCKS, HAND, SHELF, 2 and 4 SHELVES

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
	☐ USER
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 1426 82 MAR PREVIOUS EDITION IS OBSOLETE.

NATICK OP T Apr 84

Source: https://asset.library.wisc.edu/... 2023-10-21T20:27Z
Check the source to verify that this is the current version before use.