GGG-D-00643a(GSA-FSS)
May 2, 1968
SUPERSEDING
Int. Fed. Spec. GGG-D-00643(GSA-FSS)
May 13, 1964

INTERIM FEDERAL SPECIFICATION

DRIFTPIN (DOUBLE TAPER)

This Interim Federal Specification was developed by Standardization Division, Federal Supply Service, General Services Administration, Washington, D. C. 20405, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers driftpins tapered on each end for use in aligning holes in steel plates and forms prior to bolting or riveting.

1.1.1 Federal specification coverage. Federal specifications do not include all varieties of the commodity indicated by the title of the specification, but are intended to cover only those generally used by the Federal Government.

1.2 Classification.

1.2.1 Type and classes. The driftpins covered by this specification shall be of one type and the following classes as specified (see 6.1):

Type I. - Double tapered.
Class 1. - Equal length taper.
Class 2. - Unequal length taper.

2. APPLICABLE DOCUMENTS

2.1 The following specifications and standards, of the issues in effect on date of invitation for bids, or request for proposal, form a part of this specification:

Federal Standards:
Fed. Std. No. 123 - Marking for Domestic Shipment (Civilian Agencies).
Fed. Test Method Std. No. 151 - Metals; Test Methods.

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, D. C. 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D. C., Atlanta, Chicago, Kansas City, Mo., Denver, Fort Worth, San Francisco, Los Angeles, and Auburn, Wash.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

FSC 5120

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:41Z
Check the source to verify that this is the current version before use.

Military Specification:
MIL-H-15424 - Hand Tools, Packaging of.

Military Standard:
MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Material. The driftpins shall be of steel, heat treated to show a hardness of not less than 32 nor more than 45 on the Rockwell C scale when tested as specified in 4.3.

3.2 Type I, class 1, equal taper. Type I, class 1 driftpin shall be of the dimensions specified in table I.

TABLE I. Type I, class 1, equal taper

Overall length ± 1/2	Body diameter ± 1/16	Length of taper, both ends ± 1/2	Point diameter both ends ± 0.020
Inches	Inch	Inches	Inch
6-1/2	9/16	2	0.187

3.3 Type I, class 2, unequal taper. Type I, class 2 driftpin shall be of the dimensions specified in table II.

TABLE II. Type I, class 2, unequal taper

Overall length ± 1/2	Body diameter ± 1/16	Long taper		Short taper	
		Length ± 1/2	Point diameter ± 0.020	Length ± 1/2	Point diameter ± 0.020
Inches	Inch	Inches	Inch	Inches	Inch
6-1/2	9/16	3-1/2	0.250	1	0.375
7-1/2	13/16	3-1/2	.375	1	.500

3.4 Finish. The body of the driftpin shall be free from fins, burrs, or scale. Surface finish to be manufacturer's standard practice.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:41Z
Check the source to verify that this is the current version before use.

4.1.1 Inspection of materials and components. In accordance with 4.1, the supplier is responsible for insuring that materials and components used were manufactured, tested and inspected in accordance with the requirements of referenced subsidiary specifications and standards to the extent specified herein, or, if none, in accordance with this specification.

4.2 Sampling procedures. Sampling procedures shall be in accordance with MIL-STD-105. Data for sampling shall be as stated in table III.

TABLE III. Sampling data

Category	Sample unit	Inspection level	Acceptable quality level	AQL expressed in terms of	Reference
Visual examination	1 each	II	4.0	Defects per hundred units	4.3.1
Dimensional examination	1 each	S-3	2.5	Defects per hundred units	4.3.2
Testing	1 each	S-3	2.5	Defects per hundred units	4.4
Preparation for delivery	1 container	S-4	4.0	Defects per hundred units	4.5

4.3 Examination.

4.3.1 Visual examination. Each sample unit shall be examined for any nonconformance in design, material and finish.

4.3.2 Dimensional examination. Each sample unit shall be examined for any nonconformance with dimensional requirements.

4.4 Hardness test. Each sample driftpin shall be tested for hardness in accordance with method 2A3.1 of Fed. Test Method Std. No. 151 to determine compliance with 3.1.

4.5 Inspection of preparation for delivery. Preservation, packaging and packing shall be inspected in accordance with MIL-H-15424.

5. PREPARATION FOR DELIVERY

5.1 Preservation, packaging, and packing. Unless otherwise specified (see 6.1), the driftpins shall be preserved, packaged, and packed in accordance with MIL-H-15424. The level of preservation and packaging shall be A or C and the level of packing A, B, or C, as specified (see 6.1).

5.2 Marking.

5.2.1 Civil agencies. In addition to marking required by the contract or order, the unit packages and shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.2.2 Military agencies. In addition to markings required by the contract or order, the unit packages and shipping containers shall be marked in accordance with MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:41Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Ordering data. Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Class and size required (see 1.2.1).
(c) Selection of applicable level of preservation, packaging, and packing (see 5.1).
(d) Marking required (see 5.2).

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:41Z
Check the source to verify that this is the current version before use.