GGG-F-626
Interim Amendment #1 (DOD)
September 17, 1963

INTERIM AMENDMENT
TO
FEDERAL SPECIFICATION
FORK, STONE, HAND, D-HANDLE

This Interim Amendment was developed by the U. S. Army Natick Laboratories (GL), Natick, Massachusetts, based on currently available technical information. This Interim Amendment has been approved by the Department of Defense and is mandatory for use by the Departments of the Army, the Navy, and the Air Force. It is recommended that Federal Agencies use it in procurement. The General Services Administration has authorized the use of this Interim Amendment as a valid exception to Federal Specification GGG-F-626, dated October 25, 1954.

Page 1, section 2—Delete in its entirety and substitute:

"2. APPLICABLE SPECIFICATIONS AND STANDARDS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

FEDERAL SPECIFICATION

NN-H-81—Handles, Ash

FEDERAL STANDARDS

Fed. Std. No. 102—Preservation, Packaging and Packing Levels

Fed. Std. No. 123—Marking for Domestic Shipment (Civilian Agencies)

Fed. Test Method Std. No. 151—Metals; Test Methods

(Activities outside the Federal Government may obtain copies of Federal Specifications and Standards as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, D. C.)

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D. C., Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, and Auburn, Wash.)

(Federal Government activities may obtain copies of Federal Specifications and Standards and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

MILITARY SPECIFICATION

MIL-H-15424—Hand Tools; Packaging of

MILITARY STANDARDS

MIL-STD-105 — Sampling Procedures and Tables For Inspection by Attributes

MIL-STD-129 — Marking for Shipment and Storage

(Copies of Military specifications and standards required by suppliers in connection with specific procurement functions should be obtained from the procuring agency or as directed by the contracting officer.)"

Page 2, Add

"3.3.1 *Strength.* The forks shall show no fracture, breakage, or permanent deflection exceeding 1 inch when tested as specified in 4.3.2."

Pages 2 and 3, paragraphs 4.1 through 4.5—Delete and substitute:

"4.1 **Responsibility for inspection.** Unless otherwise specified in the contract or pur-

FSC 5120

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:41Z
Check the source to verify that this is the current version before use.

chase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 **Sampling for inspection and acceptance.** Sampling for inspection and acceptance shall be performed in accordance with the provisions set forth in Standard MIL–STD–105, except where otherwise indicated. The inspection lot shall be all forks of one size offered for acceptance at one time.

4.2.1 *Inspection of components and materials.* In accordance with 4.1, the supplier is responsible for insuring that components and materials used are manufactured, tested, and inspected in accordance with the requirements and standards to the extent specified, or, if none, in accordance with this specification.

4.2.2 *End product inspection.* The sample unit shall be one completely fabricated fork.

4.2.2.1 *Visual examination.* Examination of the end item shall be made in accordance with the table of defects set forth below. The inspection level shall be L5 with an acceptable quality level (AQL) of 2.5, expressed in terms of defects per hundred units.

Examine	*Defect*
Design	Any characteristic not in compliance with specified requirements.
Construction and workmanship, general.	Any part missing, or not specified type or size.
	Any part fractured, split, punctured, dented, bowed, sprung, malformed, decayed, or otherwise impaired.
Finish	Not finished as specified.
	Finish wet or tacky.
	Annual rings concealed.
	Color stain on wooded handles not fast (discolors user's hands).
Marking	Missing, incomplete, illegible, or not permanent.

4.2.2.2 *Dimensional examination.* Forks shall be examined for dimensional defects. Any dimension not within specified requirements shall be classified a defect. The inspection level shall be L5 with an AQL of 2.5, expressed in terms of defects per hundred units.

4.2.2.3 End product testing. The forks shall be tested as specified in 4.3.1 and 4.3.2 using an inspection level of L5 with an AQL of 2.5, expressed in terms of defects per hundred units.

4.2.3 *Examination of preparation for delivery.* Inspection shall be made to determine compliance with preparation for delivery requirements specified in section 5.

4.3 **Tests.**

4.3.1 *Hardness.* The hardness of alternate tines shall be measured at one point midway in the length of the tine to determine compliance with 3.4. Determinations shall be made in accordance with Method 243.1 of Federal Test Method Standard No. 151.

4.3.2 *Fork strength.* The fork shall be tested as follows to determine compliance with 3.3.1: The tines shall be clamped as illustrated in figure 1 with the longitudinal axis of the handle approximately 45 degrees to a horizontal plane. A measurement of the vertical distance "A" shall be taken. A weight of 150 pounds shall be attached to the handgrip and allowed to remain for not less than 120 nor more than 125 seconds, after which the weight shall be removed and distance "A" remeasured. The difference in distance "A" measurements is the amount of set or bend."

Pages 3 and 4, section 5—Delete in its entirety and substitute:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:41Z
Check the source to verify that this is the current version before use.

"5. PREPARATION FOR DELIVERY

(Federal Standard No. 102 shall be referred to for definitions and application of the various levels of preservation, packaging and packing for civilian agency procurements.)

5.1 Levels A, B, and C. Preservation, packaging and packing shall be in accordance with the applicable requirements for the level specified in Specification MIL–H– 15424 (see 6.2).

5.2 Marking.

5.2.1 *Civilian agencies.* In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with Federal Standard No. 123.

5.2.3 *Military requirements.* In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with Standard MIL–STD 129."

Page 4, paragraph 6.1, 4th line—Delete (see 2.2, 5.1, 5.2, and 5.3).

Page 4, paragraph 6.1—Delete subparagraph (c) and substitute "(c) Selection of applicable levels of preservation, packaging and packing (see 5.1)".

Page 4, section 7—Delete in its entirety.

Military Custodians:

Army—GL

Air Force—MOA

Project No. 5120–0399

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:41Z
Check the source to verify that this is the current version before use.