FEDERAL SPECIFICATION

OILER, HAND

This Interim Amendment was developed by the Standardization Division, Federal Supply Service, General Services Administration, Washington, D. C., 20407, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above. The General Services Administration has authorized Federal agencies to use this Interim Amendment as a valid exception to Federal Specification GGG-O-591, dated June 5, 1962

Page 1, paragraph 1.2.1, Types, classes, and styles: Add to paragraph 1.2.1 under Type II - Pump, Class A - With handle and lever operated pump, the following two styles:

"Style 1 - Rigid spout.
Style 4 - Flexible spout."

Page 6, paragraph 3.10.4: Delete and substitute the following paragraphs:

"3.10.4 Spouts: Unless otherwise indicated in the invitation for bids (see 1.2 and 6.2), one spout of the style specified in the invitation for bids shall be furnished with each oiler.

3.10.4.1 Style 1, rigid spout.- Style 1 rigid spouts shall be 6, 7, 9, 12, or 15 inches long as specified (see 6.2). If no spout length is specified, the 6-inch spout shall be furnished. Rigid spouts shall be seamless or have a welded, silver soldered or brazed, leak-proof seam and shall be not less than 0.017 inch thick. Tin-lead solders will not be acceptable. The spout shall be readily detachable and joined to the pump unit by bayonet-type joint, a threaded joint, or other suitable connection. Spouts shall be either straight, bent at the vent end, or angled at the base and bent at the vent end, as specified (see 6.2). The bend or the angle and bend shall be in the opposite direction from the handle for offset filling.

3.10.4.2 Style 4 flexible spout.- Style 4 flexible spouts shall be 7, 13, 15, or 18 inches long, as specified (see 6.2). If no spout length is specified, the 7 inch length shall be furnished. Flexible spouts shall be detachable with a threaded bushing or fitting at the base end for connecting to the adapter in the discharge end cap of the oiler. The spout fittings shall be standard thread types. The flexible steel tubing of the spout shall be asbestos lined flexible steel tube with brass bushings or fittings, silver-soldered or brazed. Tin-lead solders will not be acceptable. The discharge end spout bushing shall be either a tapered nozzle, a straight ferrule, or a threaded fitting type for attaching hollow wire, needle, or brush tip extensions. The flexible spout shall be suitable in all respects for reaching locations that would otherwise be inaccessible (see figure 8). The outside diameter of tubing shall be not less than 1/4-inch and the inside diameter shall be not less than 3/16 inch."

Page 15, paragraph 4.1: Delete and substitute:

"4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements."

FSC 4930

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:41Z
Check the source to verify that this is the current version before use.