MILITARY SPECIFICATION

PRESS, REASSEMBLY, WEAPONS TRAINER A/E27K-1 AND ASSOCIATED ADAPTERS

1. SCOPE. This specification establishes the requirements for one type of weapon trainer reassembly press designated as the A/E27K-1, hereafter referred to as the press, and nine adapters designated as the ADK-300/E27K-1, ADK-301/E27K-1, ADK-302/E27K-1, ADK-303/E27K-1, ADK-304/E27K-1, ADK-305/E27K-1, ADK-306/E27K-1, ADK-308/E27K-1, ADK-309/E27K-1, ADK-311/E27K-1, and ADK-312/E27K-1.

2. APPLICABLE DOCUMENTS. The following documents of the issue in effect on the date of invitation for bids, form a part of this specification to the extent specified herein:

SPECIFICATIONS

Military

MIL-D-1000	Drawings, Engineering and Associated Lists

STANDARDS

Military

MIL-STD-129	Marking for Shipment and Storage
MIL-STD-130	Identification Marking of U.S. Military Property
MIL-STD-810	Environmental Test Methods for Aerospace and Ground Equipment
MIL-STD-831	Test Reports, Preparation Of

DRAWINGS

Air Force

67J13280	Press, Reassembly, Weapons Trainer A/E27K-1
67E13285	Adapter, Press ADK-300/E27K-1
67D13282	Adapter, Press ADK-301/E27K-1
67D13284	Adapter, Spacer, Press ADK-302/E27K-1
67E13283	Adapter, Press ADK-303/E27K-1
67E13286	Adapter, Press ADK-304/E27K-1
67D13281	Adapter, Press ADK-305/E27K-1
67D13295	Adapter, Spacer, Press ADK-306/E27K-1
67E13287	Adapter, Press ADK-308/E27K-1

Source: https://assist.dla.mil -- Downloaded: 202640-21T15:36Z
Check the source to verify that this is the current version before use.

67E13277	Adapter, Spacer, Press ADK-309/E27K-1
67D13313	Adapter, Spacer, Press ADK-311/E27K-1
67D13314	Adapter, Spacer, Press ADK-312/E27K-1

(Copies of documents required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Preproduction. This specification makes provisions for preproduction testing.

3.2 Design and Construction. The press and adapters shall be designed and constructed in conformance to: 67J13280, 67E13277, 67D13281, 67D13282, 67E13283, 67D13284, 67E13285, 67E13286, 67D13295, 67D13313, 67D13314 and subsidiary drawings.

3.2.1 Interchangeability. Parts functionally and dimensionally interchangeable shall be identified by the same part number. When parts are not interchangeable, the criteria listed in MIL-D-1000 shall apply and new drawings shall be prepared as necessary.

3.3 Performance

3.3.1 Functional. Satisfactory functional performance of the press and adapters shall be to provide pressure and critical alignment in the reassembling of AEC Type 3B and 3C Trainers.

3.4 Environmental Requirements. The press shall operate satisfactorily during or after exposure to all the following environments. (See Test Methods.)

a. High temperature to 160°F.

b. Low temperature to -80°F.

c. Salt fog incident to storage, transportation, or service use near a large body of salt water.

d. Vibration likely to be encountered in transportation.

e. Shock which is likely to be encountered during transportation, handling and loading.

f. Sand and dust likely to be encountered during transportation, handling and storage.

3.5 Identification of Product. The press, adapters, and parts shall be marked for identification in accordance with MIL-STD-130.

Source: https://assist.dla.mil -- Downloaded: 202640-21T15:36Z
Check the source to verify that this is the current version before use.

3.6 Workmanship. The press and adapters shall be fabricated and finished in a manner that will ensure that the criteria of appearance, fit, and adherence to specified tolerances are observed. These criteria shall apply to both functional and nonfunctional parts. Particular attention shall be given to neatness and thoroughness of marking of parts and assemblies, painting, welding, threaded connectors, and freedom of parts from burrs and sharp edges which might mar associated equipment or cause injury to operating personnel.

4. QUALITY ASSURANCE PROVISIONS

4.1 Classification of Tests. The inspection and testing of the press and adapters shall be classified as follows:

a. Preproduction Tests

b. Acceptance Tests

4.2 Preproduction Testing

4.2.1 Preproduction Test Samples. The preproduction test units shall be representative of the production press, and adapters. They shall be tested at a laboratory designated by the procuring activity or at the contractor's facility if so stated in the contract.

4.2.2 Preproduction Test Reports. In the event that preproduction testing is conducted at the contractor's facility, the contractor shall prepare a preproduction test report in accordance with MIL-STD-831 and furnish three (3) complete copies to the procuring activity.

4.2.3 Preproduction Test. Preproduction test shall consist of all tests described in "Test Methods."

4.3 Acceptance Tests. Acceptance tests shall consist of the following invididual tests:

a. Examination of product

b. Conformance to drawings

c. Functional tests

4.4 Test Methods

4.4.1 Examination of Product. Each press and adapter shall be given a complete visual examination to determine compliance with all requirements of this specification for which no tests are specified including materials and workmanship. Failure to satisfy these requirements shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 202640-21T15:36Z
Check the source to verify that this is the currentversion before use.

4.4.2 Conformance to Drawings. Each press and adapter shall be inspected for strict conformance to engineering drawings, subsidiary drawings, specifications and standards referenced therein. Failure to conform to these criteria shall be cause for rejection.

4.4.3 Functional Tests

4.4.3.1 Fit Test. The press and each adapter shall be subjected to a fit test to assure that the Adapters, ADK-300/E27K-1, ADK-301/E27K-1, ADK-303/E27K-1, ADK-304/E27K-1, ADK-305/E27K-1, ADK-308/E27K-1, and Adapters, Spacer ADK-302/E27K-1, ADK-306/E27K-1, ADK-309/E27K-1, ADK-311/E27K-1, and ADK-312/E27K-1 can be assembled to the press.

4.4.3.2 Pressure Test (Press and ADK-302/E27K-1). The press shall be subjected to a pressure test with an adapter ring and the Press Spacer Adapter ADK-302/E27K-1 attached to the frame. The piston shall be elevated until 36,000 pounds force is being transferred to the ADK-302/E27K-1. Failure of the press or adapter, or any of the attached pieces of functional and nonfunctional parts will be cause for rejection under this pressure test.

4.4.4 Environmental Tests. The press shall be subjected to the following environmental tests per MIL-STD-810 in the sequence listed:

TEST	METHOD	PROCEDURE
High Temperature	501.1	I
Low Temperature	502.1	I
Temperature Shock	503.1	I
Humidity	507.1	I
Salt Fog	509.1	I
Sand and Dust	510.1	I

Where the test procedures require operation of the equipment, the functional tests of this specification shall apply. Failure to satisfy the requirements of the functional tests during or after, as applicable, subjection to the environmental tests shall be considered as failure of the press to pass the environmental tests and cause for rejection.

5. PREPARATION FOR DELIVERY

5.1 The press and adapters shall be preserved and packaged as specified by the procuring activity.

5.2 Marking. Interior and exterior containers shall be marked in accordance with MIL-STD-129. The nomenclature shall be:

PRESS, REASSEMBLY, WEAPONS TRAINER A/E27K-1
ADAPTER, PRESS ADK-300/E27K-1
ADAPTER, PRESS ADK-301/E27K-1

Source: https://assist.dla.mil -- Downloaded: 202640-21T15:36Z
Check the source to verify that this is the current version before use.

ADAPTER, SPACER, PRESS ADK-302/E27K-1
ADAPTER, PRESS ADK-303/E27K-1
ADAPTER, PRESS ADK-304/E27K-1
ADAPTER, PRESS ADK-305/E27K-1
ADAPTER, SPACER, PRESS ADK-306/E27K-1
ADAPTER, PRESS ADK-308/E27K-1
ADAPTER, SPACER, PRESS ADK-309/E27K-1
ADAPTER, SPACER, PRESS ADK-311/E27K-1
ADAPTER, SPACER, PRESS ADK-312/E27K-1

6. NOTES

6.1 Intended Use. The Press, Reassembly, Weapons Trainer A/E27K-1 and the Associated Adapters are intended for use to apply pressure and critical alignment in the reassembly of AEC Type 3B and 3C training weapons.

6.2 Government Loaned Property Option. In the event Adapter(s) or Press need to be procured separately, the contract document should require the Adapter(s), or Press, as appropriate, be furnished as Government Loaned Property for the purpose of testing the press or adapters.

6.3 First Article Test Samples. It is expected that the contract or purchase order will specify a minimum of one unit representative of the press and a set of adapters will be required as first articles and that these first articles will be subjected to the preproduction tests to determine compliance with the requirements of this specification. It is expected that the contract or purchase order shall specify the point of inspection for these tests.

6.4 Production Delivery. No production item should be delivered prior to approval of the preproduction samples.

6.5 Ordering Data. Procurement documents should specify the following:

a. Title, number and date of this specification.

b. Levels of preservation, packaging and packing.

6.6 Definitions

a. Preproduction Tests. Preproduction tests are those tests performed prior to production on representative samples of the production equipment to demonstrate that the equipment meets the requirements of this specification.

b. Acceptance Tests. Acceptance tests are those tests accomplished on representative samples of equipment submitted for acceptance under

Source: https://assist.dla.mil -- Downloaded: 202640-21T15:36Z
Check the source to verify that this is the current version before use.

a contract to determine conformance to the requirements of this specification, and to determine that the equipment is equivalent in performance and construction to the approved preproduction samples.

Custodian
Air Force - 15

Preparing Activity
Air Force - 15

WLIR
EAC/to

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:36Z
Check the source to verify that this is the current version before use.