MIL-S-38975(USAF)
AMENDMENT 4
18 November 1971
Superseding
AMENDMENT 3
18 September 1970

MILITARY SPECIFICATION

SIMULATOR, SELECTOR, BOMB-ROCKET DISPENSER
SMU-75/A

This amendment forms a part of Military
Specification MIL-S-38975(USAF), dated 1 February 1968,
and is mandatory for use by the USAF

Page 7, 8, 9, Table I. Delete and substitute attached Table I.

Page 10, paragraph 4.5.4.4, line 2. Add: "Figure 516-2 (a) and (c)" at the end of the first sentence.

Page 10, paragraph 4.5.4.5. Delete and substitute: "Vibration testing of the simulator shall be performed in accordance with MIL-STD-810, Equipment Class 1, Mounting Method A, Test Curve F of Figure 514-1, except that Curve F should be extended to 2000 cps and time schedule II of Table 514-11 should be used in place of time schedule I. The unit must satisfy the requirements of the functional test during cycling and once during each resonance."

Page 10, paragraph 4.5.5.a. Delete and substitute: "a. Vibration shall be applied to the axis parallel to the mounting screws - one cycle 20 to 2000 hz using 0.036 inch double amplitude or 20g limits (the less of the two) and sweeping at one octave/minute repeated once per hour of the test."

Custodian
Air Force - 15

SEW
EAC/ne

Preparing Activity
Air Force - 15

Project No. 1190-F-001

FSC 1190

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:35Z
Check the source to verify that this is the current version before use.