INCH POUND

MIL-S-38975(USAF)
AMENDMENT 5
31 AUG 1991
SUPERSEDING
AMENDMENT 4
18 NOV 1971

MILITARY SPECIFICATION

SIMULATOR, SELECTOR, BOMB-ROCKET DISPENSER
SMU-75/A

This amendment forms a part of Military Specification MIL-S-38975(USAF), dated 18 November 1971, and is approved for use within the Department of the Air Force and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2, Under Specifications Military delete and substitute:

delete:	"MIL-D-1000	Drawings, Engineering and Associated Lists
	MIL-I-8500	Interchangeability and Replaceability, Physical, of Component Parts for Aircraft
	MIL-E-17555	Electronic and Electrical Equipment and Associated Repair Parts, Preparation for Delivery Of"
substitute:	"DOD-D-1000	Drawings, Engineering and Associated Lists"
	MIL-I-8500	Interchangeability and Replaceability of Component Parts for Aerospace Vehicles
	MIL-E-17555	Electronic and Electrical Equipment Accessories, and Provisioned Items (Repair Parts): Packaging Of"

DISTRIBUTION STATEMENT A. Approved for public Release; distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 202640-21T15:35Z
Check the source to verify that this is the currentversion before use.

2, Under Standards Military delete and substitute:

delete:	"MIL-STD-16	Electric and Electronic Reference Designations
	MIL-STD-810	Environmental Test Methods for Aerospace and Ground Equipment"
substitute:	"MIL-STD-810	Environmental Test Methods and Engineering Guidelines"

PAGE 2

2.2, Add the following paragraph:

"2.2 Non-Government publications. The following document forms a part of this document to the extend specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN NATIONAL STANDARDS INSTITUTE (ANSI)

ANSI Y32.16	Electrical and Electronics Parts and Equipments, Reference Designations For (DOD adopted)

(Application for copies should be addressed to the American National Standards Institute (ANSI), 1430 Broadway, New York, NY 10018

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)"

3.2.1, Line 3: delete "MIL-D-1000" and substitute "DOD-D-1000"

PAGE 3

3.7, Line 2: delete "MIL-STD-16" and substitute "ANSI Y32.16"

PAGE 7, 8, 9

Page 7, 8, 9, TABLE I. Delete and substitute attached Table I.

Source: https://assist.dla.mil -- Downloaded: 202610-21T15:35Z
Check the source to verify that this is the current version before use.

TABLE I

ACCEPTANCE TESTS		
TESTER SWITCHES	TEST I TESTER LIGHTS	SIMULATOR SWITCHES
All Switches "Off" Set Simulator Switches Power "On" Safe "On" Observe Lights	A - Off or On but OFF after 20 Sec. S - On or Off for 0-20 Sec Then On NP - On WL - Off or ON for 0-20 Sec Then Off	S1 - AIR S2 - Old
All Switches "Off" Set Simulator Switches Power "On" G/A-"A" Observe Lights	TEST II A - Off 3 - 20 Sec Then On S - On 3 - 20 Sec Then Off NP - On WL - On 3 - 20 Sec Then Off	S1 - Air S2 - Old
All Switches "Off" Set Simulator Switches Power "On" Safe "On" Observe Lights	TEST III A - On 3 to 20 Sec Then Off S - Off 3 to 20 Sec Then On NP - On WL - On 3 to 20 Sec Then Off	S1 - Air S2 - Old

Source: https://assist.dla.mil -- Downloaded: 202610-21T15:35Z
Check the source to verify that this is the current version before use.

TABLE I

ACCEPTANCE TESTS		
	TEST IV	
TESTER SWITCHES	TESTER LIGHTS	SIMULATOR SWITCHES
All Switches "Off" Set Simulator Switches		S1 - GND S2 - Old
Power "On" G/A to "A" Observe Lights	A - Off S - On NP - On WL - On	Wait 20 Sec then proceed to Test V
	TEST V	
All Switches "Off" Set Simulator Switches		S1 - GND S2 - Old
Power "On" G/A to "G" Observe Lights	A - Off 3 to 20 Sec On S - On 3 to 20 Sec Off NP - On WL - On 3 to 20 Sec Off	
	TEST VI	
All Switches "Off" Set Simulator Switches		S1 - GND S2 - Old
Power "On" Safe "On" Observe Lights	A - On 3 to 20 Sec Off S - Off 3 to 20 Sec On NP - On WL - On 3 to 20 Sec Off	

Source: https://assist.dla.mil -- Downloaded: 202610-21T15:35Z
Check the source to verify that this is the current version before use.

TABLE I

ACCEPTANCE TESTS		
	TEST VII	
TESTER SWITCHES	TESTER LIGHTS	SIMULATOR SWITCHES
All Switches "Off" Set Simulator Switches Power "On" G/A to "G" Observe Lights	A - Off S - On NP - On WL - On	S1 - AIR S2 - Old Wait 20 Sec then proceed to Test V
	TEST VIII	
All Switches "Off" Set Simulator Switches Power "On" G/A - "A" Observe Lights	A - Off 3 to 20 Sec On S - On 3 to 20 Sec Off NP - On WL - Flash On, Off, On, Off	S1 - G/A S2 - New
	TEST IX	
All Switches "Off" Set Simulator Switches Power "On" Fire Signal "On" Observe Lights	A - Off after 1/2 sec NP - Off after 1/2 sec WL - Off Note: All lights turn off 1/2 sec after fire switch is closed	S1 - G/A S2 - NEW

Source: https://assist.dla.mil -- Downloaded: 202610-21T15:35Z
Check the source to verify that this is the current version before use.

TABLE I

ACCEPTANCE TESTS		
	TEST X	
TESTER SWITCHES	TESTER LIGHTS	SIMULATOR SWITCHES
All Switches "Off" Set Simulator Switches Power "On" Safe "On" Observe Lights	 A - Off S - On NP - On WL - Off	 S1 - G/A S2 - New
	TEST XI	
All Switches "Off" Set Simulator Switches Power "On" Rockets "On" Observe Lights	 A - Off S - Off After Rockets Switch Initiated NP- Off After Rockets Switch Initiated WL - Off	 S1 - G/A S2 - New

NOTE: Key to Simulator Switches
1. Old - stands for old design or type weapon.
2. New - stands for new design or type weapon.
3. G/A - stands for ground or air.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:35Z
Check the source to verify that this is the current version before use.

4.5.4.4, line 2. Add: "Figure 516-2 (a) and (c)" at the end of the first sentence.

4.5.4.5, Delete and substitute:

"Vibration testing of the simulator shall be performed in accordance with MIL-STD-810, Equipment Class 1, Mounting Method A, Test Curve F of Figure 514-1, except that Curve F should be extended to 2000cps and time schedule II of Table 514-11 should be used in place of time schedule I. The unit must satisfy the requirements of the functional test during cycling and once during each resonance."

4.5.5.a., Delete and substitute:

"Vibration shall be applied to the axis parallel to the mounting screws - one cycle 20 to 2000hz using 0.036 inch double amplitude or 20g limits (the less of the two) and sweeping at one octave/minute repeated once per hour of the test."

Preparing Activity
Air Force - 79

Custodian:
Air Force - 79

Reviewer:
Air Force - 15

(Project 1190-F030)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:35Z
Check the source to verify that this is the current version before use.