MILITARY SPECIFICATION

TRUCK, HAND, BOMB MHU-67/E

1. SCOPE

1.1 Scope. This specification covers one type of equipment designated as Truck, Hand, Bomb MHU-67/E, hereafter referred to as the hand truck.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on the date of invitation to bid, forms a part of this specification to the extent specified herein:

SPECIFICATIONS

Federal

PPP-C-650	Crates, Wood, Open and Covered

Military

MIL-P-116	Preservation, Methods Of
MIL-M-8090	Mobility Requirements, Ground Support Equipment, General Specification For
MIL-A-8421	Air Transportability Requirements, General Specification For
MIL-D-70327	Drawings, Engineering and Associated Lists

STANDARDS

Military

MIL-STD-129	Marking for Shipment and Storage
MIL-STD-130	Identification Marking of U.S. Military Property
MIL-STD-810	Environmental Test Methods for Aerospace and Ground Equipment
MIL-STD-831	Test Reports, Preparation Of

FSC 1190

Source: https://assist.dla.mil -- Downloaded: 202610-21T15:33Z
Check the source to verify that this is the current version before use.

MIL-STD-1186	Cushioning, Anchoring, Bracing, Blocking, and waterproofing; with appropriate test methods.

DRAWINGS

Air Force

64J14400	Truck, Hand, Bomb MHU-67/E
64J14425	Hand Truck Assembly
64D14428	Adapter Assembly
64J14430	Cradle Assembly

PUBLICATIONS

(Copies of documents required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Preproduction. This specification makes provision for preproduction testing.

3.2 Components. The Truck, Hand, Bomb MHU-67/E shall consist of one hand truck assembly, one adapter assembly, and one cradle assembly.

3.3 Construction

3.3.1 The hand truck shall be constructed in conformance with drawing 64J14400 and subsidiary drawings.

3.4 Performance

3.4.1 Functional. Satisfactory functional performance of the hand truck shall be to accept and secure a Bomb, Loading Practice BDU-32/E during storage, transportation, and loading operations.

3.4.2 Maneuverability

3.4.2.1 Mobility. The loaded hand truck shall be capable of Type I, Group C, Class 1 Mobility as specified in MIL-M-8090.

Source: https://assist.dla.mil -- Downloaded: 20260-21T15:33Z
Check the source to verify that this is the current version before use.

3.4.2.2 Air Transportability. The loaded hand truck shall be air transportable as specified in MIL-A-8421.

3.4.3 Environmental Requirements. The hand truck shall be capable of satisfactory performance during or after, as applicable, subjection to the following environmental conditions:

a. High temperatures to 160°F.

b. Low temperatures to -80°F.

c. Salt fog incident to storage, transportation, or service use near a large body of salt water.

d. Vibration likely to be encountered in transportation.

e. Shock which is likely to be encountered during transportation, handling and loading.

3.5 Interchangeability. Parts functionally and dimensionally interchangeable shall be identified by the same part number. When parts are not interchangeable, the criteria in MIL-D-70327 shall apply; and new drawings shall be prepared as required.

3.6 Finish. The parts shall be finished in accordance with the drawings.

3.7 Identification of Product. Equipment, assemblies, and parts shall be marked for identification in accordance with Standard MIL-STD-130.

3.8 Workmanship. The hand truck shall be fabricated and finished in a manner that will ensure that the criteria of appearance, fit and adherence to specified tolerances are observed. These criteria shall apply to all accessories and to all non-functional parts. Particular attention shall be given to neatness and thoroughness of marking of parts and assemblies, plating, painting, machine screw assemblage, welding, and freedom of parts from burrs and sharp edges which might mar associated equipment or cause injury to operating personnel.

4. QUALITY ASSURANCE PROVISIONS

4.1 Classification of Test. Inspection and testing of the hand truck shall be classified as follows:

a. Preproduction Tests

b. Acceptance Tests

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:33Z
Check the source to verify that this is the current version before use.

4.2 Preproduction Testing

4.2.1 Preproduction Test Samples. The preproduction test units shall be representative of the production hand trucks. They shall be tested at a laboratory designated by the procuring activity, or, when so stated in the contract, at the contractor's facility under supervision of the procuring activity.

4.2.2 Preproduction Test Reports. In the event that preproduction testing is conducted at the contractor's facility, the contractor shall, after completion of the preproduction test, prepare a preproduction test report in accordance with MIL-STD-831 and furnish three (3) complete copies to the procuring activity.

4.2.3 Preproduction Test. Preproduction test shall consist of all tests described in 4.5 "Test Methods."

4.3 Acceptance Test. Acceptance test shall consist of the following individual tests:

a. Examination of Product

b. Conformance to Drawings

4.4 Test Conditions. Test conditions shall be as specified for each specific test in 4.5 "Test Methods."

4.5 Test Methods

4.5.1 Examination of Product. Each hand truck shall be given a complete visual examination to determine compliance with all requirements of this specification for which no tests are specified, including materials and workmanship. Failure to satisfy these requirements shall be cause for rejection.

4.5.2 Conformance to Drawings. Each hand truck shall be inspected for strict conformance to engineering drawings and all specifications and standards referenced therein. Failure to pass this inspection shall be cause for rejection.

4.5.3 Functional Tests

4.5.3.1 Fit Test. The hand truck shall be subjected to a fit test which shall be performed at a military installation. The test shall be performed as follows:

Install and secure a Bomb, Loading Practice BDU-32/E in service configuration

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:33Z
Check the source to verify that this is the current version before use.

interference in making the above installations, excess clearances or binding or failure to mate properly with any piece of associated equipment shall be cause for rejection.

4.5.3.2 Mobility. The hand truck with a test load simulating the weight and exterior shape of the BDU-32/E Practice Bomb, shall be tested for Type I, Class I mobility in accordance with MIL-M-8090. The rejection criteria of MIL-M-8090 shall apply.

4.5.4 Air Transportability

4.5.4.1 Ramp Test. With a test load simulating the weight and exterior shape of the BDU-32/E Practice Bomb installed, the hand truck shall be subjected to the ramp test described in MIL-M-8090. Failure to satisfy the requirements of this test shall be cause for rejection.

4.5.4.2 Flight and Taxiing Load Test. With a test load simulating the BDU-32/E Practice Bomb installed, the hand truck shall be subjected to the flight and taxiing load test specified in MIL-A-8421. Failure to meet the requirements of MIL-A-8421 shall be cause for rejection.

4.5.4.3 Emergency Landing Load Test. With a test load simulating the BDU-32/E Practice Bomb installed, the hand truck shall be subjected to the emergency landing load test specified in MIL-A-8421. Failure to meet the requirements of MIL-A-8421 shall be cause for rejection.

4.5.5 Environmental Tests. The hand truck, with a test load simulating the BDU-32/E Practice Bomb, shall be subjected to the following environmental tests in the sequence in which listed:

	TEST	TEST STANDARD	METHOD	PROCEDURE
a.	High Temperature	MIL-STD-810	501	I
b.	Low Temperature	MIL-STD-810	502	I
c.	Temperature Shock	MIL-STD-810	503	I
d.	Humidity	MIL-STD-810	507	I
e.	Salt Fog	MIL-STD-810	509	I

Source: https://assist.dla.mil -- Downloaded: 202640-21T15:33Z
Check the source to verify that this is the currentversion before use.

Where the test procedure requires operation of equipment, the functional tests of this specification shall apply. Failure to satisfy the requirements of the functional tests during or after as applicable, subjection to the environmental tests shall be considered as failure to pass the environmental tests and cause for rejection.

5. PREPARATION FOR DELIVERY

5.1 Preservation and Packaging. Preservation and Packaging shall be Level A or C as specified (see 6.2).

5.1.1 Level A. - Each Hand Truck shall be packaged Method 111 in accordance with the requirements of MIL-P-116.

5.1.2 Level C. - Each Hand Truck shall be packaged in accordance with the manufacturer's commercial practice.

5.2 Packing. - Packing shall be Level A, B or C as specified (see 6.2).

5.2.1 Level A and B. - Each Hand Truck packaged as specified in 5.1 shall be packed in an open type shipping container conforming to PPP-C-650.

5.2.2 Level C. - Each Hand Truck packaged as specified in 5.1 shall be packed in a manner to insure carrier acceptance and safe delivery at destination. Containers shall be in accordance with Uniform Freight Classification Rules and Regulations of other carriers applicable to the mode of transportation.

5.3 Physical Protection. - Cushioning, anchoring, bracing and blocking as required shall be in accordance with MIL-STD-1186. Rough handling tests shall be required only when specified in the contract or order.

5.4 Marking. - In addition to any special markings required by the contract or order the shipping containers shall be marked in accordance with the requirements of MIL-STD-129. The nomenclature shall be:

TRUCK, HAND, BOMB MHU-67/E

6. NOTES

6.1 Intended Use. The Truck, Hand, Bomb MHU-67/E is intended to be used by ground crews to gain practice in ground handling of the parent weapon.

Source: https://assist.dla.mil -- Downloaded: 202640-21T15:33Z
Check the source to verify that this is the currentversion before use.

6.2 Ordering Data. Procurement documents shall specify the following:

a. Title, number and date of this specification.

b. Whether preproduction test will be conducted by procuring activity.

c. Levels of preservation, packaging and packing. (see 5.1 and 5.2)

6.2.1 Production Test Samples. It is expected that the contractor's purchase order will specify that two hand trucks will be required as first articles and that these first articles will be subjected to the preproduction test to determine compliance with the requirements of this specification. It is expected that the contract or purchase order shall specify the point of inspection for this test.

6.3 Production Delivery. No production item should be delivered prior to approval of the preproduction samples.

6.4 Sources. When requesting publications, refer to both title and number.

6.5 Definitions

a. Preproduction Tests. Preproduction tests are those tests performed prior to production on representative samples of the production equipment to demonstrate that the equipment meets the requirements of this specification.

b. Acceptance Tests. Acceptance tests are those tests accomplished on representative samples of equipment submitted for acceptance under a contract to determine conformance to the requirements of this specification, and to determine that the equipment is equivalent in performance, and construction to the approved preproduction samples.

WLIR
EAC/jg

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:33Z
Check the source to verify that this is the current version before use.