INCH-POUND
MIL-PRF-6106L
SUPPLEMENT 1
10 November 2000

PERFORMANCE SPECIFICATION

RELAYS, ELECTROMAGNETIC
GENERAL SPECIFICATION FOR

This supplement forms a part of Performance Specification
MIL-PRF-6106L, dated 10 November 2000.

SPECIFICATION SHEETS

| | | |
|---|---|---|
| MIL-PRF-6106/9 | - | Relay, Electromagnetic, Continuous Duty, 60 AMP, 3 PDT, Environmentally Sealed. |
| MIL-PRF-6106/10 | - | Relay, Electromagnetic, Normally Open, Continuous Duty, 60 AMP, 3 PST, Environmentally Sealed. |
| MIL-PRF-6106/11 | - | Relay, Electromagnetic, Normally Closed, Continuous Duty, 60 AMP, 3 PST, Environmentally Sealed. |
| MIL-PRF-6106/12 | - | Relay, Electromagnetic, (Type I), Magnetic Latch (Including Unsuppressed and Suppressed Coils), 2 Amperes, 1 PDT, Auxiliary Contacts, 25 Amperes, 3 PNO Main Contacts, Hermetically Sealed. |
| MIL-PRF-6106/13 | - | Relay, Electromagnetic, 25 Amperes, 3 PST, NO, With 2 Ampere, 1 PDT Auxiliary Contacts, Hermetically Sealed, Permanent Magnet Drive, Type I. |
| MIL-R-6106/14 | - | Relay, Electric, Permanent Drive, 50 AMP, SPDT (DB) Double Make Double Break Auxiliary Contacts (5 AMP), Hermetically Sealed. (INACTIVE FOR NEW DESIGN AFTER 10 MARCH 1989). |
| MIL-PRF-6106/15 | - | Relay, Electromagnetic, 50 Amperes, DC, SPDT, Hermetically Sealed. |
| MIL-PRF-6106/19 | - | Relay, Electromagnetic, Permanent Magnet Drive, 25 Amperes, SPDT, Hermetically Sealed. |
| MIL-PRF-6106/20 | - | Relay, Electromagnetic, Magnetic Latch, 25 Amperes, SPDT, Hermetically Sealed. |
| MIL-PRF-6106/26 | - | Relay, Electromagnetic, 50 Amperes, SPST, NC, With 5 Amperes SPDT Auxiliary, Hermetically Sealed. |
| MIL-PRF-6106/33 | - | Relay, Electromagnetic, Type I, 400 Amperes, With 5 Amperes Auxiliary Contacts, Permanent Magnet Drive, Hermetically Sealed. |
| MIL-PRF-6106/35 | - | Relay, Electromagnetic, Button, Plug Mounting Track. |
| MIL-PRF-6106/38 | - | Relay, Electromagnetic, Magnetic Latch, Permanent Magnet Drive, Low Level to 5 Amperes, 2 PDT, All Welded, Hermetically Sealed. |
| MIL-PRF-6106/39 | - | Relay, Electromagnetic, Magnetic Latch, Permanent Magnet Drive, Low Level to 5 Amperes, 4 PDT, All Welded, Hermetically Sealed. |
| MIL-PRF-6106/40 | - | Relay, Electromagnetic, Magnetic Latch, Permanent Magnet Drive, Low Level to 10 Amperes, 3 PDT, All Welded, Hermetically Sealed. |
| MIL-PRF-6106/41 | - | Relay, Electromagnetic, 25 Amperes, 3 PNO, With 2 Ampere, 1 PDT Auxiliary Contacts, Hermetically Sealed, Type I. |
| MIL-PRF-6106/43 | - | Relay, Electromagnetic, 65 Amperes, 1 PNO Double Break, Hermetically Sealed, Type I. |
| MIL-PRF-6106/48 | - | Relay, Electromagnetic, Type I, Hermetically Sealed, 100 Amperes, SPST (N.O.), With (Form 2) 5 Amperes Auxiliary Contacts. |


DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:18Z
Check the source to verify that this is the current version before use.

MS STANDARDS

| | |
|---|---|
| MS24140 | - Relay, 50 AMP, 1 PST, N.O. Type I, Hermetically Sealed. |
| MS24141 | - Relay, 100 AMP, 1 PST, N.O. Type I, Hermetically Sealed. |
| MS24142 | - Relay, 200 AMP, 1 PST, N.O. Type I, Hermetically Sealed. |
| MS24143 | - Relay, 25 AMP, 3 PST, N.O. Type I, Hermetically Sealed. |
| MS24149 | - Relay, Electromagnetic, 2 PDT, 10 Amperes, Type I, Hermetically Sealed. (INACTIVE FOR NEW DESIGN AFTER 5 JUNE 1987) |
| MS24152 | - Relay, 25 AMP, 3 PDT, N.O. Type II, Non-Hermetically Sealed (Mechanically Interlocked). (INACTIVE FOR NEW DESIGN AFTER 27 MARCH 1994) |
| MS24166 | - Relay, 50 AMP, 1 PST, N.O. Type II, Non-Hermetically Sealed. |
| MS24168 | - Relay, 100 AMP, 3 PST, N.O., Type I, Hermetically Sealed. |
| MS24171 | - Relay, 200 AMP, 1 PST, N.O., Type II, Non- Hermetically Sealed. |
| MS24172 | - Relay, 200 AMP, 1 PST, N.O. Type III, Non- Hermetically Sealed, Intermittent Duty. |
| MS24178 | - Relay, 55 AMP, 2 PST, N.O. Type II, Non- Hermetically Sealed. |
| MS24179 | - Relay, 400 AMP, 1 PST, N.O. Type III, Non- Hermetically Sealed. |
| MS24182 | - Relay, 100 AMP, 1 PST, N.O. Type I, Hermetically Sealed. |
| MS24183 | - Relay, 200 AMP, 1 PST, N.O. Type I, Hermetically Sealed. |
| MS24184 | - Relay, 300 AMP, 1 PST, N.O., Type I, Hermetically Sealed. |
| MS24185 | - Relay, 400 AMP, 1 PST, N.O. Type II, Non-Hermetically Sealed. |
| MS24187 | - Relay, Electromagnetic, 50/25 Amperes, 1 PDT (NO/NC), Type II, Non-Hermetically Sealed. |
| MS24192 | - Relay, 25 Amperes, 3 PST, N.O. Type II, Non-Hermetically Sealed. |
| MS24193 | - Relay, Electromagnetic, 50 Amperes, 3 PST, N.O. Type II, Non-Hermetically Sealed. |
| MS24376 | - Relay, 50 AMPS, 3PST, N.O. TYPE I, Hermetically Sealed. |
| MS24568 | - Relay, Electromagnetic, 10 Amperes, 4 PDT, Type I, Hermetically Sealed. (INACTIVE FOR NEW DESIGN AFTER 5 JUNE 1987) |
| MS25024 | - Relay, 10 Amperes, 4 PDT, Sealed, Class O. (INACTIVE FOR NEW DESIGN AFTER 11 DEC 84) |
| MS25030 | - Relay, 50 AMP, 2 PDT, N.O. Type II, Non-Hermetically Sealed, Mechanically Interlocked. (INACTIVE FOR NEW DESIGN AFTER 28 APR 95) |
| MS25031 | - Relay, 100 AMP, 2 PDT, N.O. Type II, Non-Hermetically Sealed, Mechanically Interlocked. (INACTIVE FOR NEW DESIGN AFTER 29 SEP 90) |
| MS25032 | - Relay, 200 AMP, 2 PDT, N.O. Type II, Non-Hermetically Sealed, Mechanically Interlocked. (INACTIVE FOR NEW DESIGN AFTER 28 SEP 90) |
| MS25033 | - Relay, 200 AMP, 1 PST, Sealed, Class O. (INACTIVE FOR NEW DESIGN AFTER 18 JAN 87) |
| MS25035 | - Relay, 25 AMP, 1 PST, Sealed, Class O. (INACTIVE FOR NEW DESIGN AFTER 14 NOV 79) |
| MS25267 | - Relays, Electromagnetic, 5 Amperes, 4 PDT, Type I, Solder Hook, Hermetically Sealed. (INACTIVE FOR NEW DESIGN AFTER 29 FEB 00) |
| MS25268 | - Relays, Electromagnetic, 5 Amperes, 4 PDT, Type I, Potted Lead, Hermetically Sealed. (INACTIVE FOR NEW DESIGN AFTER 5 JUN 87) |
| MS25269 | - Relays, Electromagnetic, 5 Amperes, 6 PDT, Type I, Hermetically Sealed. (INACTIVE FOR NEW DESIGN AFTER 15 OCT 99) |
| MS25270 | - Relays, Electromagnetic, 5 Amperes, 6 PDT, Type I, Potted Lead, Hermetically Sealed. (INACTIVE FOR NEW DESIGN AFTER 5 JUN 87) |
| MS25271 | - Relays, Electromagnetic, 10 Amperes, 4 PDT, Type I, Solder Hook, Hermetically Sealed. |
| MS25272 | - Relays, Electromagnetic, 10 Amperes, 4 PDT, Type I, Potted Lead, Hermetically Sealed. (INACTIVE FOR NEW DESIGN AFTER 5 JUN 87) |
| MS25273 | - Relays, Electromagnetic, 10 Amperes, 2 PDT, Type I, Solder Terminals, Stud Mounted, Hermetically Sealed. |
| MS25321 | - Relays, Electromagnetic, 5 Amperes, 2 PDT, Type I, Socket Mounted, Hermetically Sealed. (INACTIVE FOR NEW DESIGN AFTER 5 JUN 87) |



Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:18Z
Check the source to verify that this is the current version before use.

MS25323 - Relays, Electromagnetic, 10 Amperes, 2 PDT, Type I, Socket Mounted, Hermetically Sealed. (INACTIVE FOR NEW DESIGN AFTER 5 JUN 87)
MS25325 - Relays, Electromagnetic, 5 Amperes, 4 PDT, Type I, Socket Mounted, Hermetically Sealed. (INACTIVE FOR NEW DESIGN AFTER 5 JUN 87)
MS25327 - Relays, Electromagnetic, 10 Amperes, 4 PDT, Type I, Socket Mounted, Hermetically Sealed. (INACTIVE FOR NEW DESIGN AFTER 5 JUN 87)
MS25329 - Relays, Electromagnetic, 5 Amperes, 6 PDT, Type I, Socket Mounted, Hermetically Sealed. (INACTIVE FOR NEW DESIGN AFTER 30 SEPT 87)
MS25395 - Relays, Electromagnetic, 5 Amperes, 2 PDT, Type I, Hermetically Sealed.
MS25455 - Relays, Electromagnetic, 5 Amperes, 2 PDT, Type I, Magnetic Latch, Socket Mounted, Hermetically Sealed. (INACTIVE FOR NEW DESIGN AFTER 5 JUN 87)
MS25457 - Relays, Electromagnetic, 10 Amperes, 2 PDT, Type I, Magnetic Latch, Socket Mounted, Hermetically Sealed. (INACTIVE FOR NEW DESIGN AFTER 5 JUN 87)
MS25459 - Relays, Electromagnetic, 5 Amperes, 4 PDT, Type I, Magnetic Latch, Hermetically Sealed. (INACTIVE FOR NEW DESIGN AFTER 5 JUN 87)
MS25461 - Relays, Electromagnetic, 10 Amperes, 4 PDT, Type I, Magnetic Latch, Socket Mounted, Hermetically Sealed. (INACTIVE FOR NEW DESIGN AFTER 5 JUN 87)
MS25463 - Relays, Electromagnetic, 5 Amperes, 6 PDT, TYPE I, Magnetic Latch, Socket Mounted, Hermetically Sealed. (INACTIVE FOR NEW DESIGN AFTER 30 SEPT 87)
MS25465 - Relays, Electromagnetic, 5 Amperes, 2 PDT, Type I, Magnetic Latch, Solder Terminals, Stud Mounted, Hermetically Sealed. (INACTIVE FOR NEW DESIGN AFTER 5 JUN 87)
MS25466 - Relays, Electromagnetic, 10 Amperes, 2 PDT, Type I, Magnetic Latch, Stud Mounted, Solder Hooks, Hermetically Sealed. (INACTIVE FOR NEW DESIGN AFTER 5 JUN 87)
MS25467 - Relays, Electromagnetic, 5 Amperes, 4 PDT, Type I, Magnetic Latch, Solder Terminal, Stud Mounted, Hermetically Sealed. (INACTIVE FOR NEW DESIGN AFTER 15 OCT 99)
MS25468 - Relays, Electromagnetic, 10 Amperes, 4 PDT, Type I, Magnetic Latch, Solder Terminal, Stud Mounted, Hermetically Sealed. (INACTIVE FOR NEW DESIGN AFTER 29 FEB 00)
MS25469 - Relays, Electromagnetic, 5 Amperes, 6 PDT, Type I, Magnetic Latch, Solder Terminals, Stud Mounted, Hermetically Sealed. (INACTIVE FOR NEW DESIGN AFTER 29 FEB 00)
MS25917 - Relays, Electromagnetic, 3 Amperes, 4 PDT, Type I. (INACTIVE FOR NEW DESIGN AFTER 2 MAR 87)
MS25918 - Relay, 3 AMP, 6 PDT, Sealed, Class B8. (INACTIVE FOR NEW DESIGN AFTER 14 AUG 81)
MS25919 - Relays, Electromagnetic, 10 Amperes, 4 PDT, Type I. (INACTIVE FOR NEW DESIGN AFTER 2 MAR 87)
MS27222 - Relay, 50 AMP, 3 PST, N.O. Type I, Hermetically Sealed.
MS27242 - Relay, 100 AMP, 1 PST, N.O., Type I, Hermetically Sealed.
MS27243 - Terminal Covers - Relay.
MS27245 - Relays, Electromagnetic, 10 Amperes, 2 PDT, Type I, Hermetically Sealed. (INACTIVE FOR NEW DESIGN AFTER 5 JUN 87)
MS27247 - Relays, Electromagnetic, 10 Amperes, 2 PDT, Type I, Hermetically Sealed. (INACTIVE FOR NEW DESIGN AFTER 5 JUN 87)
MS27254 - Relays, Electromagnetic, 10 Amperes, 4 PDT, Type I, Plug-In, Hermetically Sealed. (INACTIVE FOR NEW DESIGN AFTER 5 JUN 87)
MS27255 - Relays, Electromagnetic, 10 Amperes, 4 PDT, Type I, Solder Hooks, Hermetically Sealed. (INACTIVE FOR NEW DESIGN AFTER 5 JUN 87)
MS27418 - Relays, Electromagnetic, 25 Amperes, 3 PST - NO, Type I, Hermetically Sealed, Hook and Screw Terminals, Stud and Bracket Mounted.
MS27706 - Relays, Electromagnetic, 20 Amperes, 3 PST, Mechanical Interlock, (Center Off) Load Transfer, Type I, Hermetically Sealed. (INACTIVE FOR NEW DESIGN AFTER 8 SEP 95)



Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:18Z
Check the source to verify that this is the current version before use.

| | | |
|---|---|---|
| MS27709 | - | Relays, Electromagnetic, 10 Amperes, 4 PDT, Type I, Hermetically Sealed. (INACTIVE FOR NEW DESIGN AFTER 5 JUN 87) |
| MS27714 | - | Relay, 75 AMP, 3 PST, N.O., Type I, Coil and Contacts Individually Sealed. (INACTIVE FOR NEW DESIGN AFTER 27 MAR 95) |
| MS27715 | - | Relay, 150 AMP, 3 PST, N.O., Type I, Coil and Contacts Individually Sealed. (INACTIVE FOR NEW DESIGN AFTER 27 MAR 95) |
| MS27742 | - | Relay, Magnetic Latch, 25 AMP, 3 PDT, All Welded, Hermetically Sealed. |
| MS27749 | - | Relays, Electromagnetic, 60 Amperes, 3 PDT, Magnetic Latch, Hermetically Sealed. |
| MS27750 | - | Relays, Electromagnetic, 50 Amperes, 3 PDT-NO., Center Off, Hermetically Sealed. |
| MS27751 | - | Relays, Electromagnetic, 60 Amperes, 3 PST or 3 PDT, Hermetically Sealed, Permanent Magnet Drive. |
| MS27997 | - | Relay, 25 AMP, 3 PST, N.O. Type I, Hermetically Sealed. (INACTIVE FOR NEW DESIGN AFTER 29 FEB 00) |

AIR FORCE – NAVY AERONAUTICAL STANDARDS

| | | |
|---|---|---|
| AN3303 | - | Relay, 3 AMP, 4 PDT, Sealed, Connector Mounting, Class O. (INACTIVE FOR NEW DESIGN AFTER 17 NOV 54) |
| AN3306 | - | Relay, 10 AMP, 2 PDT, Sealed, Connector Mounting, Class O. (INACTIVE FOR NEW DESIGN AFTER 17 NOV 54) |
| AN3308 | - | Relay, 10 AMP, 3 PDT, Sealed, Connector Mounting, Class O. (INACTIVE FOR NEW DESIGN AFTER 17 NOV 54) |
| AN3310 | - | Relay, 10 AMP, 4 PDT, Sealed, Connector Mounting, Class O. (INACTIVE FOR NEW DESIGN AFTER 17 NOV 54) |
| AN3314 | - | Relay, 10 AMP, 1 PDT, Unsealed, Class O. (INACTIVE FOR NEW DESIGN AFTER 17 NOV 54) |
| AN3320 | - | Relay, 25 AMP, 1 PST, Unsealed, Class O. (INACTIVE FOR NEW DESIGN AFTER 15 JUN 55) |
| AN3324 | - | Relay, 25 AMP, 1 PDT, Unsealed, Class O. (INACTIVE FOR NEW DESIGN AFTER 22 JUN 55) |
| AN3335 | - | Relay, 5 AMP, 3 PST, Unsealed, Class O. (INACTIVE FOR NEW DESIGN AFTER 17 DEC 57) |
| AN3362 | - | Relay, 100 AMP, 2 PST, Unsealed, Class O. (INACTIVE FOR NEW DESIGN AFTER 30 AUG 57) |
| AN3372 | - | Relay, 200 AMP, 2 PST, Unsealed, Class O. (INACTIVE FOR NEW DESIGN AFTER 25 NOV 57) |

Preparing Activity:
DLA - CC

(Project 5945-1113-18)



Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:18Z
Check the source to verify that this is the current version before use.