INCH-POUND


MIL-R-6106/2F(USAF)
28 September 1992
SUPERSEDING
MIL-R-6106/2E(USAF)
28 March 1990

MILITARY SPECIFICATION SHEET

RELAYS, ELECTROMAGNETIC, TYPE I, 4PDT, 10 AMPERES, PERMANENT MAGNET DRIVE, HERMETICALLY SEALED ASSEMBLY

This specification is approved for use by the Department of the Air Force, and is available for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-R-6106.




(F) FIGURE 1. Relay, outline drawing.


(F) denotes changes

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.


Source: https://assist.dla.mil -- Downloaded: 202610-17T06:19Z
Check the source to verify that this is the current version before use.




CIRCUIT A
(SEE NOTES 5 AND 6)




CIRCUIT B
(SEE NOTES 4 AND 6)




CIRCUIT C
(SEE NOTES 5, 6, AND 8)



TERMINAL LAYOUT - C (DC COILS)



TERMINAL LAYOUT - D (AC COILS)



TERMINALS

FIGURE 1. Relay, outline drawing - Continued.

Source: https://assist.dla.mil -- Downloaded: 202610-17T06:19Z
Check the source to verify that this is the current version before use.

Inches	mm	Inches	mm
.001	0.03	.140	3.56
.005	0.13	.200	5.08
.010	0.25	.270	6.86
.015	0.38	.313	7.95
.020	0.51	.400	10.16
.040	1.02	.500	12.70
.046	1.17	.800	20.32
.062	1.57	1.025	26.04
.078	1.98	1.250	31.75
.079	2.01	1.310	33.27
.094	2.39	1.910	48.51

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ±.010 (0.25 mm).
4. Coil polarity is not applicable to -002.
5. DC versions of this relay shall not operate or be damaged by reverse polarity. Semiconductors shall not be used for this purpose.
6. Permanent magnet drive consists of permanent magnet with its flux path switched and combined with the electromagnetic flux.
7. Terminal numbers shall not appear on the header. There shall be affixed to the relay a legible circuit diagram that identifies each terminal location specified.
8. Back EMF suppression circuit: JAN TX or equivalent screened semiconductors shall be used. Back EMF shall be 42 V dc maximum. Relays using suppression devices shall continue to operate should the suppression circuit be in a failure mode.
9. All terminals shall be gold plated in accordance with MIL-G-45204, type II, class 1; underplating shall be nickel, 50 to 150 microinches thick.
10. Knob and post shall be nickel plated (100 microinches minimum) 303 stainless steel.

FIGURE 1. Relay, outline drawing - Continued.

Source: https://assist.dla.mil - Downloaded: 2026-10-17T06:19Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Coil data: See table I.

Duty rating: Continuous.

Operational data:

Time current relay characteristics: Applicable (see table II).

Rated contact load: See table III.

Operate time: See table I.

Release time: See table I.

Break bounce: See table I.

Physical:

Dimensions and configuration: See figure 1.

(F) Weight (maximum): 0.17 pound (77.12 grams).

Terminal type: See figure 1.

Finish: Enclosure shall be in accordance with FED-STD-595:

-001 Black 37038
-002 Gray 36231
-003 Black 37038

Knob strength test: The rod to knob junction shall be capable of resisting an axial pull of 35 pounds without degradation.

Operational reliability: Applicable.

Identification of product: Applicable. The circuit diagram shall be oriented so that when the relay is held with the circuit diagram right side up as shown on figure 1, and rotated away from the viewer about a horizontal axis through the diagram until the header terminals face the viewer, then each terminal shall be in the location shown in the circuit diagram.

ENVIRONMENTAL CHARACTERISTICS:

(F) Temperature rating: -70°C to +125°C.

Maximum altitude rating: 80,000 feet.

Shock: MIL-STD-202, method 213, test condition A 1/:

G-level: 50 g's.

Duration: 10 ms.

Maximum duration contact opening: 10 μs.

Maximum duration contact closing: 1 μs.

1/ To be tested as complete relay assembly, see table I, footnote 1/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:19Z
Check the source to verify that this is the current version before use.

(F) TABLE I. Dash number and operating characteristics. 1/

Dash no.	Coil data										Time-milliseconds - max						Overload current amperes	Rupture current amperes	Circuit schematic	Terminal layout
	Rated			Max		Max pick-up voltage			Hold voltage 3/	Dropout voltage 3/	Operate 4/	Release 5/	Bounce							
													Main		Aux					
	Volts 2/	Freq Hz	Res Ω	Volts	Ampere	Nominal 3/	High temp test	Cont current test					NO	NC	NO	NC				
001	28 V dc	N/A	290	30	0.11	18.0	20	22.5	7.0	1.5	10	20	1	1	N/A	N/A	40	50	Fig 1A	Fig 1C
002	115 V ac	400	N/A	122	.04	90	96	103.5	30	5.0	15	50	1	1	N/A	N/A	60	80	Fig 1B	Fig 1D
003 6/	28 V dc	N/A	290	30	0.11	18.0	20	22.5	7.0	1.5	10	20	1	1	N/A	N/A	40	50	Fig 1C	Fig 1C

1/ The complete relay assembly shall consist of the following:

a. Required relay.

b. Relay, electric, bracket and socket assembly (see MIL-R-6106/5).

c. Relay electric, mounting track (see MIL-R-6106/3).

2/ CAUTION: The use of any coil voltage less than the rated coil voltage will compromise the operation of the relay.

3/ Over temperature range.

4/ With rated coil voltage.

5/ From rated coil voltage.

6/ Dash number -003 is equipped with back EMF (coil transient) suppression.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:19Z
Check the source to verify that this is the current version before use.

TABLE II. Time-current relay characteristics at +25°C. 1/ 2/

1	15A - 1 hour
2	50A - 5.0 seconds
3	100A - 1.2 seconds
4	250A - 0.2 second
5	350A - 0.1 second

1/ Caution: Compare with time-current characteristics of the associated circuit protective device.

2/ Relays shall sustain five applications (make and carry only) of power concurrently on adjacent poles at each of five different current levels for the time durations in table II. Separate relays shall be tested at 28 V dc and 115/200 V ac, 400 Hz, 3 phase. Cooling time between successive applications shall be 30 minutes. The test shall be performed on both normally open and normally closed contacts of each relay. There shall be no failures or evidence of welding or sticking and relays shall pass contact voltage drop at conclusion.

Vibration, sinusoidal 2/:

G-level: 30 g's.

Frequency range: 10 to 3,000 Hz.

Vibration scan: Applicable to group A testing.

Frequency range: 5 to 2,000 Hz.

Intensity: 0.01 inch double amplitude or ±2 g's, whichever is less.

Vibration, random 2/: MIL-STD-202, method 214, test condition IG (0.4 g^2/Hz), 15 minutes each plane, 50 to 2,000 Hz.

Shock: Test condition C.

Acceleration 2/: 15 g's.

ELECTRICAL CHARACTERISTICS:

Insulation resistance, initial: 100 megohms.

After life or environmental tests: 50 megohms.

Dielectric withstanding voltage (sea level) 3/:

	Initial	After life tests
Coil to case	1050	1050
Aux contacts	---	---
All other points	1500	1250

Dielectric withstanding voltage (altitude)

Coil to case	350	350
Aux contacts	---	---
All other points	350	350

2/ To be tested as complete relay assembly, see table I, footnote 1/.
3/ To be tested with relay inserted in socket, MIL-R-6106/5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:19Z
Check the source to verify that this is the current version before use.

TABLE III. Rated contact load (amperes per pole) (case grounded).

Type of load	Life operating cycles x 10^3	28 V dc				115 V ac, 1 phase				115/200 V ac, 3 phase 1/			
		Main		Aux		Main		Aux		Main		Aux	
		NO	NC	NO	NC	400 Hz	60 Hz	400 Hz	60 Hz	400 Hz	60 Hz	400 Hz	60 Hz
Resistive	100	10	10	---	---	10	---	---	---	10	---	---	---
Inductive	20	8	8	---	---	8	---	---	---	8	---	---	---
Inductive						(Not applicable)							
Motor	100	4	4	---	---	4	---	---	---	4	---	---	---
Lamp	100	2	2	---	---	2	---	---	---	2	---	---	---
Transfer, load 2/													
Mechanical life (reduced load)	400	2.5	2.5	---	---	2.5	---	---	---	2.5	---	---	---
Intermediate current				(Applicable per MIL-R-6106)									

1/ 115/200 V ac for 60 Hz ratings. Absence of value indicates relay is not rated for 3 phase applications.

2/ Transfer load indicates relay is suitable for transfer between unsynchronized ac power supplies at rating indicated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:19Z
Check the source to verify that this is the current version before use.

Maximum contact drop (initial): 0.150 volt.

After life test: 0.175 volt.

RFI standard (applicable to -002): MIL-STD-461.

Back EMF (coil transient): ±42 volts maximum.

(Applicable to -003)

Test temperature: Room ambient.

Point of measurement: Across coil terminals X_1 - X_2.

Coil voltage: 28 V dc.

Test method: Apply coil voltage to X_1 - X_2. With oscilloscope monitoring the coil terminals, measure and record the back electromotive force when voltage is removed.

Part or Identifying Number (PIN): M6106/2-(plus dash number from table I). Complete PIN example: M6106/2-001.

CONCLUDING MATERIAL

Custodian:
Air Force - 85

Review activities:
Air Force - 99
DLA - ES

Preparing activity:
Air Force - 85

Agent:
DLA - ES

(Project 5945-F735)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:19Z
Check the source to verify that this is the current version before use.