MIL-G-51203A(MU)
AMENDMENT 2
15 May 1968
SUPERSEDING
AMENDMENT 1
3 August 1967

MILITARY SPECIFICATION

GUN, FLAME THROWER, PORTABLE, M7

This amendment forms a part of Military Specification MIL-G-51203A(MU), 17 October 1966.

Page 3

3.4.1: Delete and substitute the following:

"3.4.1 Valve lever. The safety mechanism shall not release the valve lever when a 30 to 31 pound load is applied, when tested in accordance with 4.3.4.2(a)."

Page 9

4.3.4.1: In first sentence delete "740 to 750 pounds" and substitute "625 ± 10 pounds." In third sentence delete "340 to 350 psig" and substitute "320 ± 10 psig."

4.3.4.2(a): Delete "(a)" in its entirety and substitute the following:

"(a) Valve lever. The valve lever shall be tested using the Q58 tester as per instruction manual 136-300-166. The assembled gun shall be clamped in a vertical position with the nozzle up and with the safety valve not depressed. The weight will be placed at the index finger position and will be applied at approximately 90° to the grip surface and in the direction of travel."

Page 10

4.3.4.3(b): Delete the second sentence and substitute the following:

"The aseembled gun less the ignition cylinder and nozzle shield shall be placed in a horizontal position with the ignition lever up and the specified load applied."

Custodian
Army - MU

Preparing activity:
Army - MU(EA)

Project No. 1040-A087
FSC 1040

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:53Z
Check the source to verify that this is the current version before use.