MIL-P-51159A(MU)
AMENDMENT 1
26 November 1968

MILITARY SPECIFICATION

PRESSURE CONTROL UNIT;

FOR M10-8 MECHANIZED FLAME THROWER

This amendment forms a part of Military Specification MIL-P-51159A(MU), 1 April 1968.

Page 3

3.4.1: Delete and substitute the following:

"3.4.1 Functioning, maximum pressure. The regulator when subjected to an inlet air pressure of 3000 ± 50 psig shall have an outlet pressure of 250 to 260 psig for one hour and then an outlet pressure of 340 to 350 psig for one hour when tested as specified in 4.4.4.2."

3.4.2: Delete and substitute the following:

"3.4.2 Functioning, minimum pressure. The regulator when subjected to an inlet air pressure of 700 ± 20 psig shall have an outlet pressure of 250 to 260 psig for one hour and then an outlet pressure of 340 to 350 psig for one hour when tested as specified in 4.4.4.2"

Page 11

4.4.4.2(c): Delete and substitute the following:

"(c) Pressurize the regulator, adjust the regulator to the required outlet pressure, and allow the regulator to stabilize for a minimum period of 5 minutes."

Custodian:

Army - MU

Preparing activity:

Army - MU(EA)

Project No. 1040-A098

FSC 1040

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:51Z
Check the source to verify that this is the current version before use.