[INCH-POUND]
A-A-59243
June 16, 1998
SUPERSEDING
OO-S-2771
September 14, 1992

COMMERCIAL ITEM DESCRIPTION

SCRAPER-TRACTORS: EARTH MOVING, HYDRAULIC OPERATED, 12 AND 20 CUBIC YARD MINIMUM HEAPED CAPACITY, DED

The General Services Administration has authorized the use of this commercial item description for all Federal agencies.

1. SCOPE. This commercial item description (CID) covers self-propelled, diesel-engine-driven, hydraulic operated, 12 and 20 cubic yard (yd^3) (9.17 and 15.29 cubic metre (m^3)) heaped capacity, earth moving, scraper-tractors. The scraper-tractors covered by this CID are used for earth moving in construction projects.

2. CLASSIFICATION. The scraper-tractors shall be of the following types as specified (see 7.2):

Type I - Two driven traction wheels, 4 by 2.
Type II - Four driven traction wheels, 4 by 4.

3. SALIENT CHARACTERISTICS.

3.1 Standard commercial product. The scraper-tractors shall, as a minimum, be in accordance with the requirements of this CID and shall be the manufacturer's standard commercial product. Additional or better features which are not specifically prohibited by this CID but which are a part of the manufacturer's standard commercial product, shall be included in the scraper-tractors being furnished. A standard commercial product is a product which has been sold or is being currently offered for sale on the commercial market through advertisements or manufacturer's catalogs, or brochures, and represents the latest production model.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: Officer in Charge (Code 15E2), Seabee Logistics Center, 4111 San Pedro St., Port Hueneme, CA 93043-4410, by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 3805

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:07Z
Check the source to verify that this is the current version before use.

3.2 Interchangeability. All scraper-tractors of the same classification furnished with similar options under a specific contract shall be identical to the extent necessary to ensure interchangeability of component parts, assemblies, accessories, and spare parts.

3.3 Design.

3.3.1 Safety. All moving parts, parts subjected to high operating temperatures, and parts energized electrically which are of such a nature or so located as to become a hazard to operating and maintenance personnel shall be insulated, enclosed, or guarded. Protective devices shall not impair the operating functions. Platforms, steps, handholds, and rails shall be furnished and located, where necessary, to ensure safe, easy access by personnel to those areas requiring frequent maintenance or service. All safety systems provided for the operator shall be in accordance with Occupational Safety and Health Standards (OSHA). The scraper-tractors shall be provided with not less than the following safety equipment:

a. Windshield with power operated windshield wiper(s).
b. Horn.
c. Rearview mirror with not less than 32 square inches (206 square centimetre) reflective surface.
d. Backup alarm device conforming to SAE J 994.
e. Seat belt for operator’s seat.
f. Rollover protective structure at operator’s station.
g. Fenders over all driving wheels, front and rear.

3.3.2 Drive axles. The drive axles of the tractors and scrapers shall be equipped with an increased traction differential device, and utilize planetary positive reduction gearing or direct spur gear reduction gearing.

3.3.2.1 Type I scraper-tractor (4 by 2). The tractor of the type I scraper-tractor shall have two wheels driven by a single self-contained engine. The tractor shall be coupled to tow the scraper equipped with two nondriven wheels.

3.3.2.2 Type II scraper-tractor (4 by 4). The tractor of the type II scraper-tractor shall have two wheels driven by a single self-contained engine. The tractor shall be coupled to tow the scraper, which shall be equipped with a single self-contained engine mounted on the rear end of the scraper to provide power to two driven wheels.

3.3.3 Power to weight ratio. The scraper-tractor gross weight ratio to the net flywheel horsepower (hp) (watt (W)) shall be not greater than 375 pounds (lb) per hp (170 kilogram (kg) per W) for the type I (4 by 2), not greater than 345 lb per hp (156 kg per W) for the type II (4 by 4).

3.3.4 Capacities, cutting and spreading dimensions, turning radius, and travel speeds. The scraper-tractor shall conform to the capacities, and cutting and spreading dimensions specified in

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:07Z
Check the source to verify that this is the current version before use.

table I. The struck and heaped capacity ratings shall be in accordance with SAE J 741. The turning radius and travel speeds shall be as specified in table II.

TABLE I. Capacities, payloads, and cutting and spreading dimensions.

Types	Minimum capacities		Payload	Cutting width	Cutting depth	Spreading depth
	Struck	Heaped		minimum	minimum	minimum
	yd^3 (m^3)	yd^3 (m^3)	lb (kg)	inch (mm)	inch (mm)	inch (mm)
I	9 (6.88)	12 (9.17)	28,000 (12 701)	Not applicable	Not applicable	Not applicable
II	14 (10.70)	20 (15.29)	48,000 (21 772)	108 (2 743)	11 (279)	17 (432)

TABLE II. Turning radius and travel speeds.

Types	Maximum turning radius (outside dimension) feet (metre)	Minimum travel speed (with heaped load) mph (km/h)
I	40 (12.19)	23 (32)
II	48 (14.63)	23 (37)

3.3.5 Tractor frame. The tractor frame shall support or incorporate as integral parts the towing device(s), crankcase guard, fenders, oscillating hitch assembly, operator's stations, powerplant, and power train. Towing device(s) shall withstand a pulling force of not less than 150 percent of the scraper-tractor's gross vehicle weight (see 7.4.1). The crankcase guard shall protect the crankcase, flywheel housing, accessories, and other assemblies exposed to damage from projecting obstructions likely to be encountered during normal earth moving operations.

3.3.6 Scraper frame.

3.3.6.1 Draft frame. The draft frame shall consist of the hitch assembly housing, gooseneck, and yoke. The draft frame shall be equipped with a positive mechanical locking device to prevent separation of the tractor and scraper during lifting operations and maintenance functions.

3.3.6.2 Push frame. The push frame shall incorporate towing hook(s) and either a push plate or roller mounted on the rear of the scraper. The frame shall support the rear engine and power train on the type II (4 by 4) scraper-tractor. The push plate or roller and frame shall withstand the forces applied to it without deformation or breakage, when the scraper-tractor is push-loaded with other equipment of equal size.

3.3.7 Scraper bowl. The scraper bowl shall be of the front loading, front-lifting, open-bowl type, complete with apron, blade base, ejector, cutting edges, and side bits. The complete bowl operation shall be hydraulically operated. The bowl shall be power raised and power lowered and shall hold any position through its travel range with any load throughout the capacity range. A mechanical means shall be provided for locking the bowl in the raised position. The bowl shall be free of overload beams, structures, and hydraulic components that would obstruct loading by means of crane shovels, draglines, and loaders. The bowl shall withstand, without permanent deformation or damage, all operating forces of the apron and ejector. The bowl shall carry a rated

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:07Z
Check the source to verify that this is the current version before use.

heaped payload without permanent deformation or damage and without deflecting in overall width to an extent which would adversely affect operation or cause excessive rub plate wear. In no case shall the overall width deflection be greater than 0.50-inch (12.7 mm).

3.3.7.1 Cutting edges. The cutting edges shall consist of not less than three sections or more than four sections. All sections shall be reversible with two sections interchangeable. The cutting edges shall have a cutting width not less than that specified in table I.

3.3.7.2 Side bits. The side bits shall be reversible side-to-side and interchangeable.

3.3.8 Transmission(s) and torque converter(s). The scraper-tractor shall have full torque power shift transmission(s) and torque converter(s). The transmission system shall provide not less than five forward and one reverse speed. Both transmissions of the tractor and scraper for the type II (4 by 4) shall be controlled and shifted together. Torque converter oil coolers shall be furnished. The coolers shall maintain the temperature of the oil entering the converters at a temperature of not greater than 275 degrees Fahrenheit (°F) (135 degrees Celsius (°C)). Tractor torque converter oil temperature indicators or high temperature warning devices shall be provided and located at the operator's station. The torque converter oil temperature may be monitored by an audible warning system.

3.3.9 Steering mechanism. The steering mechanism for the scraper-tractor shall be power steering or power-assisted steering. The steering mechanism shall be capable of turning the tractor 90 degrees right or left of the longitudinal centerline of the scraper.

3.3.10 Brakes.

3.3.10.1 Service brakes. The scraper-tractor shall be equipped with full air service brake system. The brake system shall stop a fully loaded scraper-tractor from a speed of 20 miles per hour (mph) (32 kilometre per hour (km/h)) within 90 feet (27 m) from the point of brake pedal application. Brakes shall be equipped with an emergency stopping system to provide braking in the event of air pressure loss. Air reservoir(s) shall have moisture bleeder(s).

3.3.10.2 Air parking brake system. The scraper-tractor shall be equipped with an air parking brake system. The parking brake shall hold a fully loaded scraper-tractor on a 20 percent grade without the assistance of the service brakes.

3.3.11 Wheels, rims, and tires. The drive wheels of the tractor and wheels of the scraper shall be of the same size and interchangeable front to rear. The tires shall be wide base, tubeless, with all-terrain-type tread. Tire and rim sizes, ply rating, and load rating at 30 mph (48 km/h) shall conform to either the TRA Yearbook or the ETRTO Standards Manual recommendations. Tires shall be of rated capacity of not less than equal to the load imposed on each tire, measured at each wheel at the ground, with scraper-tractor loaded to rated gross vehicle weight.

3.3.12 Engine(s). The scraper-tractor shall be powered by the manufacturer's standard diesel engine(s). The power and speed of the engine(s) shall be sufficient to meet the performance

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:07Z
Check the source to verify that this is the current version before use.

requirements specified herein. For type II scraper-tractor, both engines shall be of the same make. The engine(s) shall be furnished complete with the following accessories:

a. Two-stage intake air cleaner with service indicator.
b. Fuel filter(s).
c. Hour meter(s).
d. Fuel tank(s) with sufficient capacity for not less than 8 hours operation.
e. Electric cranking.
f. Battery charging system.
g. Torque converter oil temperature indicator.
h. Radiator guard.

3.3.12.1 Batteries. Batteries shall be wet-charged, with electrolyte, and with sealed caps to prevent the intrusion of atmospheric moisture.

3.3.12.2 Exhaust. The engine(s) shall be equipped with exhaust muffler and stack. The exhaust stack outlet(s) shall be provided with rain caps, 45-degree or 90-degree bends, or automatic moisture drain.

3.3.13 Lighting. The lighting system shall be 12 volts and shall include the following:

a. Two headlamps and two forward directed floodlamps or four headlamp bright and dim system.
b. Not less than two scraper floodlamps directed to illuminate the bowl, apron, and cutting edge at each side.
c. Instrument panel lamp(s) to illuminate all instruments.

3.3.14 Hydraulic system. A hydraulic system shall be utilized for transmitting engine power to the mechanisms that operate the apron, bowl, ejector, and steering. The hydraulic system shall withstand a bursting pressure of four times the working pressure. The system, including hoses, shall be suitable for operating temperatures ranging from - 20 °F to 250 °F (- 28.8 °C to 121.1 °C). The hydraulic system shall be furnished with full flow filter(s) having a micronic rating not greater than 25.

3.3.15 Operator’s station. The operator’s station shall consist of a shock absorbing operator seat, steering wheel, a safety glass windshield equipped with power-operated windshield wiper(s), instrument panel, operating controls, and a rollover protective structure conforming to SAE J 1040. The seat shall be equipped with a seat belt conforming to SAE J 386. All controls and instruments that are not already identified to show their intended function or operation shall be clearly identified for their intended operation and function with permanently affixed identification. Decals shall not be used. Controls shall be located within the dimensional spaces specified in SAE J 898. All instruments and markings shall be in the English language or International-type symbols. All instruments and markings shall be readily visible to the operator when seated in a normal operating position. Unless the scraper-tractor is equipped with an

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:07Z
Check the source to verify that this is the current version before use.

enclosed cab with lockable door, all instruments shall be protected against damage by an anti-vandalism panel guard.

3.3.15.1 Cab. The cab shall be the manufacturer's standard fully enclosed cab. The cab shall have a hinged door and shall enclose the operator's seat, all controls, and shall not obstruct the view of the operator while seated. Closed cab accessories shall include a rearview mirror of the adjustable type, with a size of not less than 4 inches by 8 inches (102 mm by 203 mm) and mounted on the left exterior of the cab. The enclosed cab shall be furnished with an air conditioner, heater, and defroster. The air conditioner shall be the manufacturer's standard for maintaining the operator's comfort level with outside temperatures up to 115 °F (46 °C). The heater and defroster shall be the manufacturer's standard for maintaining the operator's comfort in temperatures down to - 20 °F (- 38 °C). Electric or air-powered windshield wipers for front and rear windshields, with separate controls, shall be furnished.

3.3.15.2 Noise limits. The sound level at the operator's station shall be measured in accordance with SAE J 88 and SAE J 919. If the sound level in the area occupied by the operator is 85 decibels (db(A)) or greater, a warning plate shall be permanently affixed in a conspicuous location at the operator's control station. The warning plate shall contain the following: "CAUTION - HEARING PROTECTION REQUIRED." The plate shall have a yellow background with black lettering and shall be of corrosion resistant material. The plate shall be securely affixed to the equipment with nonferrous screws, bolts, or rivets.

3.3.16 Toolbox. When specified (see 7.2), the scraper-tractor shall be provided with a lockable metallic toolbox. The toolbox shall be securely fastened to the scraper-tractor in a protected and accessible location. The toolbox shall be of sufficient size to hold the tools normally used for daily maintenance of the scraper-tractor.

3.4 Performance. The scraper-tractor shall withstand the hard usage encountered, without permanent deformation or damage, while performing the following operations:

a. The type I scraper-tractor shall load undisturbed or recompacted soil (see 7.4.2), to the struck capacity without assistance from auxiliary equipment.
b. The type II scraper-tractor shall load undisturbed or recompacted soil to the struck capacity in not greater than one minute without assistance from auxiliary equipment.
c. The scraper-tractor shall dump and spread the soil without assistance from auxiliary equipment.
d. The scraper-tractor, loaded with the minimum heaped payload specified in table I, shall travel at an average speed of not less than that specified in table II on maintained earth haul roads (see 7.4.3).
e. The scraper-tractor, loaded with the minimum heaped payload specified in table I, shall negotiate a grade having a slope of not less than 20 percent.
f. The scraper-tractor, when empty, shall traverse a longitudinal grade having a slope of not less than 30 percent and not less than 3 times the length of the scraper-tractor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:07Z
Check the source to verify that this is the current version before use.

3.4.1 Environmental conditions. The scraper-tractor engine(s) shall start and perform as specified at a temperature from - 20 °F to 125 °F (- 28.8 °C to 51.6 °C). When an ether priming system is required, it shall be of the measured shot type with a storage capacity of not less than 12 fluid ounces (355 millilitre).

3.5 Lifting and tiedown attachments. When specified (see 7.2), the scraper-tractor shall be equipped with lifting and tiedown attachments. Lifting and tiedown attachments shall conform to MIL-STD-209. A nonferrous transportation plate shall be provided and mechanically attached to the scraper-tractor. Transportation plates shall be inscribed with a diagram showing the lifting attachments and lifting slings, the capacity of each attachment, and the required length and size of each sling cable. A silhouette of the item furnished showing the center of gravity shall be provided on the transportation plate. Tiedown attachments may be identified by stenciling or other suitable marking. Tiedown marking shall clearly indicate that the attachments are intended for the tiedown of the scraper-tractor on the carrier when shipped.

3.6 Instruction plates. The scraper-tractors shall be equipped with instruction plates suitably located, describing any special or important procedures to be followed in operating and servicing the equipment. Plates shall be of a material which will last and remain legible for the life of the equipment. Plates shall be securely affixed to the equipment with nonferrous screws, bolts, or rivets.

3.7 Lubrication. Means for lubrication shall be in accordance with the manufacturer's standard practice. The lubricating points shall be easily visible and accessible. Hydraulic lubrication fittings shall be in accordance with SAE J 534. Where use of high-pressure lubricating equipment, 1,000 psi (6 895 kPa) or higher, will damage grease seals or other parts, a suitable warning shall be affixed to the equipment in a conspicuous location. The unit shall be lubricated prior to delivery with type of lubricant specified in the operator's manual and grade of lubricant recommended for ambient temperature at the delivery point. The unit shall be conspicuously tagged to identify the lubricants and their temperature range.

3.8 Cleaning, treatment, and painting. Surfaces normally painted in good commercial practice shall be cleaned, treated, and painted as specified herein. The color of the finish coat shall be as specified (see 7.2). Surfaces to be painted shall be cleaned and dried to ensure that they are free from contaminants such as oil, grease, welding slag and spatter, loose mill scale, water, dirt, corrosion product, or any other contaminating substances. As soon as practicable after cleaning and before any corrosion product or other contamination can result, the surfaces shall be prepared or treated to ensure the adhesion of the coating system. The painting shall consist of at least one coat of primer and one finish coat. The primer shall be applied to a clean, dry surface as soon as practicable after cleaning and treating. Painting shall be with manufacturer's current materials according to manufacturer's current process and the total dry film thickness shall be not less than 2.5 mil (0.06 mm) over the entire surface. The paint shall be free from runs, sags, orange peel, or other defects.

3.9 Identification plate. An identification plate will be furnished by the contracting officer for each scraper-tractor. The contractor shall stamp all necessary data in the blank spaces of the plate

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:07Z
Check the source to verify that this is the current version before use.

provided for that purpose. The plate shall be securely affixed to each scraper-tractor in a conspicuous place with nonferrous screw, bolts, or rivets. The applicable nomenclature contained in the contract item description shall be placed in the top blank.

3.10 Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within specified tolerances using conversion tables contained in the latest version of IEEE SI-10 and all other requirements of this commercial item description including form, fit and function are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the contracting officer to determine if the product is acceptable. The contracting officer has the option of accepting or rejecting the product.

3.11 Air transportability configuration. When specified (see 7.2), the scraper tractor shall be transportable by aircraft in a roll-on/roll-off configuration in accordance with MIL-STD-1791. The air transportability configuration shall be for air transport by C-5, C-17, C-130, or C-141 aircraft as specified (see 7.2).

3.12 Rail impact. When specified (see 7.2), the scraper-tractor shall meet the rail impact test requirements of MIL-STD-810.

4. REGULATORY REQUIREMENTS.

4.1 Recovered materials. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

5. QUALITY ASSURANCE PROVISIONS.

5.1 Product conformance. The products provided shall meet the salient characteristics of this commercial item description, conform to the producer’s own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial market. The government reserves the right to require proof of such conformance.

6. PACKAGING. The preservation, packing, and marking shall be as specified in the contract or order.

7. NOTES.

7.1 Source of documents.

7.1.1 Copies of standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:07Z
Check the source to verify that this is the current version before use.

7.1.2 The Federal Acquisition Regulation (FAR) and OSHA regulations may be obtained from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

7.1.3 ETRTO Standards Manual is available from the European Tyre and Rim Technical Organization, 32, Avenue Brugmann, 1060 Brussels, Belgium.

7.1.4 IEEE Standards are available from the Institute of Electrical and Electronics Engineers (IEEE), IEEE Service Center, 445 Hoes Lane, P.O. Box 1331, Piscataway, NJ 08855-1331.

7.1.5 SAE Standards and Recommended Practices is available from the Society of Automotive Engineers, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.

7.1.6 TRA Yearbook is available from the Tire and Rim Association, Inc., 175 Montrose West Avenue, Suite 150, Copley, OH 44321.

7.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this CID.
b. Type of scraper-tractor required (see 2.).
c. When the scraper-tractor is to be provided with a toolbox (see 3.3.16).
d. When lifting and tiedown attachments are required (see 3.5).
e. Color of finish coat (see 3.8).
f. When the scraper-tractor is to be configured in air transportability. Type of aircraft for which the scraper-tractor is to be configured (see 3.11).
g. When the scraper-tractor is to meet the rail impact test of MIL-STD-810 (see 3.12).

7.3 Part Identification Number (PIN). The following part identification numbering procedure is for government purposes and does not constitute a requirement for the contractor. The PIN used for items acquired to this description are created as follows:



PIN codes:

1 = Type I
2 = Type II

7.4 Definitions.

7.4.1 Gross vehicle weight. The gross vehicle weight of the scraper-tractor is the total weight of the unit when fully loaded with fuel, oil, hydraulic fluid, and the scraper bowl is loaded to heaped capacity (see 3.3.5).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:07Z
Check the source to verify that this is the current version before use.

7.4.2 Recompacted soil. Recompacted soil is soil that has been recompacted to not less than 75 percent Standard Proctor and within ± 2 percent optimum moisture (see 3.4).

7.4.3 Maintained earth haul road. A maintained earth haul road has a smooth, firm, level, earth surface that undulates or slightly flexes under load, and is watered and maintained regularly (see 3.4).

7.5 Supersession data. This commercial item description replaces Federal Specification OO-S-2771, dated September 14, 1992.

7.6 Classification cross reference. Cross reference of classification changes between this CID (see 2.) and the superseded Federal Specification OO-S-2771 is as follows:

A-A-59243	OO-S-2771
Type I	Type I
Type II	Type II
Not designated	Type III

MILITARY INTERESTS:

Custodians:
Army - AT
Navy - YD1
Air Force - 99

Review Activities:
Army - MT
Air Force - 84
DLA - CC

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

Preparing Activity:
Navy - YD1

(Project 3805-0023)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:07Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	**1. DOCUMENT NUMBER** A-A-59243	**2. DOCUMENT DATE (YYMMDD)** 980616

3. DOCUMENT TITLE
SCRAPER-TRACTORS: EARTH MOVING, HYDRAULIC OPERATED, 12 AND 20 CUBIC YARD MINIMUM HEAPED CAPACITY, DED

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME *(Last, First, Middle Initial)*	b. ORGANIZATION	
c. ADDRESS *(Include Zip Code)*	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON *(if applicable)*	**7.DATE SUBMITTED** (YYMMDD)

8. PREPARING ACTIVITY

a. NAME R. E. PAMPLONA	b. TELEPHONE *Include Area Code)* (1) Commercial 805-982-5843 (2) AUTOVON 551-5843
c. ADDRESS *(Include Zip Code)* OFFICER IN CHARGE, SEABEE LOGISTICS CENTER CODE 15E2, 4111 SAN PEDRO ST. PORT HUENEME, CA 93043-4410	**IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT:** DEFENSE QUALITY AND STANDARDIZATION OFFICE 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22401-3466 Telephone (703) 756-2340 AUTOVON 289-2340

Source: https://assist.dla.mil/Document Id: 2026-10-26T10:07Z
Check the source to verify that this is the current version before use.