NOT MEASUREMENT SENSITIVE

MIL-DTL-11132/52B
1 July 2020
SUPERSEDING
MIL-DTL-11132/52A
27 August 2015

DETAIL SPECIFICATION SHEET

BADGE, QUALIFICATION, PRE-HEALTH, ROTC, U.S. AIR FORCE

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-I-11132.



MATERIAL: Red Brass 85/15 (UNS Alloy No. C-230) or Nickel Silver 65/35 (UNS Alloy No C-752)

FINISH: Nickel Plated, (C-230 only), Mirror-like Polished and shall match The Institute of Heraldry Metal Finish Chip Number 16

DIMENSIONS:
HEIGHT: 1-1/8 inches (REF)
WIDTH: 15/16 (REF)
THICKNESS (At thickest point): 0.115 inch $\pm$ 0.010 inch

ATTACHING DEVICE:
1. The attaching device shall be prong and wing type clutch.

2. Two prongs shall be located on the vertical center line, equidistant from each end and 11/16 inch $\pm$ 1/64 inch apart.

AMSC N/A FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:26Z
Check the source to verify that this is the current version before use.

NOTE:
The term (REF) refers to the measurements taken from the Government furnished hub or die.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - IH
Air Force - 11

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2020-372)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:26Z
Check the source to verify that this is the current version before use.