INCH-POUND


MIL-DTL-11132/54C
14 November 2016
SUPERSEDING
MIL-DTL-11132/54B
10 January 2009

DETAIL SPECIFICATION SHEET


BADGE, QUALIFICATION, MARKSMANSHIP, MARKSMAN, ARMY JROTC

This specification is approved for use by all
Departments and Agencies of the Department of Defense.


The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-11132.



ASSEMBLED (See Note 2.)



PENDANT



SUSPENSION BAR

QUALIFICATION BARS

DASH NO.
-1: Air Rifle Qualification Bar
-2: Small Bore Rifle Qualification Bar

MATERIAL: Red Brass 85/15 (UNS Alloy No. C-230)

FINISH: Nickel Plated, Silver Plated, Oxidized, Relieved, and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 14.

DIMENSIONS:
SUSPENSION BAR (JROTC):
WIDTH: 1-1/2 inches (REF)
HEIGHT (including built-in suspension rings) 5/8 inch (REF)
THICKNESS (at thickest point): 0.081 ± 0.005 inch
PENDANT (Target):
DIAMETER (circumscribed; includes top & bottom built-in suspension rings):
1-7/16 inches (REF)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:26Z
Check the source to verify that this is the current version before use.

THICKNESS (at thickest point): 0.071 ± 0.005 inch
QUALIFICATION BAR (-1 or -2):
-1: AIR RIFLE:
WIDTH: 1-1/2 inches (REF)
HEIGHT (includes top & bottom built-in suspension rings): 1/2 inch (REF)
THICKNESS (at thickest point): 0.081 ± 0.005 inch
-2: SMALL BORE RIFLE:
WIDTH: 1-1/2 inches (REF)
HEIGHT (includes top & bottom built-in suspension rings): 1/2 inch (REF)
THICKNESS (at thickest point): 0.081 ± 0.005 inch

ATTACHING DEVICE:

1. Attaching device shall be prong and wing-type clutch.

2. Two prongs shall be located on the horizontal center line of the suspension bar, equidistant from each end and 1-1/4 inches ± 1/32 inch apart.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Badge shall be assembled with either the -1 or the -2 qualification bar.

3. Suspension rings and lugs shall be integral and pierced.

4. Links (jump rings) shall be fabricated from nickel plated wire with a nominal diameter of 0.050 ± 1/64 inch. The overall dimension of the links shall be 7/32 inch ± 1/64 inch in length by 5/32 inch ± 1/64 inch in width.

6. A forcer may be used to bring up the designs of the suspension bar and pendant.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2017-032)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:26Z
Check the source to verify that this is the current version before use.