MIL-S-11141F
7 October 1969
SUPERSEDING
MIL-S-11141E(MU)
6 September 1967

MILITARY SPECIFICATION

SMOKE POT, OIL, SGF2, M6

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers one type of smoke pot.

2. APPLICABLE DOCUMENTS

2.1 Government documents. The following documents of the issue in effect on date of Invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

PPP-F320- Fiberboard; Corrugated and Solid, Sheet Stock (Container Grade), and Cut Shapes.

MILITARY

MIL-P-116 - Preservation, Methods Of.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129- Marking for Shipment and Storage.

FSC 1365

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:28Z
Check the source to verify that this is the current version before use.

DRAWINGS

US ARMY MUNITIONS COMMAND

EDGEWOOD ARSENAL

DL11-7-20	- Packaging, Smoke Pot.
DL11-18-3	- Smoke Pot, Oil, SGF2, M6.
IDL11-18-3	- Smoke Pot, Oil, SGF2, M6 - Inspection Data List

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials and components.

3.1.1 Materials. All materials cited on Drawing DL11-18-3 or on the subsidiary drawings shall conform to the specifications listed thereon or to the specific characteristics set forth on the drawings.

3.1.2 Components. All components of the smoke pot shall conform to the specifications and drawings listed on Drawing DL11-18-3 and subsidiary drawings.

3.2 Assembly. The smoke pot shall be assembled as shown on Drawing D11-18-3.

3.3 Compartment leakage (drawing C11-9-62).

3.3.1 Empty. The compartment when subjected to an internal air pressure of 5.0 ± 0.5 pounds per square inch gage (psig) shall not leak air when tested as specified in 4.4.4.1(a).

3.3.2 Filled. The filled and closed compartment shall not leak fog oil when tested as specified in 4.4.4.1(b).

3.4 Filling.

3.4.1 Fuel block. The container shall be filled with approximately 75 grams (g) of fuel mixture, 10 ± 1 g of starter mixture and approximately 0.5 g of matchhead mixture (see 6.3 and 6.4). The fuel block shall be consolidated under a minimum dead-load of 6 tons.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:28Z
Check the source to verify that this is the current version before use.

3.4.2 Fog oil. The compartment (Drawing C11-9-62) shall contain 110 ± 2 g of fog oil and the filling hole sealed in accordance with Drawing C11-9-70, when tested as specified in 4.4.4.3.

3.5 Rough handling leakage. The smoke pots packed in accordance with 5.2 shall not leak fog oil when tested as specified in 4.3.4.

3.6 Functioning. The smoke pot shall ignite and emit a continuous cloud of smoke under pressure for no less than 45 seconds nor more than 105 seconds when tested as specified in 4.4.4.4.

3.7 Preproduction. Prior to the start of regular production, a pre-production lot of smoke pots shall be produced in accordance with this specification for examination and tests (see 4.3).

3.8 Workmanship. The smoke pot shall be free from foreign matter (oil or grease) and damage such as cracks, dents or deformation which could affect its use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibilitv for inspection.

4.1.1 Supplier's responsibility. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to specified requirements.

4.1.2 Objective evidence. The supplier shall provide evidence acceptable to the contracting officer that the requirements of 3.1, 3.4.1, and section 5 for which specific inspection has not been provided in this specification have been satisfied.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) Preproduction inspection (see 4.3)
(b) Quality conformance inspection (see 4.4)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:28Z
Check the source to verify that this is the current version before use.

4.3 Preproduction inspection.

4.3.1 Lot. Apreproduction lot of 200 smoke pots shall be manufactured using the same methods, materials, equipment, and processes as will be used during regular production.

4.3.2 Sampling.

4.3.2.1 For examination and nondestructive tests. Sampling shall be conducted in accordance with M1L-STD-105.

4.3.2.2 For destructive test (rough handling, leakage, and functioning). Sampling shall be conducted in accordance with MIL-STD-105 using an AQL of 1.0 percent defective. The unit of product for rough handling leakage test shall be the individual smoke pots, not the pack.

4.3.3 Inspection procedure. Examination and test shall be in accordance with table I (see 4.4.5). The sample taken for rough handling leakage shall be used for functioning test. Each smoke pot shall be tested in accordance with 4.4.4.1 (a).

Table I. Examinations and tests

Attribute	Examination or Test	AQL Percent defective
Classification of defects	4.4.3.1	As listed
Compartment leakage (empty)	4.4.4.1(a)	
Rough handling and leakage	4.3.4	1.0
Functioning	4.4.4.4	1.0
*Duds	4.4.4.4	1.0

*A dud is defined as a malfunction due to a mechanical or pyrotechnic failure.

4.3.4 Rough handling leakage and function test. Test shall be conducted as follows:

(a) Pack the sample as specified. In the event of a partial pack fill the void with fiberboard pads to form a tight pack.

(b) Drop the box eight times (one drop on each face of the box and one drop on each of the two diagonally opposite corners of the major axis of the box) from a height of 4 to 5 feet onto a concrete block 4± 1 inches thick or onto a rigid steel surface.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:28Z
Check the source to verify that this is the current version before use.

(c) Store the box fuze end down for a period of 48.5 ± 1.0 hours at ambient temperature.

(d) Remove the smoke pots from the box and remove the fuze.

(e) If there is no evidence of leakage, reassembly the fuze, and test as specified in 4.4.4.4.

4.3.5 Acceptance/rejection criteria. The preproduction lot shall meet the examinations and tests specified herein to be acceptable. The supplier shall obtain written approval from the contracting-officer prior to proceeding with regular production.

4.4 Quality conformance inspection.

4.4.1 Lot. A lot shall consist of the smoke pots produced by one manufacturer, of one interfix number, at one plant, in one unchanged process, in accordance with the same drawings, same drawing revision, the same specification and specification revision. However, no more than one interfix lot of ingredients from one manufacturer shall be used in the pyrotechnic formulation, and no more than one interfix lot of fuzes shall be represented in any one interfix lot of finished smoke pots.

4.4.2 Sampling.

4.4.2.1 For examination and nondestructive tests. Sampling shall be conducted in accordance with M1L-STD-105. The inspection level for “fuel block and nozzle clearance” shall be S-4.

4.4.2.2 For destructive tests (functioning). Sampling shall be conducted in accordance with M1L-STD-105, level S-4, using an AQL of 1.0 percent defective.

4.4.3 Inspection procedure. Examination and test shall be in accordance with table I (4.3.3). Each smoke pot shall be tested in accordance with 4.4.4.1 (a).

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:28Z
Check the source to verify that this is the current version before use.

4.4.3.1 Classification of defects. (See inspection data list IDL11-18-3 for inspection equipment required to perform the examinations prescribed in this section,)

(a)Smoke pot, oil, SGF2, M6 (Dwg D11-18-3).

Categories		Defects	Acceptance standards
Critical		None defined	
Major:	AQL	0.65 percent defective	
101		Compartment leakage (filled)	4.4.4.1(b)
Major:	AQL	1.0 percent defective	
102		Component missing or incorrectly assembled	
103		Screen holes misaligned	
104		Vent hole missing (Dwg C11-9-62)	
105		Length to offset incorrect (Dwg C11-9-57)	
106		Length (0.656) incorrect (Dwg C11-9-57)	
107		Length incorrect (Dwg D11 -9-66)	
108		Matchhead mixture covered with shellac	
109		Length (2.61) incorrect (Dwg C11-9-62)	
110		Filling weight incorrect	4.4.4.3
111		Workmanship (3.8)	
112		Fuel block and nozzle clearance	4.4.4.2
Minor:	AQL	2.5 percent defective	
201		Marking missing, illegible or incorrect	
202		Protective finish marred to bare metal or incorrect	
203		Torque in fuze incorrect	

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:28Z
Check the source to verify that this is the current version before use.

4.4.3.1 Classification of defects (continued).

(b) Preparation for delivery (section 5).

Categories	Defects
Critical:	None defined
Major:	AQL 2.5 percent defective
101	Instruction card missing or incorrect
102	Loose pack
103	Strapping missing or loose
104	Marking incorrect
Minor:	AQL 4.0 percent defective
201	Marking missing or illegible
202	Packing arrangement in shipping container incorrect
203	Key missing

4.4.4 Tests.

4.4.4.1 Compartment leakage.

(a) Empty The compartment shall be tested for leakage using the Q163 air leakage tester.

(b) Filled. The filled and closed compartment shall be placed horizontlly with the filling plug down, subjected to a temperature of 1450 ± 50F for a period of 4.0 ± .5 hours and then examined for leaks.

4.4.4.2 Fuel block and nozzle clearance. The smoke pot shall be radiographically inspected for fuel block and nozzle clearance using Inspection Standard R10-1 (see 6.2).

4.4.4.3 Fog oil weight. The weight of the oil shall be determined by subtracting the average weight of the empty compartment plus closure components from the average weight of the filled and closed compartments.

4.4.4.4 Functioning The smoke pot shall be functioned as specified on Drawing B11-18-4 except that portion of note 4 “place the smoke pot in a bucket or large metal can” shall be optional. The smoke pot shall emit a continuous cloud of smoke under pressure for the specified time (see 4.4.5).

Source: https://assist.dla.mil -- Downloaded: 202640-17T15:28Z
Check the source to verify that this is the currentversion before use.

4.4.5 Fuze failure. Independent of the disposition of the lot in accordance with 4.4.3.1 and 4.4.4.4, smoke pot failures solely due to malfunctioning of the fuze shall be evaluated in accordance with MIL-STD-105 using an AQL of 2.5 percent defective. Final disposition of the smoke pot lot shall be based upon the number of malfunctioning fuzes found in the original sample of smoke pots tested, provided all other requirements are met. Refuzing the smoke pots which had fuze failures is permitted in order to complete testing and evaluation for smoke pot performance requirements, unless the number of defective permitted in 4.4.3.1 has been exceeded or the requirements for burning time have not been met.

5. PREPARATION FOR DELIVERY

5.1 Packaging, level A. The smoke pots shall be individually packaged as specified on Drawing C11-7-20. Two keys, Drawing D22-129-1, shall be packaged together in accordance with method IC-1 of MIL-P-116, except preservative is not required.

5.2 Packaging, level A. Sixteen smoke pots, packaged as specified in 5.1, shall be packed together in one layer in either an overseas type, style I of PPP-B-601; class 2, style 4, for a type 2 load, of PPP-B-621; or a type I, class 2, grade A of MIL-B-46506 wood shipping container. The inside dimension of the shipping container shall be 11 by 11 by 6-5/8 (length, width and depth respectively). The wood shipping container, and all wood parts thereof, shall be completely imnersed for a minimum of three minutes in a water-repellent wood preservative conforming to Composition A of TT-W-572. Prior to packing the smoke pots in the treated shipping container, the preservative shall be dry when tested for dryness in accordance with MIL-5-2427. Fiberboard pads, conforming to grade W5c of PPP-F-320 shall separate the contents from the sides, ends, top and bottom of the shipping container. Additional pads shall be used as required to insure a tight pack. One instruction card, conforming to drawing B11-18-4, and one package containing two keys (see 5.1) shall be in the shipping container on top of the packed smoke pots. Closure of the shipping container shall be in accordance with the appendix to the applicable box specification, using galvanized strapping.

5.3 Marking. In addition to any special marking required by the contract or order, Interior packages shall be marked in accordance with Drawing C11-7-20 and MIL-STD-129. Shipping containers shall be marked in accordance with Drawing D11-8-8. Sufficient drying time shall be allowed after application of the wood preservative, to insure that all marking shall be clean, legible and permanent.

5.4 Palletization. When specified in the contract or order, shipping containers shall be palletized in accordance with Drawing D11-8-7.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:28Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. This smoke pot is intended for use in training troops.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.

(b) Preproduction.

(1) Time allowed for supplier submission of samples for Government test and evaluation after award of contract.
(2) Name and address of test facility and shipping instructions when testing is performed by the Government.
(3) Time required for the Government to notify the supplier whether or not to proceed with regular production.

(c) The R10-1- Inspection Standard, Smoke Pot, Oil, SGF2, M6 - will be Government furnished.

6.3 Suggested manufacturing. The following has been found to be a satisfactory procedure. The body should be placed in a mold and approximately 75 g (2.64 oz) of the fuel mixture added. The mixture should then be tamped down to present a firm, smooth surface. Ten g (0.35 oz) of the starter mixture should be poured over the fuel mixture and tamped again to present a firm, smooth surface. Approximately 0.5 g (0.018 oz) of matchhead mixture 1 should be added, in the center and the whole consolidated under a minimum dead-load (see 3.4.1), using a flat-faced ram. This information is advisory and it is understood that the requirements of 3.6 must be met regardless of the weights of mixtures used.

6.4 Precaution. Due to the hazards inherent in filling munitions with chemical agents, filling installations are advised to protect personnel from injury while filling smoke pots.

Custodian:

Army - MU
Navy - AS
Air Force - 70

Preparing activity:

Army - MU(EA)

Review activities:

Navy - 0S
Air Force - 70

Project No. 1365-0160

User activities:

Navy - MC

Source: https://assist.dla.mil -- Downloaded: 202610-17T15:28Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:28Z
Check the source to verify that this is the current version before use.

TO DETACH FORM - CUT ON THIS LINE

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE | CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)* | DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:28Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID

OFFICIAL BUSINESS

Commanding Officer
Edgewood Arsenal
ATTN: SMUEA-QAES
Edgewood Arsenal, Maryland 21010

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:28Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:28Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:28Z
Check the source to verify that this is the current version before use.

NOTICE OF INACTIVATION FOR NEW DESIGN

INCH-POUND

MIL-S-11141F
NOTICE 1
19 April 1996

MILITARY SPECIFICATION

SMOKE POT, OIL, SGF2, M6

'This notice should be filed in front of MIL-S-11141F dated 7 October 1969.

MIL-S-11141F is inactive for new design and is no longer used except for replacement purposes.

Custodian:

Army - EA
Navy - AS
Air Force - 99

Preparing activity:

Army - EA

(Project 1365-0267)

Review Activities:

Navy - OS, MC
Air Force -70

AMSC N/A

FSC 1365

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:28Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:28Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:28Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:28Z
Check the source to verify that this is the current version before use.