MILITARY SPECIFICATION

ADAPTER, SAFETY FOR FUZE, PD, M720 (LESS BOOSTER PELLET AND LEAD CUP CHARGE)

1. SCOPE

1.1 This specification covers the parts and assembly less the booster pellet and lead cup charge for one type of safety adapter designated as Adapter, Safety for Fuze, PD, M720.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposals form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-2550 - Ammunition and Special Weapons, General Specification for
MIL-I-45607 - Inspection Equipment, Supply and Maintenance of

STANDARDS

FEDERAL

FED-STD-151 - Metals, Test Methods

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)
MIL-STD-109 - Quality Assurance Terms and Definitions
MIL-STD-331 - Fuze and Fuze Components, Environmental and Performance Tests for
MIL-STD-639 - Surface Roughness Values Preferred for Army Ordnance Materiel

FSC: 1390

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:14Z
Check the source to verify that this is the current version before use.

MIL-STD-1168 - Lot Numbering of Ammunition
MIL-STD-1235 - Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

DRAWINGS

ARMY

8595508 - Cup, Closing
8595509 - Cup, Booster
9229637 - Safety Adapter with Booster for Fuze, PD, M720
9229638 - Safety Adapter for Fuze, PD, M720
9277282 - Packing and Marking for Box, Packing Ammo for Boosters without cups
9277283 - Box, Packing Ammunition for Boosters without cups
9277284 - Tray, Nesting for Boosters without cups

PUBLICATIONS

ARMY

ET-9229638 - Equipment Tabulation

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer.)

3. REQUIREMENTS

3.1 Material. - Materials shall be in accordance with applicable drawings and specifications.

3.2 Parts and Assemblies. - The parts and assemblies shall comply with all requirements specified on the applicable drawings and with all requirements specified in the applicable specifications except as provided in 6.5.

3.3 Jolt and Jumble. - The safety adapter shall comply with the requirements of MIL-STD-331, Test Nos. 101 and 102 when tested as specified in 4.3.3.5 and 4.4.5.

3.4 Transportation Vibration. - The safety adapter shall comply with the requirements of MIL-STD-331, Test No. 104 when tested as specified in 4.3.3.6 and 4.4.6.

3.5 Arming and Non-Arming. - The safety adapter shall meet the arming and non-arming requirements of drawing (dwg.) 9229638 when tested as specified in 4.4.3 and 4.4.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:14Z
Check the source to verify that this is the current version before use.

3.6 Proving Ground. - The safety adapter with booster shall comply with the following requirements when tested as specified in 4.4.7.

3.6.1 Arming Safety. - The safety adapter with booster shall not detonate the round when fired against a vertical target placed at a distance of 25 feet from the muzzle of the weapon.

3.6.2 Arming. - The safety adapter with booster shall detonate the round high order when fired against a vertical target placed at a distance of 160 feet from the muzzle of the weapon.

3.6.3 Ground or Water Impact Functioning. - The safety adapter with booster shall detonate the round high order when fired for impact on ground or water at an angle of 45° maximum at a distance of 1000 meters from the muzzle of the weapon.

3.6.4 Safety. - The safety adapter with booster shall not function prematurely.

3.7 Workmanship. - All parts shall be fabricated and finished in a thorough, workmanlike manner. They shall be free of burrs, sharp edges, cracks, unblended radii, chips, dirt, grease, corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. All required markings shall be neat and sharply defined. The requirements for surface finish are as detailed on the applicable drawings and MIL-STD-639.

3.8 First Article Inspection. - This specification makes provisions for first article inspection. Requirements for submission of first article samples by the contractor shall be as specified in the contract.

4. QUALITY ASSURANCE PROVISIONS

4.1 General Quality Assurance Provisions. - Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to Standard MIL-STD-109 in order to define terms used herein. The provisions of Specification MIL-A-2550 shall apply.

4.1.1 Submission of Product. - At the time the completed lot of product is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:14Z
Check the source to verify that this is the current version before use.

information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all of the quality assurance provisions specified within this specification.
b. Number of units of product inspected.
c. Results obtained, by defect code, for all inspections performed.
d. Drawing, specification number and date, together with an identification and date of changes.
e. Certificate of conformance on all material purchased by the contractor when such material is controlled by Government or commercial specifications referenced in any of the contractual documents.
f. Number of items in the lot.
g. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates, unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.2 First Article Inspection

4.2.1 Submission. - The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.2.2. The first article sample shall consist of the following:

20 each of two component parts (40 aggregate) as delineated in 4.3.3.3.
25 each of three subassemblies (75 aggregate) as delineated in 4.3.3.4.
80 assemblies (aggregate) as delineated in 4.3.3.5.1, 4.3.3.6.1, 4.3.3.7.2.1, 4.3.3.7.3.1 and 4.3.3.7.4.1.

The first article shall be that which has been produced by the contractor or furnished by a supplier and which have been manufactured using the same production processes, procedures and equipment which will be used in fulfilling the contract. All parts and materials, including packaging and packing, shall be obtained from the same source of supply as will be used in regular production. Prior to submission, the contractor shall inspect the sample to the degree necessary to assure that it conforms to the requirements of the contract and submit a record of this inspection with the sample, including statements of findings for materials, processes and tests. A sample containing known defects will not be submitted unless specifically authorized by the Contracting Officer. A first article sample, or portion thereof as directed by the Contracting Officer, shall also be submitted whenever there is a lapse in production for a period in excess of 90 days or whenever a change occurs in manufacturing process, material used, drawing or specification such as to significantly affect product uniformity as determined by the Government.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:14Z
Check the source to verify that this is the current version before use.

4.2.2 Inspections to be Performed. - Assemblies and components will be subjected by the Government to any or all of the examinations or tests specified in 4.3.2 or 4.3.3 of this specification and any or all requirements in the applicable drawings.

4.2.3 Proving Ground Testing. - From the sample quantity required in 4.2.1 , 60 safety adapter assemblies shall be forwarded to a Government facility designated by the Contracting Officer to be loaded and assembled as complete safety adapters with boosters, which will be forwarded to a Government proving ground for testing in accordance with 4.3.3.7.

4.2.4 Rejection - If any component parts, subassembly or assembly fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate its inspection upon any failure of a component part, subassembly or assembly to comply with any of the stated requirements.

4.3 Inspection Provisions

4.3.1 Lot Formation. - The term "lot" as used throughout this specification refers to an inspection lot, which is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance of the lot with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the lot has been produced by one manufacturer, in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Changes to the process, specification or drawing not affecting safety, performance, interchangeability or storage, as determined by the Government, shall not be deemed to alter the homogeneity of the lot. Inspection lots shall comply with MIL-STD-105. Unless otherwise approved by the Contracting Officer, the inspection lot size of end items deliverable under the contract shall be not less than the smallest weekly estimate of quantities contractually scheduled for production during the contract period, nor more than the largest monthly quantity contractually scheduled for delivery during the contract period. Inspection lots for components or subassemblies, other than the items of delivery, shall be homogeneous and of a size mutually convenient to both the contractor and the Government Inspector. Each lot of safety adapter metal parts shall be numbered in accordance with MIL-STD-1168. Each lot shall contain:

a. Component parts of one interfix lot number from one manufacturer.
b. Subassemblies of one interfix lot number from one manufacturer.
c. Assemblies of one interfix lot number from one manufacturer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:14Z
Check the source to verify that this is the current version before use.

4.3.2 Examination.-Inspection for Critical defects (and Major defects, when so specified), shall be 100 percent. Sampling plans and procedures for Major and Minor defects shall be in accordance with MIL-STD-105 except that continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the procuring activity. Also, at the option of the procuring activity, AQL's and sampling plans may be applied to individual characteristics listed using an AQL of 0.65 percent for each Minor defect and an AQL of 0.40 percent for each Major defect, except where 100 percent inspection is specified. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.3.4.

4.3.2.1 Cup, closing (see dwg. 8595508).

Categories	Defects	Method of Inspection	Code No.
Critical:			
	1. Split, cut or crack, in cup	Visual	01001
Major:	AQL 0.65 percent		
	101. Length under flange	Gage	01002
	102. Outside diameter, maximum (max)	Gage	01003
	103. Thickness of base	Gage	01004
	104. Foreign matter	Visual	01005
Minor:	AQL 0.65 percent		
	201. Evidence of poor workmanship (see 3.7)	Visual	01006

4.3.2.2 Cup, booster (see dwg. 8595509)

Categories	Defects	Method of Inspection	Code No.
Critical: None defined			
Major:	AQL 1.0 percent		
	101. Inside diameter, (max.)	Gage	02001
	102. Pitch diameter of threads	Gage	02002
	103. Minor diameter of threads	Gage	02003
	104. Outside diameter	Gage	02004
	105. Length of thread, (min)	Gage	02005
	106. Defective metal	Visual	02006
	107. Cut, score, or gouge on inside wall ..	Visual	02007
	108. Foreign matter	Visual	02008

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:14Z
Check the source to verify that this is the current version before use.

Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.7)	Visual	02009

4.3.2.3 Body (see dwg. 8595537 covering a detail of dwg. 9229638).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 1.5 percent		
101.	Pitch diameter of large external thread	Gage	03001
102.	Major diameter of large external thread	Gage	03002
103.	Pitch diameter of small external thread	Gage	03003
104.	Major diameter of small external thread	Gage	03004
105.	Pitch diameter of internal thread	Gage	03005
106.	Minor diameter of internal thread	Gage	03006
107.	Effective length of internal thread	Gage	03007
108.	Overall length of body (max)	Gage	03008
109.	Diameter of M hole, (min)	Gage	03009
110.	Staking hole in thread, missing ..	Visual	03010
111.	Burrs	Visual	03011
112.	Defective metal	Visual	03012
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.7)	Visual	03013

4.3.2.4 Safety adapter Sub-assembly (see dwg. 9229638).

Categories	Defects	Method of Inspection	Code No.
Critical:			
1.	Interference condition which precludes return of either spring-loaded detent from the fully open position to the position of engagement in the rotor recess. (Check prior to non-arming test)	Visual/ Manual	04001

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:14Z
Check the source to verify that this is the current version before use.

2.	Rotor not locked in unarmed position (see 6.6.3) (Check immediately prior to packing)	Visual/ Manual	04002
Major:	AQL 1.0 percent		
101.	Length from base of body to top of plates, (max.)	Gage	04004
102.	Loose cover plate	Visual/ Manual	04005
103.	Any part missing	Visual	04006
104.	Any part broken or deformed	Visual	04007
105.	Staking hole missing	Visual	04008
106.	Staking missing or inadequate	Visual	04009
107.	Burrs	Visual	04010
108.	Foreign matter	Visual	04011
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.7)	Visual	04012

4.3.2.5 Safety Adapter with Booster (less lead charge and booster pellet) (see dwg. 9229637).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	None defined		
Minor:	AQL 1.0 percent		
201.	Marking missing, incorrect or illegible	Visual	05001
202.	Evidence of poor workmanship (see 3.7)	Visual	05002

4.3.2.6 Packing and Marking for Box, Packing Ammunition for Boosters without Cups (see dwg. 9277282).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.40 percent		
101.	Assembly damaged so that contents are exposed or likely to become exposed	Visual	06001

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:14Z
Check the source to verify that this is the current version before use.

Minor:	AQL 1.5 Percent		
201.	Contents move when shaken	Manual	06003
202.	Marking misleading, incorrect or illegible	Visual	06004
203.	Label missing	Visual	06005

4.3.2.7 Box, Packing, Ammunition for Boosters without Cups (see dwg. 9277283).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 1.0 Percent		
101.	Board broken	Visual	07001
102.	Hardware missing, broken or loose .	Visual-Manual	07002
103.	Contents exposed	Visual	07003
104.	DOD code marking missing, misleading or illegible	Visual	07004
105.	Strapping missing, broken or loose	Visual	07005
Minor:	AQL 1.5 Percent		
201.	Hardware improperly applied or engaged	Visual-Manual	07006
202.	Contents move when shaken	Manual	07007
203.	Car seal missing, unsealed or improperly positioned	Visual-Manual	07008
204.	Marking misleading, incorrect or illegible	Visual	07009

4.3.3 Testing

4.3.3.1 Arming - Major Defect - Code No. 08001. - This test shall be performed 100 percent. Any safety adapter whose rotor fails to become locked-in with the detonator in line with the flash hole, when subjected to the arming spin requirement of dwg. 9229638, shall be classified as a defective and removed from the lot. The tests shall be performed as specified in 4.4.3 using equipment in accordance with 4.3.4.

4.3.3.2 Non-Arming - Critical Defect - Code No. 09001. - This test shall be performed 100 percent, subsequently to the arming test of 4.3.3.1. Any safety adapter whose spring loaded detents fail to remain locked in the rotor when subjected to the non-arming spin requirement of dwg. 9229638 shall be

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:14Z
Check the source to verify that this is the current version before use.

classed as defective and removed from the lot. The test shall be performed as specified in 4.4.4 using equipment in accordance with 4.3.4.

4.3.3.3 Hardness - Major Defect - Code No. 10001. - Twenty (20) samples from each lot of the following components shall be subjected to the hardness test. This test shall be performed as specified in 4.4.1 and FED-STD-151 using equipment in accordance with 4.3.4. Failure of any of these components to comply with the applicable requirements shall be cause for rejection of the lot.

Component Part	Drawing Number
Wheel, Escape	8595539
Pin, Balance	8595540

4.3.3.4 Static Load - Major Defect - Code No. 11001. - Twenty-five (25) samples from each lot of the following subassemblies shall be subjected to the static load test. This test shall be performed as specified in 4.4.2 using equipment in accordance with 4.3.4. Failure of any subassembly to comply with the applicable requirements shall be cause for rejection of the lot.

Subassemblies	Drawing Number
No. 1 Gear and Pinion Assembly	8594673
No. 2 Gear and Pinion Assembly	8574681
Escape Wheel Assembly	8595538

4.3.3.5 Jolt and Jumble - Critical Defect - Code No. 12001

4.3.3.5.1 First Three Lot Testing. - Beginning with the first lot produced and continuing until three consecutive lots have complied with the applicable requirements when tested in 4.4.5, a sample of ten (10) assemblies shall be randomly selected from each lot for these tests. If any assembly fails to comply with the applicable requirements, the lot shall be rejected.

4.3.3.5.2 Subsequent Lot Testing. - After three consecutive lots have met the criteria specified in 4.3.3.5.1, a sample of five (5) assemblies shall be selected from each lot for these tests. If any assembly fails to comply with the applicable requirements, the lot shall be rejected.

4.3.3.6 Transportation Vibration - Critical Defect - Code No. 13001

4.3.3.6.1 First Three Lot Testing. - Beginning with the first lot produced and continuing until three consecutive lots have complied with the applicable requirements when tested as specified in 4.4.6, a sample of ten

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:14Z
Check the source to verify that this is the current version before use.

(10) assemblies shall be selected from each lot for these tests. If any assembly fails to comply with the applicable requirements, the lot shall be rejected.

4.3.3.6.2 Subsequent Lot Testing. - After three consecutive lots have met the criteria specified in 4.3.3.6.1, a sample of five (5) assemblies shall be selected from each lot for this test. If any assembly fails to comply with the applicable requirements, the lot shall be rejected.

4.3.3.7 Proving Ground

4.3.3.7.1 Premature Burst - Critical Defect - Code No. 14001

4.3.3.7.2 Arming Safety - Critical Defect - Code No. 15001

4.3.3.7.2.1 Lot Testing. - A sample of 20 assemblies shall be randomly selected from each lot for this test. If one or more assemblies fail to meet the non-arming requirement, the lot shall be rejected. Testing shall be conducted in accordance with 4.4.7.1.

4.3.3.7.3 Arming - Major Defect - Code No. 16001

4.3.3.7.3.1 Lot Testing. - A sample of 40 assemblies shall be randomly selected from each lot for this test. If two or more assemblies fail to meet the arming requirement, the lot shall be rejected in accordance with 4.4.7.2.

4.3.3.8 Retest. - If for any reason the proof director considers that the test conditions have detrimentally affected the test results, he shall declare the results invalid and perform a new test on additional samples as required.

4.3.4 Inspection Equipment. - The inspection equipment required to perform the examinations and tests prescribed in this section is identified by Equipment Tabulation ET-9229638 (see 6.3).

4.3.4.1 Government Rights to Documentation. - Inspection equipment drawings and lists provided and revised in accordance with the requirements of the ET may be used by DOD activities for design, procurement, manufacture, testing, evaluation, production and receiving inspection, overhaul, shipping, storage, identification of items at overhaul, general maintenance of equipment, construction, survey and whenever inspection equipment drawings are needed.

4.3.4.2 Supply and Maintenance. - Supply and maintenance of the equipment listed on the ET shall be in accordance with Specification MIL-I-45607.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:14Z
Check the source to verify that this is the current version before use.

4.3.4.3 Government Use of Contractor's Inspection Equipment. - The contractor shall make available to the Government all inspection equipment necessary for determining conformance with contract requirements. Personnel for operating the equipment and verification of its accuracy shall be supplied by the contractor for the performance of examination or test by the Government.

4.4 Test Methods and Procedures

4.4.1 Hardness. - The test shall be performed using the value as specified on the applicable drawing. The sample units shall be tested in an area which is solidly supported in order to obtain valid readings. The median value of three hardness readings taken on each sample unit shall be used as the individual reading. All tested samples shall be scrapped.

4.4.2 Static Load. - The sample units shall be tested to the value specified on the applicable drawing. All tested samples shall be scrapped.

4.4.3 Arming. - The unarmed safety adapter shall be spun (in a counterclockwise direction when viewed from the top) for a period of ten (10) seconds max. at a constant rpm as specified on dwg. 9229638. The safety adapter shall be in the armed position at the completion of the test. After the test has been performed, the rotor shall be returned to the unarmed position (see 6.6.1 and 6.6.3).

4.4.4 Non-Arming. - The unarmed safety adapter shall be spun (in a counterclockwise direction when viewed from the top) for a period of three (3) seconds min. at a constant rpm as specified on dwg. 9229638. The safety adapter shall not be armed at the completion of the test. The non-arming test shall be the last spin to which the safety adapter is subjected prior to packing.

4.4.5 Jolt and Jumble. - The safety adapter assemblies shall be tested in accordance with the procedures specified in MIL-STD-331, Test Nos. 101 and 102, except that after completion of the jolt test, the assemblies shall not be disassembled but shall be subjected to the jumble test. The assemblies shall then be disassembled to determine compliance with the applicable requirements.

4.4.6 Transportation Vibration. - The safety adapters shall be tested in accordance with the procedures specified in MIL-STD-331, Test No. 104. After this test, the safety adapter shall also be subjected to the arming and non-arming requirements (see dwg. 9929638).

4.4.7 Proving Ground. - These tests shall be conducted at a Government proving ground in accordance with the acceptance test procedure. The sample safety adapters shall be assembled to complete XM657E2 cartridges, inert-loaded with T2 supplementary charge and fired from a 152MM gun cannon.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:14Z
Check the source to verify that this is the current version before use.

4.4.7.1 Arming Safety. - The test samples shall be fired against a suitable supported one inch plywood target of adequate size plated 25 feet from the muzzle of the weapon. The safety adapter with booster shall not detonate the round prior to or upon impact with this target. Observation for impact element functioning is required.

4.4.7.2 Arming. - The test samples shall be fired against a suitable supported one inch plywood target of adequate size placed 160 feet from the muzzle of the weapon. The safety adapter with booster shall detonate the round high order upon impact with this target. Observation for impact element functioning is required.

5. PREPARATION FOR DELIVERY

5.1 Packing

5.1.1 Level C. - The safety adapter shall be packed as specified in dwg. 7548175 with the exceptions as noted in 5.1.2.

5.1.2 Closing cups (dwg. 8595509) and booster cups (dwg. 8595509) may be shipped separately in accordance with the best commercial practices.

5.2 Marking. - Marking shall be as specified in dwg. 7548175.

6. NOTES

6.1 Ordering Data. - Procurement documents shall specify the following:

a. Title, number and date of this specification.

b. Data cards. - Data cards shall be prepared for each lot in accordance with the information specified in MIL-STD-1167.

6.2 Inspection Code Numbers. - The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government.

6.3 Inspection Equipment Designs. - Inspection equipment designs are of two types - Government Special Inspection Equipment (SIE) designs and contractor designs. SIE designs are designated by drawing numbers on the Equipment Lists referenced on the Equipment Tabulation. Design responsibility for all other inspection equipment is assigned to the contractor. Equipment to be designed by the contractor is designated "CD". The contractor need not furnish any design when a complete Government SIE design is provided. Unless otherwise specified, however, the contractor may submit alternate or modified contractor designs of SIE in accordance with 6.3.2 and 6.3.3 should he elect to do so.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:14Z
Check the source to verify that this is the current version before use.

6.3.1 SIE Designs. - SIE designs may consist of any of the following:

a. Detailed drawings which completely depict all information necessary for the fabrication and use of the item of inspection equipment.

b. A source control drawing or a specification control drawing as defined in MIL-STD-100.

c. An envelope drawing, as defined in MIL-STD-100, which establishes the criteria which a detail design shall meet. When envelope drawings are specified, the contractor shall prepare designs which comply with the criteria therein.

6.3.2 Contractor Designs. - Contractor designs are required for all inspection equipment for which SIE designs are not specified and may include commercial equipment which the contractor proposes to use. (Commercial equipment is defined as unmodified equipment which is cataloged and available for purchase by the general public.) Contractor designs shall include appropriate operating instructions, calibration procedures and maintenance procedures. Commercial equipment shall be fully described by catalog listings or other means which provide sufficient information to permit identification and evaluation by the Government and may include illustrations and engineering data. Designs shall be prepared for any special fixture(s) required to be used with commercial equipment or with SIE designs if not otherwise covered thereby (see 6.3.1.c). Designs shall be of the category and form (per MIL-D-1000 specified in the Contract Data Requirements Lists (DD Form 1423). The contractor is referred to MIL-HDBK-204, "Inspection Equipment Design" for guidance. The specification number and the applicable five-digit defect code number (or other specific identifying information) from Section 4 of this specification shall be referenced on each contractor design, together with the component or assembly drawing number and revision letter to which the specific design applies.

6.3.3 Submission of Designs for Approval. - Contractor designs shall be approved by the Government prior to fabricating or procuring the equipment. Designs shall be submitted for approval in accordance with the stipulations, time frame and distribution specified in the Contract Data Requirements List (DD Form 1423) or in the contract. Partial submission of inspection equipment designs is permissible and encouraged. However, the completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will normally be accomplished within one month after receipt.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:14Z
Check the source to verify that this is the current version before use.

6.5 Components manufactured in strict accordance with applicable drawings represent one set of conditions which will result in satisfactory performance. Dimensions which are specifically required by Classification of Defects, as listed in Section 4, and those which affect external profile assembly are mandatory. Pertaining to other dimensions, it is recognized that current mass production methods may occasionally produce parts which are not in full compliance with all dimensional requirements, but which may provide adequate safety adapter performance. Therefore the contractor, at his own risk, may utilize these parts provided there is no adverse effect on safety adapter functionability. This relaxation of requirements applies to "after the fact" deviations only, to dimensions only, on applicable drawings, and does not constitute authority to establish new dimensions or to relax efforts to achieve the specified limits. The procedure for accomplishing dimensional changes is available under the established engineering change system. Nothing above is to be construed as relieving the contractor of any responsibility in connection with performance of the safety adapter.

6.5.1 The contractor shall maintain records showing deviations from dimensional requirements, the extent of such deviations, the amount of material involved and the date the material is introduced into the assembly line. Copies of these records shall be forwarded to the agency assigned custody of the technical data.

6.6 Armed/Unarmed Safety Adapters

6.6.1 Armed. - Rotor is locked by the spring loaded rotor lock pin in the position in which the detonator is fully visible through the flash hole.

6.6.2 Partially Armed. - Rotor not locked by both spring loaded detents.

6.6.3 Unarmed. - Rotor locked by both spring loaded detents with the detonator not at all visible through the flash hole.

6.7 Submission of Test Data. - In addition to the normal distribution of records, when the booster is procured by the Department of the Army, one copy of all ballistic test data will be forwarded to each of the following:

Commanding Officer
Picatinny Arsenal
ATTN: SMUPA-QA-A-F and
SMUPA-AD-F-E
Dover, New Jersey 07801

6.8 This specification includes the requirements of PA-PD-3088 dated 25 January 1968.

Custodian:
Army-MU

Preparing Activity:
Army-MU

Project Number: 1390-A-002

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:14Z
Check the source to verify that this is the current version before use.

FOLD

Department of the Army
Picatinny Arsenal
Dover, New Jersey 07801

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD 314

OFFICIAL BUSINESS

Commander
Picatinny Arsenal
ATTN: SMUPA-QA-A
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:14Z
Check the source to verify that this is the current version before use.