MIL-B-63104A(AR)
29 AUGUST 1977

SUPERCEDING
MIL-A-63104(AR)
9 DECEMBER 1976

MILITARY SPECIFICATION

BODY ASSEMBLY (DUMMY), ALTERNATIVE, FOR M132, PARTS FOR AND LOADING ASSEMBLING AND PACKING

This specification is approved for use by the U.S. Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Departments and Agencies of the Department of Defense.

*1. SCOPE

1.1 This specification contains requirements not normally covered by the drawings and provides quality assurance for the fabrication of parts, assemblies and inert loading of a practice mine to simulate the M56 anti-tank mine.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. - The following documents of the issue in effect on date of invitation for bids or request for proposal, forms a part of this specification to the extent specified herein.

SPECIFICATIONS

MIL-W-12332 - Welding, Resistance, Spot, Seam and projection; For Fabrication, Assemblies of Low Carbon Steel.

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions General Specification For

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes

FSC: 1345

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:11Z
Check the source to verify that this is the current version before use.

MIL-STD-650 - Explosive: Sampling, Inspection and Testing
MIL-STD-1169- Packaging, Packing and Marking for Shipment of Inert Ammunition Component

DRAWINGS

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

9312801 - Body Assembly, Dummy - Alternative
9312807 - Mine Body Assembly, Weldment
9312851 - Packing and Marking For Box, Wood For Body Assembly, Dummy, Alternative

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer).

*3. REQUIREMENTS

3.1 Material. - Materials shall be in accordance with the applicable drawings and specifications.

3.2 Components and assembly. - The component and assembly shall comply with all requirements specified on drawing (dwg.) 9312801 or 9312807 and associated drawings and with all requirements specified in applicable specifications and standards.

3.3 Mechanical properties. - Cold-working or heat-treating (including quenching-and-tempering, normalizing, normalizing-and-tempering, annealing, and stress-relieving) operations, shall be performed in such a manner as to produce the specified properties uniformly throughout the entire lot. The contractor shall determine the detailed procedures to produce parts meeting the required mechanical properties. These procedures shall be documented and submitted with the first article sample to the Contracting Officer. Changes in these procedures shall also be documented and submitted to the Contracting Officer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:11Z
Check the source to verify that this is the current version before use.

3.4 First article inspection. - This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.5 Workmanship. - All parts and assemblies shall be fabricated and finished in a thorough, workmanlike manner. They shall be free of burrs, chips, sharp edges, cracks and surface cracks, unblended radii, surface defects, dirt, grease, and rust, corrosion products, and other foreign matter. The cleaning method used shall not be injurious to any parts, nor shall the parts be contaminated by the cleaning agents. All required markings shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

*4.1 Responsibility for inspection and standard quality assurance provision. - Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this specification.

*4.2 Classification of inspection. - The following type of inspections shall be conducted on this item:

a. First Article Inspection
b. Quality Conformance Inspection

* 4.3 First article inspection

4.3.1 Submission. - The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.3.2 and 4.3.3. The first article sahll consist of the quantities as indicated in Table I.

4.3.2 Inspections to be performed. - See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. - (See MIL-A-48078)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:11Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
	Body Assembly, Dummy - Alternative, For M132	1 OF 3	See Below
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Wire Body Assembly (Weldment) (Dwg. 9312807)				
	Examination for defects	25		3.2	4.4.2.1
	Weld Strength	10		3.2	4.5.3
	Fin Assembly, End (Dwg. 9312806)				
	Examination for Defects	25		3.2	4.4.2.2
	Fin Assembly, Side (Dwg. 9312805)				
	Examination for Defects	25		3.2	4.4.2.3
	Cap, End (Dwg. 9312804)				
	Examination for Defects	25		3.2	4.4.2.4
	Plate, Top (Dwg. 9321803)				
	Examination for Defects	25		3.2	4.4.2.5
	Body (Dwg. 9312802)				
	Examination for Defects	25		3.2	4.4.2.6

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:11Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS MIL-B-63104A(AR)

PARAGRAPH	TITLE		SHEET 2 OF 3		DRAWING NUMBER See Below
	Body Assembly, Dummy - Alternative, For M132				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL O:: 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Body Assembly, Dummy - Alternative (Dwg. 9312801-1)				
	Examination for Defects	25		3.2	4.4.2.7
	Weight	10		3.2	4.5.2.1
	Center of Gravity	10		3.2	4.5.2.2
	Chamber Gage	10		3.2	4.5.2.3
	Fin, Spring (Dwg. 9321466)				
	Examination for Defects	25		3.2	4.4.2.8
	Torque Test	10		3.2	4.5.1
	Fin Assembly, Side, Altered (Dwg. 9312847)				
	Examination for Defects	25		3.2	4.4.2.3
	Fin Assembly, End, Altered (Dwg. 9312848)				
	Examination for Defects	25		3.2	4.4.2.2
	Assembly, Body (Dummy) (Dwg. 9312801-2)				
	Examination for Defects	25		3.2	4.4.2.10
	Weight	10		3.2	4.5.2.1
	Center gravity	10		3.2	4.5.2.2
	Chamber gage	10		3.2	4.5.2.3

NOTES:

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:11Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63104A(AR)

PARAGRAPH	TITLE	SHEET 3 OF 3	DRAWING NUMBER
	Body Assembly, Dummy - Alternative, For M132		See Below
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Fin force test (Side fins)	10		3.2	4.5.2.4
	Fin force test (end fins)	10		3.2	4.5.2.5
	Specific Gravity	(a)		3.2	4.5.4
	Body Assembly (Eyeleted)				
	(Dwg. 9324908)				
	Examination for Defects	25		3.2	4.4.2.11
	Pull Test	25		3.2	4.5.5
	Cap, End				
	(Dwg. 9324906)				
	Examination for Defects	25		3.2	4.4.2.12
	Fin, End				
	(Dwg. 9324905)				
	Examination for Defects	25		3.2	4.4.2.13
	Fin, Side				
	(Dwg. 9324904)				
	Examination for Defects	25		3.2	4.4.2.14

NOTES: (a) One specimen as indicated in 4.4.3.1 shall be used as the submitted sample.

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:11Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection. -

*4.4.1 Inspection lot formation. - Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination (See MIL-A-48078). - Unless otherwise specified in the Classification of Defects and Test tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:11Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.1	Mine Body Assembly (Weldment)	1	1	9312807
				NEXT HIGHER ASSEMBLY 9312801

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Components missing or improperly assembled		0.40%	3.2	Visual
102	Minimum amount of welds		0.40%	3.2	Visual
103	Weld Strength	10	(a)	3.2	4.5.3/9212807
Minor					
201	Evidence of poor workmanship		1.0%	3.5	Visual

NOTES: (a) The lot shall be rejected if one or more assemblies are classed defective.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:11Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63104A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.2	Fin Assembly, End, Altered		9312848
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Components missing or improperly staked		0.40%	3.2	Visual
102	Presence of rod staking		0.40%	3.2	Visual
103	Overall length		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.0%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:11Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63104A(AR)

PARAGRAPH	TITLE			SHEET 1 OF 1	DRAWING NUMBER 9312847
4.4.2.3	Fin Assembly, Side, Altered				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Components missing or improperly mounted		0.40%	3.2	Visual
102	Presence of rod staking		0.40%	3.2	Visual
103	Overall length		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.0%	3.5	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:11Z
Check the source to verify that this is the current version before use.

PARAGRAPH	TITLE		SHEET OF		DRAWING NUMBER
4.4.2.4	Cap, End		1 1		9312804
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Outer diameter		0.40%	3.2	Gage
102	Location of pockets		0.40%	3.2	Gage
Minor					
201	Depth of pockets		0.65%	3.2	Gage
202	Evidence of poor workmanship		1.0%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:11Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63104A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.5	Plate, Top		9312803
			NEXT HIGHER ASSEMBLY
			9312801

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Location of bend		0.40%	3.2	Gage
102	Width		0.40%	3.2	Gage
Minor					
201	Length		0.65%	3.2	Gage
202	Evidence of poor workmanship		1.0%	3.5	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:11Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63104A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9312802
4.4.2.6	Body				NEXT HIGHER ASSEMBLY 9312901
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Indentations protruding past any outside surface		0.40%	3.2	Gage
102	Outer Radius		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.0%	3.5	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:11Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.7	Body Assembly, Dummy - Alternative				9312801
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Components missing, damaged or misaligned		0.40%	3.2	Visual
102	Fins move freely on assembly		0.40%	3.2	Manual
103	Weight	200/ Pour Lot	(a)	3.2	4.5.2.1
104	Center of gravity	200	(a)	3.2	4.5.2.2
105	Chamber Gage		100%	3.2	4.5.2.3
106	Filler hole tape missing		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		1.0%	3.5	Visual

NOTES: (a) The lot shall be rejected if two (2) or more are classed defective.

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:11Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63104A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9321466
4.4.2.8	Spring, Fin				NEXT HIGHER ASSEMBLY 9312801
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Torque Test	(a)25/ batch		3.3	4.5.1/9321466
Minor 201	Length of wire lead, minimum		0.65%	3.2	Gage
202	Evidence of poor workmanship		1.0%	3.5	Visual

NOTES: (a) The heat treat batch shall be rejected if two (2) or more springs are classed defective.

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:11Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63104A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.9	Cap, Top		9312835
			NEXT HIGHER ASSEMBLY 9312801

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Outer diameter		0.40%	3.2	Gage
102	Location of Pockets		0.40%	3.2	Gage
Minor					
201	Depth of pockets		0.65%	3.2	Gage
202	Evidence of poor workmanship		1.0%	3.5	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:11Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE			SHEET 1 OF 1		DRAWING NUMBER
4.4.2.10	Assembly, Body (Dummy)					9312801-2
						NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST		NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined					
Major						
101	Components missing, damaged or misaligned			0.40%	3.2	Visual
102	Fins move freely on assembly			0.40%	3.2	Manual
103	Weight	(a)	200/pour lot		3.2	4.5.2.1
104	Center of Gravity	(a)	200/pour lot		3.2	4.5.2.2
105	Chamber gage			100%	3.2	4.5.2.3
106	Fin force test (side fins)			0.40%	3.2	4.5.2.4
107	Fin force test (end fins)			0.40%	3.2	4.5.2.4
108	Filler hole tape missing			0.40%	3.2	Visual
Minor						
201	Evidence of poor workmanship			1.0%	3.5	Visual

NOTES:
(a) The lot shall be rejected if two (2) or more samples are classed defective.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:11Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63104A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9324908
4.4.2.11	Body Assembly (Eyeleted)				NEXT HIGHER ASSEMBLY 9312801
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Maximum height		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.0%	3.2	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:11Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63104A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.12	Cap, End		9324906
			NEXT HIGHER ASSEMBLY 9312801

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Cylinder rivet hole location		0.40%	3.2	Gage
102	Cylinder rivet hole diameter		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.0%	3.2	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:11Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63104A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.13	Fin End		9324905
			NEXT HIGHER ASSEMBLY 9312801

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Overall length		0.40%	3.2	Gage
102	Stop hinge location		0.40%	3.2	Gage
103	Minimum width		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.0%	3.5	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74 4810

20

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:11Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-B-63104A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.14	Fin, Side		9324904
			NEXT HIGHER ASSEMBLY 9312801

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Overall length		0.40%	3.2	Gage
102	Stop hinge location		0.40%	3.2	Gage
103	Minimum width		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		1.0%	3.5	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:11Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. - Testing is described in the first article and quality conformance inspection tables.

*4.4.3.1 Specific gravity test of filler mixture. - Major Defect - A ten (10) to fifteen (15) gram specimen of the cast filler mixture shall be selected from each pour lot and tested as specified in 4.5.4. If the sample fails to comply with the specific gravity specified on drawing number 9312801, the pour lot shall be rejected.

4.4.3.2 Pull test (See Dwg. 9324908), Major Defect. - The first three (3) mine bodies per day undergoing the eyelet assembly and the last three (3) mine bodies per day undergoing the eyelet assembly shall be considered as the test samples representing the contractor's process control. The contractor shall not proceed with his production if one (1) or more of the first three (3) daily samples is classed defective. If this occurs, the contractor shall correct the process deficiency and submit another sample before starting new product. In the event one (1) or more of the last three (3) samples per day is classed defective the entire day's production shall be rejected and not forwarded for additional secondary operations.

*4.4.4 Inspection equipment. - The inspection equipment required to perform the examinations and tests prescribed herein is described in the 'Paragraph Reference/Inspection Method' column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein.

4.5 Test methods and procedures. -

*4.5.1 Fin spring torque test. - The spring shall be mounted in an approved fixture to prevent it from rotating. The loads shall then be applied and the displacement measured against the specified angles per the specified applied torque. The spring shall not break or crack during the application of the forces and the spring shall return to within ten (10) percent of the original position. Any spring failing to comply with all of the specified requirements shall be classed defective. (Non-destructive test).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:11Z
Check the source to verify that this is the current version before use.

4.5.2 Mine body assembly - dummy - alternative. -

*4.5.2.1 Weight. - The mine body assembly shall be weighed using Government approved scales. Any mine assembly failing to meet the specified weight requirements shall be classed defective. (Non-destructive Test).

*4.5.2.2 Center of gravity. - The complete mine body assembly shall be tested for the specified requirement using Government approved test equipment. Any mine assembly failing to comply with all of the specified requirements shall be classed defective. (Non-destructive Test).

*4.5.2.3 Chamber gage. - The complete mine body assembly after loading shall be gaged simultaneously for all dimensions in a chamber gage. Any mine assembly failing to fit inside the chamber gage shall be classed defective and removed from the lot. (Non-destructive Test)

*4.5.2.4 Fin force test. - The mine body shall be rigidly fixtured as the specified force is applied to each fin for a minimum of ten (10) seconds. The force shall be removed and the fins shall return to the specified angle. Any sample failing to comply with all of the specified requirements shall be classed defective (Non-destructive Test).

*4.5.3 Weld strength. - The body shall be securely held and the fins pulled by mechanical means until the fins separate from the body. The separated parts shall show evidence of the weld holding per the requirement of 7.3.3.1 of MIL-W-12332. Any welded assembly failing to comply with all of the requirements shall be classed defective. (Destructive Test).

*4.5.4 Specific gravity. - The specific gravity of the cast filler mixture shall be determined in accordance with Method 203.1 described in Standard MIL-STD-650. (Non-Destructive Test).

4.5.5 Pull test. - The mine body shall be rigidly fixtured while the specified force is applied across the top plate for a minimum period of fifteen (15) seconds. The mine body shall be classed defective if two (2) or more eyelets fail to hold during test (Destructive Test).

*5. PREPARATION FOR DELIVERY

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:11Z
Check the source to verify that this is the current version before use.

5.1 Preservation and packaging. -

5.1.1 The mine assemblies shall be preserved and packaged in accordance with Dwg. No. 9312851.

5.2 Packing and marking. -

5.2.1 The mine assemblies shall be packed and marked in accordance with Dwg. No. 9312851.

5.3 Shipping. - When components of more than one lot are shipped, each lot shall be kept separate, and the division between lots clearly indicated to prevent mixing of the lots in transit.

6. NOTES

*6.1 Intended use. - The mine body assembly shall be used as a practice item for M56 Anti-tank mines when used with the M56 canister assembly.

*6.2 Ordering data. - Procurement documents shall specify the following:

a. Title, number and date of this specification.
b. Provisions for outmission of first article samples.
c. Provisions of MIL-A-48078.

6.3 Submission of inspection equipment designs for approval. (See MIL-A-48078) - Submit equipment designs as required to:

Commander
ARRADCOM
ATTN: DRDAR-QAA-I
Dover, New Jersey 07801

6.4 Distribution of ammunition data cards. - Distribution of data cards shall include the following:

Commander
ARRADCOM
ATTN: DRDAR-QAA-Q
Dover, New Jersey 07801

6.5 The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:11Z
Check the source to verify that this is the current version before use.

This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project Number: 1345-A-194

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:11Z
Check the source to verify that this is the current version before use.