MIL-C-63284A(AR)
22 January 1982
SUPERSEDING
MIL-C-63284(AR)
14 July 1978
AMENDMENT 4
27 October 1980

MILITARY SPECIFICATION

CASE ASSEMBLY, CARRYING, FOR FIRING DEVICE, DEMOLITION, M122

This specification is approved for use by the U. S. Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers quality assurance provisions and preparation for delivery for the carrying case assembly for the M122 demolition firing device.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified (see 6.2), the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification For.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-810 - Environmental Test Methods.
MIL-STD-1188- Commercial Packaging of Supplies and Equipment.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 202640-23T02:32Z
Check the source to verify that this is the current version before use.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

DRAWINGS (See 6.4)

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

11828867 - Carrying Case Assembly For Firing Device, Demolition: M122.

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.1.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Material. Materials shall be in accordance with applicable drawings, specifications and standards.

3.2 Parts and assemblies. The parts and assemblies shall comply with all requirements specified on drawing 11828867, all associated drawings, and with all requirements specified in applicable specifications and standards.

3.3. Handle strength. The handle and handle mounts shall not indicate deformation or damage to the case or handle while supporting an internal load of eighty five (85) pounds plus or minus five (±5) pounds when the case is suspended for a minimum of two (2) minutes when tested as specified in 4.5.1.

3.4 Opening and closure. The loaded case shall be capable of opening and closing without the aid of tools or implements in accordance with 4.5.2.

3.5 Leakage. The carrying case shall maintain a minimum air pressure of nine tenths pounds per square inch (0.9 p.s.i.) for a minimum of five (5) minutes before performing the handle strength (3.3) and drop tests (3.6). The carrying case shall maintain a minimum air pressure of four tenths pounds per square inch (0.4 p.s.i) for a minimum of five (5) minutes after performing the handle strength (3.3) and drop tests (3.6). The handle and drop tests shall apply as specified in the inspections of paragraphs 4.3 and 4.4.

3.6 Drop test. The case, with inserts (cushions) installed and with the firing device components in their respective storage cells, shall be capable of withstanding the drop test specified in 4.5.4.

Source: https://assist.dla.mil -- Downloaded: 202640-23T02:32Z
Check the source to verify that this is the current version before use.

3.7 Marking. The following marking shall be molded or stamped into the exterior of the case on the base approximately in the center, located under the handle with letters one-fourth (1/4) inch high. Alternatively, a nameplate, appropriately sized to contain the required information, may be permanently attached in lieu of stamping or molding. The marking shall contain the following:

Case, Assembly, Carrying, For Firing Device, Demolition, M122
11828867
MFR's Part Number

3.8 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.9 Workmanship. All parts and assemblies shall be fabricated and finished in a thorough, workmanlike manner, and all manufacturing, processing, and assembly operations shall be correctly performed. They shall be clean and free of burrs, sharp edges, cracks, gouges, surface defects, chips, dirt, grease and oil (except where specifically required), corrosion products, and other foreign matter. The cleaning method used shall not be injurious to any part or assembly nor shall they be contaminated by the cleaning agents. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material. All required markings and stamping shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).

b. Quality conformance inspection (see 4.4).

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated below and Table I.

Source: https://assist.dla.mil -- Downloaded: 202640-23T02:32Z
Check the source to verify that this is the current version before use.

Part description	Drawings	Quantity
Carrying Case Assembly	11828867	10
Base Assembly	11828865	10
Cover Assembly	11828866	10
Edge Extrusion, Female	11828856	10
Edge Extrusion, Male	11828861	10
Insert, Base	11828862	10
Insert, Cover	11828857	10
Shell	11828864	10

4.3.2 Inspection to be performed. See MIL-A-48078 and Table 1 specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 202640-23T02:32Z
Check the source to verify that this is the current version before use.

TABLE 1 - FIRST ARTICLE INSPECTION.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63284A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
	Carrying Case Assembly				See Below
					NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Carrying Case Assembly (Dwg. 11828867)				
	Examination for defects	10		3.2	4.4.2.1
	Leakage Test	10(a)		3.5	4.5.3
	Handle Strength Test	10		3.3	4.5.1
	Drop Test	10		3.6	4.5.4
	Opening and Closure Test	10(b)		3.4	4.5.2
	Base Assembly (Dwg. 11828865)				
	Examination for defects	10		3.2	4.4.2.2
	Cover Assembly (Dwg. 11828866)				
	Examination for Defects	10		3.2	4.4.2.3

NOTES: (a) Leakage test shall be performed before and after handle strength and drop test.
(b) Opening and closure test shall be performed last.

Source: https://assist.dla.mil -- Downloaded: 2026-02-23T02:32:22
Check the source to verify that this is the current version before use.

TABLE 1 - FIRST ARTICLE INSPECTION.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63284A(AR)

PARAGRAPH (Cont'd)	TITLE: Carrying Case Assembly		SHEET 2 OF 2		DRAWING NUMBER: See Below NEXT HIGHER ASSEMBLY: -
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Edge Extrusion, Female (Dwg. 11828856) Examination for defects	10		3.2	4.4.2.4
	Edge Extrusion, Male (Dwg. 11828861) Examination for defects	10		3.2	4.4.2.5
	Insert, Cover (Dwg. 11828857) Examination for Defects	10		3.2	4.4.2.6
	Shell (Dwg. 11828864) Examination for Defects	10		3.2	4.4.2.7
	Insert, Base (Dwg. 11828862) Examination for defects	10		3.2	4.4.2.8

NOTES:

Source: https://assist.dla.mil - Downloaded: 20201020T00:02Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination. See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the classification of Defects and Tests Tables, sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 202610-23T02:32Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63284A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 2	DRAWING NUMBER
4.4.2.1	Carrying Case Assembly		11828867
			NEXT HIGHER ASSEMBLY: -

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Handle strength test		0.40%	3.3	4.5.1
102	Drop test		0.40%	3.6	4.5.4
103	Case leakage test (Note a)		100%	3.5	4.5.3
104	Opening and closure		0.40%	3.4	4.5.2
105	Extrusion edge, base insert, gasket, shell, air valve, or cover insert loose or improperly secured		0.40%	3.2	Visual - Manual
106	Warning label peeling		0.40%	3.2	Visual
107	Part missing (air valve, corner, female extrusion gasket, edge extrusion, clamp assembly, keeper plate, or warning label)		0.40%	3.2	Visual
108	Part or assembly damaged (cracked or dented)		0.40%	3.2	Visual
109	Arrow on warning label not pointing in counter clockwise direction for open position		0.40%	3.2	Visual
110	Arrow on warning label not pointing in clockwise direction for close position		0.40%	3.2	Visual

-cont'd-

NOTES: a. Leakage test shall be performed after the handle strength test. Any case which fails to comply with the specified requirements shall be classed defective.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:32Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63284A(AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
Cont'd.	Carrying Case Assembly				11828867
					NEXT HIGHER ASSEMBLY
					–
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Minor					
201	Rivet missing		0.65%	3.2	Visual
202	Coating, paint or epoxy missing from rivet, extrusion or shell		0.65%	3.2	Visual
203	Label marking or marking on base assembly incorrect, illegible or missing		0.65%	3.2	Visual
204	Poor workmanship (excl. 108)		1.0%	3.9	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-10-23 02:32Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63284A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.2	Base Assembly				11828865
					NEXT HIGHER ASSEMBLY 11828867
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Inside width		0.40%	3.2	Gage
102	Inside length		0.40%	3.2	Gage
103	One clamp not offset		0.40%	3.2	Visual
104	Orientation of base insert with respect to the handle incorrect		0.40%	3.2	Visual
Minor					
201	Location of rivet holes for clamp assembly		0.65%	3.2	Visual
202	Poor workmanship		1.0%	3.9	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-0-23T02:322
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63284A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.3	Cover Assembly				11828866
					NEXT HIGHER ASSEMBLY
					11828867
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Inside width		0.40%	3.2	Gage
102	Inside length		0.40%	3.2	Gage
103	One clamp not offset		0.40%	3.2	Visual
104	Orientation of cover insert with respect to the air valve incorrect		0.40%	3.2	Visual
105	Vee notch of cover insert not in line with the air valve		0.40	3.2	Visual
Minor					
201	Location of rivet holes for keeper plate assembly from female extrusion		0.65%	3.2	Visual
202	Poor workmanship		1.0%	3.9	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-03-25T02:32Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63284A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.4	Edge Extrusion, Female		11828856
			NEXT HIGHER ASSEMBLY
			11828866

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Depth of gasket groove		0.40%	3.2	Gage
102	Inside width		0.40%	3.2	Gage
103	Inside length		0.40%	3.2	Gage
Minor					
201	Weld workmanship unsatisfactory		0.65%	3.2	Visual
202	Poor workmanship		1.0%	3.9	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-03-25T02:32Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63284A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.5	Edge Extrusion, Male	1 OF 1	11828861
			NEXT HIGHER ASSEMBLY: 11828865

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Height of male portion incorrect		0.40%	3.2	Gage
102	Inside width		0.40%	3.2	Gage
103	Inside length		0.40%	3.2	Gage
Minor					
201	Weld workmanship unsatisfactory		0.65%	3.2	Visual
202	Poor workmanship		1.0%	3.9	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-10-23 02:32Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63284A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.6	Insert, Cover				11828857
					NEXT HIGHER ASSEMBLY
					11828866
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Position of Vee notch		0.40%(a)	3.2	Gage
102	Location of cavity		0.40%(a)	3.2	Gage
103	Length of cavity		0.40%(a)	3.2	Gage
104	Width of cavity		0.40%(a)	3.2	Gage
105	Depth of cavity		0.40%(a)	3.2	Gage
Minor					
201	Poor workmanship		1.0%	3.9	Visual

NOTES: a. See 4.4.5 for alternative method of inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:32Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63284A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.7	Shell		11828864
			NEXT HIGHER ASSEMBLY
			11828865 and 6

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Inside length		0.40%(a)	3.2	Gage
102	Inside width		0.40%(a)	3.2	Gage
103	Inside depth		0.40%(a)	3.2	Gage
Minor					
201	Poor workmanship		1.0%	3.9	Visual

NOTES: a. See 4.4.5 for alternative method of inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-02-23T02:32:22
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63284A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.8	Insert, Base				11828862
					NEXT HIGHER ASSEMBLY
					11828865
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	(See Note a)				
101	Location of transmitter cavity		0.40%	3.2	Gage
102	Length of transmitter cavity		0.40%	3.2	Gage
103	Width of transmitter cavity		0.40%	3.2	Gage
104	Depth of transmitter cavity		0.40%	3.2	Gage
105	Location of 18V battery cavity		0.40%	3.2	Gage
106	Length of 18V battery cavity		0.40%	3.2	Gage
107	Width of 18V battery cavity		0.40%	3.2	Gage
108	Depth of 18V battery cavity		0.40%	3.2	Gage
109	Location of 1.5V battery cavity		0.40%	3.2	Gage
110	Diameter of 1.5V battery cavity		0.40%	3.2	Gage
111	Depth of 1.5V battery cavity		0.40%	3.2	Gage
112	Location of antenna cavity		0.40%	3.2	Gage
113	Length of antenna cavity		0.40%	3.2	Gage
114	Width of antenna cavity		0.40%	3.2	Gage
115	Depth of antenna cavity		0.40%	3.2	Gage
116	Location of receiver cavity		0.40%	3.2	Gage
117	Length of receiver cavity		0.40%	3.2	Gage
118	Width of receiver cavity		0.40%	3.2	Gage
119	Depth of receiver cavity		0.40%	3.2	Gage
120	Total height		0.40%	3.2	Gage
Minor					
201	Poor workmanship		1.0%	3.9	Visual

NOTES: a. See 4.4.5 for alternative method of inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-02-23T02:32Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article and Quality Conformance Inspection Tables.

4.4.4 Inspection Equipment. The inspection equipment required to perform the inspections and tests prescribed in this specification is identified in the "Paragraph Reference/Inspection Method" column in the tables starting with paragraph 4.4.2.1, and the test method paragraph (See 4.5). The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078, and 6.3 herein.

4.4.5 Dimensional control of molded parts. (The requirements of this paragraph apply to those dimensions which are considered "as molded" and which do not undergo subsequent operations.) In place of the normal sampling and inspections associated with the Classification of Defects, and with the approval of the Contracting Officer, and after a curing time for the parts has been approved (See Note 1), a sample of five (5) parts (as molded) from each cavity shall be inspected dimensionally to qualify a new or reworked cavity for use in production. The molded part shall carry the individual cavity identification when more than one cavity is used in production. As a control of each cavity during production, the above quantity of parts from each cavity shall be inspected for at least the defects listed after continuous production of each 5,000 parts or at the end of each week, whichever occurs first. Of the five (5) samples, one (1) sample shall be the last part produced. If any defective parts are found during qualification of the cavity, the cavity producing the defective part shall not be used in production. If any defective parts are found when inspection is performed for the control of the cavity, the cavity producing the defective part shall be removed from production. Further, that portion of production since the last control check shall be returned to the contractor for inspection for each separate type of defect according to MIL-STD-105 using an AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect. All cavities removed from production because of some fault, may, after reworking, be returned to production providing they pass the qualification test above. The contractor may request a change of inspection frequency providing he presents objective evidence to the contracting officer to substantiate the request.

NOTE 1: To establish the curing time, dimensionally check ten (10) parts from each cavity at periodic intervals (e.g. every 30, 60, etc. mins.) until dimensional stability is attained. The curing time will be from the time the part comes out of the mold until dimensional stability is attained. The inspection data used in determining the curing time shall be sent to Commander, ARRADCOM, Dover, New Jersey 07801, ATTN: DRDAR-QAT-M. If any new change in material, cycle time, a reworked cavity, or a new cavity is used, a new curing time shall be established and approved.

4.5 Methods of inspection.

4.5.1 Handle strength test. The handle test shall be performed with an internal load as specified in paragraph 3.3. The case shall be lifted off the floor or ground and suspended by the handle for the minimum time specified in 3.3. Any sample that breaks or causes deformation to the case shall be classed defective.

Source: https://assist.dla.mil -- Downloaded: 202640-23T02:32Z
Check the source to verify that this is the current version before use.

4.5.2 Opening and closure test. The case shall comply with the specified requirements before and after testing in accordance with 4.5.1. After completing the requirements of 3.3, the case shall be tested again for the opening requirements. Any case failing to comply with all other specified requirements shall be classed defective.

4.5.3 Leak test. A compressed air supply shall be connected to the air valve of the case. The case shall be pressurized and examined in accordance with the requirements of 3.5 using approved measuring equipment. Any case failing to comply with all the specified requirements shall be classed defective.

4.5.4 Drop test. The free-fall drop test shall be conducted as specified in MIL-STD-810, Method 516.2, Procedure II, except that the drop height shall be forty-eight (48) inches, minimum. Any case failing to comply with all the specified requirements shall be classed defective.

5. PACKAGING

5.1 Preservation and packaging.

5.1.1 Commercial packaging. The carrying case assemblies shall be preserved and packaged in accordance with MIL-STD-1188.

5.2 Packing.

5.2.1 Commercial packing. The carrying case assemblies shall be packed in accordance with MIL-STD-1188.

5.3 Marking. Marking of the boxes shall comply with MIL-STD-1188.

5.4 Shipping. When carrying case assemblies of more than one lot are shipped together, each lot shall be kept separate and the division between lots clearly indicated to prevent mixing of the lots in transit.

6. NOTES

6.1 Intended use. The assemblies covered by this specification are intended for use as a carrying case for the M122 Demolition Firing Device.

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of inspection equipment designs for approval. (See MIL-A-48078). Equipment designs shall be submitted as required to: Commander, U.S. Army Armament Research and Development Command, ATTN: DRDAR-QAT-I, Dover, New Jersey 07801. Request letter of submittal should state contractor, contract number, specification number, item nomenclature, and classification of defects and test paragraph number.

Source: https://assist.dla.mil -- Downloaded: 202640-23T02:32Z
Check the source to verify that this is the currentversion before use.

6.4 Drawings. Drawings listed in Section 2 of this specification under the heading "U.S. Army Armament Research and Development Command" (ARRADCOM) may also include drawings prepared by, and identified as, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, or Picatinny Arsenal drawings. Technical data originally prepared by these activities are now under the cognizance of ARRADCOM.

6.5 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodian:
Army-AR

Preparing activity:
Army-AR

Project 1375-A222

Source: https://assist.dla.mil -- Downloaded: 202610-23T02:32Z
Check the source to verify that this is the current version before use.