MIL-C-63461 (AR)
AMENDMENT 5
23 March 1988

SUPERSEDING
AMENDMENT 4
25 October 1985

MILITARY SPECIFICATION

CONTAINER, AMMUNITION, METAL, FOR PROPELLING CHARGES AND CARTRIDGES

This amendment forms a part of Military Specification MIL-C-63461 (AR), dated 20 July 1981, and is approved for use within the U. S. Army Armament, Munitions, and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

1.1 Scope. Delete "and for packing cartridges".

2.1 Specifications, Military:

Delete "MIL-W-12332 - Welding Resistance, Spot, Seam and Production....."

Substitute "MIL-W-12332 - Welding Resistance, Spot, Seam and Projection....."

PAGE 2

2.1 Standard, Military:

Delete "MIL-STD-1188 - Commercial Packaging of Supplies and Equipment"

2.1 Drawings:

Delete: "US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND (ARRADCOM)" and Substitute: "US ARMY ARMAMENT RESEARCH AND DEVELOPMENT CENTER (ARDC)

Add: "9349398 - Container, Ammo Metal: PA103"

2.2 Other publications: Add "ASTM - D3951 Commercial Packaging"

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:55Z
Check the source to verify that this is the current version before use.

3.2 Containers: After "(dwgs.) 9331196 through 9331205" add "and 9349398"

3.3.1 Tensile strength (if applicable.) Add the following subparagraph:

"3.3.1.1 Tensile strength of body material. The tensile strength of the body material shall not be less than 47,000 pounds per square inch (psi) nor greater than 53,000 psi when tested as specified in 4.5.1".

3.4 Painted surface. Delete in its entirety and substitute:

"3.4 Painted surface. The painted surfaces of the container shall comply with the requirements of TT-C-490. However, the film thickness and salt spray requirements of TT-C-490 shall not apply to the interior surfaces and interior welded spots and sharp corners of the exterior surface of the container.

3.5 Cover assembly. Delete in its entirety and substitute:

"3.5 Cover assembly. Upon assembly of the cover assembly to the body assembly (body weldment), the cover assembly shall freely engage and rotate within the body assembly. As the cover assembly is rotated with the "Y" handle in the open position, the "Y" handle shaft ends shall freely engage into the respective bayonet slots of the rim. When the "Y" handle is rotated toward the closed position, the "Y" handle shall push the spring clip out of the way and snap into place (closed position) and the spring clip shall return to its original position locking the "Y" handle. When the "Y" handle is returned to the open position it shall push the spring clip out of the way permitting a 180° rotation of the "Y" handle to the open position with the spring clip returning to its normal position. Rotation of the cover assembly will permit disengagement from the body assembly."

Add new paragraphs as follows:

"3.8 Air Pressure test.

3.8.1 Air pressure of unpainted cover assembly. The unpainted cover assembly shall withstand an internal air pressure of three pounds per square inch (psi) minimum (min), for five (5) seconds under water, without apparent leakage occurring when tested as specified in 4.5.8.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:55Z
Check the source to verify that this is the current version before use.

3.8.2 Air pressure of unpainted body assembly. The unpainted body assembly shall withstand an internal air pressure of three psi min., for five (5) seconds under water, without apparent leakage occurring when tested as specified in 4.5.8.1.

3.8.3 Air pressure of painted container assembly.

3.8.3.1 Pressure drop method. The sealed container shall withstand the internal air pressure specified in the applicable container assembly drawing for one of the test times specified without apparent leakage occurring when tested as specified in 4.5.8.2.1.

3.8.3.2 Gage method. The sealed container shall withstand an internal air pressure of three psi min., for the time specified in the applicable container assembly drawing, without apparent leakage occurring when tested as specified in 4.5.8.2.2.

3.8.3.3 Water immersion method. The sealed container shall withstand an internal air pressure of three psi min., for five seconds min. under water, without apparent leakage occurring when tested as specified in 4.5.8.2.3."

PAGE 5

* Table I. First Article Inspection. Under "Body assembly (weldment) unpainted" add:

"d) Weld strength of stacking plug to body (see Note) 5 (samples) 3.2 4.5.10/Dwg. 9331684"

PAGE 6

Table I. FIRST ARTICLE INSPECTION. Add the following:

"Cover weldment.

a)	Examination for defects	10 (samples)	3.2	4.4.2.1.1
b)	Weld strength (of shaft ass'y to cover)	3 (samples)	3.2	4.5.9/Dwg 9331692"

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:55Z
Check the source to verify that this is the current version before use.

PAGE 8

* 4.4.2.1 Clamp. Delete Major Defects 102, 103, and 104 and substitute:

"Major

102 True position of holes with datums -A-, -B- and -C- 0.40% 3.2 Gage

103 True position of holes with datum -A 0.40% 3.2 Gage"

PAGE 9

* 4.4.2.2 Spring. Delete Major Defects 102, 103 and 104 and substitute:

"Major

102 True position of holes with datum -A-, -B- and -C- 0.40% 3.2 Gage

103 True position of holes with datum -A- 0.40% 3.2 Gage"

PAGE 10

* 4.4.2.3 Support, shaft. Delete Major Defects 105, 107, 108, 111, 112 and 113 and substitute:

"Major

111 True position of rivet holes with datums -A-, -C- and -D- 0.40% 3.2 Gage"

PAGE 12

4.4.2.5..Handle. Classification of Defects, Delete:

"103. Vertical location of small hole... .40% 3.2 Gage
104. Horizontal location of small hole... .40% 3.2 Gage
201. Distance from center of shaft hexhole to outer edge of tabs. .40% 3.2 Gage".

Source: https://assist.dla.mil -- Downloaded: 20261O-23T02:55Z
Check the source to verify that this is the currentversion before use.

PAGE 15

4.4.2.8 Retainer, Major Defects, Delete:

"103. Wall thickness .40% 3.2 Gage
104. Inside depth .40% 3.2 Gage"

4.4.2.10 Gasket. Add major defect as follows:

"108. Location of hole (section A-A) .40% 3.2 Gage"

PAGE 18

4.4.2.11 Cover weldment. Add minor defects as follows:

"202. Distance from centerline of weld to edge (5 places) .65% 3.2 Gage
203. Distance from centerline of weld to edge (1 place) .65% 3.2 Gage"

PAGE 19

4.4.2.12 Cover Assembly, prior to painting. Add following major defect:

"104. Distance from top of rod (in closed position) to inside surface of the gasket retainer section of cover (.725 ± .020) 0.40% 3.2 Gage"

PAGE 21

* 4.4.2.14 Rim. Major defects 102 and 104. In each of these defects, change "hole" to "slot".

Major defects 103 and 105. Delete in their entirety and substitute:

"103. Diameter of small holes on side of rim 0.40% 3.2 Gage

105. Location of small holes on side of rim. 0.40% 3.2 Gage".

Source: https://assist.dla.mil -- Downloaded: 20261-23T02:55Z
Check the source to verify that this is the current version before use.

PAGE 22

4.4.2.15 Ring.

Major defect 102. Change "large hole" to "larger slot"

* Major defect 103. Delete in its entirety and substitute:

"103. Diameter of small holes on side of ring 0.40% 3.2 Gage"

Major defect 104. Delete in its entirety and substitute:

"104. Location of larger slot 0.40% 3.2 Gage"

* Major defect 105. Delete in its entirety and substitute:

"105. Location of small holes on side of ring. 0.40% 3.2 Gage"

PAGE 25

* 4.4.2.18 Plug, stacking. Delete all Major Defects and substitute:

"Major

101. Diameter of indexing projections 0.40% 3.2 Gage.

102. Location of indexing projections 0.40% 3.2 Gage.

103. Length of plug 0.40% 3.2 Gage

104. Width of plug 0.40% 3.2 Gage"

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:55Z
Check the source to verify that this is the current version before use.

4.4.2.19 Body weldment (Body Assembly), prior to painting
* Major defect 101. Delete in its entirety and substitute:

"101. True position of slots of ring(s), rim and holes of stacking plug 0.40% 3.2 Gage"

Major defect 102. Delete in its entirety.

Major defect 103. Delete in its entirety.

Add major defect as follows:

"106. .885 Location of bayonet slot of rim with respect to edge of body (Section A-A) 0.40% 3.2 Gage"

PAGE 28

4.4.3.1 Tensile strength. Delete in its entirety and substitute the following:

"4.4.3.1 Tensile strength. (see 3.3.1), Major Defect. Six (6) bodies shall be randomly selected for this test. From each body, three (3) specimens shall be selected at random for determination of body material tensile strength. Also, from each body, four (4) specimens approximately equally spaced along the axis shall be taken at right angles to the weld and the tensile strength of their welds shall be determined. Each of these values shall be compared with the lowest determined value of the body material tensile strength for compliance with the requirement of 3.3.1. If one or more specimens (longitudinal body weld or body material) fail to comply with 3.3.1 or 3.3.1.1, that sample body shall be classed defective. If two or more sample bodies are classed defective, the lot shall be rejected."

4.4.3.5 Deflection load of spring. Delete in its entirety.

4.4.3.8.1 Air pressure of unpainted cover assembly: Delete: "(see applicable container assembly dwg. (see 2.1)) and substitute: "see 3.8.1".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:55Z
Check the source to verify that this is the current version before use.

4.4.3.8.2 Air pressure of unpainted body assembly: Delete: "(see applicable container assembly drawing (see 2.1))" and substitute: "see 3.8.2".

4.4.3.8.3 Air pressure of painted container assembly: Delete "(see applicable container assembly drawing (see2.1)) and substitute: "see 3.8.3".

* Add new paragraph as follows:

"4.4.3.9 Weld strength of stacking plug to body. (See dwg. 9331684), Major Defect. Three (3) bodies shall be randomly selected for this test. From each body two (2) stacking plug welds shall be tested in accordance with 4.5.10. If one or both welds fail to comply with the requirement, the body shall be classed defective. If one or more bodies are classed defective, the lot shall be rejected."

4.5.5 Deflection load of spring: Delete in its entirety.

4.5.8 Air pressure test: Delete in its entirety and substitute:

"4.5.8 Air pressure test.

4.5.8.1 Air pressure of unpainted cover assembly and unpainted body assembly (water immersion method). Subject the cover assembly and container body to the specified internal air pressure for the test time specified. For the cover assembly, apply the pressure when the cover assembly is assembled to a master body assembly (or its equivalent) equipped with a gasket. For the body assembly, apply the pressure when the body assembly is assembled to a master cover (or equivalent) and gasket. The master cover and the master body assembly shall be provided with satisfactory means for applying and maintaining the pressure during the test and for showing evidence of leakage. Observation shall be made for the presence of bubbles. No bubbles (other than surface bubbles) shall be permitted. A cover assembly or body assembly which does not meet the requirements, shall be classed defective.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:55Z
Check the source to verify that this is the current version before use.

4.5.8.2 Air pressure of painted container assembly

4.5.8.2.1 Pressure drop method. Apply the internal air pressure, specified on the applicable container assembly, to the container. Observation shall be made for a pressure drop exceeding the requirement for the corresponding test time (as specified on the applicable drawing). A container which exceeds the requirement shall be classed defective.

4.5.8.2.2 Gage method. The gage used to test for this requirement shall have a calibrated scale of 0.1 psi per division. Spacing between graduations shall allow for visual resolution capability of .025 psi. With this gage, no indication of leakage shall be allowed (no visual) movement of gage needle). A container which does not meet the requirement shall be classed defective."

4.5.8.2.3 Water immersion method. The container shall be immersed in water and pressurized to the specified air pressure for the required time. Observation shall be made for the presence of bubbles. No bubbles (other than surface bubbles) shall be permitted. A container which does not meet the requirement shall be classed defective."

PAGE 30

Add new paragraph as follows:

"4.5.9 Weld strength of shaft assembly to cover (First Article Inspection Only) - The strength of the weld shall be determined in accordance with ASTM-E8".

* Add new paragraph as follows:

"4.5.10 Weld strength of stacking plug to body. The strength of the weld shall be determined in accordance with ASTM-E8."

5.2 Packing, second sentence:

Delete: "MIL-STD-1188" and substitute "ASTM-D3951"

5.3 Marking, first sentence:

Delete: "MIL-STD-1188" and substitute "ASTM-D3951"

Source: https://assist.dla.mil -- Downloaded: 20261-23T02:55Z
Check the source to verify that this is the current version before use.

6.2 Drawings: Delete in its entirety and substitute:

"6.2 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research and Development Center (ARDC) may also include drawings prepared by, and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, Picatinny Arsenal, or US Army Armament Research and Development Command (ARRADCOM) drawings. Technical data originally prepared by these activities is now under the cognizance of ARDC."

6.3 Submission of inspection equipment for design approvals: Delete in its entirety and substitute:

"6.3 Submission of inspection equipment for design approvals - See MIL-A-48078. Submit designs as required to: Commander, US Army Armament Research and Development Center, ATTN: AMSMC-QAR-I, Dover, New Jersey 07801-5001."

Paragraph 6.4; second sentence:

Delete: "US Army Armament Research and Development Command, ATTN: DRDAR-QAR-Q, Dover, New Jersey 07801"
Substitute: "US Army Armament Research and Development Center, ATTN: AMSMC-QAR-Q, Dover, New Jersey 07801-5001."

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 8140-A761)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:55Z
Check the source to verify that this is the current version before use.