MIL-C-82294B(SA)
14 June 1978
SUPERSEDING
MIL-C-82294A(SA)
2 October 1973

MILITARY SPECIFICATION

CAP, UTILITY, DARK BLUE

This specification is approved for use by Naval Supply Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements for a utility cap fabricated of a polyester and cotton poplin blend fabric treated with a durable water repellent finish.

1.2 Classification. The cap shall be of one type only and in the following sizes (see 6.2):

Sizes 6-1/2, 6-3/4, 7, 7-1/4, 7-1/2, and 7-3/4

2. APPLICABLE DOCUMENTS

2.1 Issue of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATION

FEDERAL

V-T-276 - Thread, Cotton
UU-P-31 - Paper; General Specifications and Methods of Testing

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Navy Clothing & Textile Research Facility, 21 Strathmore Road, Natick MA 01760 by using the self-addressed standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 8405

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:00Z
Check the source to verify that this is the current version before use.

DDD-B-1199 - Binding Textile, Cotton, Bias-cut
DDD-L-20 - Label; for Clothing, Equipage and Tentage (General Use)
PPP-B-636 - Box Fiberboard
PPP-T-45 - Tape, Gummed, Paper, Reinforced and Plain, for Sealing and Securing

MILITARY

MIL-B-17757 - Boxes, Shipping, Fiberboard, (Modular Sizes)
MIL-C-41831 - Cloth, Nylon, Knitted, Raschel
MIL-T-43548 - Thread, Polyester, Cotton-covered
*MIL-C-43482 - Cloth, Poplin, Cotton and Polyester (Water Repellent)

STANDARDS

FEDERAL

FED-STD-191 - Textile Test Methods
FED-STD-751 - Stitches, Seams and Stitchings

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage

*LAWS AND REGULATIONS

U.S. POSTAL SERVICE MANUAL

(Copies of the manual may be obtained from the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issues in effect on date of invitation for bids or request for proposal shall apply:

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Applications for copies should be addressed to the American Trucking Association, ATTN: Traffic Department, 1616 P Street, N.W., Washington, D.C. 20036.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:00Z
Check the source to verify that this is the current version before use.

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 Riverside Plaza, Chicago, Illinois 60606).

3. REQUIREMENTS

3.1 Guide sample. Samples, when furnished, are solely for guidance and information to the contractor (see 6.3). Variations from this specification may appear in the sample, in which case this specification shall govern.

* 3.2 First article. When specified, the contractor shall furnish sample caps for first article inspection and approval (see 4.3 and 6.2).

3.3 Material.

* 3.3.1 Basic material. The basic material shall be water repellent treated cotton and polyester poplin shade blue 3346 conforming to Class 2 of MIL-C-43482.

3.3.2 Visorboard. The materials for the visorboard shall be composed of high alpha cellulose wood pulp, wet web impregnated with compounded neoprene. The material shall conform to the following requirements when tested as specified in Table IV (see 6.5).

Thickness, inch (mm)	0.060 ± 0.003 (1.52 ± .08)
Weight, lbs/yd^2 (g/m^2) min.	1.77 (96.0)
Tearing strength, gram/centimeters, min.	
-Machine direction	1412
-Cross direction	1642
Tensile strength, lbs/in (N/m)	
-Machine direction	135 (23625)
-Cross direction	86 (15050)
Stretch, percent, max.	
-Machine direction	11.0
-Cross direction	22.0

Accelerated aging - No evidence of embrittlement, stiffening, development of stickiness or delamination.

Resistance to perspiration - No evidence of embrittlement, stiffening, development of stickiness or delamination.

Resistance to water - The material shall show no evidence of shrinking or warping or delamination.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:00Z
Check the source to verify that this is the current version before use.

Neoprene content (percent)	
-Max	35.0
-Min	15.0

3.3.3 Front crown panel stiffener. The material for the front crown stiffener shall be raschel knitted nylon cloth conforming to MIL-C-41831.

3.3.4 Sweatband interlining and sizing strip. The sweatband interlining and sizing strip material shall be spun bonded polyester cloth, style 2470, manufactured by E. I. duPont de Nemours, Inc., Wilmington, Delaware, or a functionally interchangeable equivalent. (See 6.6).

* 3.3.5 Cotton binding bias-cut. The binding for the crown seam shall be 1 inch (2.5cm) wide, made of cotton and shall conform to Type IV, class 2 of DDD-B-1199. As an alternate the bias-cut binding may be cut from the basic material specified in 3.3.1.

* 3.3.6 Thread

3.3.6.1 Thread, polyester, cotton-covered. The thread for seaming and stitching shall be polyester, cotton-covered shade Black AA, CA 66043, Ticket No. 50 and 70, 2 or 3 ply conforming to MIL-T-43548.

3.3.6.2 Thread, cotton. As an alternate to the polyester, cotton-covered thread, a cotton thread may be used. When this option is exercised, the thread shall conform to Type 1C2, 3 ply, ticket No. A and 00, shade Black AA, CA 66043 of V-T-276.

3.3.6.3 Colorfastness. The dyed thread shall show fastness to light, perspiration and laundering equal to or better than the standard sample when tested in specified in V-T-276 or MIL-T-43548. When no standard sample is available, the dyed thread shall show a minimum of "good" fastness to light, perspiration and laundering when tested as specified in V-T-276 or MIL-T-43548.

3.3.7 Labels. Each cap shall have a combination label conforming to Type I, class 4 of DDD-L-20. The fastness to laundering and dry-cleaning of DDD-L-20 shall apply. The label content shall be as follows:

ITEM DESCRIPTION:	CAP UTILITY
CONTRACT NO.	DLA-100-00-0-0000 (EXAMPLE)
STOCK NO:	8405-00-000-0000 (EXAMPLE)
SIZE:	7 (EXAMPLE)
NAME OF SUPPLIER:	

3.4 Design. The cap shall be made of water repellent cotton/polyester poplin fabric. It shall be of a ski type design with a multi stitched visor. The cap shall have a nylon mesh stiffener and a neoprene impregnated visorboard. The sweatband shall be of basic material interlined with a spun bonded polyester material (see figure 1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:00Z
Check the source to verify that this is the current version before use.

3.4.1 Figure. The figure is furnished for information only. If there are any inconsistencies between the specification and the figure, the specification shall govern.

3.5 Patterns and Blocks. Standard patterns and a block will be funished by the Government to the supplier for use in cutting working patterns and reproducing wood or metal blocks. The contractor's working patterns and blocks shall be identical to the Government standards. Neither the Government patterns nor the working patterns shall be altered in any way. The standard block shall be returned to the Government in good condition.

3.5.1 List of pattern parts. The component parts of the cap shall be cut from the materials as specified in accordance with the number of parts required for the manufacturing process as follows:

Material	Nomenclature of Pattern Parts	Cut Parts
Cloth, poplin Cotton and polyester	Top crown	1
	Side crown panel	2
	Front crown panel	2
	Visor (top ply)	1
	Visor (bottom ply)	1
Alpha cellulose wood pulp	Visor board	1
Nylon, raschel knitted cloth	Front crown panel (stiffener)	1

NOTE: Patterns are not furnished for sizing strip, sweatband, sweatband interlining and bias tape.

3.6 CONSTRUCTION

3.6.1 Stitches, seams, and stitching. Stitch, seam and stitching types specified in Table I shall conform to FED-STD-751. Wherever two or more methods for seam or stitch types are given for the same part of the operation, any one may be used. Where stitch type 401 is used, the looper, that is the underthread shall be on the inside of the cap. Seam allowances, shall be maintained with seams properly sewn so that no raw edges, runoffs, twists, pleats or open seams will result. Unless otherwise specified, top stitching or edge stitching shall be 1/8 to 3/16 inch (0.3 to 0.5cm) from folded edge.

3.6.2 Thread breaks and ends of seams. Ends of all seams and stitchings when not caught in other seams or stitchings shall be backtacked not less than 1/4 inch (0.6cm). The ends of a continuous line of stitching shall be overlapped not less than 1/2 inch (1.3cm) Thread breaks (all stitch types) shall be secured by stitching back of the break not less than 1/2 inch (1.3cm). Skipped stitches or thread breaks (401 stitch type) may be repaired using 301 stitch type.

3.6.3 Stitches per inch. The minimum and maximum number of stitches per inch shall be as specified in table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:00Z
Check the source to verify that this is the current version before use.

3.7 Manufacturing operations requirements. The cap shall be manufactured in accordance with operation requirements specified in Table I. The contractor is not required to follow the exact sequence of operations provided the finished cap is identical to that produced by following the sequence as listed in Table I.

3.7.1 Shade and size marking. The component parts of the cap shall be marked to insure a uniform shade and size throughout the cap. Any method may be used except:

(1) Metal fastening devices
(2) Sew-on shade tickets
(3) Adhesive type tickets which discolor or adhere to the material upon removal of tickets

NOTE: The use of ink pad numbering machine, rubber stamp or pencil is allowed, provided the numbering does not show on the outside of the cap and wherever possible, is covered by the seam allowance.

3.7.2 Blocking. The blocking of the cap as required in Table I shall be performed with a one or two piece steam heated machine, and dried.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:00Z
Check the source to verify that this is the current version before use.

Table I - Construction of Utility Cap

No.	Description of Operation	Stitch Type	Seam and Stitching Type	Stitches Per Inch	Thread	
					Needle	Bobbin or Looper
1.	Cutting. a. Cut the caps in strict accordance with patterns furnished, which shall show size, directional (warp) lines for cutting, and notches for the proper assembly of all component parts. b. Cut all parts from the same piece of material except the visor (bottom ply), front crown panel (inner ply), side crown panel (inner ply) and the sweatband which may be cut from ends. Parts cut from ends shall approximate the shade of the main lay. c. Cut material for sweatband on the bias or straight of sufficient width to measure 1 1/8 (± 1/16) inches (2.9 ± 0.2cm) wide on the finished cap. d. Cut front crown interlining stiffener with the heavy filling lines across the width of the stiffener. e. Cut sweatband interlining 1 (± 1/16) inches (2.5 ± 0.2cm) wide and of sufficient length to conform to operation 9 and applicable head measurements of Table II. f. Cut the sizing strip 7/16 (± 1/16) inch (1.1 ± 0.2cm) wide and it shall be of sufficient length to comply with operation 7 and to meet the applicable head measurements specified in Table II. The sizing strip shall be cut slightly longer than the head size in order to meet the finished head measurement.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:00Z
Check the source to verify that this is the current version before use.

Table I - Construction of Utility Cap (cont'd)

No.	Description of Operation	Stitch Type	Seam and Stitching Type	Stitches Per Inch	Thread	
					Needle	Bobbin or Looper
1.	Cutting. (cont'd) NOTE: Operations c, e, and f: These materials may be cut off a roll but must meet the requirements of Table II.					
*2.	Replacement of defective components. During the spreading, cutting and manufacturing process, components having material defects or damages that are classified as defects in section 4 shall be removed from production and replaced with non-defective and properly matched components.					
3.	Shade and size marking. (See 3.7.1) a. Mark, ticket or bundle all components except parts cut from ends, to insure a uniform shade and size throughout the cap.					
4.	Make visor. a. The visor shall be made of two plies of the basic material interlined with a visorboard.					
	b. Seam the outer edge of the top and bottom ply of the visor pieces together along the outer arc 3/16 (± 1/16) inch (0.5 ± 0.2cm) from the edge. Turn to finished position.	301 or 401	SSa-1	12-14	50 50	50 70
	c. Insert visorboard so that it is up against front edge. The stitching shall be on the underside of visor.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:00Z
Check the source to verify that this is the current version before use.

Table I - Construction of Utility Cap (cont'd)

No.	Description of Operation	Stitch Type	Seam and Stitching Type	Stitches Per Inch	Thread	
					Needle	Bobbin or Looper
1.	Cutting. (cont'd) NOTE: Operations c, e, and f: These materials may be cut off a roll but must meet the requirements of Table II.					
*2.	Replacement of defective components. During the spreading, cutting and manufacturing process, components having material defects or damages that are classified as defects in section 4 shall be removed from production and replaced with non-defective and properly matched components.					
3.	Shade and size marking. (See 3.7.1) a. Mark, ticket or bundle all components except parts cut from ends, to insure a uniform shade and size throughout the cap.					
4.	Make visor. a. The visor shall be made of two plies of the basic material interlined with a visorboard.					
	b. Seam the outer edge of the top and bottom ply of the visor pieces together along the outer arc 3/16 (± 1/16) inch (0.5 ± 0.2cm) from the edge. Turn to finished position.	301 or 401	SSa-1	12-14	50 50	50 70
	c. Insert visorboard so that it is up against front edge. The stitching shall be on the underside of visor.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:00Z
Check the source to verify that this is the current version before use.

Table I - Construction of Utility Cap (cont'd)

No.	Description of Operation	Stitch Type	Seam and Stitching Type	Stitches Per Inch	Thread	
					Needle	Bobbin or Looper
4.	Make visor (cont'd)					
	d. Stitch the two plies of the basic material (visor pieces only), along the inner edge (arc). The stitching shall be not more than 1/32 inch (0.1cm) from edge of visorboard interlining. Do not catch visorboard in the stitching.	301 or 401 or 101	SSa-1	6-12	50 50 50	50 70
	e. Stich four rows of stiching through all plies of material 1/4 (± 1/16) inch (0.6 ± 0.2cm) apart following the contour of the outer arc. The outer row shall be 1/4 (± 1/16) inch (0.6 ± 0.2cm) from the outer arc.	301	SSv-4	8-10	50	50
5.	Crown.					
	a. The crown shall consist of two front crown panel pieces, two side crown panel pieces and one top crown piece, all made of the basic material.					
	b. Position front crown interlining (stiffener) to inner front crown panel 1/4 to 5/16 inch (0.6 to 0.8cm) down and centered from top, with approximately the same distance throughout the rounded portion. Stay stitch center vertically from top to bottom.	301	SSv-1	6-12	50	50
	c. Stay stitch interlining (stiffener) to inner front crown panel along the bottom edge 1/8 to 3/16 inch (0.3 to 0.5cm) from edge.	301	SSbd-1	6-12	50	50
	d. Place outer front crown panel piece over the inner front crown panel piece with attached stiffener and stitch 1/8 to 3/16 inch (0.3 to 0.5cm) around all edges.	101 or 301 or 401	SSa-1	6-12	50 50 50	 50 70

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:00Z
Check the source to verify that this is the current version before use.

Table I - Construction of Utility Cap (cont'd)

No.	Description of Operation	Stitch Type	Seam and Stitching Type	Stitches Per Inch	Thread	
					Needle	Bobbin or Looper
5.	Crown. (cont'd)					
	e. Insert top crown between inner and outer side crown panels and stitch 1/4 (± 1/16) inch (0.6 ± 0.2cm) from edge, matching notches.	301 or 401	SSq-2(a)	6-12	50 50	50 70
	f. Turn outer side crown panel down and top stitch 3/32 (± 1/32) inch (0.3 ± 0.1cm) along folded edge through all plies.	301 or 401	SSq-2(b)	6-12	50 50	50 70
	g. Stitch 1/4 (± 1/16) inch (0.6 ± 0.2cm) inch from edge the outer and side edges of the side crown panels together.	301 or 401	SSa-1	6-12	50 50	50 70
	h. Stitch front crown panel assembly to top crown and side crown panel assembly 3/16 (± 1/16) inch (0.5 ± 0.2cm) from raw edge.	301 or 401	SSa-1	6-12	50 50	50 70
*	j. Operation 5d and 5g may be eliminated when other subsequent operations are performed properly.					
6.	Attach binding.					
	a. Bind seamed edges of front crown panel assembly and top crown and side panel assembly 1/4 to 5/16 inch (0.6 to 0.8cm) from fold.	301	LSy-2(a)	6-12	50	50
	b. Turn crown assembly to finished position and top stitch the crown front along curved edge 3/32 (± 1/32) inch (0.3 ± 0.1cm) from fold catching the binding in the seam.	301	LSy-2(b)	10-14	50	50

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:00Z
Check the source to verify that this is the current version before use.

Table I - Construction of Utility Cap (cont'd)

No.	Description of Operation	Stitch Type	Seam and Stitching Type	Stitches Per Inch	Thread	
					Needle	Bobbin or Looper
7.	Attach sizing strip.					
	a. With the bottom edge of cap and one edge of sizing strip even, stitch sizing strip to inside bottom of cap 1/8 (± 1/16) inch (0.3 ± 0.2cm) from edge. The ends of sizing strip shall overlap 1 (± 1/4) inches (2.5 ± 0.6cm).	101 or 301 or 401	SSab-1	6-12	50 50 50	 50 70
	OR					
	As an alternate, the ends shall be abutted with the abutted seam of the sizing strip staggered approximately 2 inches (5.1cm) from sweatband seam.					
8.	Attach visor to crown.					
	a. Prior to sewing visor to crown, place a cut or notch 1/2 inch (1.3cm) long in the center of material seam allowance on the visor.					
	b. Position visor on outside crown assembly with the cut or notch in visor centered with the stitching on inside crown front. Stitch 3/8 (± 1/16) inch (1.0 ± 0.2cm) from edge of front crown, the visor to crown assembly. There shall be no puckering between front crown panel and visor on the completed assembly. The interlining (stiffener) of the front crown and visor shall not be caught in the stitching.	101 or 301	SSa-1	6-12	50 50	 50
9.	Make sweatband.					
	a. Place one edge of sweatband interlining even with one edge of sweatband. Stitch the interlining to the sweatband material 1/8 (± 1/16) inch (0.3 ± 0.2cm) from edge.	101 or 301	SSaa-1	6-12	50 50	 50
	b. Fold sweatband material over sweatband interlining and edge stitch the raw edges together.	503 or 504	SSa-1	6-12	50 50	50 50
	OR					

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:00Z
Check the source to verify that this is the current version before use.

Table I - Construction of Utility Cap (cont'd)

No.	Description of Operation	Stitch Type	Seam and Stitching Type	Stitches Per Inch	Thread	
					Needle	Bobbin or Looper
9.	Make sweatband. (cont'd)					
	As an alternate, operations a and b may be combined in one operation using a folder. When a folder is used, operation 9b will not be required.	503 or 504		6-12	50 50	50 50
	c. Abut the ends of sweatband and stitch them together.	304	FSa-1	16-20	50	50
10.	Attach sweatband.					
*	a. Position folded edge of sweatband on outer bottom edge of cap 1/4 to 3/8 inch (0.6 to 1.0cm) in from the edge. Stitch 3/32 inch (± 1/32) inch (0.2 ± 0.1cm) from edge joining sweatband to bottom crown assembly. The sweatband shall be fitted to the cap without stretching or twisting. The stitching shall be caught in the sizing strip.	301 or 401	LSa-1	10-14	50 50	50 70
*	b. Turn to finish position and top stitch bottom of cap from visor to visor around back.	301	EFa-1	10-14	50	50
11.	Attach label.					
	a. Center label over the zig-zag stitching on the sweatband and stitch 3/32 (± 1/32) inch (0.2 ± 0.1 cm) overedge on all four sides of the label.	301	LSbj-1	6-12	50	50
	NOTE: This operation may be done on the sweatband prior to assembly.					
12.	Clean and block cap.					
	a. Trim thread ends and remove loose threads.					
	b. Remove shade markings.					
	c. Steam and dry cap on the appropriate size block.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:00Z
Check the source to verify that this is the current version before use.

3.8 Sizes and measurements. Sizes and measurements of the finished caps shall be as shown in Table II. All measurements and tolerances are expressed in inches and centimeters.

Table II - Sizes and finished measurements

Cap size	Front crown height A	Back crown height B	Visor length C	Head Circumference 1/
6 1/2	3 3/8 (8.6)	3 3/8 (8.6)	2 5/8 (6.7)	20 1/2 (52.1)
6 3/4	3 3/8 (8.6)	3 3/8 (8.6)	2 5/8 (6.7)	21 1/4 (54.0)
7	3 3/8 (8.6)	3 3/8 (8.6)	2 5/8 (6.7)	22 (55.9)
7 1/4	3 3/8 (8.6)	3 3/8 (8.6)	2 5/8 (6.7)	22 3/4 (57.8)
7 1/2	3 3/8 (8.6)	3 3/8 (8.6)	2 5/8 (6.7)	23 1/2 (59.7)
7 3/4	3 3/8 (8.6)	3 3/8 (8.6)	2 5/8 (6.7)	23 1/4 (61.6)
Tolerance	± 1/8 (0.3)	± 1/8 (0.3)	± 1/8 (0.3)	± 1/4 (0.6)

NOTE: A, B, and C refer to figure 1.

A. The measurement shall be taken from center base of visor to center top of crown front.
B. The measurement shall be taken from back center bottom of crown side panel to center back seam of crown top.
C. The measurement shall be taken from center back of visor at base of front crown to outer center of visor.

1/ The measurement shall be taken around the inside bottom edge of crown on the finished cap.

3.9 Workmanship. The finished cap shall conform to the quality established by this specification. The occurrence of defects shall not exceed the applicable acceptable quality level.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification were such inspections are deemed necessary to assure supplies and services conform to the prescribed requirements.

4.1.1 Certificate of compliance. Where certificates of compliance are submitted, the Government reserves the right to check test such items to determine the validity of the certification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:00Z
Check the source to verify that this is the current version before use.

* 4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

1. First article inspection (see 4.3).
2. Quality conformance inspection (see 4.4).

4.3 First article inspection. When required, the first article submitted in accordance with 3.2 shall be inspected for compliance with design, construction, workmanship, appearance and dimensional requirements.

4.4 Quality conformance inspection. Inspection shall be performed in accordance with MIL-STD-105, except where otherwise indicated.

4.4.1 Component and material inspection. In accordance with 4.1 above, components and materials shall be inspected and tested in accordance with the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document.

4.4.1.1 Testing of components. In addition to the quality assurance provisions of the referenced specifications, components listed in Table IV shall be tested for the characteristics shown therein. The methods of testing specified in FED-STD-191 and UU-P-31, wherever applicable, and as specified herein shall be followed. All test reports shall contain the individual values utilized in expressing the final result. The sample size shall be in accordance with Table III and the lot shall be unacceptable if one or more units fail to meet any requirements specified. The sample unit for the visor interlining (visorboard) shall be 2 continuous yards (1.8m). The lot size shall be expressed in units of pounds.

Table III - Sample size

Lot size	Sample size
800 or less	2
801 up to and including 22,000	3
22,001 and over	5

Table IV - Testing of Components

Component	Characteristic	Requirement paragraph	Test Method
Visorboard	Thickness	3.3.2	5030
	Weight	3.3.2	5041
	Tensile Strength	3.3.2	171 of UU-P-31
	Tearing Strength	3.3.2	170 of UU-P-31
	Stretch	3.3.2	171 of UU-P-31
	Accelerated aging	3.3.2	2/
	Resistance to perspiration	3.3.2	5680
	Resistance to water	3.3.2	3/
	Neoprene content	3.3.2	1/

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:00Z
Check the source to verify that this is the current version before use.

Table IV - Testing of components (cont'd)

Component	Characteristic	Requirement paragraph	Test Method
Sweatband Interlining and Sizing Strip (spunbonded polyester)	Material identification and construction	3.3.4	1/

1/ A certificate of compliance is acceptable for this requirement.
2/ The material shall be kept in a circulating air oven for 15 days at 100°C. The test shall be of 1 determination and the result reported as pass or fail.
3/ The material shall be soaked in water at room temperature for 24 hours. The test shall be of 1 determination and the result reported as pass or fail.

4.4.2 Examination of the end item. Examination of the end item shall be in accordance with 4.4.2.1 and 4.4.2.2. The applicable inspection levels and acceptable quality levels (AQL's) shall be as indicated in 4.4.2.3. The sample unit shall be one finished cap. The lot size shall be expressed in units of caps.

4.4.2.1 Visual examination. The caps shall be examined for defects in color, design, material construction, workmanship and marking and the defects classified in accordance with the list below:

Defect	Classification Major	Minor
MATERIAL DEFECTS AND WORKMANSHIP DAMAGES		
a. Any hole, needle chew, cut or tear	X	
b. Weakening defect such as slub, smash, float	X	
c. Any outside part shaded		X
d. Any visible mend or burn	X	
CLEANNESS		
a. Any spot or stain on outside		X
b. Thread ends not trimmed or loose thread not removed (on major portion of cap)		X
c. Two or more shade size markings not removed		X
d. Shade marking exposed or readily visible on outside of cap		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:00Z
Check the source to verify that this is the current version before use.

Defect	Classification Major	Minor
COMPONENTS AND ASSEMBLY		
Any component part of operation omitted or not as specified (unless otherwise classified herein)	X	
CUTTING		
Any part not cut in accordance with directional lines indicated on patterns or in accordance with specification requirements	X	
BLOCKING		
a. Blocking omitted	X	
b. Burned or scorched	X	
c. Poorly blocked		X
SEAMS AND STITCHING		
a. Accuracy of stitching		
1. Part of garment caught in any unrelated stitching operation	X	
2. Seams puckered, twisted, or pleated (unless otherwise classified herein)		X
3. Ends of all seams and stitchings when not caught in other seams or stitchings backtacked less than 1/4 inch (0.6cm)		X
4. Ends of a continuous line of stitching overlapped less than 1/2 inch (1.3cm)		X
5. Thread breaks not secured or stitching back of the break less than 1/2 inch (1.3cm)		X
b. Gauge of stitching		
1. Irregular, i.e., unevenly gauged, not uniform		X
2. Beyond range of width specified or varies more than 1/16 inch (0.2cm) when no range is specified		X
c. Open seams or runoffs		
1. Up to 1/4 inch (0.6cm) inclusive		X
2. More than 1/4 inch (0.6cm)	X	

NOTE: One or more broken stitches or two or more continuous skipped or runoff stitches constitutes an open seam.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:00Z
Check the source to verify that this is the current version before use.

Defects	Classification Major	Minor
SEAMS AND STITCHING (cont'd)		
d. Raw edges		
1. On outside		
-more than 1/4 inch to 3/4 inch (0.6 to 1.9cm)		X
-more than 3/4 inch (1.9cm)	X	
2. On inside		
-more than 3/4 inch (1.9cm)		X
e. Seam and stitch types		
1. Not specified seam or stitch type		X
2. Looper thread on outside (when 401 stitch is used)		X
f. Stitch tension		
1. Loose tension resulting in loose seam	X	
2. Loose tension recognized by loosely exposed loops of lower or top thread		X
3. Tight tension (stitches break when normal strain is applied to the seam or stitching)	X	
g. Stitches per inch		
1. Less than minimum or more than maximum as specified		X
h. Overedge stitching on seams		
1. When required, omitted for 2 or more inches (5.1cm) on one or more seams		X
i. Seam direction		
Any seam not facing the direction specified when caught in subsequent stitching operation		X
VISOR		
a. Outer edge of the two plies of visor pieces not sewn completely along outer arc	X	
b. Inner edge of visor stitching not sewn from side to side		X
c. Visorboard not held between visor plies tightly causing wrinkles on visor	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:00Z
Check the source to verify that this is the current version before use.

Defect	Classification Major	Minor
VISOR (cont'd)		
d. Inner edge of visor stitching sewn through visor		X
e. Less than or more than four rows of stitching on visor or stitchings not properly centered on visor or not following contour of outer arc		X
f. Four rows of stitching less than 3/16 inch (0.5cm) or more than 5/16 inch (0.8cm) apart		X
g. Cut omitted in visor causing bulk, tight tension when sitching visor to cap		X
h. Visor not centered with stitching on crown front		X
i. Stitching of visor less than 5/16 inch (0.8cm) or more than 7/16 inch (1.1cm) from edge		X
j. Pucker on front crown panel where visor is joined	X	
k. Stitching not on bottom underside of visor at outer arc		X
CROWN		
a. Nylon stiffener omitted or not placed on crown front in accordance with notches	X	
b. Stitch omitted from top to bottom through center of stiffener and front crown piece		X
c. Stitch omitted through bottom of stiffener and inner crown piece from side to side		X
d. Outer and inner front crown pieces stitched more than 1/8 inch (0.3cm) along outer edge		X
e. Stitching around entire front crown assembly not of proper gauge		X
f. Stitching of top crown to inner side crown panel less than 3/16 inch (0.5cm) or more than 5/16 inch (0.8cm) along edge		X
g. Outer side crown panel stitching to top crown and inner side crown panel less than 3/16 inch (0.5cm) or more than 5/16 inch (0.8cm)		X
h. Top stitching on outer side crown panel less than 1/16 inch (0.2cm) or more than 1/8 inch (0.3cm) along edge	X	
i. Inner side crown panel not caught in top stitching of outer side crown panel	X	
j. Stitching of inner and outer side crown panels less than 3/16 inch (0.5cm) or more than 5/16 inch (0.8cm)		X
k. Stitching of front crown panel to top crown and side crown panel assembly less than 1/8 inch (0.3cm) or more than 1/4 inch (0.6cm)		X
l. Any twisting or puckering of front crown when attached to crown assembly		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:00Z
Check the source to verify that this is the current version before use.

Defect	Classification Major	Minor
COTTON BINDING		
a. Omitted	X	
b. Binding strip other than bias-cut	X	
c. Edge of binding strip not folded over the plies of material where top crown and front crown stiffener are joined		X
d. Stitching of binding strip less than 1/8 inch (0.3cm) or more than 1/4 inch (0.6cm) around edge		X
e. Stitching of front crown binding strip less than 1/16 inch (0.2cm) or more than 3/32 inch (0.3cm)		X
SIZING STRIP		
a. Sizing strip omitted	X	
b. Sizing strip stitching not on inside bottom edge of cap		X
c. Ends of sizing strip not overlapped		X
d. Abutted ends causing distortion		X
e. Ends not abutted		X
f. Abutted ends causing pointed edges		X
SWEATBAND		
a. Edge stitching of folded sweatband material omitted	X	
b. Sweatband interlining exposed more than 1/8 inch (0.3cm) on sweatband when completed		X
c. Ends of sweatband not abutted		X
d. Lapped edge of sweatband to crown less than 1/4 inch (0.6cm) or more than 1/2 inch (1.3cm)		X
e. Abutted ends not centered at back of cap		X
f. Folded edge of sweatband not attached to outside bottom edge of crown assembly		X
g. Sweatband stitching to cap less than 1/16 inch (0.2cm) or more than 3/8 inch (1.0cm)		X
h. Sweatband pleated or puckered	X	
i. Sweatband exposed below bottom edge of cap		X
* j. Stitching not caught in sizing strip		X
LABEL		
a. Omitted, incorrect, illegible	X	
b. Not centered over zig-zag stitching at center back of cap		X
c. Label not secured by stitching on all four sides		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:00Z
Check the source to verify that this is the current version before use.

4.4.2.2 Dimensional examination. The cap shall be examined for defects in dimensions in accordance with the following:

Any measurement deviating from nominal dimensions and tolerances specified shall be scored as a measurement defect.

4.4.2.3 Inspection levels and acceptable quality levels. The inspection levels and acceptable quality levels (AQL's) expressed in defects per 100 units, for visual and dimensional examination shall be as follows:

	AQL's	Inspection level
For examination in 4.4.2.1:		
Major	2.5	II
Total (Major and Minor combined)	15.0	II
For examination in 4.4.2.2:		
One class	4.0	S-3

4.4.3 Examination of packaging requirements. An examination shall be made to determine that packaging, packing and marking complies with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully prepared for delivery except that it need not be sealed. Defects of closure listed below shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 and the AQL shall be 2.5 defects per 100 units.

Examine	Defect
Marking (exterior and interior)	Omitted, incorrect, illegible, of improper size, location, sequence or method of application
Materials	Any component missing, damaged or not as specified
Workmanship	Inadequate application of components, such as incomplete closure of container flaps, improper taping, loose strapping, or inadequate stapling; bulging or distortion of container
Content	Number of caps per package and shipping container is more or less than specified Size shown on item not as specified on package or shipping container

Source: https://assist.dla.mil - Downloaded: 2026-10-23T07:00Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Preservation-Packaging. Packaging shall be level A or C as specified (see 6.2).

5.1.1 Level A. Each cap shall be neatly folded in half by bringing the back portion of the crown toward the front of the cap. Twelve caps of one size only shall be nested and placed with the visor flat in a fiberboard box conforming to style RSC, Type CF, Variety SW, class domestic, grade 125 of PPP-B-636. Inside dimensions of each box shall be 14 3/4 inches (37.5cm) in length, 7 1/2 inches (19.0cm) in width and 6 1/4 inches (15.9cm) in depth. The nested caps shall be protected in the box with crumpled tissue paper in the voids above the visor on one end and beyond the folded crown at the opposite end. Box closure shall be secured with a minimum 2 inches (5.1cm) width gummed paper tape conforming to type III, grade B of PPP-T-45.

5.1.2 Level C (Commercial Packaging).- The caps shall be packaged to afford adequate protection against physical damage during shipment from the supplier to the first receiving activity. The package and the quantity per package shall be the same as that normally used by the contractor for retail distribution.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A. Thirty-six caps of one size only, packaged as specified in 5.1, shall be packed in a fiberboard shipping container assembled, closed and reinforced conforming to class weather-resistant, grade V2s, size 2 of MIL-B-17757. Level A packages shall be packed flat, three in length within the shipping container. Toward the end of the contract or when there are less than the required amount of the same size per container, mixed sizes may be packed within the same shipping container.

5.2.2 Level B. Thirty-six caps of one size only, packaged as specified in 5.1, shall be packed in a fiberboard shipping container assembled and closed conforming to class domestic, grade 275, size 2 of MIL-B-17757. Level A packages shall be packed flat three in length within the shipping container. Toward the end of the contract or when there are less than the required amount of the same size per container, mixed sizes may be packed within the same shipping container.

5.2.2.1 When specified (see 6.2) the shipping container shall be a grade V3c, V3s or V4s fiberboard box fabricated in accordance with MIL-B-17757 and closed in accordance with the appendix of the box specification.

5.2.3 Level C - (Commercial). Caps, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. The quantity per shipping container shall be the same as that used by contractor for retail distribution. Containers shall be in accordance with U. S. Postal Service Manual, Uniform Freight Classification Rules or National Motor Freight Classification Rules, as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:00Z
Check the source to verify that this is the current version before use.

5.3 Marking. In addition to any special marking required by the contract or order, interior packages and shipping container shall be marked in accordance with MIL-STD-129.

5.3.1 Labels, mixed sizes. Each shipping container packed with mixed sizes shall have securely attached to the end and side, directly under the printing and stenciling, a white paper label 5 by 4 inches (12.7 by 10.2cm) with the words "MIXED SIZES" plainly printed or stamped thereon and under these words shall be legibly printed or stamped the correct quantity and sizes contained therein.

6. NOTES

6.1 Intended use. The cap is intended to be worn with the utility trousers, shirt and jacket as the Navy enlisted man's working uniform.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) Sizes required (see 1.2).
(c) When first article sample is required (see 3.2).
(d) Selection of applicable levels of packaging and packing (see 5.1 and 5.2).
(e) When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).

6.3 Samples, patterns and blocks. For access to samples, patterns and blocks, address the procuring activity issuing the invitation for bids, (see 3.1 and 3.5).

* 6.4 Changes from previous issue. The margins of this specification are marked with an asterisk to indicate where changes (additions, modification, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

6.5 The material for visorboard has been obtainable from Texon, Inc., South Hadly, Mass. 01705 (see 3.3.2).

6.6 Equal item. Prior to the use of an "interchangeable" item, the supplier shall submit the item with supporting data to the contracting officer for subsequent approval or disapproval by the responsible Military Agency.

Custodian:
Navy - SA

Preparing Activity:
Navy - SA

Project No. 8405-N750

☆U.S. GOVERNMENT PRINTING OFFICE: 1978 — 703-122/3160

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:00Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-C-82294B(SA) CAP, UTILITY, DARK BLUE

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1426 1 OCT 76

Replaces edition of 1 Jan 72 which may be used.

S/N 0102-LF-001-4260

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:00Z
Check the source to verify that this is the current version before use.