MILITARY SPECIFICATION

FIN ASSEMBLIES, MORTAR CARTRIDGE, 81MM, M28, M29

This specification is approved for use within the U.S. Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers requirements and quality assurance provisions for the Fin Assemblies M28 and M29 for use on 81MM Mortar Ammunition.

2. APPLICABLE DOCUMENTS

2.1 Government documents

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified (see 6.2), the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards and supplement thereto, cited in the solicitation.

SPECIFICATIONS

MILITARY

MIL-H-6088 - Heat Treatment of Aluminum Alloys
MIL-A-48078 - Ammunition Standard Quality Assurance Provisions, General Specification for

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1169 - Packaging, Packing and Marking for Shipment of Inert Ammunition Components

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U S Army Armament Research Development and Engineering Center, Attn AMSMC-QA, Dover, New Jersey 07801-5001 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.
Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:40Z
Check the source to verify that this is the current version before use.

2.1.2 Other Government documents, drawings and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS

U.S. ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

9327831 - Fin Mortar Cartridge, 81MM, M28
9381586 - Fin, Mortar Cartridge, 81MM, M29

(Copies of specifications, standards, handbooks, drawings and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issue of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of the documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

PUBLICATIONS

AMERICAN NATIONAL STANDARDS INSTITUTE (ANSI)

ANSI B 46.1 - Surface Texture

(Application for copies should be addressed to: American National Standards Institute (ANSI), 1430 Broadway, New York, NY 10018).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

E-8 - Tension Testing of Metallic Materials

(Copies may be purchased directly from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:40Z
Check the source to verify that this is the current version before use.

2.3 Order of precedence. In the event of a conflict between the text of this specification and references cited herein, (except for associated detain specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall superseded applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Material. Materials shall be in accordance with the applicable drawings and specifications. Materials shall be free of defects such as cracks, splits, porosity, shrinkage, cold shuts, pipe-type defects, planar defects, inclusions etc. This is a pressure vessel application.

3.2 Components and assemblies. The components and assemblies shall comply with all requirements specified on drawings (dwgs.) 9327831 or 9381586 and associated drawings, and with all requirements specified in applicable specifications and standards. Threads and flashholes shall be free of burrs or foreign matter which may interfere with further assembly or proper functioning.

3.3 Heat treatment. Heat treatment equipment, procedures and controls shall be in accordance with MIL-H-6088. The material shall be solution heat treated in such a manner as to avoid overheating of the material or cracking during quenching.

3.4 Hydrostatic test. Each fin housing shall be able to withstand a hydrostatic load of 17,250 ± 250 p.s.i. when tested in accordance with 4.5.3. Each fin housing that successfully meets the requirements of this test shall be permanently stamped with the letter "H" .125 inch height by .01 inch maximum depth on the outside surface following the nomenclature.

3.5 Blade security test. Selected assemblies shall pass a 175 ± 25 inch-pound torque test (see 4.5.2).

3.6 First article inspection. When specified in the contract or purchase order, a sample shall be subjected to first article inspection in accordance with the technical provisions herein (see 4.3 and 6.2).

3.7 Workmanship. All parts and assemblies shall be fabricated in a thorough workmanlike manner. Threads shall be full and undamaged for the entire minimum length as required by the applicable drawings. No part shall have a burr which might be

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:40Z
Check the source to verify that this is the current version before use.

injurious to personnel handling the item. No part or assembly shall contain dirt, grease, chips, rust, corrosion, or other foreign matter. The cleaning method used shall not be injurious to any part nor shall parts be contaminated by the cleaning agent. All required markings shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of section 3 and 5. The inspections set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspections. - The following types of inspections shall be conducted on this item:

a. First Article Inspection

b. Quality Conformance Inspection

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.3.2. The first article sample

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:40Z
Check the source to verify that this is the current version before use.

shall consist of the items as required per Table I. Total quantities are as follows.

Part description	Drawings	Quantity
Fin Assembly, M28 or M29	9327831 or 9381586	10
Fin	9327834 or 9381092	5
Housing	9327833	5
Housing, prior to drilling of flash holes		10

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:40Z
Check the source to verify that this is the current version before use.

TABLE I First article inspection

MIL-F-70546(AR)

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
	Fin, M28, M29, Components and Assemblies				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Fin assembly (dwgs. 9327831 or 9381586)				
	Examination for defects	10	100%	3.2	4.4.2.4
	Fin (dwgs. 9327834 or 9381092)				
	Examination for defects	5	100%	3.2	4.4.2.3
	Tension Test	2	100%	3.2	4.5.5.1
	Housing, Cartridge (dwg. 9327833)				
	Examination for defects	5	100%	3.2	4.4.2.2
	Tension Test	2	100%	3.2	4.5.5.2
	Housing, Cartridge, prior to drilling flashholes				
	Hydrotest	10	100%	3.4	4.5.3

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:40Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078 and the following as applicable:

4.4.1.1 Cartridge housing lots. A cartridge housing lot shall consist of material of the same alloy that has been heat treated in the same heat treating equipment at the same temperature in one unchanged process. A cartridge housing lot may consist of more than one solution heat treatment batch. A solution heat treat batch shall consist of the same alloy that has been thermally treated at the same time by the same method in the same furnace equipment at the same time and temperature in one unchanged process.

4.4.1.2 Fin stock lots. The fin stock lot shall consist of extruded stock of the same alloy that has been thermally treated by the same method in the same furnace equipment at the same temperature and time in one unchanged process regardless of the solution heat treating method utilized. Each fin stock lot representing material that has been solution heat treated after extrusion, must be solution heat treated at the same time in the same furnace using the same temperature and time in that furnace.

4.4.2. Examination. See MIL-A-48078. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:40Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9327833
4.4.2.1	Housing, Cartridge, prior to drilling flash-holes				NEXT HIGHER ASSEMBLY 9327831 or 9381586
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Special A	Hydrotest		100%	3.4	4.5.3
Major 101	Tension test (from bar stock)		100%	3.2	4.5.5.1
Minor	None defined				

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:40Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70546(AR)

PARAGRAPH	TITLE		SHEET 1 OF 3		DRAWING NUMBER
4.4.2.2	Housing				9327833
					NEXT HIGHER ASSEMBLY
					9327831 or 9381586
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Special A	Hydrostatic test stamp missing		100%	3.2	Visual
Major 101	Large outside diameter (OD) of housing		0.40%	3.2	Gage
102	Diameter of knurl		0.40%	3.2	Gage
103	Rear OD		0.40%	3.2	Gage
104	Distance from front face to front shoulder		0.40%	3.2	Gage
105	Depth of ignition cartridge cavity		0.40%	3.2	Gage
106	Presence of burr or foreign matter in ignition ctg. cavity or flashholes		0.40%	3.2	Visual
107	Distance from rear face to rear shoulder		0.40%	3.2	Gage
108	Distance from rear face to front shoulder		0.40%	3.2	Gage
109	Length of forward thread undercut		0.40%	3.2	Gage
110	Length of rear thread, min.		0.40%	3.2	Gage
111	Runout of large OD with forward thread and forward shoulder		0.40%	3.2	Gage

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:40Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 2 OF 3		DRAWING NUMBER
4.4.2.2	Housing (Cont'd)				9327833
					NEXT HIGHER ASSEMBLY 9327831 or 9381586
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
112	Runout of rear OD with forward thread and forward shoulder		0.40%	3.2	Gage
113	True position of flashholes with forward shoulder		0.40%	3.2	Gage
114	True position of rear thread with rear OD		0.40%	3.2	Gage
115	Forward thread major diameter undersize		0.40%	3.2	Gage
116	Pitch diameter (PD) of forward thread		0.40%	3.2	Gage
117	True position of ignition cartridge cavity with large OD		0.40%	3.2	Gage
118	True position of ignition cartridge cavity with PD of rear thread		0.40%	3.2	Gage
119	PD of rear thread		0.40%	3.2	Gage
120	Minor diameter of rear thread oversize		100%	3.2	Gage
121	Diameter of cartridge cavity		0.40%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:40Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 3 OF 3		DRAWING NUMBER 9327833
4.4.2.2	Housing (Cont'd)				NEXT HIGHER ASSEMBLY 9327831 or 9381586
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
122	Flashhole(s) missing		100%	3.2	Gage
123	Flashholes excessive in number		0.40%	3.2	Visual
124	Diameter of flashholes		0.40%	3.2	Gage
125	Length of knurl		0.40%	3.2	Gage
126	Distance between flashholes rows incorrect		0.40%	3.2	Gage
127	Presence of flashhole burr(s) on large OD		0.40%	3.2	Visual
128	Incorrect angle on top flashholes		0.40%	3.2	Gage
129	Distance from front shoulder to angle flashhole		0.40%	3.2	Gage
130	Housing ID damaged under knurl		0.40%	3.2	Visual
Minor					
201	Distance from knurl to rear shoulder		0.65%	3.2	Gage
202	Radii missing or incorrect		0.65%	3.2	Visual (See 6.5)
203	Surface finish improper		0.65%	3.2	Visual (See 6.6)
204	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:40Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70546(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.3	Fin	1 OF 2	9327834
			NEXT HIGHER ASSEMBLY: 9327831 or 9381586

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Runout of hub diameter with forward inside diameter (ID)		0.40%	3.2	Gage
102	Large OD of fin blades		0.40%	3.2	Gage
103	Rear OD of fin blades		0.40%	3.2	Gage
104	Forward ID		0.40%	3.2	Gage
105	Diameter of hub		0.40%	3.2	Gage
106	Distance from front face to rear chamber		0.40%	3.2	Gage
107	Distance from front face to basic diameter fo counterbore at rear		0.40%	3.2	Gage
108	Depth of counterbore at rear		0.40%	3.2	Gage
109	Diameter of counterbore		0.40%	3.2	Gage
110	Runout of counterbore with ID		0.40%	3.2	Gage
111	Distance from center axis to bend line		0.40%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:40Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70546(AR)

PARAGRAPH	TITLE	SHEET 2 OF 2	DRAWING NUMBER
4.4.2.3	Fin (Cont'd)		9327834
			NEXT HIGHER ASSEMBLY 9327831 or 9381586

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
112	Distance from rear face to bend line		0.40%	3.2	Gage
113	Thickness of blades (6 places)		0.40%	3.2	Gage
114	Angle between blades		0.40%	3.2	Gage
115	Angle at front of blades		0.40%	3.2	Gage
116	Overall length		0.40%	3.2	Gage
117	Chamfer angle forward of blade cant		0.40%	3.2	Gage
118	Blade(s) damaged or defective		0.40%	3.1	Visual
119	Tension test		100%	3.2	4.5.5.2
Minor					
201	Distance between bend lines on rear face		0.65%	3.2	Gage
202	Radii or chamfers missing or incorrect		0.65%	3.2	Visual/6.5
203	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2022-10-23T10:40Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.4	Fin Assembly, M28 or M29	1 of 1	9327831 or 9381586
			NEXT HIGHER ASSEMBLY: 9327839 or 9352621

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Special A	Blade security test		0.040%	3.5	Gage/4.5.2
Major 101	Distance from rear face to shoulder, max		0.40%	3.2	Gage
102	True position of blades with forward thread and shoulder		0.40%	3.2	Gage
103	Gap between blades and housing, max		0.40%	3.2	Gage
104	Horizontal and vertical T.I.R. of blades(6) with forward thread and shoulder		0.40%	3.2	Gage
105	Height of blade cant (6 blades)		0.40%	3.2	Gage
Minor 201	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:40Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article and Quality Conformance Inspection tables.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed in this specification is identified either directly or by reference, in the "Paragraph Reference/Inspection Method" column of the Quality Conformance Inspection tables herein. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein.

4.5 Methods of inspection.

4.5.1 Materials, components and processes. Compliance with all requirements of Section 3 of this specification shall be ascertained by current and continuing examination of inspection and test data to determine that all components (parts, subassemblies, and materials) have been inspected and tested and found to comply with their respective drawing and specification requirements, and that all specified manufacturing processes have been followed.

4.5.1.1 Visual and mechanical inspections. The visual, manual and mechanical inspections and tests shall verify compliance with the requirements of Sections 3 and 5 of this specification in accordance with 4.4.2 herein and Table I.

4.5.2 Blade security test. Units selected for this test shall be held in a fixture which does not damage the surface of the housing. The housing shall be held securely in a fixture while 175 $\pm$ 25 inch-pounds torque is applied to the fin blades in either direction. Fin cants must not be contacted during the test. The torque shall be applied and held for three seconds. Rotation of the blades shall be cause for classifying the assembly as defective.

4.5.3 Hydrostatic test. After final machining but prior to drilling flash holes and prior to gaging, each cartridge housing shall be subjected to a hydrostatic test to determine compliance with the requirements of 3.4. The housing shall be tested using equipment capable of performing the test accurately and consistently. In performing the test, the pressure will be applied gradually until the required minimum pressure is reached and held for three seconds. The equipment shall be calibrated prior to the start of each day's operation and at intervals of not over 4 hours of continuous operation. It shall also be calibrated prior to restarting the operation after a lay-off of three hours or more.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:40Z
Check the source to verify that this is the current version before use.

If it has been found that the equipment is out of calibration in such a direction that the pressure was actually lower than required, the housings tested since the last satisfactory calibration shall be retested after the calibration error has been corrected. Rupture, cracking, or bulging shall be evidence of failure and cause for rejection of the housing. Each housing which has successfully passed the test shall be stamped in accordance with 3.4. Use of the threads for a hydrostatic seal is not mandatory and may result in an adverse change of the thread form. The hydrotest may be performed on the housing prior to machining the threads if the wall thickness is in conformance with the drawing requirements.

4.5.4 Flashhole inspection.

4.5.4.1 Missing flashholes. Each fin housing shall be inspected by a non-visual system capable of determining the presence of the required number of flash holes.

4.5.4.2 Excess flashholes. Each fin housing shall be inspected by a method capable of determining the presence of flash holes in excess of the drawing requirement.

4.5.5 Tension test.

4.5.5.1 Cartridge housing stock. From each 1000 pounds of bar stock at least one tensile test specimen shall be prepared representing a standard size "R" type specimen in accordance with ASTM Method E-8. Procedures and equipment for performing the test shall be in accordance with ASTM E-8. Failure to meet the drawing requirements shall cause rejection of the lot.

4.5.5.2 Fin stock. The requirements of the test shall be as in 4.5.5.1 except that the specimens shall be of the flat type and shall be taken from the blade area.

5. PACKAGING

5.1 Packaging, packing and marking. Packaging, packing and marking shall be in accordance with the requirements of level C in MIL-STD-1169.

6. NOTES

6.1 Intended use. The components covered by this specification are intended for use on the mortar cartridges, 81MM, M819 or M853.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:40Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of inspection equipment for design approvals. See MIL-A-48078. Submit designs as required to Commander, U.S. Army Armament Research, Development and Engineering Center, ATTN: AMSMC-QAT-I(D), Dover, NJ 07801-5001

6.4 Drawings. Drawings listed in Section 2 of this specification under the headings U.S. Army Armament Research, Development and Engineering Center (ARDEC) may also include drawings prepared by, and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal and U.S. Armament Research and Development Command (ARRADCOM) drawings. Technical data originally prepared by these activities is now under the cognizance of ARDEC.

6.5 Visual examination qualification. When compliance with the applicable requirements is in doubt as a result of visual examination, these characteristics may be measured or gaged to determine acceptability.

6.6 Surface roughness. The roughness comparison specimens prescribed by ANSI-B46.1 shall be used as a basis for surface roughness determination. Four power (4X) magnification may be used in performing visual examination.

6.7 Subject term (key word) listing.

Ammunition, mortar
Assembly, fin
Cant, fin
Flashholes
Hydrostatic
Overheating
Quenching
Vessel, pressure

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1315-A678)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:40Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-F-70546	FIN ASSEMBLIES, MORTAR CARTRIDGE, 81 MM, M28, M29

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:40Z
Check the source to verify that this is the current version before use.