INCH-POUND

MIL-G-70790(AR)
07 JUNE 1995

MILITARY SPECIFICATION

GUN, MACHINE, 40MM MK19 MOD 3

This specification is approved for use by the U.S. Army Armament Research, Development and Engineering Center, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification establishes the performance, functioning, and quality assurance requirements for an air cooled, blow-back operated automatic weapon firing 40mm grenades from ground mounts and combat vehicles.

1.2 Type. Weapons shall be of the following types:

Type I - Manually Operated
Type II - Remotely Operated

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards and handbooks. The following specifications, standards and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation (see 6.2)

SPECIFICATIONS

MILITARY

MIL-C-372 - Cleaning Compound, Solvent: for Bore of Small Arms and Automatic Aircraft Weapons
MIL-W-13855 - Weapons: Small Arms and Aircraft Armament Subsystems, General Specification for

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document, should be addressed to: Commander U.S. Army ARDEC, ATTN: AMSTA-AR-EDE-S, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1010
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:00Z
Check the source to verify that this is the current version before use.

MIL-W-63150 - Weapons and Support Material, Standard Quality Assurance Provisions for
MIL-L-14107 - Lubricating Oil, Weapons, Low Temperature
MIL-L-46000 - Lubricant, Semi Fluid (Automatic Weapons)
MIL-L-46150 - Lubricant, Weapons, Semi-fluid (High Load - Carrying Capacity)

FEDERAL

P-D-680 - Dry Cleaning Solvent

STANDARDS

MILITARY

MIL-STD-109 - Quality Assurance Terms and Definitions Property
MIL-STD-130 - Identification Marking of U.S. Military
MIL-STD-1189 - Standard Department of Defense Bar Code Symbology

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Naval Publications and Forms Center (ATTN: NPODS), 5801 Tabor Avenue, Philadelphia, PA, 19120-5099.)

DRAWINGS

3269419 - 40mm Machine Gun MK19 MOD 3 Assembly Group 1
3269423 - Sight Calibration
3269501 - Solenoid
3269494 - Tool, Combination Assembly
5830052 - Carriage and Cradle Assembly
6507135 - Mount, Tripod, Machine Gun: Cal .50, M3
8886326 - Cartridge, 40mm, Practice, M385
9241371 - Cartridge, 40mm, HE, M383
9275763 - Dummy Cartridge, 40mm, High Velocity, M922
9287851 - Cartridge, 40mm, HEDP, M430
9399372 - Cartridge, 40mm, M918 TP

PUBLICATIONS

TM9-1010-230-10 - Operators Manual and Component List, Machine Gun 40mm, MK19 MOD 3
TM9-1010-230-23&P - Organizational and Intermediate Maintenance Manual Including Repair Parts List, Machine Gun 40mm MK19 MOD 3

(Copies of drawings and publications required by contractors in connection with specific procurement functions should be obtained from the contracting activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:00Z
Check the source to verify that this is the current version before use.

2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, (except for associated detail specifications, specification sheets or MS standards) the text of this specification takes precedence. Nothing in this specification, however, shall supersede applicable laws and regulation unless specific exemption has been obtained.

3. REQUIREMENTS

3.1 Materials and construction. The machine gun and its parts shall conform to the material and construction requirements specified herein, on Drawing (Dwg) 3269419, and drawings applicable thereto, and shall be in accordance with the applicable material and construction processes of MIL-W-13855.

3.2 Design. The machine gun and its parts shall conform to the design specified herein, all the requirements of Dwg. 3269419, and drawings applicable thereto, and shall be in accordance with the applicable design provisions of MIL-W-13855. The machine gun shall successfully pass the pre-firing and post-firing inspections specified in 4.5.1 and 4.5.12, respectively.

3.3 Gun sight and bore calibration. When the machine gun sight is properly calibrated, the vertical alignment guide on the target shall be parallel with the right hand side of the weapon's sight frame, the boresight cross hairs shall be within the 1 inch diameter circle on the target and the line of sight for 300 meters and 1000 meters shall be within their respective line of sight target as specified on Dwg. 3269423.

3.4 Ammunition compatibility. The machine gun shall be capable of being cycled with the M922 Cartridge, Dwg. 9275763, without binding, stoppage or excessive effort.

3.5 Performance characteristics. The machine gun shall be capable of meeting the following requirements when the M383 cartridge (Dwg. 9241371), M385A1 cartridge (Dwg. 8886326), M430 cartridge (Dwg. 9287851), or M918 cartridge (Dwg. 9399372) is fired from it.

3.5.1 Proof inspection. The machine gun shall withstand the firing of one M385A1 40mm cartridge without any evidence of part failure, deformation or loosening.

3.5.2 Firing modes. The machine gun shall have a firing mode which is fully automatic with single shot firing achievable. When conditioned at -50°F to +155°F and fired, the machine gun shall not unintentionally stop or "run away" (See 6 .7.1).

3.5.3 Belt pull. The machine gun shall be capable of functioning when a belt of 28 rounds freely hangs from it. During testing, the weapon shall not unintentionally stop or "run away" (See 6.7.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:00Z
Check the source to verify that this is the current version before use.

3.5.4 Cyclic rate of fire. The machine gun shall have a cyclic rate of fire from 325 to 375 rounds per minute for the M430 and M918 cartridges and 335 to 385 rounds per minute for M385A1 and M383 cartridges when fired from a M3 tripod mount. During testing the weapon shall not unintentionally stop or "run away" (See 6.7.1).

3.5.5 Trunnion load. When fired, the machine gun shall exhibit a trunnion load of 800 pounds maximum. During testing the weapon shall not unintentionally stop or "run away" (See 6.7.1).

3.5.6 Angle of fire. The machine gun shall be capable of automatic fire at any angle between 70 degrees depression and 70 degrees elevation. During testing the machine gun shall not unintentionally stop or "run away" (See 6.7.1).

3.5.7 Accuracy. When assembled to a Government approved mount, and boresighted, the machine gun shall fire the specified complement of rounds which shall hit a vertical target which is 14 meters square and placed at a distance of 1000 meters from the weapon's muzzle. this distance and target size may be reduced if an equivalent test procedure is submitted by the contractor and approved by the Government. During testing the weapon shall not unintentionally stop or "run away" (See 6.7.1).

3.5.8 Reliability.

3.5.8.1 Stoppages. The machine gun shall exhibit a Mean Rounds Between Stoppages (MRBS) of 1100 minimum at an 85% Confidence Level. A stoppage is defined as an unintentional interruption of firing that takes less than 60 seconds to correct by immediate action or by minor adjustment.

3.5.8.2 Failures. The machine gun shall exhibit a Mean Rounds Between Failure (MRBF) of 3300 minimum at an 85% Confidence Level. A failure is defined as a stoppage that takes longer than 60 seconds to clear or repair. A failure is also defined as a "run away" or any kind of safety related defect (as determined by the Government). No failures of this type ("run away" or safety) shall be permitted.

3.5.8.3 Barrel life. The machine gun's barrel shall have a minimum life of 10,000 rounds. Barrel life shall have been reached when the average muzzle velocity, periodically measured during the test, is less than that at the beginning of the test by more than ten times the standard deviation of the muzzle velocity at the beginning of the test.

3.5.8.4 Receiver life. The machine gun's receiver shall have a minimum life of 25,000 rounds. Receiver life shall have been reached when material failures (cracks or breakage) occur in those areas of the receiver in which a potential safety hazard as determined by the Government could exist.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:00Z
Check the source to verify that this is the current version before use.

3.6 Interchangeability. Unless otherwise specified on the drawings, all parts and assemblies from prior and current manufactured guns and spare parts, shall be interchangeable. After interchange the machine gun shall be capable of meeting the requirements specified in 3.3 through 3.5.8.4

3.7 Marking. Each machine gun and each part for which marking is prescribed shall be clearly marked in accordance with MIL-STD-130. Each receiver shall be identified with a serial number which shall be assigned by the procuring activity.

3.8 First article inspection. When specified (see 6.2), a sample shall be submitted to first article inspection (see 6.3) in accordance with 4.3.

3.9 Workmanship. As prescribed in MIL-W-63150, the machine gun shall be manufactured and assembled with a quality of workmanship which assures freedom from any defect which might adversely affect life, strength or reliability. Particular attention shall be given to neatness and thoroughness of assembly and assurance against burrs, sharp edges, corrosion and foreign materials. Surfaces shall be continuous and free from pits, scratches and gouges. Threaded fasteners shall be properly torqued in accordance with industry standards. All rivets shall be tight and properly swaged and headed. Unless otherwise specified, metal surfaces shall be in accordance with the applicable drawings as specified in the contractual document of which this specification is a part. Components assembled using operations requiring staking, riveting or heading shall be touched-up in accordance with MIL-W-13855.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may utilize his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. In addition, unless specified herein or in the contract, the provisions of MIL-W-63150 apply and are hereby made a part of this detail specification. Reference shall be made to MIL-STD-109 to define terms used herein

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:00Z
Check the source to verify that this is the current version before use.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual nor does it commit the Government to acceptance of any defective material.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First Article Inspection (see 4.3)

b. Quality Conformance Inspection (see 4.4)

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2 unless otherwise specified in the contract. The first article sample shall consist of the following items in sample quantities as indicated.

Part description	Drawings	Quantity
Gun, Machine, 40mm MK19 MOD 3	3269419	8

4.3.2 Inspections to be performed. First article weapons shall be tested in accordance with Table I. Any test samples may be subjected, by the Government, to any or all of the examinations and tests specified herein, in the contract or on the applicable drawings.

4.3.2.1 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the Inspection Method column in Table I.

4.3.3 Rejection. If any component, assembly or weapon fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate its inspection upon any failure of a weapon to comply with any of the stated requirements. In the event of rejection, the Government reserves the right to require the contractor to take corrective action and submit a new first article quantity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:00Z
Check the source to verify that this is the current version before use.

TABLE I. FIRST ARTICLE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-G-70790(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
	Gun, Machine, 40mm, MK19 MOD 3	1 OF 2	3269419
			NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Pre-firing inspection	8 ACC-0 REJ-1	3.2, 3.9	4.5.1
	Ammunition compatability inspection	8 ACC-0 REJ-1	3.4	4.5.2
	Gun sight and bore calibration	8 ACC-0 REJ-1	3.3	4.5.3
	Proof inspection	8 ACC-0 REJ-1	3.5.1	4.5.4
	Firing modes			
	Ambient	8 ACC-0 REJ-1	3.5.2	4.5.5
	Hot	8 ACC-0 REJ-1	3.5.2	4.5.5
	Cold	8 ACC-0 REJ-1	3.5.2	4.5.5
	Belt Pull	8 ACC-0 REJ-1	3.5.3	4.5.6
	Cyclic rate of fire	8 ACC-0 REJ-1	3.5.4	4.5.7
	Accuracy	8 ACC-0 REJ-1	3.5.7	4.5.11

NOTES:

1/ Ammunition required for performance of functioning tests is listed on Table II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:00Z
Check the source to verify that this is the current version before use.

TABLE I. FIRST ARTICLE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-G-70790(AR)

PARAGRAPH	TITLE Gun, Machine, 40mm, MK19 MOD 3	SHEET 2 OF 2	DRAWING NUMBER 3269419
			NEXT HIGHER ASSEMBLY
CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH / INSPECTION METHOD REFERENCE
	Trunnion load	8 ACC-0 REJ-1	3.5.5 / 4.5.8
	Angle of fire		
	Elevated	8 ACC-0 REJ-1	3.5.6 / 4.5.9
	Depressed	8 ACC-0 REJ-1	3.5.6 / 4.5.10
	Interchangeability	8 2/	3.6 / 4.5.13
	Reliability demonstration	2 3/	3.5.8 / 4.5.14
	Post firing inspection	8 ACC-0 REJ-1	3.2 3.9 / 4.5.12

NOTES:

1/ Ammunition required for peformance of functioning tests in listed on Table II.

2/ The first article sample shall be rejected if any machine gun fails to comply with the specified tests or post-firing inspection after interchange.

3/ The first article sample shall be rejected if any machine gun fails to meet the reliability requirement. The acceptance criteria shall be as follows: Failures - Acc 4, Rej 5; Stoppages - Acc 17, Rej 18.

AMSMC Form 1570a-E, 1 Jul 89 Replaces AMSMC Form 1570a, 1 Apr 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:00Z
Check the source to verify that this is the current version before use.

TABLE II

AMMUNITION REQUIRED FOR
FIRST ARTICLE TEST

Test	M385A1	M430
Proof Inspection	1	0
Firing modes		
Ambient	30	30
Hot	30	30
Cold	30	30
Belt pull	28	28
Trunnion load	1/	1/
Angle of fire		
Elevated	8	0
Depressed	8	0
Cyclic rate of fire	30	30
Accuracy	18	18
Interchangeability	183 2/	166 2/
Reliability	25,344 3/	

NOTES:

1/ Performed concurrently with belt pull test.
2/ Quantity represents performing firing modes, belt pull, cyclic rate of fire, trunnion load, angle of fire (when applicable) and accuracy tests after interchange.
3/ Represents number of rounds required to complete firing cycle as specified in paragraph 4.5.14.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:00Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot.

4.4.1.1 Machine guns. The number of machine guns in an inspection lot shall not be greater than one month's production or 400 guns produced, whichever is less.

4.4.2 Examination. The examinations listed in this specification shall be performed on inspection lots as defined in 4.4.1 of this specification.

a. Sampling plans. Sampling plans are incorporated in this specification either by reference to appropriate military standards or by stipulating other specific acceptance criteria.

b. Quality conformance inspection. Quality conformance inspection shall be in accordance with Table III.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:00Z
Check the source to verify that this is the current version before use.

TABLE III. QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 1 OF 2	DRAWING NUMBER
	Gun, Machine, 40mm, MK19 MOD 3		3269419
			NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Major				
101	Proof mark missing from barrel	100% ACC-0 REJ-1	3.2	Visual
102	Magnetic particle inspection mark missing from barrel	100% ACC-0 REJ-1	3.2	Visual
103	Pre-firing inspection	100% ACC-0 REJ-1	3.2, 3.9	4.5.1
104	Ammunition compatability inspection	100% ACC-0 REJ-1	3.4	4.5.2
105	Gun sight and bore calibration	100% ACC-0 REJ-1	3.3	4.5.3
106	Proof inspection	100% ACC-0 REJ-1	3.5.1	4.5.4
107	Firing mode - Ambient	100% ACC-0 REJ-1	3.5.2	4.5.5
108	Belt pull 4/	100% ACC-0 REJ-1	3.5.3	4.5.6

NOTES:

1/ Ammunition required for performance of functioning tests is listed on Table IV.

2/ If any weapon fails to comply with the applicable requirement the lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:00Z
Check the source to verify that this is the current version before use.

TABLE III. QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE Gun, Machine, 40mm, MK19 MOD 3	SHEET 2 OF 2	DRAWING NUMBER 3269419
			NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Major				
109	Cyclic rate of fire	100% ACC-0 REJ-1	3.5.4	4.5.7
110	Accuracy 4/	100% ACC-0 REJ-1	3.5.7	4.5.11
111	Interchangeability	3 5/ 2/	3.6	4.5.13
112	Reliability demonstration	1 3/	3.5.8.1	4.5.14
113	Post-firing inspection	100% ACC-0 REJ-1	3.5.8.2 3.2, 3.9	4.5.12

NOTES:

3/ Performed every three months of production or 1200 guns, whichever is less. Failure to comply with the applicable requirement shall result in rejection of all machine guns complete and in-process in the contractor's facilities. The acceptance criteria shall be as follows: Failures -ACC 0, REJ 1; Stoppages -ACC 3, REJ 4. Corrective action procedure by the contractor shall be reviewed and approved by the Government.

4/ Performed concurrently with Firing Mode Test.

5/ Sample of weapons shall be selected from every 400 produced or one months production whichever is smaller.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:00Z
Check the source to verify that this is the current version before use.

TABLE IV

AMMUNITION REQUIRED FOR
QUALITY CONFORMANCE INSPECTION

Test	Quantity of M385A1 ammunition required per weapon 1/
a. Proof Inspection	1
b. Firing mode - Ambient	28
c. Belt pull	2/
d. Cyclic rate of fire	10
e. Accuracy	2/
f. Interchangeability	39 3/
g. Reliability demonstration	6,600

NOTES:

1/ Quantity of weapons per lot (sample or 100%) is specified in "Conformance Criteria column of Table III.

2/ Performed concurrently with the firing mode test.

3/ Represents ammunition consumed after (39 Rds) interchange.

Source: https://assist.dla.mil -- Downloaded: 202640-23T04:00Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the Quality Conformance Inspection Tables. Testing shall be conducted in accordance with methods and procedures specified in 4.5.

4.4.3.1 Test Samples. The quantities for the various tests shall be specified in the Quality Conformance Inspection Tables.

4.4.3.2 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the Inspection Method column in Table III. The contractor shall submit for approval inspection equipment designs and procedures in accordance with the terms of the contract. See 6.3 herein.

4.5 Methods of inspection.

4.5.1 Pre-firing inspection. Prior to proof-firing the machine gun, the following visual and operational checks shall be made. Reference should be made to technical documentation to locate the components which are mentioned in the following steps:

Step 1. Perform a visual inspection of the assembled gun for completeness, workmanship and visible damage that could adversely affect life, function or reliability.

Step 2. Install the machine gun on an approved mount or stand. Inspection is to be performed as follows:

a. Raise the top cover assembly, 3269406, and verify that the following parts operate freely:

(1) Cover Lock, 3269478 (with top cover closed, then open)
(2) Round Positioning Block, 3269439
(3) Alignment Guide Assembly, 3269403
(4) Primary Pawl, 3269436
(5) Secondary Pawl, 3269438
(6) Feed Slide Assembly, 3269407
(7) Feed Pawls (2), 3269428
(8) Feed Tray Pawl, 3269490
(9) RH Extractor, 3269449
(10) LH Extractor, 3269448
(11) Ogive Plunger Assembly, 3269405
(12) Charger Handle Lock (RH), 3269516
(13) Charger Handle Lock (LH), 3269516
(14) Receiver Sear, 3269470 (with bolt removed)
(15) LH Bolt Finger, 2680959 (with bolt removed, run dummy round through bolt face and ensure round passes freely through LH and RH bolt fingers.)
(16) RH Bolt Finger, 2680956 (with bolt removed, run dummy round through bolt face and ensure round passes freely through LH and RH bolt fingers.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:00Z
Check the source to verify that this is the current version before use.

(17) Pawl, 3269489 (with bolt removed, run dummy round through bolt face and ensure round stop pawl snaps behind round case rim prior to compression of LH & RH bolt finger springs.)
(18) Cocking lever, 3269443 (check with bolt removed)
(19) Safety Lever, 3269518 (with bolt removed and safety in SAFE position)

b. With bolt in battery position and top cover raised, position feed slide assembly fully to left and verify top cover closes freely.

c. With safety in FIRE position, using the MK15 MOD0 (RH) and MK16 MOD 0 (LH) chargers, 3269408 and 3269409, pull the bolt, 3269461, to the rear until sear is engaged. The bolt and chargers shall move freely without binding.

d. Hold the chargers to the rear to restrain the bolt. Disengage the sear and allow the bolt to return slowly to battery. There shall be no binding of the sear, bolt or chargers.

e. Repeat step 2.c. With the safety in the SAFE position, after searing, depress trigger, Dwg. 3269533 to assure that bolt will not return to battery.

f. Move safety to FIRE position. Hold the chargers to the rear to restrain the bolt. Disengage the sear and allow the bolt to return slowly to battery. There shall be no binding of the sear, bolt or chargers.

g. Verify that the bolt timing is set as specified.

h. Charge gun, return chargers to stow position, move safety to FIRE position, depress trigger, raise top cover and verify firing pin is protruding from bolt face. (return safety to SAFE position).

i. Verify that the firing pin is being retracted as the bolt travels rearward (being pulled by the chargers). This can be determined by watching the firing pin point disappear into the bolt face as the bolt is moved rearward from the battery position.

j. Verify letters "P" and "M" appear on the barrel, indicating satisfactory completion of proof firing and magnetic particle inspection of the barrel.

k. Solenoid Checks.

(1) Depress sear spring pin, 3269420, rotate sear housing cap, 3269471, 90 degrees and lift cap out of sear housing.
(2) Position solenoid, 3269501, into sear housing with tab end in line with gun axis, press into sear housing and rotate either right or left. (Solenoid will locate with pin once in correct lock position).
(3) Connect solenoid to 24-28VDC using firing switch cable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:00Z
Check the source to verify that this is the current version before use.

(4) Verify that gun will charge with safety in SAFE position, and that firing switch activation does not release bolt from sear position.

(5) Verify that gun will charge with safety in FIRE position, and that firing switch activation releases bolt from sear position.

(6) Remove firing switch cable and solenoid and replace sear housing cap.

4.5.2 Ammunition compatibility check. Install the machine gun on an approved mount or stand. The ammunition compatibility check shall be performed as follows:

a. Install feed throat, raise the Top Cover and assure that Bolt Ass'y is in the battery position.

b. Feed four (4) linked M922 rounds into the weapon until the first round is latched in position by the Secondary Feed Pawl.

c. Move Feed Slide Assembly to left and close Top Cover. Charge weapon, verify Sear is engaged, return Chargers to stow position and verify that rounds have been fed across feeder.

d. Move the safety to FIRE, release the Sear, and verify Ogive Plunger returns to rest position.

e. Raise Top Cover, verify the Extractors, 3269448 and 3269449, are seated properly on the ammunition case rim. Close top cover.

f. Pull the Bolt Ass'y to the rear until it sears and return the Chargers fully forward to stow position. There shall be no binding of the Sear, Bolt Ass'y or Chargers.

g. Place the weapon Safety in the SAFE position.

h. Looking through the slot in the Charger, verify the ammunition is seated firmly against the Bolt face, and that Round Stop Pawl, 3269489, protrudes from Bolt face above the seated ammunition.

i. Place the weapon Safety in the FIRE position

j. Release the Sear and verify Ogive Plunger returns to rest position. Charge the weapon and return Chargers to stow position. Repeat this process until all four (4) dummy rounds have been fed through the weapon. Verify no malfunctions occurred and no discrepancies were noted.

k. Using the Combination Tool Assembly, 3269494 or equivalent tool, inserted through the charger slot remove last M922 round from the weapon.

Source: https://assist.dla.mil -- Downloaded: 202610-23T04:00Z
Check the source to verify that this is the current version before use.

1. Pulling the Chargers to the rear, hold one Charger to restrain the Bolt Ass'y, Disengage the Sear and allow the Bolt Ass'y to return slowly to battery.

NOTE: CATCH THE EJECTED DUMMY ROUNDS AS THEY COME OUT THE BOTTOM OF THE WEAPON TO PREVENT DAMAGE TO THE ROUNDS.

4.5.3 Gun sight and bore calibration check. Install the machine gun on an approved mount or stand. Gun sight and bore calibration check shall be performed as follows:

a. Fabricate suitable target to dimensions shown on Dwg. 3269423.

b. Remove flash suppressor from gun (if necessary).

c. Align center line of barrel perpendicular to target and on approximate center of "boresight" target cross hairs with muzzle end of barrel at distance from target shown on Dwg. 3269423.

d. Raise the gun sight, ensure that the Sight Frame mark (center line or center punch mark) aligns with the windage scale center mark on the Frame Base.

e. Align the vertical line on target parallel with the right outside edge of gun sight (hereinafter referred to as vertical alignment).

f. Insert 40mm boresight kit with adapter or approved alternative into the muzzle end of the barrel.

g. View through boresight and align boresight and target cross hairs.

h. Verify:

(1) Vertical alignment.

(2) Intersection of boresight cross hairs are aligned with "boresight" target cross hairs.

(3) Set the line of sight aperture for "300" meters. The line of sight should be on the "300" meter line of sight target

(4) Line of sight with the aperture set for "1000" meters. The line of sight should be within the 3 inch diameter target circle on the "1000" meter line of sight target

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:00Z
Check the source to verify that this is the current version before use.

WARNING

During the following firing tests, the gun shall be operated and fired in accordance with the instructions contained in the TM9-1010-230-10. unless otherwise specified, the gun shall be fired at an elevation of 5 ± 5 degrees. Observe all local firing range safety procedures during all firing tests. The mount is to be adjusted so that M430 and M383 ammunition cannot impact closer than 300 yards from the mount.

NOTE

If any firing tests are interrupted by a stoppage caused by faulty links, defective ammunition, or improper operating procedures, the test shall be repeated. If the stoppage is caused by broken or deformed parts or other defect of the gun, the gun shall be rejected. If repairs or replacements of any kind are required, the guns shall be re-subjected to the firing tests. A report of any repair, replacement, malfunction, excessive wear or discrepancy of any kind shall be documented on a discrepancy record and processed in accordance with a Government approved product quality assurance program plan.

4.5.4 Proof inspection. The test shall be performed as follows:

a. Mount the gun on a carriage and cradle assembly (Dwg. 5830052) installed on a M3 tripod mount (Dwg. 6507135) or an approved equivalent.

b. Load one (1) round of M385A1 ammunition and fire the machine gun.

c. Inspect the machine gun and verify there are no signs of failure, deformation, or loosening of any parts.

4.5.5 Firing mode.

a. Mount the machine gun on a carriage and cradle assembly (Dwg. 5830052) installed on an M3 tripod mount (Dwg. 6507135) or an approved equivalent.

b. Depress sear spring pin, Dwg. 3269420, rotate sear housing cap, Dwg. 3269471, 90 degrees, and lift cap out of sear housing.

c. Position solenoid, Dwg. 3269501, into sear housing with tab end in line with gun axis, press into sear housing and rotate either right or left. (Solenoid will locate with pin once it is in correct lock position).

d. Connect solenoid to 24-28VDC using firing switch cable.

e. Load the appropriate number (See Table II or IV) of linked rounds into the gun.

f. Fire the gun in two to three round bursts using the remote firing switch until ammunition 1s expended.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:00Z
Check the source to verify that this is the current version before use.

g. Inspect the gun and verify there is no evidence of damage, failure, stoppage or sear failure.

h. Remove firing switch cable and solenoid and replace sear housing cap.

NOTE

For cold temperature testing, the machine gun and ammunition shall be conditioned for eight hours minimum at -50° F ± 5° F prior to firing. The weapon and ammunition shall be at this temperature when firing begins. The weapon shall be lubricated with MIL-L-14107, or approved equivalent for the cold test firing.

For hot temperature testing, the machine gun and ammunition shall be conditioned for eight hours minimum at +155° F ± 5° F prior to firing. The weapon and ammunition shall be at this temperature when firing begins.

4.5.6 Belt pull. The belt pull test shall be conducted as follows:

a. Mount the machine gun on a carriage and cradle assembly (Dwg. 5830052) installed on a M3 tripod mount (Dwg. 6507135) or an approved equivalent.

b. Load a twenty-eight (28) round belt hanging free within an approved feed chute.

c. Fire the twenty-eight (28) round belt in two (2) to four (4) round bursts.

4.5.7 Cyclic rate of fire. The cyclic rate of fire shall be conducted as follows:

a. Mount the machine gun on a carriage and cradle assembly (Dwg. 5830052) installed on a M3 tripod mount (Dwg. 6507135) or an approved equivalent with cyclic rate correlation.

b. Load ten (10) round belts, as applicable.

c. Fire the belt(s) in ten (10) round bursts.

d. Results for each machine gun shall not be averaged but individually compared with the cyclic rate requirement.

4.5.8 Trunnion load. The test shall be performed as follows:

a. For First Article Inspection, this test shall be performed concurrently with the belt pull test.

Source: https://assist.dla.mil -- Downloaded: 202640-23T04:00Z
Check the source to verify that this is the current version before use.

b. Mount a Quartz Force Link Cell Kistler Model 9362 with a Charge Amplifier Model 504E and a Filter Model 545A (or equivalent) directly below receiver (below locking pin) integral with the mount and in alignment with the receiver Buffers, Dwg. 3269551.

c. Record a time-load trace of recoil using a Honeywell Visicorder Model 1858 with a TCD (tape compatible differential) Amplifier Model 1887 or approved alternative equipment.

d. Trunnion load forces are to be measured at the mounting point. The last three (3) rounds of the belt fired shall be discounted.

4.5.9 Angle of fire, elevated.

a. Mount the machine gun on an approved mount.

b. Load eight (8) linked M385A1 rounds and elevate gun to 70 ± 5 degrees.

c. Fire the eight (8) rounds in a single burst.

d. Inspect the gun and verify that there is no evidence of damage or stoppage.

4.5.10 Angle of fire, depressed.

a. Mount the machine gun on an approved mount.

b. Load eight (8) linked M385A1 rounds and depress gun to 70 ± 5 degrees below horizontal.

c. Fire the rounds in one to two round bursts.

d. Inspect the gun and verify that there is no evidence of damage or stoppage.

4.5.11 Accuracy.

a. Mount the machine gun on an approved fixed mount.

b. Load the appropriate number (See Table II or IV) of linked rounds into the gun.

c. Raise the gun sight aperture to the 1000 meter range marking.

d. Using the sight, train and elevate the machine gun to acquire a 14 meter target at a known 1000 meter range. Contractor may submit for approval a proposed equivalent Sight Accuracy Verification Procedure.

e. Fire the rounds in two to three round bursts.

f. Verify that all rounds strike the target.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:00Z
Check the source to verify that this is the current version before use.

g. Inspect the gun and verify that there is no evidence of damage, failure, stoppage or sear failure.

h. Those guns that do not remain within the acceptable deviation will be recalibrated and retested until sight/bore calibration is achieved.

4.5.12 Post firing inspection. After completion of all testing and cleaning and prior to preservation and packing, a visual and manual inspection shall be performed on the gun and on its component parts. The inspection shall consist of the following characteristics:

a. Improper cleaning.
b. Specified protective coating missing.
c. Evidence of poor quality.
d. Manufacturing operations incomplete.
e. Improper assembly.
f. Poor workmanship.
g. Parts damaged.
h. Finish improper.
i. Marking incorrect or illegible.

4.5.13 Interchangeability.

4.5.13.1 First article. The interchange schedule for first article shall be submitted to Commander, U.S. Army Armament Research, Development and Engineering Center, Attn: AMSTA-AR-QAC-C, Picatinny Arsenal, NJ 07806-5000, for approval. The interchange of parts shall be performed after all inspections and tests are completed. After completion of the interchange, the machine guns shall successfully pass the tests specified in 4.5.2, 4.5.3, 4.5.5, 4.5.6. 4.5.7, 4.5.8, 4.5.9, 4.5.10 and 4.5.11.

4.5.13.2 Quality conformance. The interchangeability test for the weapons shall be performed after all inspections and tests are completed. Two (2) MK19 MOD 3 40mm Machine Guns shall be selected (by the government representative) from each months production or lot of 400 guns produced whichever is less. A third MK19 will be provided as GFE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:00Z
Check the source to verify that this is the current version before use.

a. The following items must be replaced upon disassembly and therefore must be on hand for the Interchangeably Test. These parts will be replaced without penalty to the Interchangeability Test and w111 be referred to as "replaceable".

Part No.	Nomenclature	Qty (per gun)
MS21255-16	Screw, Cap, Soc. Hd.	2
2655776	Screw, Set, Nylon, Point	4
2680889	Screw, Cap, Fl. Hd.	2
MS20995-C32	Wire, Safety, Cres	As Req
NAS1351C3LN10	Screw, Cap, Soc. Hd.	3
MS24665-300	Pin, Cotter (Split)	2
MS14145-L6	Nut, Self Locking	2
MS24665-1010	Pin, Cotter, (split)	1
MS90727-28L	Screw, Cap, Slflkg, Hex Hd.	3
MS16562-217	Pin, Spring	1
MS171512	Pin, Spring	1
MS171533	Pin, Spring	2
3269487	Spring, Guide Rod	1
3269416	Stop Kit, Feed Slide	1

b. The three guns shall be designated as Gun 1, Gun 2 and Gun 3. All guns shall be kept separate until otherwise instructed. These guns shall be disassembled and the parts/subassemblies/partial assemblies from each gun divided into five (5) Non-mating groups as listed by Table V discarding all "replaceable".

c. The guns shall be reassembled in accordance with the Table VI "MK19 3 Gun Interchange Matrix".

Table V
Component Interchange

Group 1

Bolt, Shoulder, Sltd Hd	2690962 (2)
Pin, Shoulder, Hdls	3269420
Lock Plate Assembly	5526198
Spring, Helical, Cprsn	3269425
Lever, Cocking	3269443
Bolt Buffer Assembly	3269402
Extractor, LH	3269448
Extractor, RH	3269449
Retainer, Pin	3269450 (2)
Pin, Firing	3269456
Washer, Front	3269459
Receiver	3269460
Washer, Spring	3269474 (2)
Pawl, Feed Tray	3269490
Lever, Safety	3269518
Pin, Recoil	3269553
Spring, Hld, Cprsn, Cres	MS24585-C140

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:00Z
Check the source to verify that this is the current version before use.

Table V (Continued)

Group 2

Spring, Helical Cprsn	2813531 (2)
Alignment Guide Assembly	3269403
Pin Assembly, Back Plate	3269404
Lever, Drive, Primary	3269426
Rod, Pawl, Secondary	3269434
Rod, Pawl, Primary	3269435
Tube, Outside	3269440 (2)
Rod, Inner	3269442 (2)
Cover, Firing Pin	3269452
Spring, Plunger, Ogive	3269455
Spring, Shuttle	3269462
Cover, RH	3269463
Cover, LH	3269464
Sear, Firing Pin	3269467
Pin, Cover	3269472 (2)
Housing, Sear and Safety	3269473, 3269498, 3269519, 3269520, MS16562-215 (2)
Pin, Extractor	3269476 (2)
Slide, Charger	3269480 (2)
Spring, Pawl, Feed	3269497 (2)
Spring, Pawl, Primary	3269502
Spring, Pawl	3269515
Spring, Sear	3269517
Pin, Safety Mechanism	3269522
Suppresser, Flash	3268529
Rod, Operating	3269535
Spring, Hlcl, Cprsn, Cres	MS24585C13 (2)

Group 3

Bolt, Finger, RH	2680956
Bolt, Finger, LH	2680959
Cam, Follower	2680964
Secondary Drive Lever Assembly	3269412
Spring, Firing Pin	3269417
Cam, Vertical	3269427
Slide, Feed, Outer	3269432
Pawl, Secondary	3269438
Block, Round Positioning	3269439
Tube, Middle	3269441 (2)
Sleeve, Bolt	3269444 (2)
Sear, Receiver	3269470
Pin, Cocking Lever	3269475
Housing, Charger, RH (Partial assembly)	3269506, 3269513, MS24585-1063, MS171506
Housing, Charger, LH (Partial Assembly)	3269507, 3269513 MS24585-1063, MS171506
Spring, Firing Pin Sear	3269525

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:00Z
Check the source to verify that this is the current version before use.

Table V (Continued)

Body Mgt Plate and Grips	3269534, 5009369 (2), 5009394 (2), 7265561 (2)
Receiver Buffer Bodies and Internal Components	3269551, 3269552, 3269554, 3269555, 2680901
Sear, Buffer	5526201
Rod, Sear Buffer	5526202
Pin, Grooved, Hdls	5526204
Pin, Straight, PNH	MS20392-1C21
Spring, Helical, Cprsn	MS24585-C181

Group 4

Housing, Spring and Rod, Guide	3269429, 3269481
Pawl, Primary	3269436
Housing, Spring, Ogive	3269437
Barrel, 40MM Grenade	3269442
Bolt/Pawl/Pin/Spring	3269461, 3269489, 3269526, MS24585-2121
Cap, Sear Housing	3269471
Top Cover Assembly	3269406
Spring, Secondary Pawl	3269486
Pin, Locking	3269491
Lock, Lever, Drive	3269492
Slide, Safety	3269499
Arm, RH and Handle Assembly	3269503, 6313800
Arm, LH and Handle Assembly	3269524, 6313800
Sight Assembly	3269545
Washer, Buffer	5526203 (2)
Cam, Follower, Double	5526209
Pin, Straight, Hdls	MS9389-84 (2)

Group 5

Spring, Finger	2813529 (2)
Pawl, Feed	3269428 (2)
Slide, Feed, Inner	3269430
Tray, Feed	3269431
Spring, Recoil	3269433 (2)
Sear, Bolt	3269457
Plunger, Ogive	3269483
Washer	3269493
Back Plate	3269512
Lock, Charger Handle	3269516 (2)
Pin, Safety Lever	3269521
Pin, Sear	3269523
Plate, Trigger, Manual	3269533
Spring, Sear, Inner	5526208
Spring, Helical, Cprsn, Cres	MS24585-C56
Pin, Str, Hds	MS9842-14

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:00Z
Check the source to verify that this is the current version before use.

Table VI
MK19 3 GUN INTERCHANGE MATRIX

TEST GUN NUMBER 1
Group 1 from Gun 1
Group 2 from Gun 2
Group 3 from Gun 3
Group 4 from Gun 3
Group 5 from Gun 1

TEST GUN NUMBER 2
Group 1 from Gun 2
Group 2 from Gun 3
Group 3 from Gun 1
Group 4 from Gun 1
Group 5 from Gun 2

TEST GUN NUMBER 3
Group 1 from Gun 3
Group 2 from Gun 1
Group 3 from Gun 2
Group 4 from Gun 2
Group 5 from Gun 3

d. Following reassembly, the three test guns shall successfully pass the tests specified in 4.5.2, 4.5.3, 4.5.5, 4.5.6 (ambient only), 4.5.7, and 4.5.11. After completion of the interchange test and subsequent testing, the machine guns shall be subjected to the inspections specified in 4.5.12.

e. Due to the nature and complexity of assembly 3269552 (Buffer Rod Assembly), the Interchangeability Test for these parts shall be a separate test. To verify interchangeability, a government representative shall observe the assembly of three units, from each lot of 300 or less, as performed by the manufacturer. This representative shall ensure that pieces are chosen at random when assembly is performed. If there is any doubt that the piece's were not chosen at random, the representative shall request that the unit in question be disassembled and reassembled using different parts. If the newly chosen pieces fail to mate, the lot(s) involved shall be carefully examined to verify proper manufacture.

4.5.14 Reliability.

a. Mount the machine gun on a carriage and cradle assembly (Dwg. 5830052) installed on a M3 tripod mount (Dwg. 6507135) or an approved equivalent.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:00Z
Check the source to verify that this is the current version before use.

b. Load forty-eight (48) linked M385A1 rounds and fire the following schedule until the prescribed quantity of rounds are expended:

Number of rounds	
48	Single shot (3 second intervals between shots)
48	5-round bursts (3 second intervals between bursts)
48	20-round bursts (10 second intervals between bursts)
48	48-round continuous burst

NOTE

At the beginning of the test and at the beginning of each subsequent 1152 round cycle, three (3) 10-round vertical dispersion targets shall be fired single shot at a range of 50 meters. Velocity shall be recorded (on each dispersion round) for determination of conformance to barrel life requirements.

c. Weapon maintenance during the test shall be performed as follows:

Every 576 rounds -

(1) Field strip the bolt and backplate, primary and secondary drive lever, vertical cam, feeder slide, alignment guide and ogive plunger assemblies.
(2) Visually inspect.
(3) Wipe these assemblies, along with the sear and inside of the receiver, with a clean rag and recoat with MIL-L-46150 or MIL-L-46000 lubricant.
(4) Clean barrel with bore brush using MIL-C-372 cleaning compound or approved equivalent.

Every 1152 rounds -

Completely disassemble, visually inspect, clean and recoat with appropriate lubricant and clean barrel with bore brush using MIL-C-372 cleaning compound or approved equivalent.

Every 2,304 rounds -

(1) Completely disassemble, visually and magnetic particle inspect, clean and recoat with appropriate lubricant and clean barrel with bore brush using MIL-C-372 cleaning compound or approved equivalent.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:00Z
Check the source to verify that this is the current version before use.

(2) Magnetic Particle inspect parts, shown on the following list, to assure that no safety or catastrophic failures are imminent.

Nomenclature	Dwg. Number
Barrel, 40MM Grenade	3269422
Bolt	3269461
Cover, Firing Pin	3269452
Pin, Firing	3269456
Sear, Bolt	3269457
Sear, Firing Pin	3269467
Receiver	3269460
Plate, Lock	3269421
Tray, Feed	3269431

d. During the test, observation shall be made to determine compliance with the applicable requirements. After the test the necessary calculations shall be made to determine compliance with the applicable reliability requirements.

5. PACKAGING

5.1 Preservation, packaging, packing, and marking shall be in accordance with Special Packaging Instructions SPI-3269419 or as specified by the procurement activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory)

6.1 Intended use. The machine gun is intended for anti-personnel and light anti-armor use. It may be fired from a ground mounted tripod, from a turret or from free or fixed mounts in ground vehicles, helicopters, riverboats or ships.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number and date of this specification.

b. Quantity required and delivery schedules.

c. Serialization requirements.

d. First article sample requirements, if other than that specified in Section 4 of this specification.

e. Quality conformance inspection requirements, if other than that specified in Section 4 of this specification

f. Packaging requirements, if other than that specified in Section 5 of this specification.

Source: https://assist.dla.mil -- Downloaded: 202610-23T04:00Z
Check the source to verify that this is the current version before use.

g. Responsibility for furnishing ammunition, links, boresights, boresight adapters and mounts.

h. Responsibility for conditioning chambers, test firing facilities, equipment and operating procedures.

i. Disposition of machine guns tested for reliability.

6.3 First article. When first article inspection is required, the contracting officer should provide specific guidance to offerors whether the item(s) should be preproduction sample, a first article sample, a first production item, a sample selected from the first production items, a standard production item from the contractor's current inventory (see 3.8), and the number of items to be tested as specified in 4.3. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for examinations, approval of first article test results, and disposition of first articles. Invitations for bids should provide that the Government reserves the right to waive the requirement of samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract. Bidders should not submit alternate bids unless specifically requested to do so in the solicitation.

6.4 Submission of inspection equipment designs for approval. Submit equipment designs as required to Commander, U.S. Army Armament Research, Development and Engineering Center, ATTN: AMSTA-AR-QAC-C, Picatinny Arsenal, NJ 07806-5000. Request letter of submittal shall state contractor, contract number, specification number, item nomenclature and classification of defects or test.

6.5 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research, Development and Engineering center (ARDEC) may also include drawings prepared by, and identified as, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, Picatinny Arsenal, US Army Armament Research and Development Command (ARRADCOM) or US Army Armament Research and Development Center (ARDC) drawings. Technical data originally prepared by these activities is now under the cognizance of ARDEC.

6.6 Subject term (key word) listing.

Ammunition, 40mm, High Velocity Grenade
Gun, Machine

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:00Z
Check the source to verify that this is the current version before use.

6.7 Definitions.

6.7.1 Runaway. A "runaway" gun is one which experiences uncontrolled automatic fire for one round or more.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1010-A140)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:00Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL–G–70790	950607

3. DOCUMENT TITLE: GUN, MACHINE, 40MM MK19 MOD 3

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets if needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code)	
U.S. ARMY ARDEC STANDARDIZATION OFFICE	(1) Commercial 201–724–6674	(2) AUTOVON DSN–880–6674
c. ADDRESS (Include Zip Code) ATTN: AMSTA–AR–EDE–S PICATINNY ARSENAL, NJ 07806–5000	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041–3466 Telephone (703) 756–2340 AUTOVON 289–2340	

DD Form 1426, OCT 89 — *Previous editions are obsolete.* — 198/290

Source: https://assist.dla.mil -- Downloaded: 202610-23T04:00Z
Check the source to verify that this is the current version before use.