MIL-R-52676A(ME)
30 June 1975
SUPERSEDING
MIL-R-52676(ME)
23 December 1969

MILITARY SPECIFICATION

RECTIFIER SECTION, TOPOGRAPHIC MAPPING SET, TRUCK MOUNTED, PACKAGING OF

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers requirements for preservation, packaging, packing, and marking of a rectifier section, topographic mapping set, truck-mounted, SC 6675-97-CL-E37, NSN (6675-00-526-4629) or (6675-00-914-4664 for MAP).

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

Federal

PPP-B-601	- Boxes, Wood, Cleated-Plywood.
PPP-B-636	- Boxes, Shipping, Fiberboard.
PPP-P-40	- Packaging and Packing of Hand Tools.

Military

MIL-P-116	- Preservation-Packaging, Methods of.
MIL-R-3593	- Refrigeration and Cooling Equipment (Excluding Household Refrigerators), Packaging of.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:29Z
Check the source to verify that this is the current version before use.

MIL-D-4827	- Developer, Photographic, Paper, Armed Forces Developer No. 25.
MIL-P-10603	- Pumps and Pumping Units, Centrifugal, Power-Driven, For Water, Packaging of.
MIL-R-11254	- Rectifier, Projection Printing, Photogrammetric: 9-1/2 Inch Aerial Roll Film; Vertical Projection, 0 to 20 Degree Tilt, with 0.7 to 3.3 Magnification at 20 Degree Tilt, Autofocusing.
MIL-G-28554	- Generator Sets, Mobile Electric Power; Packaging of.

STANDARDS

Military

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-281	- Automobiles, Trucks, Truck-Tractors, Trailers and Trailer Dollies; Preservation and Packaging of.

(Copies of specifications and standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations, Inc., ATTN: Tariff Order Section, 1616 P Street, NW, Washington, DC 20036.)

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, ATTN: Tariff Publishing Officer, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:29Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Preproduction pack. The supplier shall furnish a preproduction pack for examination within the time frame specified (see 6.2) to prove prior to starting production packaging that the applied preservation, packaging, packing, and marking comply with the requirements of this specification. Examination shall be as specified in Section 4 and shall be subject to surveillance and approval by the Government (see 6.3). The preproduction pack may be prepared utilizing either the preproduction set or a production set. If the preproduction model set is utilized, any preservation, packaging and packing shall be removed by the supplier at no expense to the Government, when requested by the Government, to facilitate comparison between the preproduction set and the production set.

3.2 Material. Material shall be as specified herein and in applicable specifications and standards. Materials not specified shall be selected by the supplier and shall be subject to all provisions of this specification. Materials shall be free of defects.

3.3 Preservation and packaging. Preservation and packaging shall be Level A or C, as specified (see 6.2).

3.3.1 Level A.

3.3.1.1 Preservatives. Preservatives specified herein shall conform to the applicable specifications listed in and shall be applied in accordance with MIL-P-116.

3.3.1.2 Methods of preservation. Methods of preservation indicated by symbols herein shall conform to the corresponding symbols in MIL-P-116.

3.3.1.3 Handtools. The hammer, knives, pliers, screwdriver, shears, key set, pin vises, and open-end and pipe wrenches and wrench sets shall be preserved and packaged in accordance with PPP-P-40, Level A. The preserved and packaged tools shall be placed in the toolbox furnished as a set component.

3.3.1.4 Truck/van. The components and accessories of the truck/van shall be preserved in accordance with MIL-STD-281, Level A (mobile), and as follows.

3.3.1.4.1 Screw jacks. The screws of the jacks shall be coated with Type P-11 preservative and the screws fully retracted into the jacks. Exterior unpainted surfaces of the jacks shall be coated with Type P-1 preservative. The jacks shall be secured in the stowage compartment on the truck/van body.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:29Z
Check the source to verify that this is the current version before use.

3.3.1.4.2 Power cable, cable reel and cover. The cable assembly shall be wound on the cable reel provided and the reel secured to prevent the cable from unwinding. The reel cover shall then be placed on the cable reel.

3.3.1.4.3 Heating and air conditioning unit. The heating and air conditioning unit shall be preserved in accordance with MIL-R-3593, Level A.

3.3.1.5 Generator set (MAP). The generator set, accessories, repair parts, tools, and publications shall be preserved, packaged, packed, and marked in accordance with MIL-G-28554, Level A.

3.3.1.6 Centrifugal pump (MAP). The pump, repair parts, tools, and publications shall be preserved, packaged and packed in accordance with MIL-P-10603, Level A.

3.3.1.7 Glycerin. Glycerin contained in bottles shall not require unit packaging.

3.3.1.8 Pipe-to-hose adapters, pipe bushings, pipe caps, pipe elbows, pipe nipples, and pipe reducers. Items requiring the application of a contact preservative in accordance with MIL-P-116 shall be coated with Type P-1 preservative. The fittings shall be placed in the chest provided.

3.3.1.9 Gaskets, ferrotype plates and stirring rods. These items in the quantity required for each set shall be preserved Method IC-1.

3.3.1.10 Dusting brushes, flask brushes, paint brushes, and scrub brushes. The bristles and hair of each brush shall be protected by an envelope or by fiber pads to prevent deformation. Each brush shall then be preserved Method IC-1.

3.3.1.11 Electrical connector plug, print paddles, manual inflating pump, photographic print roller, drafting scales, pencil sharpener, stereoscope, squeegee, rolls of tape, and drafting triangles. Each item shall be preserved Method IC-1 or IC-2 when the item is furnished in a supplier's commercial container.

3.3.1.12 Photographic paper. Each box of photographic paper shall be preserved Method IC-2. The container shall be the supplier's commercial container.

3.3.1.13 Staples and knife blades. Each box of staples and each package of knife blades shall be preserved Method IC-2. The container shall be the supplier's commercial container.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:29Z
Check the source to verify that this is the current version before use.

3.3.1.14 Photographic developer. The cans of photographic developer shall be packaged in accordance with MIL-D-4827, Level A.

3.3.1.15 Wastepaper basket, processing trays, folding chairs, glass graduates, desklights, staplers, folding-leg tables, and paper trimmer. Items furnished in the supplier's commercial container shall be preserved Method IC-2. Items furnished without containers shall be packaged in close-fitting boxes conforming to PPP-B-636, W5c or W6c, as applicable to weight of the item. Closure and sealing of the boxes shall be in accordance with the appendix to the box specification.

3.3.1.16 Filter set. Each filter of the filter set shall be individually preserved Method IC-1, then all of the filters shall be packaged together in a close-fitting box conforming to PPP-B-636, W6c. The box shall be provided with separators fabricated of the same material as the box and placed between each of the filters. As an alternate, each filter set, when wrapped, cushioned and contained in the supplier's commercial container, shall be preserved Method IC-2.

3.3.1.17 Cargo trailer (MAP). The cargo trailer shall be preserved in accordance with MIL-STD-281, Level A (mobile).

3.3.1.18 Hose assemblies. Each hose assembly shall be coiled to the minimum safe diameter and each coil secured with not less than four evenly spaced ties of cotton tape or twine.

3.3.1.19 Printer, contact, photographic. The printer shall be preserved Method IIa by bolting directly through the barrier material to the mounting provided for the printer.

3.3.1.20 Interval timers. Each interval timer shall be preserved Method IIb. The inner container shall be the supplier's standard commercial container or a close-fitting box conforming to PPP-B-636, Class Domestic, Variety sw, Grade 125, and the outer container conforming to PPP-B-636, W5c. Closure shall be in accordance with the appendix to the box specification.

3.3.1.21 Projection printing rectifier. The rectifier, repair parts, tools, and publications shall be preserved in accordance with MIL-R-11254, Level A, except the rectifier shall be secured directly through the barrier material to its mounting within the van in lieu of the crate base specified therein.

Source: https://assist.dla.mil -- Downloaded: 202640-22T21:29Z
Check the source to verify that this is the current version before use.

3.3.1.22 Dehumidifier and photographic print drier. Each of these items shall be preserved Method IIa by bolting the items directly through the barrier material to their mounting provisions within the van.

3.3.1.23 Other components. Other components not specifically specified herein shall be preserved and packaged as specified for components of similar design and construction.

3.3.1.24 Consolidated packaging. Packaged and unpackaged components that cannot be placed in the drawers, toolboxes, compartments, cabinets, or shelves shall be consolidated packaged together in close-fitting boxes conforming to PPP-B-601, Domestic Type, Style I. The boxes shall be of a size to fit into the available space within the van body or truck cab. Strapping of the boxes shall not be required. The boxes shall be immobilized within the van body or truck cab using blocking, bracing or strapping, as required, and applied in a manner not to damage the items or the set components to which the boxes are secured.

3.3.2 Level C. The components of the set including the truck/van shall be preserved and packaged to afford protection against deterioration and damage from the supplier to the initial destination.

3.4 Packing. Packing shall be Level A or C, as specified (see 6.2).

3.4.1 Level A. The truck/van, containing the set components prepared for shipment as specified in 3.3, shall be shipped unboxed (mobile). The packed generator set (MAP) and the packed pump (MAP) shall be placed inside the van body if space is available. The units shall be secured to prevent movement within the van body. When space is not available for securing within the van body, the generator set and pump shall be placed and secured in the cargo trailer (MAP) if a trailer is furnished. The cargo trailer, preserved as specified in 3.3, shall be shipped (mobile) separately from but at the same time as the mobile van. Van wheels and cargo trailer wheels shall be free to rotate. If a trailer is not furnished, the packed generator and the packed pump shall be shipped separately from but at the same time as the truck/van.

3.4.2 Level C. The truck/van, containing the set components and preserved and packaged as specified in 3.3, shall be prepared for shipment unboxed (mobile) in a manner to assure carrier acceptance and safe delivery to destination at the lowest ratings of the carrier in compliance with Uniform Freight Classification rules or National Motor Freight Classification rules.

3.5 Marking. In addition to any special marking required by the contract or purchase order, packages, consolidated containers, unboxed (mobile) truck/vans, and trailers shall be marked in accordance with MIL-STD-129 (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:29Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Material inspection. The supplier is responsible for insuring that supplies and materials used are manufactured, examined and tested in accordance with referenced specifications and standards.

4.2 Classification of inspections. Inspections shall be classified as follows:

(a) Preproduction pack inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).

4.3 Preproduction pack inspection.

4.3.1 Examination. The preproduction pack shall be examined for the defects listed in 4.4.4. Presence of one or more defects shall be cause for rejection of the preproduction pack.

4.4 Quality conformance inspection.

4.4.1 Inspection stages.

(a) The first stage shall include inspection of procedures, methods, materials, containers, and packaging marking prior to placing the packages in location in the van or prior to placing the packages into consolidated containers.
(b) The second stage shall include inspection of closure and marking of the consolidated containers and the arrangement, blocking and bracing of the located items and blocking and bracing of consolidated containers in the van.
(c) The third stage shall include inspection of the closed and marked mobile truck/van as prepared for shipment and of the cargo trailer as prepared for shipment when a trailer is furnished.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:29Z
Check the source to verify that this is the current version before use.

4.4.2 Unit of product. For the purpose of inspection, all packages or packs, prepared for any applicable inspection stages that will comprise a complete pack, shall be considered a unit of product.

4.4.3 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.4.4 Examination. Samples selected in accordance with 4.4.3 shall be examined for the defects marked "X" for the applicable level in Table I. Acceptable quality level (AQL) shall be 2.5 percent defective.

Table I. Classification of Defects

	Defect	Level A	Level C
101.	Materials, methods and containers not as specified. Each incorrect material, method or container shall constitute one defect (see 3.2, 3.3, 3.4).	X	X
102.	Handtools not preserved and packaged in accordance with the referenced document as specified (see 3.3.1.3).	X	-
103.	Truck/van components and accessories not preserved and packaged in accordance with the referenced document as specified (see 3.3.1.4).	X	-
104.	Screw jacks not preserved and stowed as specified (see 3.3.1.4.1).	X	-
105.	Power cable not wound on reel or reel not secured and covered as specified (see 3.3.1.4.2).	X	-
106.	Heating and air conditioning unit not preserved in accordance with the referenced document as specified (see 3.3.1.4.3).	X	-
107.	Generator set not preserved, packaged and packed in accordance with the referenced document as specified (see 3.3.1.5).	X	-
108.	Centrifugal pump not preserved, packaged and packed in accordance with the referenced document as specified (see 3.3.1.6).	X	-
109.	Pipe fittings not preserved and placed in the chest as specified (see 3.3.1.8).	X	-
110.	Bristles and hair of brushes not protected to prevent deformation as specified (see 3.3.1.10).	X	-
111.	Photographic developer not packaged in accordance with the referenced document as specified (see 3.3.1.14).	X	-
112.	Filter sets not preserved and packaged as specified (see 3.3.1.16).	X	-
113.	Cargo trailer not preserved in accordance with the referenced document (see 3.3.1.17).	X	-

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:29Z
Check the source to verify that this is the current version before use.

Table I. Classification of Defects (Cont'd)

Defect	Level A	Level C
114. Hose assemblies not coiled and secured as specified (see 3.3.1.18).	X	-
115. Rectifier not preserved in accordance with the referenced document (see 3.3.1.21).	X	-
116. Other components not specifically specified not preserved and packaged as specified (see 3.3.1.23).	X	-
117. Consolidated packaging not as specified (see 3.3.1.24).	X	-
118. Packing not as specified (see 3.4.1).	X	-
119. Marking missing, illegible, incorrect, or incomplete (see 3.5).	X	X

5. PREPARATION FOR DELIVERY

(This section not applicable to this specification.)

6. NOTES

6.1 Intended use. This specification is intended to be used for direct reference in contracts or purchase orders for the preservation, packaging, packing, and marking of a rectifier section, topographic mapping set, truck-mounted, SC6675-97-CL-E37, NSN (6675-00-526-4629) or (6675-00-914-4664 for MAP).

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) Time frame required for submission of the preproduction pack (see 3.1).
(c) Level of preservation and packaging and level of packing required (see 3.3 and 3.4).
(d) Any special marking required (see 3.5).

6.3 Preproduction pack. Any changes or deviations of production packs from the approved preproduction pack will be subject to the approval of the contracting officer. Approval of the preproduction pack will not relieve the supplier of his obligation to preserve, package, pack, and mark the set components in accordance with this specification.

Custodian:

Army - ME

Review activity:

Army - SM

Preparing activity:

Army - ME

Project No. 6675-A193

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:29Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:29Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Mobility Equipment Research
and Development Center
Attn: AMXFB-DS
Ft. Belvoir VA 22060

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:29Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:29Z
Check the source to verify that this is the current version before use.