MILITARY SPECIFICATION

SHIPPING AND STORAGE CONTAINER, WARHEAD SECTION: M511

1. SCOPE

1.1 This specification covers requirements, quality assurance provisions, and the preparation for delivery criteria for one type of shipping and storage container, entitled, Shipping and Storage Container, Warhead Section: M511, which is used with the Lance warhead section.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-T-5021	- Tests, Aircraft Welding Operator's Certification.
MIL-W-8611	- Welding, Fusion, of Steels and Corrosion and Heat-Resisting Alloys.
MIL-W-45205	- Welding, Inert-Gas, Metal Arc, Aluminum Alloys Readily Weldable for Structures, Excluding Armor.
MIL-W-50508	- Mounts Resilient (for use in Ammunition Shipping Containers).

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-810	- Environmental Test Methods.
MIL-STD-1169	- Packaging, Packing and Marking for Shipment of Inert Ammunition Components.

DRAWINGS

ORDNANCE CORPS

8859012 - Finishing Requirements for Ferrous Metal Containers.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:30Z
Check the source to verify that this is the current version before use.

9219390 - Container, Shipping and Storage Warhead Section M511.
ET-9219390 - Equipment Tabulation.
9219391 - Upper Shell Assembly.
9219392 - Lower Shell Assembly.
9219401 - Mounts, Resilient.
9219404 - Support Plate.
9220214 - Adapter.
9231557 - Gasket, EMR Shielding.
9248981 - Cradle Assembly.
9216660 - Shipping and Storage Container for Lance Warhead Sections and Adaption Kits, Packaging and Marking.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The container and parts shall comply with all requirements specified on the drawing (dwg) 9219390, with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the drawing and herein.

3.3 First article testing. Requirements for the submission of first article samples by the contractor shall be as specified in the contract (see 4.2).

3.4 Performance characteristics. The container shall comply with all the requirements on dwg 9219390 and with all requirements in this specification. When loaded with the warhead section or equivalent load, the container shall withstand all environmental and handling tests prescribed herein without evidence of puncture, loose parts, broken or permanently set structural members; distorted or cracked resilient mounts or separation of welds which would render the container unusable or unserviceable. (Note: Minor dents or creases in non-structural members, bent rings or eyes and cracks in wooden skids shall not be considered in determining the useability or serviceability of the container.)

3.5 Function. The container shall support an inert warhead section equivalent to the M234 as described in 4.4.1 in its suspension frame and shall provide an adequate fit at all points of attachment when secured as described in 4.4.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:30Z
Check the source to verify that this is the current version before use.

3.6 Pressure retention. The container, prepared in accordance with 4.4.2, shall withstand an internal pressure of 3.5 ± 0.5 pounds per square inch gage (psig) for 30 minutes minimum when tested as specified in 4.4.3. The permissible leakage during this period shall not exceed a pressure drop of 0.1 psig.

3.7 Environmental testing. The container shall comply with MIL-STD-810, visual inspection and failure criteria, section 3. The container shall also comply with 4.3.3.1 before and after each environmental test. Testing shall be as specified in 4.4.4. Tests shall be conducted in the order specified.

3.7.1 Shock. The container, prepared in accordance with 4.4.2, shall withstand the free fall drops specified in 4.4.4 without evidence of damage as described in 3.4.

3.7.2 Vibration. The container, prepared in accordance with 4.4.2, shall withstand the vibration spectrum defined in Table I without evidence of damage as described in 3.4.

Table I

Frequency Hertz (Hz)	Input Gravity Unit (g) Double Amplitude (da)	Total Sweep Time (Minutes)	Bi-Directional Sweep Time (Minutes)	No. of Sweeps
5-9-5	0.3" DA	5.6	1.4	4
9-26-9	± 1.3 g	14.4	3.6	4
26-52-26	0.036" DA	9.6	2.4	4

3.8 Stacking. The container, prepared in accordance with 4.4.2, shall withstand the weight equal to two identically prepared containers, stacked one on another in the manner prescribed in 4.4.6, without evidence of damage as described in 3.4.

3.9 Hoisting. The container, prepared in accordance with 4.4.2, shall be lifted with each of the four (4) lifting bars in accordance with 4.4.7 without evidence of damage as described in 3.4.

3.10 Cleaning and painting. All components shall be cleaned and painted as specified in dwg 8859012.

3.11 Components. For components to be used in the container, objective evidence indicating that resilient mounts, dwg 9219401, conform to MIL-M-50508 and gaskets, EMR shielding, conform to dwg 9231557, shall be made available to the Government representative.

3.12 Welding operators. Welding shall be performed only by class A operators currently certified in accordance with MIL-T-5021. Class B operators may be used, provided a representative sample of welding corrosion resisting steel to low carbon steel is submitted to Picatinny Arsenal for approval.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:30Z
Check the source to verify that this is the current version before use.

3.13 Welding. Welds shall be reasonably smooth and free of craters. They shall exhibit characteristics of fusion penetration and soundness of weld deposit representative of good welding practice. They shall be free of irregularities which indicate lack of good practice on the part of the operator. All welding fluxes, scale, weld spatter, acids, or basic solutions shall be removed prior to application of any finish coatings. Welding shall comply with MIL-W-8611 and MIL-W-45205.

3.14 Workmanship.

3.14.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

3.14.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.14.3 Burrs. Parts shall be free from burrs.

3.14.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.14.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection.

4.2.1 Quantity to be submitted. When the contract requires first article inspection, the contractor shall submit 1 complete assembly (see dwg 9219390) for first article testing to the testing facility designated in the invitation for bids or request for proposal.

4.2.2 Inspection and testing to be performed. The first article inspection sample shall be subjected to the inspections and tests specified in Table II. Tests shall be conducted in order specified in Table II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:30Z
Check the source to verify that this is the current version before use.

Table II
First article inspection and tests

Inspection or Test
1. Classification of characteristics (see 4.3.2.1)
2. Function (see 3.5)
3. Pressure retention (see 3.6)
4. Stacking (see 3.8)
5. Hoisting (see 3.9)
6. Vibration (see 3.7.2)
7. Shock (see 3.7.1)
8. Pressure retention (see 3.5)

4.2.3 Inspection equipment. The inspection and testing specified in 4.2.2 shall be accomplished by using the gages and test equipment specified in 4.3.4.1.

4.2.4 Rejection. If any item fails to comply with any of the applicable requirements, the first article sample shall be rejected.

4.3 Quality conformance inspection.

4.3.1 Lot formation. The formation of an inspection lot and related functions shall be in accordance with Section 5, MIL-STD-105. A lot shall consist of parts and assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision.

4.3.1.1 Inspection lot. An inspection lot shall be the quantity of parts, subassemblies, or assemblies from the same lot, which are submitted to inspection for Government acceptance.

4.3.2 Product inspection examination. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table (see Table III and Table IV), and inspected for all characteristics in the applicable classification. Any characteristics in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:30Z
Check the source to verify that this is the current version before use.

Table III
Major Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-72	all	140-141	124	256-259	177	541-549	230
73	72	142	125	260-262	178	550-559	231
74	73	143-144	126	263-265	179	560-569	232
75	74	145	127	266-268	180	570-579	233
76	75	146-147	128	269-271	181	580-590	234
77	76	148-149	129	272-275	182	591-601	235
78	77	150	130	276-278	183	602-613	236
79	78	151-152	131	279-282	184	614-625	237
80	79	153-154	132	283-285	185	626-637	238
81-82	80	155-156	133	286-289	186	638-649	239
83	81	157	134	290-293	187	650-662	240
84	82	158-159	135	294-296	188	663-676	241
85	83	160-161	136	297-300	189	677-690	242
86	84	162-163	137	301-304	190	691-704	243
87	85	164-165	138	305-308	191	705-719	244
88-89	86	166-167	139	309-312	192	720-735	245
90	87	168	140	313-316	193	736-751	246
91	88	169-170	141	317-320	194	752-768	247
92	89	171-172	142	321-324	195	769-785	248
93	90	173-174	143	325-329	196	786-804	249
94-95	91	175-176	144	330-333	197	805-823	250
96	92	177-178	145	334-338	198	824-842	251
97	93	179-180	146	339-342	199	843-863	252
98	94	181-182	147	343-347	200	864-884	253
99-100	95	183-184	148	348-352	201	885-907	254
101	96	185-187	149	353-356	202	908-930	255
102	97	188-189	150	357-361	203	931-955	256
103	98	190-191	151	362-366	204	956-981	257
104-105	99	192-193	152	367-372	205	982-1008	258
106	100	194-195	153	373-377	206	1009-1036	259
107	101	196-197	154	378-382	207	1037-1066	260
108-109	102	198-200	155	383-388	208	1067-1098	261
110	103	201-202	156	389-393	209	1099-1131	262
111	104	203-204	157	394-399	210	1132-1166	263
112-113	105	205-207	158	400-405	211	1167-1204	264
114	106	208-209	159	406-411	212	1205-1243	265
115	107	210-212	160	412-417	213	1244-1285	266
116-117	108	213-214	161	418-424	214	1286-1330	267
118	109	215-217	162	425-430	215	1331-1378	268
119	110	218-219	163	431-437	216	1379-1429	269
120-121	111	220-222	164	438-443	217	1430-1483	270
122	112	223-224	165	444-450	218	1484-1542	271
123-124	113	225-227	166	451-457	219	1543-1605	272
125	114	228-230	167	458-465	220	1606-1673	273
126-127	115	231-232	168	466-472	221	1674-1747	274
128	116	233-235	169	473-480	222	1748-1827	275
129-130	117	236-238	170	481-488	223	1828-1914	276
131	118	239-241	171	489-496	224	1915-2010	277
132-133	119	242-243	172	497-504	225	2011-2115	278
134	120	244-246	173	505-513	226	2116-2232	279
135-136	121	247-249	174	514-521	227	2233-2361	280
137	122	250-252	175	522-530	228	over 2361	298
138-139	123	253-255	176	531-540	229		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:30Z
Check the source to verify that this is the current version before use.

Table IV
Minor Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-9	all	14-16	12	28-33	16	77-121	20
10	9	17-18	13	34-41	17	122-273	21
11	10	19-22	14	42-54	18	over 273	22
12-13	11	23-27	15	55-76	19		

4.3.2.1 Classification of characteristics (see 3.2). Critical, major and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.3.2.1.1 Cradle assembly (see dwg 9248981).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Component missing or improper	Visual
102.	Component damaged or loose	Visual/Manual
103.	Components improperly assembled	Visual
104.	Welding improper or insufficient	Visual
105.	Inability to assemble with lower shell assembly (dwg 9219392)	Visual/Manual
106.	Improper cleaning and painting procedures (see 3.10)	Visual
107.	Incorrect width between mounting holes for resilient mount in mounting bars	Gage
108.	Incorrect length from thrust plate to end of cradle	Gage
109.	Perpendicularity of thrust plate with mounting bars	Gage
110.	Objective evidence relating to material missing or improper (see 3.1)	Visual
Minor:		
201.	Protective coating missing, improper, or damaged exposing base metal	Visual
202.	Evidence of poor workmanship (see 3.14)	Visual
203.	Radii missing and sharp edges not broken	Visual/Manual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:30Z
Check the source to verify that this is the current version before use.

4.3.2.1.2 Upper shell assembly (see dwg 9219391).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Component missing or improper	Visual
102.	Component damaged or loose	Visual/Manual
103.	Components improperly assembled	Visual
104.	Improper or insufficient welding	Visual
105.	Improper cleaning and painting procedures (see 3.10)	Visual
106.	Surface not free from weld and weld spatter	Visual
107.	Evidence of finish on surface specified as unfinished (see note)	Visual
108.	Mislocation of stacking pad V angle and holes (4)	Gage
109.	Objective evidence relating to material missing or improper (see 3.1)	Visual
Minor:		
201.	Protective coating missing, improper, or damaged exposing base metal	Visual
202.	Evidence of poor workmanship (see 3.14)	Visual

Note: 100% inspection required.

4.3.2.1.3 Lower shell assembly (see dwg 9219392).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Component missing or damaged	Visual
102.	Component loose or improper	Visual/Manual
103.	Components improperly assembled	Visual
104.	Improper or insufficient welding	Visual
105.	Improper cleaning and painting procedures (see 3.10)	Visual
106.	Surface as indicated in note not free of weld and weld spatter	Visual
107.	Evidence of finish on surface specified as unfinished (see note)	Visual
108.	Mislocation of lifting brace sets (4)	Gage
109.	Mislocation of shear mount bracket assembly (4)	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:30Z
Check the source to verify that this is the current version before use.

110. Mislocation of formed channel (4).....Gage
111. Weld securing adapter (9220214) to lower shell incorrect.....Visual
112. Improper or insufficient welding of formed bar (dwg 9220211).....Visual
113. Wooden runner (skid) unserviceable (split more than 3" long which extends through the skid).....Visual
114. Objective evidence relating to material missing or improper (see 3.1).....Visual

Minor:
201. Protective coating missing, improper, or damaged exposing base metal.....Visual
202. Evidence of poor workmanship (see 3.14).....Visual
203. Sharp edges of lower skin and heads (fwd and aft) unbroken in area of gasket track.....Visual/Manual

Note: 100% inspection required.

4.3.2.1.4 Support plate (see dwg 9219404).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Inability to mate with warhead station 100	Gage
102.	Objective evidence relating to material missing or improper (see 3.1)	Visual
Minor:		
201.	Protective finish missing, improper, or damaged exposing base metal	Visual
202.	Improper finish	Visual
203.	Evidence of poor workmanship (see 3.14)	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:30Z
Check the source to verify that this is the current version before use.

4.3.2.1.5 Container, shipping and storage, warhead section (see dwg 9219390).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Component missing or improper	Visual
102.	Component damaged or loose	Manual/Visual
103.	Components improperly assembled	Visual
104.	Improper or insufficient welding	Visual
105.	Incorrect torque (see table)	Gage
106.	Adhesive extends beyond rubber portion of EMR gasket (see note)	Visual
107.	Improper seating of EMR gasket to lower closure flange	Visual
108.	Improper seating of EMR gasket to desiccant door	Visual
109.	Mislocation of skids, "V" notches, and holes (4)	Gage
110.	Inability or undue effort required to fit, assemble and remove desiccant door over weld studs at forward end of container	Manual
111.	Cushions (see dwg 9248698) web thickness incorrect	Gage
112.	Lower cushion radii incorrect	Gage
113.	Upper cushion radii incorrect	Gage
114.	Any gasket nicked, cut, or damaged to the extent of rendering it unusable	Visual
115.	Records container cover missing, unserviceable; gasket missing, cut, unserviceable	Visual
116.	Structural damage which will preclude use of container for intended purpose	Visual
117.	Container cover S/N does not agree with container base S/N on aft end of container	Visual
118.	Quick access cover loose or unserviceable, environmental gasket missing or unserviceable	Manual/Visual
119.	Cover alignment pins damaged, loose or missing	Visual
120.	Objective evidence relating to material missing or improper (see 3.1)	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:30Z
Check the source to verify that this is the current version before use.

Minor:
201. Marking improper, illegible or missing.....Visual
202. Evidence of poor workmanship (see 3.14).....Visual
203. Protective finish missing, improper, or damaged exposing base metal.....Visual

Note: 100% inspection required.

4.3.2.1.6 Preparation for delivery (see 5).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Packing missing or improper	Visual
	102. Marking not in accordance with applicable drawing	Visual
Minor:		
	201. Evidence of poor workmanship (see 3.14)	Visual

4.3.3 Testing. All tests shall be performed. Tests shall be performed in the order specified below:

Test	Test Classification
a. Function	Major
b. Pressure retention	Major

None of these tests are considered destructive and samples so tested may be returned to the lot.

4.3.3.1 Function and pressure retention. Each container shall be tested in accordance with 4.4.2 and 4.4.3. If any item fails to comply with 3.5 and 3.6, the item shall be rejected and removed from the lot.

4.3.4 Acceptance inspection equipment.

4.3.4.1 Major characteristics and tests. Inspection and testing shall be performed with the acceptance inspection equipment, operating instructions, and calibration instructions specified on the Equipment Lists (EL). Els for assemblies are listed on the Equipment Tabulation, ET-9219390. When either of the conditions listed below exist, the contractor shall design required equipment or specify suitable

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:30Z
Check the source to verify that this is the current version before use.

commercial equipment and obtain approval prior to use on the contract.

a. Any deviation from equipment or procedures specified on the EL is desired (see 6.3).
b. The code "CD" is listed in the "Part or Identifying Number" column on the EL (see 6.1.2).

4.3.4.2 Minor characteristics and tests. Acceptance inspection equipment for minor characteristics is not specified on ELs. The acceptance inspection equipment, operating instructions and calibration instructions used by the contractor for minor classification inspection shall be approved by the Government representative authorized by the procuring agency.

4.4 Test methods. The tolerances specified herein are absolute with no allowance for test equipment inaccuracy. The tolerances used by the manufacturer shall be equal to the absolute tolerances less the accuracy tolerances of the test equipment used.

4.4.1 Test load. The test load shall consist of an inert M234 Warhead Section or an equivalent load having the same weight, weight distribution, center of gravity and configuration.

4.4.2 Function. The warhead section or test load (see 4.4.1) shall be placed in the suspension frame and secured as indicated in dwg 9216660. The upper shell assembly shall be oriented properly and assembled to the lower shell assembly with bolts provided on lower shell assembly. During mating of upper to lower shell assembly, there shall be no requirement for the use of tools. The bolts shall not bind or hang-up in the slots on the upper shell and shall engage without excessive physical force when tightened to the torque specified in dwg 9219390. The forward door shall be seated flush on the forward head assembly without interference of studs with holes in forward door and the nuts used to secure the door shall not bind when tightened to the torque specified in dwg 9219390. All other mating parts shall be capable of being assembled and shall be tightened to the torque specified in dwg 9219390.

4.4.3 Pressure retention. The container, test loaded (see 4.4.1) assembled, sealed and prepared as though for shipment, shall be pressurized with compressed air to 3.5 $\pm$ 0.5 psig. Any relief valves shall be either blocked off or removed with attachment holes plugged. The pressurized container shall be submerged* in water (water temperature may be uncontrolled if the supply temperature ranges between +51.8°F and 68°F) and examined for evidence of air bubbles. A recurring and steady stream of air bubbles shall be cause for rejection.

*Alternately, the pressure retention test may be performed measuring pressure loss by any means (pressure gages or manometers) capable of reading or recording values to the nearest

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:30Z
Check the source to verify that this is the current version before use.

0.1 psi. The container, while at the required pressure and the air source off, shall be maintained in this condition for a minimum of thirty (30) minutes. Any loss in pressure exceeding 0.1 psi shall be cause for rejection.

4.4.4 Environmental testing (see 3.7).

4.4.4.1 Shock. The container, test loaded (see 4.4.1), assembled, sealed and prepared as though for shipment (see 4.4.2) shall withstand the shock tests described in 4.4.4.1.1, 4.4.4.1.2, 4.4.4.1.3 and 4.4.4.1.4. Upon completion of each test, the container shall be inspected and any evidence of damage as described in 3.4 shall be cause for rejection.

4.4.4.1.1 Cornerwise drop test. One corner of the container shall be supported on a block approximately five inches high and the other corner at the same end shall be supported on a block approximately twelve inches high. The opposite end of the container shall be raised and allowed to drop freely onto a concrete or similarly hard surface from heights of 12, 24 and 36 inches. This identical test shall be performed on the diagonally opposite corner of the container.

4.4.4.1.2 Edgewise drop test. One end of the container shall be supported on a block approximately five inches high and positioned perpendicular to its skids. The opposite end of the container shall be raised and allowed to fall freely onto a concrete or similarly hard surface from heights of 12, 24 and 36 inches. This identical test shall be performed on the opposite end of the container.

4.4.4.1.3 Impact test. Each end of the container shall be subjected to one impact. The container shall be freely suspended and swung as a pendulum against a solid, flat and vertical barrier. The longitudinal axis of the container shall be perpendicular to the barrier and the end being impacted resting against it. The container shall be pulled back from the barrier to a point where the impact velocity will equal 10.5 feet per second (fps) + 1.5 fps and then released and allowed to swing freely against the barrier.

4.4.4.1.4 Roll-over test. The container shall be positioned on its skids on a concrete or similarly hard surface. The container shall be tipped slowly sidewise until it falls freely and by its own weight from base to side, side to top, top to other side and side to base, thus completing one revolution.

4.4.4.2 Vibration. The container prepared as described in 4.4.1 and 4.4.2 shall be mounted rigidly on a fixture capable of being readily positioned in the three mutually perpendicular axes. The container shall be vibrated to the requirements in 3.7.2 in each of its three mutually perpendicular major axes. Upon completion of this test, the container shall be inspected and any evidence of damage as described in 3.4 shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:30Z
Check the source to verify that this is the current version before use.

4.4.5 Stacking. The container shall be prepared as described in 4.4.1 and 4.4.2. A test load equal to weight and weight distribution of 2 identically prepared containers shall be applied to the container upper shell assembly stacking pad support points. Upon completion of this test, the bottom container shall be inspected for any evidence of damage as described in 3.4 and such evidence shall be cause for rejection of the container.

4.4.6 Hoisting test. The container shall be prepared as described in 4.4.1 and 4.4.2 and suspended free of the ground by means of a hoisting device from each of its four (4) lifting bars individually (Note: Bars on cover assembly are not to be utilized for lifting the container assembly). Upon completion of each hoisting test, the bar being tested shall be inspected. Any evidence of damage described in 3.4 shall be cause for rejection of the container.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.1.1 Level A. The container shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169(MU).

5.1.2 Level C. The container shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169(MU).

5.2 Packing.

5.2.1 Levels A and C. The container shall be packed in accordance with the applicable instructions contained in MIL-STD-1169(MU).

5.3 Marking. Marking shall be in accordance with dwg 9219390.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

6.1.1 Procurement requirements.

a. Title, number, and date of this specification.

b. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

6.1.2 Contract data requirements (see 4.3.4.1). Data specified in 4.3.4.1 will be delivered as identified on a numbered DD Form 1664 when required on a DD Form 1423 incorporated in the contract.

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:30Z
Check the source to verify that this is the current version before use.

6.3 Acceptance inspection equipment (see 4.3.4.1). The contractor shall obtain approval from the Commander, Picatinny Arsenal, Dover, New Jersey 07801, ATTN: SARPA-QA-T.

6.4 Supersession data. This specification supersedes the requirements of Purchase Description PA-PD-2020A, dated 14 November 1973, with Amendment 1, dated 9 September 1974.

Custodian:
Army - PA

Preparing activity:
Army - PA

Project No. NUOR-A056

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:30Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:30Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:30Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314



OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

COMMANDER
Picatinny Arsenal
ATTN: SARPA-QA-N-Q
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:30Z
Check the source to verify that this is the current version before use.