MIL-C-13139E (PA)
1 April 1974
SUPERSEDING
MIL-C-13139D (MU)
30 August 1968

MILITARY SPECIFICATION

CHARGE, DEMOLITION, SHAPED, 15 POUND M2A3 AND M2A4 PARTS FOR

*This specification is approved for use by all Departments and Agencies of the Department of the Defense.

1. SCOPE

1.1 This specification covers the parts for one type of demolition item designated as Charge, Demolition, Shaped, 15 lb., Practice M2A3 and HE, M2A4.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

*MILITARY

MIL-A-2550 - Ammunition, General Specification For

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)
MIL-STD-109 - Quality Assurance Terms and Definitions
MIL-STD-1168 - Lot Numbering of Ammunition
MIL-STD-1169 - Packaging, Packing and Marking for Shipment of Inert Ammunition Components.

FSC: 1375

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:06Z
Check the source to verify that this is the current version before use.

MIL-STD-1235 - Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

*DRAWINGS

U.S. ARMY PICATINNY ARSENAL

8861579 - Cone
9230162 - Charge, Demolition, Shaped, 15 lb., M2A3 and M2A4, Parts Arrangement

(Copies of specifications, standards, drawings and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

3. REQUIREMENTS

3.1 Material. - Materials shall be in accordance with applicable drawings and specifications.

3.1.1 The glass from which the cone is made shall be clear potash-soda-lead-silicate having a minimum density of 3.00 grams per cubic centimeter.

3.2 Parts and sub-assemblies. - The parts and sub-assemblies shall comply with all requirements specified on Drawings (dwg.) 8861579 and 9230162 as applicable, and with all requirements specified in applicable specifications.

3.3 Water absorption. - Each body assembly and stand-off sleeve, shall absorb not more than 5 percent of moisture when immersed for 24 hours, minimum, in water maintained at 68 plus or minus 2 degrees Fahrenheit (F.).

3.4 Strength of body assembly and stand-off sleeve. - The body assembly and stand-off sleeve, after painting and immersion for 24 hours, minimum, in water maintained at 68 plus or minus 2 degrees F., shall withstand a static load of 100 pounds, minimim, for 1 minute, minimum, with 1/16 inch, maximum, loss in height.

3.5 Leakproofness of body assembly. - The body assembly, when pressurized to 2.5 p.s.i. internally with air, shall not

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:06Z
Check the source to verify that this is the current version before use.

exhibit leakage more than that indicated by a drop of a mercury manometer differential of more than 60 percent in 5 seconds.

3.6 Fit of stand-off sleeve. - The gap between the body and the stand-off sleeve shall not exceed 0.2 inch when a static load of 20 plus or minus 1/2 pound is applied.

3.7 Annealing of glass cone. - The glass cone shall be fully annealed to relieve all undue strains which might cause failure.

3.8 Heat shock test of glass cone. - The glass cone shall not break or show cracks when tested for resistance to heat shock.

3.9 Workmanship. - All parts shall be fabricated and finished in a thorough, workmanlike manner. The parts shall show no evidence of porosity, warpeage, checks, cracks, lamination or blisters. The parts shall be free of chips, dirt, grease, flux, rust and other foreign matter. The cleaning agent used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. Surface coatings shall be continuous except for a few light scratches not exposing base material. All required markings shall be neat and sharply defined. The finished cones shall be free from surface stones, checks and chips. Well buried stones of a maximum dimension of 3/16 inch, blisters of maximum demension of 1/8 inch and hairline blisters will be allowed. Slight discoloration of the plunger and mold surfaces will be allowed, provided they do not indicate flaws or imperfections which would adversely affect the function of the case. The shear mark shall be as near the apex of the cone as practicable.

3.10 First article inspection. - This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

4. QUALITY ASSURANCE PROVISIONS

*4.1 Responsibility for Inspection.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection re-

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:06Z
Check the source to verify that this is the current version before use.

quirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to MIL-STD-109 to define terms used herein. The provisions of MIL-A-2550 shall apply.

4.1.1 Submission of Product.-At the time each completed lot of items deliverable under the contract is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted.

a. A statement that the lot complies with all of the quality assurance provisions specified in this specification.
b. Drawing and specification number and date, together with identification and date of changes thereto.
c. A statement that all material purchased by the contractor meets requirements, when such material is controlled by Government or commercial specifications referenced in any of the contractual documents, and that certificates of conformance are on file and available for review.
d. Number of items in the lot.
e. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agents authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

*4.2 First Article Inspection

4.2.1 Submission.-Prior to the start of regular production the contractor shall submit a first article sample (see 6.1c) to a Government approved facility as designated by the contracting officer for evaluation in accordance with the provisions of 4.2.2 and 4.2.3. The first article sample shall consist of 5 complete sets of parts and sub-assemblies (i.e. 5 each of every component and sub-assembly, which have been produced by the contractor or furnished by a supplier and which have been manufactured using the

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:06Z
Check the source to verify that this is the current version before use.

same production processes, procedures and equipment which will be used in fulfilling the contract. All parts and materials including packaging and packing shall be obtained from the same source of supply as will be used in regular production. Prior to submission, the contractor shall inspect the sample to the degree necessary to assure that it conforms to the requirements of the contract and submit a record of this inspection with the sample, including a certificate of conformance for materials. A sample containing known defects will not be submitted unless specifically authorized by the Contracting Officer. A first article sample, or portion thereof, as directed by the Contracting Officer, shall also be submitted whenever there is a lapse in production for a period in excess of 90 days or whenever a change occurs in manufacturing process, material used, drawing or specification such as to significantly affect product uniformity as determined by the Government.

4.2.2 Inspections to be performed.-Assemblies and components will be subjected by the Government to any or all of the examinations and tests specified in this specification and any or all requirements of the applicable drawings.

4.2.3 Rejection. - If any component or subassembly fails to comply with any or all of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate its inspection upon any failure of an inert component or subassembly to comply with any of the stated requirements.

*4.3 Inspection provisions

4.3.1 Lot formation.-The term "inspection lot" as used in this specification is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer in one unchanged process using the same materials and methods in accordance with the same drawings, same drawing revisions, same specifications and same specification revisions and complies with the provisions for submission of product as specified in MIL-STD-105. Changes to the process, specifications, or drawings not

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:06Z
Check the source to verify that this is the current version before use.

affecting safety, performance, interchangeability, or storage, as determined by the Government, shall not be deemed to alter the homogeneity of an inspection lot. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein regardless of the type of sampling procedure which is being applied to determine conformance with requirements. Lot numbering, as required, shall be in accordance with MIL-STD-1168. Each lot of shaped charges shall contain:

a. Body assemblies from not more than one lot interfix number from one manufacturer.
b. Glass cones from not more than one batch from one manufacturer.

*4.3.2 Examination.-The examinations listed in the following subparagraphs shall be performed on inspection lots (see 4.3.1) of the components or assemblies designated in the applicable paragraph headings. Inspection for critical defects (and major defects, when so specified) shall be 100 percent. Sampling plans for major and minor defects shall be in accordance with MIL-STD-105 except that continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the Government. Instead of applying the AQL's designated herein to the groups of major and minor defects listed, the contractor may elect to apply an AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect. When this method is elected, it shall be applied to all of the major and minor defects listed in the applicable sub-paragraph of this section, except where 100 percent inspection is specified, and be documented as part of the contractor's inspection system. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.3.4.

4.3.2.1 Well, detonator (see dwg. 8858399 covering a detail of dwg. 9230162).

Categories	Defects	Method of Inspection	Code No. (see 6.2)
Critical:	None defined		
Major:	AQL 0.65 percent		
101.	Diameter of cavity, minimum (min)	Gage	01001

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:06Z
Check the source to verify that this is the current version before use.

102.	Depth of cavity, min.	Gage	01002
103.	Outside diameter of body, maximum (max.)	Gage	01003
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.9)	Visual	01004

4.3.2.2 Adapter, well, detonator (see dwg. 8858398 covering a detail of dwg. 9230162).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.40 percent		
101.	Pitch diameter of thread, min..	Gage	02001
102.	Minor diameter of thread, max..	Gage	02002
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.9)	Visual	02003

4.3.2.3 Detonator well assembly (see dwg. 8858397 covering a detail of dwg. 9230162).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.40 percent		
101.	Concentricity of inside diameter with thread	Gage	03001
Minor:	AQL 1.00 percent		
201.	Assembled length of adapter, min.	Gage	03002
202.	Evidence of poor workmanship (see 3.9)	Visual	03003

4.3.2.4 Well, detonator (alternative) (see dwg. 8858400 covering a detail of dwg. 9230162).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:06Z
Check the source to verify that this is the current version before use.

Categories	Defects	Method of Inspection	Code No.
Critical: None defined			
Major:	AQL 1.00 percent		
101.	Pitch diameter of thread, min.	Gage	04001
102.	Minor diameter of thread, max.	Gage	04002
103.	Diameter of small cavity, min.	Gage	04003
104.	Depth of cavity, min.	Gage	04004
105.	Outside diameter of small end, min.	Gage	04005
106.	Depth of thread cavity, min.	Gage	04006
107.	Concentricity of inside diameter with thread	Gage	04007
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.9)	Visual	04008

4.3.2.5 Cap, closing (see dwg. 8861582 covering a detail of dwg. 9230162).

Categories	Defects	Method of Inspection	Code No.
Critical: None defined			
Major: None defined			
Minor:	AQL 1.50 percent		
201.	Internal depth, min.	Gage	05001
202.	Flange improperly formed	Visual	05002
203.	Evidence of poor workmanship (see 3.9)	Visual	05003

4.3.2.6 Closing cap assembly (see dwg. 8861568 covering a detail of dwg. 9230162).

Categories	Defects	Method of Inspection	Code No.
Critical: None defined			
Major:	AQL 0.40 percent		
101.	Concentricity of inside diameter of cap with thread	Gage	06001

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:06Z
Check the source to verify that this is the current version before use.

Minor:	AQL 1.00 percent		
201.	Color coding improper	Visual	06002
202.	Evidence of poor workmanship (see 3.9)	Visual	06003

4.3.2.7 Cone (see dwg. 8861579 covering a detail of dwg. 9230162).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 1.00 percent		
101.	Concentricity of large outside diameter with basic diameters.....	Gage	07001
102.	Location of large basic diameter	Gage	07002
103.	Excessive wall thickness variation	Gage	07003
104.	Material improper for type	Visual/ Manual	07004
105.	Location of small basic diameter	Gage	07005
Minor:	AQL 1.50 percent		
201.	Large outside diameter, max. ..	Gage	07006
202.	Total height, max.	Gage	07007
203.	Evidence of poor workmanship (see 3.9)	Visual	07008

4.3.2.8 Cone assembly (see dwg. 8861572 covering a detail of dwg. 9230162).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.40 percent		
101.	Mismatch at ring bottoms excessive	Gage	08001
102.	Cone loose	Manual	08002

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:06Z
Check the source to verify that this is the current version before use.

Minor:	AQL 1.50 percent		
201.	Staple missing	Visual	08003
202.	Protective coating missing	Visual	08004
203.	Evidence of poor workmanship (see 3.9)	Visual	08005

4.3.2.9 Container, cone (see dwg. 8861570 covering a detail of dwg. 9230162).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.65 percent		
101.	Location of upper basic diameter	Gage	09001
102.	Concentricity of small inside diameter with basic diameter ..	Gage	09002
103.	Large outside diameter	Gage	09003
104.	Location of lower basic diameter	Gage	09004
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.9).....	Visual	09005

4.3.2.10 Body assembly, prior to attaching carrying straps (see dwg. 8861569 covering a detail of dwg. 9230162).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.65 percent		
101.	Concentricity of container of cone	Gage	10001
102.	Cone assembly insecure	Manual	10002
103.	Reinforcing ring missing or improperly crimped	Visual	10003
Minor:	AQL 1.00 percent		
201.	Gap at base, max.	Gage	10004
202.	Evidence of poor workmanship (see 3.9)	Visual	10005

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:06Z
Check the source to verify that this is the current version before use.

4.3.2.11 Body assembly (see dwg. 8861569 covering a detail of dwg. 9230162).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.40 percent		
101.	Bare spot on interior surface	Visual	11001
Minor:	AQL 1.50 percent		
201.	Color code improper	Visual	11002
202.	Carrying strap missing or improperly assembled	Visual/ Manual	11003
203.	Evidence of poor workmanship (see 3.9)	Visual	11004

4.3.2.12 Sleeve, stand-off (see dwg. 8861567 covering a detail of dwg. 9230162).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.40 percent		
101.	Total length, max.	Gage	12001
102.	Distance shoulder to end	Gage	12002
Minor:	AQL 1.00 percent		
201.	Color code improper	Visual	12003
202.	Evidence of poor workmanship (see 3.9)	Visual	12004

4.3.3 Testing

4.3.3.1 Water absorption (see 3.3) - Major defect - Code No. 13001. - Prior to attaching carrying straps, a sample of five (5) units of each molded part shall be selected from each 8 hours production for this test. Testing shall be as specified in 4.4.1 using the applicable equipment of 4.3.4. Failure of one or more units of a sample in meeting the requirement shall cause that portion of production represented by the sample to be rejected. (Non-destructive test)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:06Z
Check the source to verify that this is the current version before use.

4.3.3.2 Strength of body assembly and stand-off sleeve (see 3.4) - Major defect - Code No. 11005 and Code No. 12005, respectively. - A sample of five (5) body assemblies and five (5) stand-off sleeves shall be selected from each 8 hours production for this test. Testing shall be as specified in 4.4.2 using the applicable equipment of 4.3.4. Failure of one or more units of a sample in meeting the requirement shall reject the product represented by the sample. (Destructive test)

4.3.3.3 Leakproofness of body assembly (see 3.5). - Major defect - Code No. 11006. - This test shall be performed 100 percent as specified in 4.4.3 using the applicable equipment of 4.3.4. Any assembly exhibiting more than the specified leakage shall be classed defective and removed from the lot. (Non-Destructive Test)

4.3.3.4 Leakproofness of closing cap assembly (see dwg. 8861568) - Major defect - Code No. 06004. - This test shall be performed 100 percent as specified in 4.4.3 using the applicable equipment of 4.3.4. Any assembly exhibiting leakage shall be classed defective and removed from the lot. (Non-destructive test)

4.3.3.5 Fit of closing cap assembly (see dwg. 8861582) - Major defect - Code No. 06005. - A sample of twenty-five (25) closing cap assemblies and twenty-five (25) body assemblies minus cone assembly shall be selected from each lot for this test. Testing shall be as specified in 4.4.4 using the applicable equipment of 4.3.4. Failure of one or more combinations in meeting the requirement shall reject the lot. Any unit failing to meet the requirement shall be classed defective and removed from the lot. (Non-destructive test)

4.3.3.6 Fit of stand-off sleeve (see 3.6) - Major defect - Code No. 12006. - A sample of twenty-five (25) stand-off sleeves and twenty-five (25) body assemblies shall be selected from each lot for this test. Testing shall be as specified in 4.4.5 using the applicable equipment of 4.3.4. Failure of 4 or more combinations in meeting either requirement shall reject the lot. Any combination failing either requirement shall be classed defective and removed from the lot. (Non-destructive test)

4.3.3.7 Density of glass cone (see 3.1.1) - Major defect - Code No. 12007. - Ten (10) sample cones in each lot shall be checked to determine compliance with the density requirements. Testing shall be as specified in 4.4.6 using the applicable

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:06Z
Check the source to verify that this is the current version before use.

equipment of 4.3.4. If any sample cone fails to meet this requirement, this failure shall be considered cause for rejection of the lot represented. (Non-destructive test)

4.3.3.8 Heat shock test of glass cone (see 3.8) - Major defect - Code No. 12008. - The sampling plan for this requirement shall be in accordance with MIL-STD-105, using Code Letter F and an AQL of 2.50 percent. The test shall be performed as specified in 4.4.7. (Non-destructive test)

4.3.3.9 Annealing of glass cone (see 3.7) - Major defect - Code No. 12009. - This test shall be performed one hundred percent. Any glass cone which fails to comply with the applicable requirements shall be classed defective and removed from the lot. Testing shall be performed as specified in 4.4.8 using applicable equipment of 4.3.4. (Non-destructive test)

4.3.4 Inspection Equipment.-Inspection equipment required to perform the inspections prescribed in this specification is identified in the Examination (4.3.2) and Test Method (4.4) paragraphs herein. See 6.3 for details concerning responsibilities for inspection design and approval.

4.4 Test methods and procedures

4.4.1 Water absorption. - After painting, each body assembly and each stand-off sleeve shall be weighed and identified to that weight. (The scale or balance used shall be capable of determining weight to the nearest gram.) The component shall then be immersed in the temperature controlled water for the specified time, be removed from the water, surface dried and then re-weighed. Determine the increase in weight and calculate the percent water absorption.

4.4.2 Strength of body assembly and stand-off sleeve. - The body assembly and sleeve shall be placed in its normal vertical functioning position on a flat surface. A measurement shall be made from the flat surface to the highest point on the unit and that point identified. The unit shall then be immersed in the temperature controlled water for the specified period, be removed from the water and surface dried. The unit shall be positioned as for measurement and the required load applied for the specified period. The unit shall then be measured to the point previously identified. Any unit exhibiting an excessive loss in height shall be classed defective.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:06Z
Check the source to verify that this is the current version before use.

4.4.3 Leakproofness of body assembly and closing cap assembly. - The unit shall be assembled to the applicable test equipment, the required internal pressure applied, and observation made for leakage for the specified period. Any unit exhibiting more than the specified leakage shall be classed defective.

4.4.4 Fit of closing cap assembly. - The samples of closing cap assemblies and cone containers shall be segregated into combinations consisting of one unit of each. The closing cap assembly shall be assembled to its cone container using applicable equipment. Failure to require a force fit shall class a combination defective.

4.4.5 Fit of stand-off sleeve. - The samples of stand-off sleeves and body assemblies shall be segregated into combinations of one unit of each. The stand-off sleeve shall be placed on a level surface, the body assembly placed thereon, and the required load applied to the top of the body assembly. The gap between the components shall be measured, the assembly picked up and given a sharp shake toward ejection of the sleeve. If the gap is excessive or the sleeve disassembles when shaken, the combination shall be classed defective.

4.4.6 Density of glass cone. - The density shall be obtained by weighing the sample cone, first in air and then, while freely suspended in distilled water. The density shall be caclculated by means of the following formula:

$$\frac{Wa}{Wa-Ww} = \text{Density}$$

where:

Wa = weight of cone in air
Ww = weight of cone in water

4.4.7 Heat shock test. - The sample cone shall be conditioned at 7 degrees plus or minus 2 degrees Centigrade (C.) for twenty (20) minutes minimum. The convex surface of the cones shall then be placed for two minutes, minimum, into water maintained at 95 degrees plus or minus 5 degrees Centigrade (C.). Observation shall be made for compliance with the applicable requirement.

4.4.8 Annealing of glass cone. - The cones shall be examined by means of a polariscope to determine whether the glass has been

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:06Z
Check the source to verify that this is the current version before use.

relieved of all strains. Cones showing evidence of unrelieved strains shall be rejected.

5. PREPARATION FOR DELIVERY

5.1 Packing and marking. - The completed assemblies shall be packed and marked in accordance with MIL-STD-1169.

*6. NOTES

6.1 Ordering data.-Procurement documents shall specify the following:

a. Title, number and date of this specification.
b. Data cards. - Data cards shall be prepared for each lot in accordance with the information specified in Standard MIL-STD-1167.
c. Provisions for submission of first article samples.

6.2 Inspection code numbers.-The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government. They should be cited as references on drawings of equipment designs submitted by the contractor to the Government for approval (see 6.3.3).

6.3 Inspection Equipment Designs.-Inspection equipment designs are of two types - Government Special Inspection Equipment (SIE) designs and contractor designs. SIE designs are designated by drawing numbers under the "Method of Inspection" headings in Section 4. Design responsibility for all other inspection equipment is assigned to the contractor. The contractor need not furnish any design when a complete Government SIE design is provided. Unless otherwise specified, however, the contractor may submit alternate or modified contractor designs of SIE in accordance with 6.3.2 and 6.3.3 should he elect to do so.

6.3.1 SIE designs.-SIE designs may consist of any of the following:

a. Detailed drawings which completely depict all information necessary for the fabrication and use of the item of inspection equipment.
b. A source control drawing or a specification control drawing as defined in MIL-STD-100.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:06Z
Check the source to verify that this is the current version before use.

c. An envelope drawing, as defined in MIL-STD-100, which establishes the criteria which a detailed design shall meet. When envelope drawings are specified, the contractor shall prepare designs which comply with the criteria therein.

6.3.2 Contractor designs.-Contractor designs are required for all inspection equipment for which SIE designs are not specified and may include commercial equipment which the contractor proposes to use. (Commercial equipment is defined as unmodified equipment which is cataloged and available for purchase by the general public). Contractor designs shall include appropriate operating instructions, calibration procedures and maintenance procedures. Commercial equipment shall be fully described by catalog listings or other means which provide sufficient information to permit identification and evaluation by the Government and may include illustrations and engineering data. Designs shall be prepared for any special fixture(s) required to be used with commercial equipment, or with SIE designs if not otherwise covered thereby (see 6.3.1c). Designs shall be of the category and form (per MIL-D-1000) specified in the Contract Data Requirements Lists (DD Form 1423). The contractor is referred to MIL-HDBK-204, "Inspection Equipment Design" for guidance. The specification number and the applicable five digit defect code number (or other specific identifying information) from Section 4 of this specification shall be referenced on each contractor design together with the component or assembly drawing number and revision letter to which the specific design applies.

6.3.3 Submission of Designs for Approval.-Contractor designs shall be approved by the Government prior to fabricating or procuring the equipment. Designs shall be submitted for approval to Commander Picatinny Arsenal, ATTN: SARPA-QA-A-M, Dover, New Jersey 07801 in accordance with the stipulations, time frame and distribution specified in the Contract Data Requirements List (DD Form 1423) or in the contract. The contractor must include in his submission of designs a listing of any and all Government SIE designs which will be utilized. Partial submission of inspection designs is permissible and encouraged. However, the completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will normally be accomplished within one month after receipt.

6.4 The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications,

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:06Z
Check the source to verify that this is the current version before use.

corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Army-PA

Preparing Activity:
Army-PA

Project Number: 1375-A-070

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:06Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 **1426**

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:06Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

U.S.MAIL

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
Picatinny Arsenal
ATTN: SARPA-QA-A
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:06Z
Check the source to verify that this is the current version before use.