MIL-T-13132B(ME)
20 January 1971
SUPERSEDING
MIL-T-13132A(CE)
3 April 1962

MILITARY SPECIFICATION

TANK, COLD DIP, PRESERVATIVE AND SOLVENT

1. SCOPE

1.1 This specification covers a sheet-steel tank for use in cold preservative and solvent dipping operations.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

Federal

PPP-B-601	- Boxes, Wood, Cleated-Plywood.
PPP-B-636	- Box, Fiberboard.

Military

MIL-P-116	- Preservation, Methods of
MIL-P-514	- Plates, Identification, Instruction and Marking, Blank.
MIL-T-704	- Treatment and Painting of Materiel.

STANDARDS

Military

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-130	- Identification Marking of U. S. Military Property.
MIL-STD-1186	- Cushioning, Anchoring, Bracing, Blocking and Waterproofing; With Appropriate Test Methods.

FSC 4940

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:05Z
Check the source to verify that this is the current version before use.

DRAWINGS

ME

DL13216E9941 - Tank, Cold Dip, Preservation.

(Copies of specifications, standards, and drawings required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification

(Application for copies should be addressed to the Tariff Publishing Officer, Room 202, Union Station, 516 West Jackson Boulevard, Chicago, Illinois 60606.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations, Inc., ATTN: Tariff Order Section, 1616 P Street NW, Washington, D. C. 20036.)

3. REQUIREMENTS

3.1 Description. The tank shall be in accordance with Data List DL13216E9941 and as specified herein.

3.1.1 Drawings. The drawings forming a part of this specification are engineering design drawings. No deviation from the prescribed dimensions or tolerances is permissible without prior approval of the contracting officer. Any data (e.g. shop drawings, layouts, flow sheets, processing procedures, etc.) prepared by the supplier or obtained from a vendor to support fabrication and manufacture of the production item shall be made available, upon request, for inspection by the contracting officer or his designated representative.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:05Z
Check the source to verify that this is the current version before use.

3.2 First article.

3.2.1 First-produced tank. The supplier shall furnish a tank for examination and test within the time frame specified to prove that his production methods will produce tanks that comply with the requirements of this specification. Examination and tests shall be as specified in section 4 and shall be subject to surveillance and approval by the Government (see 6.3).

3.3 Material. Material shall be as specified herein and as shown on the applicable drawings. Materials not specified shall be selected by the supplier and shall be subject to all provisions of this specification.

3.4 Tank. The tank shall be constructed as shown on the drawings. All seams shall be welded and shall not leak when tested as specified in 4.5.2.2. The tank shall be provided with a gravity drainage system which will allow complete drainage of the tank through a 1-1/4-inch drain valve.

3.5 Drain rack. The tank shall be equipped with a removable perforated steel drain rack constructed in accordance with the drawings. The rack shall permit the excess preservation compound draining from the parts to return to the tank. The rack shall not interfere with the opening or closing of the lid.

3.6. Lid. The tank lid shall be as shown on the drawings. The lid shall be held in the open position by a fusible fire link. The link shall release and permit the lid to close when the temperature reaches 220° F. to 250° F. The fire link shall not interfere with the manual opening and closing of the lid.

3.7 Identification marking. The tank shall be identified in accordance with MIL-STD-130. The marking shall be applied to the tank on plates conforming to MIL-P-514, type I, style 1, composition C of type I, grade A, class 1 material. Plates shall be attached by screws, bolts, or rivets in a conspicuous protected location.

3.8 Treatment and painting. The portions of the tank and its components normally painted, shall be cleaned, treated and painted in accordance with MIL-T-704, type A, color and gloss as specified.

3.9 Workmanship. All parts, components, and assemblies of the tank including castings, forgings, molded parts, stampings, bearings, seals, machined surfaces, and welded parts shall be clean and free from sand, dirt,

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:05Z
Check the source to verify that this is the current version before use.

fins, pits, sprues, scale, flux, and other harmful, extraneous material. External surfaces shall be free from burrs, sharp edges, and corners except when sharp edges and corners are required.

3.9.1 Steel fabrication. Steel used in the fabrication of the tank shall provide original quality surface finish and shall be free from kinks and sharp bends. Steel having an eroded surface is not acceptable. The forming of material shall be done by methods that will not cause damage to the metal. Shearing and chipping shall be done neatly and accurately. Corners shall be square and true. Burned surfaces of flame-cut material shall be free of slag. Precautions shall be taken to avoid overheating, and heated metals should be allowed to cool slowly except where heat treatment is required. All bends of a major character shall be made with metal dies or fixtures to insure uniformity of size and shape.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Component and material inspection. The supplier is responsible for insuring that components and materials used are manufactured, examined and tested in accordance with referenced specifications and standards.

4.2 Classification of inspection. Inspection shall be classified as follows:

(a) First-produced tank inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).
(c) Inspection of preparation for delivery (see 4.6).

4.3 First-produced tank inspection.

4.3.1 Examination. The tank shall be examined as specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.3.2 Tests. The tank shall be tested as specified in 4.5.2. Failure to pass either test shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:05Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Sampling. Sampling for examination and tests shall be in accordance with MIL-STD-105.

4.4.2 Examination. Samples selected in accordance with 4.4.1 shall be examined for the defects listed in 4.5.1. AQL shall be 6.5 percent defective.

4.4.3 Tests. Samples selected in accordance with 4.4.1 shall be tested as specified in 4.5.2. AQL shall be 2.5 percent defective.

4.5 Inspection procedure.

4.5.1 Examination. The tanks shall be examined for the following defects:

101. Dimensions and assembly not as shown on the drawing.
102. The temperature-sensitive lid-closing device interferes with manual operation of the lid.
103. Dirty components.
104. Treatment and painting not as specified.
105. Identification marking missing.

4.5.2 Tests.

4.5.2.1 Lid-closing device. The temperature-sensitive device for the lid shall be heated to an ambient temperature between 220° F. and 250° F. Failure of the lid to automatically close at the ambient temperature specified shall constitute failure of this test.

4.5.2.2 Leaks. The tank shall be filled with a solvent. Any evidence of leaks shall constitute failure of this test.

4.6 Inspection of preparation for delivery.

4.6.1 Preproduction pack inspection.

4.6.1.1 Examination. The preproduction pack shall be examined for the defects specified in 4.6.2.4. Presence of one or more defects shall be cause for rejection of the preproduction pack.

4.6.2 Quality conformance inspection of pack.

4.6.2.1 Inspection stages. Inspection shall be in two stages as follows:

(a) The first stage shall include inspection of the preservation, packaging and consolidated packaging of the tank.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:05Z
Check the source to verify that this is the current version before use.

(b) The second stage shall include inspection of contents, closing and marking of the shipping container.

4.6.2.2 Unit of product. For the purpose of inspection, a tank prepared for either stage of inspection shall be considered a unit of product.

4.6.2.3 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.6.2.4 Examination. Samples selected in accordance with 4.6.2.3 shall be examined for the following defects. AQL shall be 2.5 percent defective.

106. Materials or containers not as specified. Each incorrect material or container shall constitute one defect.
107. Metal surfaces not coated as required.
108. Drain rack not packaged as specified.
109. Consolidated packaging not as specified.
110. Packing not as specified.
111. Strapping not zinc coated for level A.
112. Marking illegible, incomplete, incorrect or missing.

5. PREPARATION FOR DELIVERY

5.1 Preproduction pack. The supplier shall furnish a preproduction pack for examination within the time frame specified to prove, prior to starting production packaging and packing, that the applied preservation, packaging, packing and marking comply with the preparation for delivery requirements of this specification. Examination shall be as specified in section 4 and shall be subject to surveillance and approval by the Government (see 6.4).

5.2 Preservation and packaging. Preservation and packaging shall be level A or C as specified.

5.2.1 Level A.

5.2.1.1 Tank. Unpainted metal surfaces of the tank requiring a contact preservative in accordance with MIL-P-116 shall be coated with type P-1 preservative. The preservative shall conform to the applicable specification listed in and shall be applied in accordance with MIL-P-116. The drain rack shall be packaged in a close-fitting box conforming to PPP-B-636, W5c, style optional.

5.2.1.2 Consolidated packaging. The packaged drain rack shall be placed in the compound compartment of the tank. Cushioning and blocking shall be provided to control or prevent movement of the rack within the tank. The lid of the tank shall be closed and secured.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:05Z
Check the source to verify that this is the current version before use.

5.2.2 Level C. Each tank and components shall be preserved and packaged to afford protection against deterioration and damage from the supplier to the initial destination.

5.3 Packing. Packing shall be level A, B, or C as specified.

5.3.1 Level A. Each complete tank, preserved and packaged as specified in 5.2 shall be packed in a close-fitting box conforming to PPP-B-601, overseas type, style optional. Blocking, bracing and cushioning, in accordance with MIL-STD-1186, shall be provided to control or prevent movement of the tank within the box. Strapping shall be zinc coated.

5.3.2 Level B. Each complete tank shall be packed as specified in 5.3.1 except that the box shall be domestic type and strapping need not be zinc coated.

5.3.3 Level C. Each complete tank shall be packed to assure carrier acceptance and safe delivery to destination at the lowest ratings of the carrier in compliance with Uniform Freight Classification rules or National Motor Freight Classification rules.

5.4 Marking. In addition to any special marking required by the contract or purchase order, packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The tank is intended for use in applying the cold preservative compounds and petroleum solvents of MIL-P-116.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Time frame required for submission of first-produced tank (see 3.2.1).
(c) Time frame required for submission of the preproduction pack (see 5.1).
(d) Level of preservation and packaging and level of packing required (see 5.2 and 5.3).

6.3 First-produced tank. Any changes or deviations of production tanks from the approved first-produced tank during production will be subject

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:05Z
Check the source to verify that this is the current version before use.

to the approval of the contracting officer. Approval of the first-produced tank will not relieve the supplier of his obligation to furnish tanks conforming to this specification.

6.4 Preproduction pack. Any changes or deviations of production packs from the approved preproduction pack will be subject to the approval of the contracting officer. Approval of the preproduction pack will not relieve the supplier of his obligation to preserve, package, pack and mark the tanks in accordance with this specification.

Custodian:

Army - ME

Preparing activity:

Army - ME

Project No. 4940-A191

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:05Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
U. A. ARMY MOBILITY EQUIPMENT COMMAND
RESEARCH, DEVELOPMENT AND ENGINEERING DIRECTORATE
ATTN: AMSME-RZG
FORT BELVOIR, VIRGINIA 22060

OFFICIAL BUSINESS

POSTAGE AND FEES PAID

DEPARTMENT OF THE ARMY
U. S. ARMY MOBILITY EQUIPMENT COMMAND
RESEARCH, DEVELOPMENT AND ENGINEERING DIRECTORATE
ATTN: AMSME-RZG
FORT BELVOIR, VIRGINIA 22060

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:05Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

MIL-T-13132B(ME) Tank, Cold Dip, Preservative and Solvent

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO (If "yes", in what way?)

4. REMARKS (Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)

SUBMITTED BY (Printed or typed name and activity - Optional)

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:05Z
Check the source to verify that this is the current version before use.