MIL-C-50007B
21 August 1968
SUPERSEDING
MIL-C-005000-7A(MU)
23 September 1966
MIL-C-50007
22 May 1959

MILITARY SPECIFICATION

CHUTE, CONTAMINATED CLOTHING, M1

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers one type of clothing chute for protective shelters.

2. APPLICABLE DOCUMENTS

2.1 Government documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

U-T-30	-	Talcum; Powder, Plain or Borated.
FF-S-111	-	Screw, Wood.
QQ-S-781	-	Steel Strapping, Flat.
TT-W-572	-	Wood-Preservative, Water-Repellent.
UU-P-271	-	Paper, Wrapping, Waterproofed Kraft.
PPP-B-621	-	Boxes, Wood, Nailed and Lock-Corner.
PPP-C-843	-	Cushioning Material, Cellulosic.
PPP-F-320	-	Fiberboard; Corrugated and Solid, Sheet Stock (Container Grade), and Cut Shapes.
PPP-T-60	-	Tape: Pressure-Sensitive Adhesive, Waterproof, for Packaging.

FSC 4240

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:13Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

DRAWINGS

US ARMY MUNITIONS COMMAND

Edgewood Arsenal

DL5-79-3 - Chute, Contaminated Clothing, M1.
D150-2-1 - Marking Diagram for Shipping Containers.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

AMERICAN TRUCKING ASSOCIATIONS, INC.

National Motor Freight Classification Rules

(Application for copies should be addressed to the American Trucking Associations, 1616 P Street, N. W., Washington, D. C. 20036.)

UNIFORM CLASSIFICATION COMMITTEE

Uniform Freight Classification

(Application for copies of these ratings, rules, and regulations should be addressed to Uniform Classification Committee, 202 Union Station, 516 West Jackson Boulevard, Chicago, Illinois 60606.)

Source: https://assist.dla.mil -- Downloaded: 20261O-22T20:13Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Materials and components.

3.1.1 Materials. All materials cited on Drawing DL5-79-3 or on the subsidiary drawings, shall conform to the specifications listed thereon or to specific characteristics set forth on the drawings.

3.1.2 Components. All components of the chute shall conform to the specifications and drawings listed on Drawing DL5-79-3 and subsidiary drawings.

3.2 Manufacture and assembly. The chute shall be manufactured and assembled as specifie/ on Drawing E5-79-3.

3.3 Performance. The chute shall satisfy the following requirements when tested as specified in 4.2.4:

(a) The door shall be in positive contact with the gasket, all around, when the discharge end of the chute is resting on a horizontal surface.

(b) The angle at which a 1/4-inch gap appears along the lower edge of the door, upon tilting the chute, shall be between 34° and 45°, measured from the vertical to the plane of the front in a plane perpendicular to the tilt-axis.

3.4 Workmanship. The chute shall be free from contamination (foreign matter) and damage such as dents, cracks or deformation which would impair its use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.

4.1.1 Supplier's responsibility. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to specified requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:13Z
Check the source to verify that this is the current version before use.

4.1.2 Objective evidence. The supplier shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5 for which specific inspection has not been provided in this specification have been satisfied.

4.2 Quality conformance inspection.

4.2.1 Lotting. A lot shall consist of the chutes produced by one manufacturer, at one plant, from the same materials, under essentially the same manufacturing conditions.

4.2.2 Sampling for examination and nondestructive tests. Sampling shall be conducted in accordance with MIL-STD-105.

4.2.3 Inspection procedure for examination and nondestructive tests. Sample chutes and the level A preparation for delivery shall be examined and tested in accordance with the classification of defects and MIL-STD-105.

4.2.3.1 Classification of defects.

(a) Front (Dwg D5-79-5).

Categories	Defects
Critical:	None defined
Major:	AQL 1.0 percent defective
101	0.249 diameter holes
102	Location of 0.249 diameter holes

(b) Body (Dwg E5-79-4).

Categories	Defects
Critical:	None defined
Major:	AQL 1.0 percent defective
101	Size of wire bead
102	Location of wire bead
103	Body height
104	Body length

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:13Z
Check the source to verify that this is the current version before use.

4.2.3.1 Classification of defects (continued).

(c) Chute, contaminated clothing, M1 (Dwg E5-79-3).

Categories	Defects	Acceptance standards
Critical:	None defined	
Major:	AQL 1.5 percent defective	
101	Performance	4.2.4
	AQL 1.0 percent defective	
102	Component missing or incorrectly assembled	
103	Welding incorrect or inadequate	
104	Protective finish missing, inadequate, or incorrect	
105	Workmanship (see 3.4)	
Minor:	AQL 2.5 percent defective	
201	Transition piece incorrect	

(d) Preparation for delivery (section 5).

Categories	Defects
Critical:	None defined
Major:	AQL 4.0 percent defective
101	Chute assembly not packaged as specified
102	Class or style of shipping container incorrect
103	Chute incorrectly packed in shipping container

4.2.4 Performance test. The painted and assembled chute shall be tested as follows:

(a) With the discharge end of the chute resting on a horizontal surface, push the lower edge of the door inward a few inches, allow it to return slowly to the closed position, and examine for compliance with 3.3(a).

(b) Starting with the chute oriented as in (a), tilt it slowly backward until a 1/4-inch gap appears between the lower edge of the door and the gasket. Check for compliance with 3.3(b).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:13Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Packaging, level A. The surface of the transition piece shall be sprinkled with talcum powder conforming to U-T-30. The transition piece shall be tucked within the body of the chute assembly. Cellulosic cushioning material conforming to type II, class B of PPP-C-843 shall be placed between the mounting screws and the butyl cloth transition piece to prevent rupture of the cloth. The cushioned transition piece shall be held in place with 2 inch wide pressure sensitive tape conforming to class 1 of PPP-T-60. The door on the chute shall be secured in a closed position with class 1, minimum 2 inch wide, pressure sensitive tape conforming to PPP-T-60.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A. A nailed wood base, fabricated of 1-5/8 inch thick material having outside dimension of 17-7/8 by 23 by 5-5/8 inches shall be placed over the door frame. The chute mounting flange shall be fastened to the wood base at each corner by 1-1/2 inch, No. 10 wood screws conforming to style 2S of FF-S-111. Chute and base shall be separated by paper conforming to class E-1 of UU-P-271. The chute assembly, fastened to the wood base and packaged as specified in 5.1, shall then be packed in a nailed wood box conforming to class 2, style 2, 2-1/2, 4, or 4-1/2 of PPP-B-621 having inside dimensions of 29 by 18 by 26-3/4 inches. Fiberboard pads conforming to type CF or SF, class domestic, variety SW, minimum grade 200 of PPP-F-320 shall be placed between the item and the top, bottom, sides, and ends of the box to prevent movement of the item within the box. The box shall be closed and strapped in accordance with the appendix thereto. Strapping conforming to type I, class B of QQ-S-781 shall be used. The box or the finished wood parts thereof, shall be completely immersed for a minimum of 3 minutes in a water repellent wood preservative conforming to type II composition A of TT-W-572.

5.2.2 Level B. The chute assembly shall be packed as specified in 5.2.1, except that the box shall conform to class 1, style 2, 2-1/2, 4, or 4-1/2 of PPP-B-621. No wood preservative is required. Strapping conforming to type I, class A of QQ-S-781 shall be used.

5.2.3 Level C. The chute assembly, packaged as specified in 5.1, shall be packed to insure carrier acceptance and safe delivery to the first domestic destination for immediate use. Containers shall be in compliance with Uniform Freight Classification rules or National Motor Freight Classification Rules.

Source: https://assist.dla.mil -- Downloaded: 2026l0-22T20:13Z
Check the source to verify that this is the current version before use.

5.3 Marking. In addition to any special marking required by the contract or order, unit packages shall be marked in accordance with MIL-STD-129. Shipping containers shall be marked in accordance with Drawing D150-2-1 (marking diagram for shipping containers). All markings on the shipping container shall be clear, legible, and permanent after application of the wood preservative specified in 5.2.1.

6. NOTES

6.1 Intended use. The chute is intended for conveying contaminated clothing from the undressing area of a protective shelter without loss of static pressure or re-introduction of contaminants.

6.2 Ordering data. Procurement documents should specify the following:

(a) The title, number, and date of this specification.
(b) The level of packing required (see section 5).

Custodians:

Army - MU
Navy - YD
Air Force - 84

Review activities:

Navy - YD
Army - MD

Preparing activity:

Army - MU(EA)

Project No. 4240-0179

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:13Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:13Z
Check the source to verify that this is the current version before use.