MILITARY SPECIFICATION

TRANSPONDER SET, AN/DKW-3A (V)

This amendment forms a part of Military Specification MIL-T-85398C(AS), dated 14 October 1983, and is approved for use by the Naval Air Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 14

* In 3.5.1.4.10.3 Sync signal, first sentence delete "bit 2 of word 2" and substitute "word 2 bit 1", and delete "bit 2 word 18." and substitute "word 18 bit 1."

PAGE 15

In paragraph 3.5.1.4.10.2 Clock, add the sentence, "This output shall be TTL level, capable of sourcing 0.5 mA and sinking 3.2 mA."

In paragraph 3.5.1.4.10.3 Sync signal, add the sentence, "This output shall be TTL level, capable of sourcing 0.5 mA and sinking 3.2 mA."

PAGE 18

In paragraph 3.5.1.5.3.2 Sync signal, change the last sentence from "sinking 20 mA" to "sinking 3.2 mA."

In paragraph 3.5.1.5.3.3 Telemetry data bit clock, change the last sentence from "sinking 20 mA" to "sinking 3.2 mA."

FSC 5821

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:46Z
Check the source to verify that this is the current version before use.

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Preparing activity:
Navy - AS

(Project 5821-N170)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:46Z
Check the source to verify that this is the current version before use.