MIL-T-85413/6A(AS)
28 February 1986
SUPERSEDING
MIL-T-85413/6
27 August 1982
Amendment 1
8 June 1983

MILITARY SPECIFICATION SHEET

TEST SET, COMPUTER

MEMORY LOADER-VERIFIER

AN/ASM-607(V)6

This specification is approved for use within Naval Air System Command, Department of the Navy and is available for use by all Departments and agencies of the Deparment of Defense.

The requirements for acquiring the Computer Memory Loader-Verifier (MLV) Test Set described herein shall consist of this specification and the latest issue of MIL-T-85413(AS).

3. REQUIREMENTS.

3.1 Item description. The AN/ASM-607(V)6 shall differ from other MLVs in that this configuration will allow interfacing with the CP-985/ASQ-155, the CP-1391/ASQ-155A and the CP-1180/AWG-21 avionics computers on-board the A-6E aircraft.

3.2 Item identification. The AN/ASM-607(V)6 shall be manufactured in accordance with Drawing 1164AS230-6. This unit shall differ from other items described in the latest issue of MIL-T-85413(AS) in the following areas.

a. Nomenclature: AN/ASM-607(V)6

b. Case Assembly: In accordance with Drawing 1164AS547 including the following subassembly drawings.

Computer Cable Assembly (PCU), Drawing 1164AS557
Junction Box Assembly, Drawing 1164AS548 and 1164AS384
Power Cable Assembly, Drawing 1164AS607 and 1164AS347
Computer Cable Assembly (CP-985/1391), Drawing 1164AS558
Computer Cable Assembly (CP-1180), Drawing 1164AS381

FSC 4920

AMSC N/A

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

AMSC N/A

Source: https://assist.dla.mil -- Downloaded: 202610-23T10:48Z
Check the source to verify that this is the current version before use.

c. Control Panel Assembly: In accordance with Drawing 1164AS233-6 including the following subassembly drawings.

Circuit Card Assembly, I/O (CP-1180); Drawing 1164AS396
Circuit Card Assembly, I/O (CP-985/1391); Drawing 1164AS565
Circuit Card Assembly, CPU; Drawing 1164AS636

3.3 Operation. The operation of the MLV is controlled by software installed on the Tape Transport Unit (TTU) by the procuring activity. With this software, the AN/ASM-607(V)6 is capable of performing the following functions.

3.3.1 Self-test. The self-test software is designed to measure MLV system readiness and consists of a power-up built-in-test (BIT), interface test, display test and Magnetic Tape Memory (MTM) test.

3.3.2 Diagnostic tests. By using fault isolation diagnostic software in conjunction with the OF-65/ASM Test Set Adapter Group (TSAG) hardware, faults are detected to the MLV shop-replaceable assembly (SRA) level. Tests include a memory test, interface circuitry test, Central Processing Unit (CPU) test, magnetic tape memory test, and display/keyboard test.

3.3.3 System. General AN/ASM-607(V)6 system operations shall include, but are not limited to, the following:

a. Loading avionics programs from the MTM into the avionics computers.

b. Comparing the contents of the computer memory to data stored on the MTM.

c. Inspection and modification of computer memory.

d. Displaying the identity of the avionics program residing in computer memory.

4. QUALITY ASSURANCE PROVISIONS.

First article tests, quality conformance tests and acceptance tests shall be performed in accordance with the requirements of the latest issue of MIL-T-85413(AS) and the contract.

Preparing activity:
Navy-AS

(Project 4920-N416)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:48Z
Check the source to verify that this is the current version before use.