MIL-T-85413/7A(AS)
28 February 1986
SUPERSEDING
MIL-T-85413/7
27 August 1982
Amendment 1
8 June 1983

MILITARY SPECIFICATION SHEET

TEST SET, COMPUTER

MEMORY LOADER-VERIFIER

AN/ASM-607(V)7

This specification is approved for use within Naval Air Systems Command, Department of the Navy and is available for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the Computer Memory Loader-Verifier (MLV) Test Set described herein shall consist of this specification and the latest issue of MIL-T-85413(AS).

3. REQUIREMENTS.

3.1 Item description. The AN/ASM-607(V)7 shall differ from other MLVs in that this configuration will allow interfacing with the AN/AYK-14(V) family of avionics computers.

3.2 Item identification. The AN/ASM-607(V)7 shall be manufactured in accordance with Drawing 1164AS230-7. This unit shall differ from other items described in the latest issue of MIL-T-85413(AS) in the following areas.

a. Nomenclature: AN/ASM-607(V)7

b. Case Assembly: In accordance with Drawing 1164AS534 including the following subassembly drawings.

Junction Box Assembly, Drawing 1164AS578
Computer Cable Assembly, Drawing 1164AS596
Power Cable Assembly, Drawing 1164AS607

FSC 4920

AMSC N/A

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:48Z
Check the source to verify that this is the current version before use.

c. Control Panel Assembly: In accordance with Drawing 1164AS233-7 including the following subassembly drawings.

Circuit Card Assembly, I/O (CSC); Drawing 1164AS368
Circuit Card Assembly, CPU; Drawing 1164AS636

3.3 Operation. The operation of the MLV is controlled by software installed on the Tape Transport Unit (TTU) by the procuring activity. With this software, the AN/ASM-607(V)7 is capable of performing the following functions.

3.3.1 Self-test. The self-test software is designed to measure MLV system readiness and consists of a power-up built-in-test (BIT), interface test, display test and Magnetic Tape Memory (MTM) test.

3.3.2 Diagnostic tests. By using fault isolation diagnostic software in conjunction with the OF-65/ASM Test Set Adapter Group (TSAG) hardware, faults are detected to the MLV shop-replaceable assembly (SRA) level. Tests include a memory test, interface circuitry test, Central Processing Unit (CPU) test, magnetic tape memory test, and display/keyboard test.

3.3.3 System. General AN/ASM-607(V)7 system operations shall include, but are not limited to, the following:

a. Controlling the avionics computer for purposes of loading avionics flight and maintenance programs from the MTM of the MLV into the avionics computer.

b. Releasing control of the computer to allow execution of the program.

c. Monitoring and displaying results of program execution via the MLV display.

d. Controlling, inspecting and modifying the avionics computer processor and emulator.

e. Transfering computer memory onto the MLV MTM.

4. QUALITY ASSURANCE PROVISIONS.

First article tests, quality conformance tests and acceptance tests shall be performed in accordance with the requirements of the latest issue of MIL-T-85413(AS) and the contract.

Preparing activity:
Navy-AS

(Project 4920-N417)

Source: https://assist.dla.mil -- Downloaded: 202610-23T10:48Z
Check the source to verify that this is the current version before use.