USER ACTIVITIES:
NAVY - MC, OS, SH

REVIEWER ACTIVITIES:
AIR FORCE - 84
DLA - 16

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.



TABLE I. DASH NUMBERS.

DASH NO	A	B	C	D	E	F	T_1	T_2	R_1	R_2	R_3	CORNER RADIUS	TEMPER
001	.565	.750	.750	90°	95.5°	.063	.063	.063	.120	.120	.040	.040	T3511
003	.565	.750	.750	90°	95.5°	.063	.063	.063	.120	.120	.040	.040	O

REQUIREMENTS:

1. MATERIAL. ALUMINUM ALLOY 2024, (UNS A92024) AS SPECIFIED IN QQ-A-200/3.
2. FORMING PROCESS. EXTRUDED (CODE E).
3. PART NUMBER. THE PART NUMBER CONSISTS OF THE BASIC MS NUMBER, PLUS A FORMING PROCESS CODE, PLUS A DASH NUMBER FROM TABLE I.

EXAMPLE: MS14387E001

- DASH NUMBER FROM TABLE I
- EXTRUDED (SEE REQUIREMENT 2)
- BASIC MS NUMBER

4. MARKING. ALUMINUM AND ALUMINUM ALLOYS SHALL BE MARKED IN ACCORDANCE WITH FED-STD-184 WITH THE EXCEPTION THAT A PART NUMBER FROM THIS MILITARY STANDARD SHALL BE INCLUDED AS PART OF THE IDENTIFICATION MARKING.

NOTES:

1. ALL DIMENSIONS ARE IN INCHES.
2. STANDARD LENGTH OF BAR IS 10' MINIMUM, 12' MAXIMUM.
3. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BIDS, OR REQUEST FOR PROPOSAL, EXCEPT THE REFERENCED ADOPTED INDUSTRY DOCUMENTS SHALL GIVE THE DATE OF THE ISSUE ADOPTED.
4. FOR DESIGN FEATURE PURPOSES THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN.

APPROVED 22 May 1984 REVISED

P. A. AS Other Cost MR 99	INTERNATIONAL INTEREST	TITLE: ZEE, STYLE I ALUMINUM ALLOY 2024	MILITARY STANDARD MS14387
PROCUREMENT SPECIFICATION: QQ-A-200	SUPERSEDES:		PAGE 1 OF 1

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:41Z
Check the source to verify that this is the current version before use.