FED SUP CLASS
6615



NOTES

1. MATERIAL CORROSION RESISTANT STEEL, CL 416, COND A IN ACCORDANCE WITH QQ-S-763
2. SURFACE ROUGHNESS SURFACE CONDITION FINISH DESIGNATIONS IN ACCORDANCE WITH USASI B46.1 - 1962
3. HEAT TREAT HARDEN TO ROCKWELL C28 TO C38 (125,000 TO 150,000 PSI,. IN ACCORDANCE WITH MIL-H-6875
4. REMOVE ALL BURRS AND BREAK ALL SHARP EDGES
5. DIMENSIONS IN INCHES UNLESS OTHERWISE SPECIFIED, TOLERANCES DECIMALS ± .005, DIMENSIONING AND TOLERANCING IN ACCORDANCE WITH USASI Y14.5 - 1966

FOR DESIGN FEATURE PURPOSES THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID

APPROVED 10 Jan 69 REVISED

Project No. 6615-N006

P.A. NAVY - AS Other Cust	TITLE WASHER, SPECIAL	MILITARY STANDARD MS3351(AS)
PROCUREMENT SPECIFICATION MIL-N-81604	SUPERSEDES	SHEET 1 OF 1

DD FORM 1 SEP 67 672-1 (Limited coordination)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

PLATE NO 17549

This standard has been approved by the NAVAL AIR SYSTEMS COMMAND Department of the NAVY and is mandatory for use by that activity. All other military activities are required to apply this standard where suitable

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:02Z
Check the source to verify that this is the current version before use.