MILITARY SPECIFICATION

COUPLING, HALVES-QUICK DISCONNECT,

AIR HOSE, BOWES TYPE

This interim amendment is issued for use by the Naval Ship Engineering Center with Military Specification MIL-C-3486B, dated 15 April 1966.

Page 3

3.3, delete and substitute:

"3.3 Pressure and operating force.

"3.3.1 Hydrostatic pressure. All couplings and fittings shall withstand, without leakage or other indications of failure, the hydrostatic pressure test specified in 4.4.2.

"3.3.2 Operating force. The compressive force to operate the coupling shall be 5 to 7 pounds when measured in accordance with 4.4.3."

Page 4

4.1, delete and substitute:

"4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements."

4.2.2.3, delete and substitute:

"4.2.2.3 Sampling for pressure and operating force tests. A random sample of couplings and fittings shall be selected from each lot of material in accordance with table III for the tests of 4.4.2 and 4.4.3.

Table III - Sampling for pressure and operating force tests

| Number of couplings and fittings in lot | Number of couplings and fittings in sample | Acceptance number (Defectives) | Rejection number (Defectives) |
|---|---|---|---|
| Under 25 | 6 | 0 | 1 |
| 26 to 50 | 8 | 0 | 1 |
| 51 to 100 | 9 | 0 | 1 |
| 101 to 200 | 10 | 0 | 1 |
| 201 to 500 | 15 | 0 | 1 |

"

Page 5

4.4.2, lines 4 and 5: Delete "3.3" and substitute "3.3.1."

Add as paragraph 4.4.3:

"4.4.3 Operating force test. The compressive force to operate the coupling shall be measured and shall conform to 3.3.2."

FSC 4730

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:05Z
Check the source to verify that this is the current version before use.

Figure 1, piece number 5, spring: Add "0.093 ± 0.003 inch"

Preparing activity
Navy - SH
(Project 4730-N383)



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:05Z
Check the source to verify that this is the current version before use.