MILITARY SPECIFICATION

SIRENS, ELECTRIC-MOTOR-OPERATED, VEHICULAR

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers weatherproof electric-motor-driven sirens with and without a flasher light for vehicles.

1.2 Classification. Sirens covered by this specification shall be of the following types and classes, as specified (see 6.2):

Type I - With flasher light.
Type II - Without flasher light.
Class A - 6-volt.
Class B - 12-volt.
Class C - 24-volt.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified (see 6.2), the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

QQ-S-781	- Strapping, Steel, and Seals.
PPP-B-601	- Boxes, Wood, Cleated-Plywood.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: USA Belvoir Research and Development Center, ATTN: STRBE-DS, Fort Belvoir, VA 22060-5606 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 6350

Source: https://assist.dla.mil -- Downloaded: 202610-16T18:04Z
Check the source to verify that this is the current version before use.

PPP-B-636 - Boxes, Shipping, Fiberboard.
PPP-B-640 - Boxes, Fiberboard, Corrugated, Triple-Wall.
PPP-F-320 - Fiberboard; Corrugated and Solid, Sheet Stock (Container Side), and Cut Shapes.

MILITARY

MIL-V-173 - Varnish, Moisture-and-Fungus-Resistant (for Treatment of Communications, Electronic, and Associated Equipment).
MIL-P-514 - Plates, Identification, Instruction and Marking, Blank.
MIL-T-704 - Treatment and Painting of Materiel.
MIL-C-13486 - Cable, Special Purpose, Electrical: Low-Tension, Heavy Duty Single-Conductor and Multiconductor.

STANDARDS

FEDERAL

FED-STD-595 - Colors.

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-130 - Identification Marking of US Military Property.
MIL-STD-461 - Electromagnetic Interference Characteristics Requirements for Equipment.
MIL-STD-810 - Environmental Test Methods.
MIL-STD-889 - Dissimilar Metals.

(Copies of specifications, standards, and drawings required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. The issues of the documents which are indicated as DoD adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable.

SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT

Rule 442 - Usage of Solvents.

Source: https://assist.dla.mil -- Downloaded: 202610-16T18:04Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to South Coast Air Quality Management District, 9150 Flair Drive, El Monte, CA 91731.)

AMERICAN NATIONAL STANDARDS INSTITUTE, INC. (ANSI)

S1.4 - Sound Level Meters, Specification for.
S1.13 - Methods for the Measurements of Sound Pressure Levels.

(Application for copies should be addressed to the American National Standards Institute, Inc., 1430 Broadway, New York, NY 10018.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 Standard Practice for Commercial Packaging.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Description. The siren shall consist of a body, rotor, electric motor, mounting bracket and, when specified (see 3.10 and 3.11), a motor control switch and a motor cable. The maximum overall dimensions of the siren including the mounting bracket and flasher light, when applicable, shall be not more than 20 inches long, 12 inches high, and 10 inches wide. The weight of the siren, including the mounting bracket and the flashing light, shall not exceed 35 pounds. Motor and light shall be constructed for use with electrical ground return systems.

3.2 First article. The contractor shall furnish a siren for examination and testing within the time frame specified (see 6.2) to prove prior to starting production that his production methods and choice of design detail will produce sirens that comply with the requirements of this specification. Examination and tests shall be as specified in section 4 and shall be subject to surveillance and approval by the Government (see 6.3).

3.3 Material. Material shall be as specified herein. Materials not specified shall be selected by the contractor and shall be subject to all provisions of this specification.

3.3.1 Material deterioration and control. The siren shall be fabricated from compatible materials, inherently corrosion resistant or treated to provide

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:04Z
Check the source to verify that this is the current version before use.

protection against the various forms of corrosion and deterioration that may be encountered in any of the applicable operation and storage environments to which the item may be exposed.

3.3.2 Dissimilar metals. Dissimilar metals shall not be used in intimate contact with each other unless protected against galvanic corrosion. Dissimilar metals and methods of protection are defined and detailed in MIL-STD-889.

3.3.3 Identification of materials and finishes. The contractor shall identify the specific material, finish, or treatment for use with components and sub-components, and shall make information available upon request to the contracting officer or designated representative.

3.4 Temperature conditions. The sirens shall operate in any ambient temperature from +125° F to -40° F. The siren shall not be damaged by storage at ambient temperatures of +155° F for a period of 4 hours, and at -65° F for a period of 12 hours.

3.5 Operating characteristics. The sound produced by the siren shall start with a heavy growl and rise in pitch to a shrill shriek. When operating from a battery at 10 percent below rated voltage, the siren shall reach its highest peak pitch tone in not more than 6 seconds from the time the starting switch is closed; the sound level produced by the siren shall be not less than 110 decibels when measured on the axis of the siren at a distance of 6 feet. The highest fundamental tone shall be 1,000 Hz ±100 Hz.

3.6 Body. The body and air entrance grille shall be constructed so as to exclude the direct entrance or accumulation of rain, sleet, snow, or frost. Openings in the grille shall allow an unrestricted flow of air into the rotor. Width of the openings shall not exceed 1/4 inch.

3.7 Rotor. The siren rotor shall be dynamically balanced and shall be not less than 5-1/2 inches in diameter.

3.8 Motor. The motor shall be a direct-current type.

3.8.1 Bearings. The bearings shall be the prelubricated ball type, sealed and shielded, or the self-alining, self-lubricating, sleeve type.

3.9 Mounting bracket. The mounting bracket shall permit mounting the siren on a horizontal surface and shall be designed to minimize vibration of the siren. A metal plate not less than 5 by 7 by 3/16-inch thick and reinforcing panel of the same size but not less than 1/8-inch thick shall be furnished for mounting the siren. Four 5/16-inch holes shall be drilled in a rectangular pattern through the plate and the reinforcing panel. Holes shall be spaced 4 and 6 inches, center to center. A soft rubber gasket the same size and hole spacing as the reinforcing plate shall be furnished to seal the mounting plate when mounting the siren on a vehicle. Four corrosion-resistant bolts with lockwashers and nuts shall be furnished. Bolts shall be 5/16-inch diameter and not less than 1 inch long.

Source: https://assist.dla.mil -- Downloaded: 20260-16T18:04Z
Check the source to verify that this is the current version before use.

3.10 Motor-control switch. When specified (see 6.2), a motor-control switch shall be furnished with each siren. The switch shall be a normally open, momentary-contact type that remains in the "On" position only as long as pressure is applied. The switch shall be hand or foot-operated, as specified (see 6.2), and shall be either a heavy-duty, direct-conduct type or an electromagnetic, remote-operated type, as specified (see 6.2). The switch housing shall be of steel, aluminum alloy, or plastic. All contact terminals shall have a current-carrying capacity of not less than 150 percent of the full-load current of the siren, except that the current-carrying capacity of the energizing switch contact terminals of electromagnetic switches shall be not less than 200 percent of the full-load current of the solenoid. The switch shall be furnished with mounting bolts.

3.11 Siren cable. When specified (see 6.2), 10 feet of cable shall be furnished with each siren for connecting the siren motor to the battery and control switch. The cable shall conform to MIL-C-13486, type I, class A, and shall have a current-carrying capacity of not less than 125 percent of full-load current of the motor.

3.12 Electromagnetic interference. The electromagnetic interference emission characteristics of the siren shall be in accordance with MIL-STD-461, class C3, group I.

3.13 Fungus and moisture resistance. The electrical circuitry, including all components and connections, except as specified below, shall be protected from the effects of fungus growth and moisture by an overall treatment with a varnish conforming to MIL-V-173, composition I or II, as applicable (see 3.13.1), with 7 ±1 percent salicylanilide or 1 percent copper 8-quinolinolate (by weight) based on the nonvolatile content of the varnish:

a. Components or circuit elements that are inherently fungus and moisture resistant or which are hermetically sealed need not be treated.
b. Components or circuit elements whose functions will be adversely affected by the varnish coating shall not be treated.

When used, the varnish shall be applied by spray, brush, or a combination of both to give a dry-film thickness of not less than 1 mil to component or element surfaces previously cleaned and prepared so that the surfaces are free from all foreign matter which would interfere with the adherence or function of the varnish.

3.13.1 Composition. Composition II shall be used only in the case when local air pollution regulations governing the application of varnish precludes the use of composition I. When composition II is used, the contractor shall provide evidence to the Government that the use of composition II is required, and shall certify that the composition II material complies with Rule 442, South Coast Air Quality Management District, El Monte, CA.

3.14 Identification marking. The siren shall be identified in accordance with MIL-STD-130. The marking shall be applied to the siren on identification

Source: https://assist.dla.mil -- Downloaded: 20260-16T18:04Z
Check the source to verify that this is the current version before use.

plates conforming to MIL-P-514, type III, composition C. Plates shall be attached by screws, bolts, or rivets in a location where the plates will be both visible and legible.

3.15 Treatment and painting. The sirens shall be cleaned, treated, and painted in accordance with MIL-T-704, type A. Color of the finish coat shall be red conforming to FED-STD-595, color No. 11136.

3.16 Type I siren (with flasher light). Type I sirens shall be equipped with a flasher light mounted on the front of and integral with the siren. The light shall be mounted in resilient waterproof gaskets and shall be equipped with a flasher unit to provide 75 to 100 flashes per minute. A red plastic lens shall be mounted directly in front of the lamp and shall cover the lens area of the lamp. The plastic shall be not less than 1/8-inch thick. The lamp shall be equipped with not less than 15 feet of cable, in addition to the siren cable, to provide for independent operation of the siren and flashing light.

3.17 Type II siren (without flasher light). Type II sirens shall be as specified for type I except that the flasher light is not required.

3.18 Class A, 6-volt. Class A sirens shall operate on 6 volts direct current (dc).

3.18.1 Type I. Type I, class A sirens shall be equipped with Trade No. 4078 or 4080 lamps. Current consumption of the lamp and the siren shall not exceed 46 amperes (amps).

3.18.2 Type II. Current consumption of type II, class A sirens shall not exceed 36 amps.

3.19 Class B, 12-volt. Class B sirens shall operate on 12 volts dc.

3.19.1 Type I. Type I, class B sirens shall be equipped with Trade No. 4478 or 4480 lamps. Current consumption of the lamp and siren shall not exceed 31 amps.

3.19.2 Type II. Current consumption of type II, class B sirens shall not exceed 26 amps.

3.20 Class C, 24-volt. Class C sirens shall operate on 24 volts dc.

3.20.1 Type I. Type I, class C sirens shall be equipped with Trade No. 4578 or 4880 lamps. Current consumption of the lamp and siren shall not exceed 21 amps.

3.20.2 Type II. Current consumption of type II, class C sirens shall not exceed 18 amps.

3.21 Workmanship. All parts, components, and assemblies of the siren including castings, forgings, molded parts, stamping, bearings, seals, machined

Source: https://assist.dla.mil -- Downloaded: 20260-16T18:04Z
Check the source to verify that this is the current version before use.

surfaces, and welded parts shall be clean and free from sand, dirt, fins, pits, sprues, scale, flux, and other harmful extraneous material. All edges shall be rounded or beveled.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Component and material inspection. The contractor is responsible for insuring that components and materials used are manufactured, examined, and tested in accordance with referenced specifications and standards.

4.2 Classification of inspections. Inspections shall be classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).
c. Inspection of packaging (see 4.6).

4.3 First article inspection.

4.3.1 Examination. The first article siren shall be examined as specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.3.2 Tests. The first article siren shall be tested as specified in 4.5.2.1 through 4.5.2.4, in the order shown. Failure of any test shall be cause for rejection.

4.4 Quality conformance inspection.

4.4.1 Sampling. Sampling for examination and tests shall be in accordance with MIL-STD-105.

4.4.2 Examination. Samples selected in accordance with 4.4.1 shall be examined as specified in 4.5.1. AQL shall be 2.5 percent defective for major defects, and 4.0 percent defective for minor defects.

4.4.3 Tests. Samples selected in accordance with 4.4.1 shall be tested as specified in 4.5.2.2 and 4.5.2.3. AQL shall be 2.5 percent defective.

4.5 Inspection procedure.

4.5.1 Examination. The sirens shall be examined for the following defects:

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:04Z
Check the source to verify that this is the current version before use.

Major

101. Components missing.
102. Dimensions and weight not as specified.
103. Material not as specified.
104. Materials are not resistant to corrosion and deterioration or treated to be made resistant to corrosion and deterioration for the applicable storage and operating environment.
105. Contractor does not have documentation available for identification of material, material finishes or treatments.
106. Dissimilar metals as defined in MIL-STD-889 are not effectively insulated from each other.
107. Body not as specified.
108. Rotor not as specified.
109. Motor not as specified.
110. Mounting bracket not as specified.
111. Motor-control switch not as specified, when applicable.
112. Siren cable not as specified, when applicable.
113. Fungus and moisture resistance not as specified.
114. Flasher light not as specified (type I siren only).
115. Lamps and lens not as specified (type I siren only).
116. Workmanship not as specified.

MINOR

201. Identification marking not as specified.
202. Treatment and painting not as specified.
203. Technical publications missing or not as specified, when applicable.
204. Mounting bolts, lockwashers, nuts and gasket missing or not as specified.

4.5.2 Tests.

4.5.2.1 Environmental.

4.5.2.1.1 Storage. The siren shall be placed in a temperature controlled chamber, and the temperature shall be raised to 155° F and held for 4 hours. The temperature shall then be lowered to -65° F and held for 12 hours. The siren shall be removed from the chamber, allowed to return to room temperature, and examined. Any evidence of damage (see 6.4) shall constitute failure of this test.

4.5.2.1.2 Operation. The siren shall be tested as specified in MIL-STD-810, method 501.2 (high temperature), procedure I, except that the temperature shall be 125° F. The siren shall then be tested as specified in MIL-STD-810, method 502.2 (low temperature), procedure I, except that the temperature shall be -40° F. Failure of the siren to produce a sound starting with a heavy growl and rising in pitch to a shrill shriek at either temperature or any evidence of damage shall constitute failure of this test.

Source: https://assist.dla.mil -- Downloaded: 20260-16T18:04Z
Check the source to verify that this is the current version before use.

4.5.2.2 Sound level and pitch peak. This test shall be conducted at 10 percent below rated voltage. The sound level and pitch peak tone shall be determined in accordance with ANSI S1.2 except that the microphone shall be placed 6 feet from the siren. Sound level meters shall conform to ANSI S1.4. The sound level meter shall have been calibrated not more than 6 months prior to the date of the tests. Determination of sound level shall be made with the siren and the microphone 10 feet above ground or other surface, and 50 feet from any large reflecting surface. Nonconformance to 3.5 shall constitute failure of this test.

4.5.2.3 Electric loads. Electric loads shall be determined by inserting a calibrated ammeter in the line and observing the readings. Type I sirens shall include the flasher light. Nonconformance to 3.18, 3.19, or 3.20, as applicable, shall constitute failure of this test.

4.5.2.4 Electromagnetic interference. The siren shall be tested to determine conformance to 3.12. The contractor shall furnish the contracting officer the reports required by MIL-STD-461, except that the time interval for submission of reports shall be as specified (see 6.2). Disapproval of the report shall constitute failure of this test.

4.6 Inspection of packaging.

4.6.1 Quality conformance inspection of pack.

4.6.1.1 Unit of product. For the purpose of inspection, a completed pack prepared for shipment shall be considered a unit of product.

4.6.1.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.6.1.3 Examination. Samples selected in accordance with 4.6.1.2 shall be examined for the following defects. AQL shall be 2.5 percent defective.

117.	Materials and containers not as specified for level A or B.
118.	Contents not immobilized as specified for level A.
119.	Box not closed and sealed as specified for level A.
120.	Gross weight or size exceeds the limitations of the applicable box specification for level A or B.
121.	Preservation and packing not in accordance with the referenced document as specified for commercial.
122.	Strapping not as specified for level A.
123.	Marking missing, illegible, incorrect, or incomplete for level A, B, or commercial.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or commercial, as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:04Z
Check the source to verify that this is the current version before use.

5.1.1 Level A. Each complete siren shall be placed in a close-fitting box conforming to PPP-B-636, W5c, style optional. The contents shall be immobilized within the box in a manner to prevent movement or damage by the use of fiberboard pads or cut shapes fabricated from fiberboard conforming to PPP-F-320, class weather-resistant, variety and grade optional. The box shall be closed and sealed as specified for method V in the appendix to the box specification.

5.1.2 Commercial. Each complete siren shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or commercial, as specified (see 6.2).

5.2.1 Level A. Sirens of like description, preserved as specified in 5.1, shall be packed together in a close-fitting box conforming to PPP-B-601, overseas type, style optional, in quantities not to exceed the weight limitation of the box. Box closure and strapping shall be in accordance with the appendix to the box specification. The strapping shall conform to QQ-S-781, class 1, type I or IV, size as applicable. Unless otherwise specified (see 6.2), strapping shall be finish B. When specified (see 6.2), strapping shall be finish A.

5.2.2 Level B. Sirens of like description, preserved as specified in 5.1, shall be packed together in a close-fitting box conforming to PPP-B-636, V3c, V11c, V13c, or V15c, style optional; or PPP-B-640, class 2, style optional. The gross weight or size shall not exceed the limitations of the applicable box specification. Box closure and strapping shall be in accordance with the appendix to the applicable box specification.

5.2.3 Commercial. Sirens, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Marking.

5.3.1 Military. Marking for military levels of protection (level A or B) shall be in accordance with MIL-STD-129.

5.3.2 Commercial. Marking for commercial packaging shall be in accordance with ASTM D 3951. In addition, weight and cube data shall be marked on the shipping container.

6. NOTES

6.1 Intended use. The sirens are for use on military equipment to secure right-of-way.

6.2 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this specification.
b. Type and class of siren required (see 1.2).

Source: https://assist.dla.mil -- Downloaded: 202640-16T18:04Z
Check the source to verify that this is the current version before use.

c. Date of issue of DoDISS applicable and exceptions thereto (see 2.1.1).
d. Time frame required for submission of preproduction model (see 3.2).
e. When the motor control switch shall be furnished, whether it shall be hand- or foot-operated, and type of switch required (see 3.10).
f. When motor cable shall be furnished (see 3.11).
g. Time interval for submission of electromagnetic interference reports (see 4.5.2.4).
h. Degree of preservation and degree of packing required (see 5.1 and 5.2).
i. When other than finish B strapping is required (see 5.2.1).

6.3 First article. Any changes or deviations of production sirens from the approved preproduction model during production will be subject to the approval of the contracting officer. Approval of the preproduction model will not relieve the contractor of his obligation to furnish sirens conforming to this specification.

6.4 Definitions. The following definition shall apply throughout this specification:

6.4.1 Damage. Damage is corrosion, deformation, loosening, breakage, or any condition resulting in malfunctioning of the siren or any component or part.

6.5 Data requirements. The contracting officer should include requirements for such data as technical publications, instructional materials, illustrated parts lists, and contractor's maintenance and operation manual to be furnished with each siren. The data should contain the following warning: "The siren produces a 110 dB sound level at 6 feet. A noise hazard survey should be taken at the operator's and passenger's position of any military equipment using the siren and appropriate precautions taken."

Custodians:
Army - ME
Air Force - 99

Review activities:
Army - ER
DLA - GS
Air Force - 82

Preparing activity:
Army - ME

Project 6350-0087

☆U.S. GOVERNMENT PRINTING OFFICE: 1984—765-048/A4239

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:04Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY
USA Belvoir R&D Center
STRBE-DS
Fort Belvoir, VA 22060-5606

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
USA Belvoir R&D Center
STRBE-DS
Fort Belvoir, VA 22060-5606

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:04Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-S-3485D	Sirens, Electric-Motor-Operated, Vehicular

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:04Z
Check the source to verify that this is the current version before use.