O.K.

MIL-C-19437B(MC)
12 September 1983
SUPERSEDING
MIL-C-19437A(MC)
21 November 1966

MILITARY SPECIFICATION

CHEST, TOOL: CARPENTER OR COMPANY

This specification is approved for use by Marine Corps, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers one type and size wooden chest with removable tray.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. Unless otherwise specified, the following specifications, standards, and handbooks of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

FF-H-111	- Hardware, Builders', Shelf and Miscellaneous.
FF-N-105	- Nails, Brads, Staples and Spikes: Wire, Cut and Wrought.
QQ-A-250	- Aluminun and Aluminum Alloy Plate and Sheet, General Specification for.
QQ-W-428	- Wire, Steel, High Carbon, Round, Uncoated for Mechanical Springs, General Purpose.
TT-P-636	- Primer Coating, Alkyd, Wood and Ferrous Metals.
TT-V-121	- Varnish, Spar, Water Resisting.

Beneficial comments (recommendations, additions, deletions), and any pertinent data which may be of use in improving this document, should be addressed to Commandant of the Marine Corps, Headquarters Marine Corps (Code LMA-1), Washington, DC 20380, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426), appearing at the end of this document, or by letter.

FSC 5140

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T12:51Z
Check the source to verify that this is the current version before use.

LLL-B-810 - Building Board (Hardboard) Hard Pressed, Vegetable Fiber.
MMM-A-188 - Adhesive, Urea-Resin Type (Liquid and Powder).
PPP-B-566 - Boxes, Folding, Paperboard.
PPP-B-636 - Box, Shipping, Fiberboard.
PPP-B-676 - Boxes, Setup.
PPP-T-76 - Tape, Packaging, Paper (for Carton Sealing).

MILITARY

MIL-P-116 - Preservation, Methods of.
MIL-H-[illegible] - Hinges, Chest, Offset.
DOD-P-15328 - Primer (Wash), Pretreatment (Formula No. 117 for Metals) (Metric).
MIL-S-52768 - Enamel, Alkyd, Camouflage.

STANDARDS

FEDERAL

FED-STD-H28 - Screw-Thread Standards for Federal Services.

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-147 - Palletized Unit Loads.
MIL-STD-731 - Quality of Wood Members for Containers and Pallets.
MIL-STD-810 - Environmental Test Methods.
MIL-STD-889 - Dissimilar Metals.
MIL-STD-1188 - Commercial Packaging of Supplies and Equipment.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

DRAWINGS

MARINE CORPS

297B1 - Chest, Tool, Carpenter or Co. (Assembly).
297B2 - Chest, Tool, Carpenter (Modified).

LAWS AND REGULATIONS

US Department of Commerce Publications

PS-1-66 - Softwood Plywood, Construction and Industrial.

1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T12:51Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. The issues of the documents which are indicated as DoD adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM) STANDARDS:

D2016 - Standard Test Methods for Moisture Content of Wood.

(Application for copies should be addressed to American National Standards Institute, Inc., 1430 Broadway, New York, NY 10018.)

(Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2.1), the contractor shall furnish a sample unit for first article inspection and approval. The first article shall be a preproduction sample, or it may be a standard production item from the contractor's current inventory.

3.2 Material. The chest shall be made from materials specified herein. The chest may contain reclaimed materials provided such materials will not jeopardize its intended use and performance. The reclaimed materials shall have been reprocessed, remanufactured or recycled in a manner which will restore them to the same chemical composition and physical properties as the materials originally selected for use in the chest.

3.2.1 Lumber. Lumber for solid wooden parts of the chest shall be any of the following species: douglas-fir, southern yellow pine, white ash, beech, birch, hard maple, oak or pecan. Lumber shall be uniformly dried to an average moisture content of from 8 to 14 percent at time of machining (see 3.4.7). The minimum board width shall be 2 inches (50.8 mm). Slope of grain of machined components shall not exceed 1 inch (25.4 mm) in 15 inches (381 mm). Machined components shall be free of decay, splits, wane, warp and unsound knots.

3.2.2 Plywood. Plywood used in construction shall conform to group 1, exterior type, grade B-B medium density overlay of PS-1-66.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T12:51Z
Check the source to verify that this is the current version before use.

3.2.3 Hardboard. Hardboard shall be 1/8 inch (3.2 mm) thick and shall conform to type I, surface 1, finish A, design A of LLL-B-810.

3.2.4 Metal components. Steel sheet and strips shall be low carbon steel. Aluminum material shall be constructed of 52S temper 0 aluminum alloy sheet conforming to QQ-A-250.

3.2.4.1 Dissimilar metals. The use of dissimilar metals in intimate contact with each other shall be avoided wherever possible. When the use of dissimilar metals cannot be avoided, an interposing material which will eliminate or minimize galvanic corrosion shall be used. Dissimilar metals shall be as defined in MIL-STD-889.

3.2.5 Nails. Nails shall be made of steel wire and shall conform to the requirements of FF-N-105. Nails used in the assembly shall be cement-coated, acid etched, or mechanically modified (screw type or annular-ring type).

3.2.6 Hardware, miscellaneous. All screws, nuts, bolts, washers, lock washers and rivets shall be of commercial quality. All threaded hardware shall be in accordance with the applicable requirements of FED-STD-H28.

3.2.7 Hinges. The hinges shall be in accordance with MIL-H-10044.

3.2.8 Hasp and staple plate. The hasp and staple plate shall conform to FF-H-111.

3.2.9 Spring handles. Handle spring shall be constructed of hard-drawn steel conforming to class B of QQ-W-428 (see 4.7.7).

3.2.10 Adhesives

3.2.10.1 High temperature. High temperature setting resin adhesives shall conform to the requirements of type III of MMM-A-188, except that the shear strength by compression loading requirement and the curing cycle requirement shall not apply.

3.2.10.2 Room and intermediate temperature. These adhesives shall conform to types I and II of MMM-A-188.

3.3 Design. The chest shall consist of a body, lid and removable tray, and shall be equipped with metal hardware and handles.

3.4 Construction. The construction of the chest and its component parts shall be as shown in Drawing No. 297B1 and as specified herein. Two or more boards may be used in the construction of any end or side of the chest body provided that no board be less than 2 inches (50.8 mm) wide. Such multiple piece construction shall not be used elsewhere in the chest. The sides and ends of the body of the chest, when made of two or more boards, shall have torgue and groove glued joints. Except for the top and bottom of the chest, which shall be plywood (see 3.2.2), and the bottom of the tray, which shall be hardboard (see 3.2.3), the chest shall be constructed of lumber specified in 3.2.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T12:51Z
Check the source to verify that this is the current version before use.

3.4.1 Wood members. Wood members (see 6.3) shall be selected and cut so that allowable defects or imperfections will not occur in positions that would interfere with the prescribed fabrication or assembly of the chest.

3.4.2 Decay (see 6.3). Visible decay shall not be permitted. Stains and discolorations not associated with decay will be acceptable, except that discoloration which interferes with surface finish shall not be acceptable.

3.4.3 Knots (see 6.3). Sound knots, loose knots, knot holes, knot clusters, and decay shall be measured and restricted as specified in 4.7.2.

3.4.4 Checks, splits, and shakes (see 6.3). Through checks, splits, and shakes that are longer than the width of the member will not be permitted. Seasoning checks that do not extend through the full thickness of the members are permitted (see 4.7.3).

3.4.5 Warp (see 6.3). Wood members shall be selected and cut so that allowable twist will not interfere with the prescribed fabrication or assembly of the chest (see 4.7.4).

3.4.6 Cross grain (see 6.3). The slope of the cross grain, resulting either from diagonal sawing or from twisted or spiral grain in the log, or both, shall be no steeper than 1 inch (25.4 mm) in 10 inches (254 mm). Slope of cross grain shall be measured by the angle between the general direction of the grain and the longitudinal axis of the wood member and shall be expressed as a ratio. When a wood member contains both diagonal and spiral grain, the combined damaging effect shall be taken into account (see 4.7.5).

3.4.7 Moisture content (see 6.3). Wood members in the chests shall have a moisture content at the time of fabrication no greater than 14 percent nor less than 8 percent of their kiln-dry weight (see 4.7.6).

3.5 Dimensions. Dimensions of the chest shall be as specified in Drawing Numbers 297B1 and 297B2. Dimensions shall be given in the sequence of length, width, and depth.

3.6 Finish.

3.6.1 Primer pretreatment. Primer pretreatment for steel surfaces shall conform to DOD-P-15328.

3.6.2 Primer. Paint primer shall conform to TT-P-636.

3.6.3 Varnish. Varnish shall conform to TT-V-121.

3.6.4 Enamel. The enamel shall be lusterless forest green conforming to MIL-E-52798.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T12:51Z
Check the source to verify that this is the current version before use.

3.7 Marking. Each chest shall be marked with the manufacturer's name and address. All markings shall be limited to an area of 12 square inches (7742.4 sq. mm) and shall be placed in a lower corner of a side panel.

3.8 Workmanship. The finished chest and components shall be free of burrs, slivers, splinters and rough or sharp edges. Components shall not be broken, cracked or malformed. The enamel shall level out to be a continuous dry adherent film thickness without runs, drips or streaks. The coating shall be free from inbedded foreign matter and shall show no evidence of peeling, flaking or blistering.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspections. The inspections specified herein are classified as follows:

1. Materials inspection (see 4.4).
2. First article inspection (see 4.5).
3. Quality conformance inspections (see 4.6).
4. Inspection of packaging (see 4.8).

4.3 Inspection conditions. Unless otherwise specified herein, all inspections shall be performed in accordance with the test conditions specified in "Test Conditions" of MIL-STD-810.

4.4 Materials inspection. Materials inspection shall consist of certification, supported by verifying data that the materials specified for use are in accordance with the applicable referenced specifications or requirements prior to such fabrication.

4.5 First article inspection. First article inspection shall be performed by the contractor after award of contract and prior to production, at a location acceptable to the Government. First article inspection shall be performed on sample units which have been produced with equipment and procedures normally used in production. First article approval is valid only on the contract under which it is granted, unless extended by the Government to other contracts.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T12:51Z
Check the source to verify that this is the current version before use.

4.5.1 First article sample. Statistical sampling and inspection of the first article shall be in accordance with MIL-STD-105 for general inspection level II. The acceptable quality level (AQL) shall be 2.5 percent defective for major defects and 4.0 percent defective for minor defects.

4.5.2 First article inspection routine. Defects shall be classified as specified in Table I. The first article sample(s) shall be subjected to the inspection routine specified in Table II in the order shown. One or more major defects shall be cause for refusal to grant first article approval.

TABLE I - Tests and Inspection.

Examination	Defect(s)	Classification Major	Classification Minor
Finish	Color of finish not as specified.		X
	Finish is not uniform or smooth.		X
	Areas of no film.		X
	Wet or tacky finish.		X
	Not free of grit or course particles.		X
Design, construction, and workmanship.	Chest not assembled to true 90 degree angles.	X	
	Lid does not fit down into body.	X	
	Splintered, jagged or sharp wooden or metal edges.	X	
Fastening devices	Rivets and other fasteners not properly set, peened or secured.		X
Finished dimensions	Length, width, or height not as specified.	X	
Materials	Components missing, damaged or otherwise defective.	X	
Identification marking	Missing, illegible, incorrect, or not as specified.		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T12:51Z
Check the source to verify that this is the current version before use.

TABLE II - Quality conformance inspections.

Inspection	Requirement paragraph	Test method paragraph
Group A		
Visual examination- - - - -	3.4, 3.5	4.5.2
Design, construction, and workmanship - - - - -	3.3, 3.4, 3.8	4.5.2
Wood Decay- - - - - - - - -	3.4.2	4.7.1
Knots - - - - - - - - - - -	3.4.3	4.7.2
Shakes, Checks, and Splits- - - - - - - -	3.4.4	4.7.3
Warp- - - - - - - - - - - -	3.4.5	4.7.4
Group B		
Cross Grain - - - - - - - -	3.4.6	4.7.5
Moisture Content- - - - - -	3.4.7	4.7.6

4.6 Quality conformance inspection. Quality conformance inspection shall consist of group A and B inspections specified in Table II. Statistical sampling and inspection shall be in accordance with MIL-STD-105 for normal inspection, single sampling. The inspection level shall be II and the AQL shall be 2.5.

4.6.1 Inspection lot. An inspection lot shall consist of items produced under essentially the same conditions, and offered for inspection at the same time.

4.6.2 Rejected lots. If an inspection lot is rejected, the supplier may withdraw the lot, rework it to correct the defects, or screen out the defective units, as applicable, and reinspect. Such lots shall be separate from new lots and shall be clearly identified as reinspected lots. Rejected lots shall be reinspected, using tightened inspection. A lot shall not be resubmitted more than one time.

4.7 Tests. Examination and tests shall be performed as specified herein. Other test methods may be substituted upon written approval by the procuring activity, provided the supplier has demonstrated that the results obtained properly correlate with those obtained using the methods specified herein. The supplier must also demonstrate that such substitution does not relax the requirements of this document.

4.7.1 Decay. Any form of visible decay shall not be permitted except in knots. Stains and discoloration not associated with decay will be acceptable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T12:51Z
Check the source to verify that this is the current version before use.

4.7.2 Knots. The sum of the sizes of all knots in any 6-inch (152.4-mm) length shall not exceed twice the size of the largest permitted knot of 1 inch (25.4 mm). Two or more knots of maximum or near maximum permissible size shall not be allowed in the same 6-inch (152.4 mm) length on a face. Any combination of knots that, in the judgement of the lumber grader, will make the material unfit for its intended use, shall be cause for rejection.

4.7.3 Shakes, checks and splits. Any combination of shakes, checks, and splits shall be based on the grader's judgment. Where a combination of two checks in opposite faces, a check and a split, a check and a shake, or a split and a shake may later become a single horizontal shear plane, the sum of the sizes in the combination is restricted to the allowable size of shakes. Where such a combination is not additive in this way, only the largest single characteristic is considered.

4.7.4 Warp. The bow in a member shall not exceed 1/32 inch (0.79 mm) per foot of length. The cup in a member shall not exceed 1/8 inch (3.18 mm) in an 8-inch (203.2 mm) width, 1/16 inch (1.59 mm) in a 4-inch (101.6 mm) width, or a like proportion in other widths.

4.7.5 Calculating the combined slope of cross grain. The combined damaging effect of slope of cross grain can be computed by combining the apparent slope of grain on two adjacent faces of a member. When each of the slopes are expressed as a ratio to 1, i.e., 1 in 18 and 1 in 12, the combined slope is the square root of the sum of the squares of the two slopes as stated in MIL-STD-731 (combined slope $= \sqrt{(1/18)^2 + (1/12)^2} = \sqrt{.01}$ or 1 in 10).

4.7.6 Moisture content. Lumber shall be tested prior to machining for moisture content in accordance with ASTM D 2016.

4.7.7 Handle lifting capacity. The handles and attaching hardware shall be tested to determine structural integrity. With a dummy load of 150 pounds (68 kg), the chest shall be raised 10 times to a height of not less than 24 inches (609.6 mm). At the end of the test period, the handle assembly shall be inspected for any defects.

4.8 Packaging inspection. Packaging shall be inspected to determine compliance with the requirements specified in Section 5. The sample plan shall be in accordance with MIL-STD-105 for normal inspection, single sampling. The inspection level shall be S-4 and the AQL shall be 2.5.

5. PACKAGING

5.1 Preservation-packaging. Preservation shall be level A or commercial as specified (see 6.2.1).

5.1.1 Level A.

5.1.1.1 Preservative application. Preservatives shall not be used.

Source: https://assist.dla.mil -- Downloaded: 202640-18T12:51Z
Check the source to verify that this is the current version before use.

5.1.1.2 Unit packaging. Unit packaging shall be in accordance with the methods prescribed in MIL-P-116.

5.1.1.3 Intermediate packaging. Chests, packaged as described in 5.1.1.2, shall be placed in intermediate containers conforming to PPP-B-566 or PPP-B-676. Intermediate containers shall be uniform in size, shape, and quantities, shall be of minimum tare and cube and shall contain multiples of five unit packages, not to exceed 50 unit packages. No intermediate packaging is required when the total quantity shipped to a single destination is less than 50 units.

5.1.2 Commercial. Commercial packing shall be in accordance with MIL-STD-1188. This level shall conform to the contractor's commercial practice.

5.2 Packing. Packing shall be level A, B, or commercial as specified (see 6.2.1).

5.2.1 Level A. The tool chests shall be packed in fiberboard containers conforming to PPP-B-636, class weather resistant, style optional, special requirements. In lieu of the closure and waterproofing requirement in the appendix of PPP-B-636, closure waterproofing shall be accomplished by sealing all seams, corners, and manufacturer's joint with tape conforming to PPP-T-76. Banding (reinforcement requirements) shall be applied in accordance with the appendix thereto.

5.2.2 Level B. The chest shall be packed in fiberboard containers conforming to PPP-B-636, class domestic, style optional, special requirements. Closures shall be in accordance with the appendix thereto.

5.2.3 Commercial. Commercial packing shall be in accordance with MIL-STD-1188.

5.2.4 Unitized loads. Unitized loads, commensurate with the level of packing specified in the contract, shall be used whenever total quantities for shipment to one destination equals 40 cubic feet or more. Quantities less than 40 cubic feet need not be unitized. Unitized loads shall be uniform in size and quantities to the greatest extent practicable.

5.2.4.1 Level A. Chests packed as specified in 5.2.1, shall be unitized on pallets in conformance with MIL-STD-147, load type I, with a fiberboard cap (storage aid 4) positioned over the load.

5.2.4.2 Level B. Chests packed as specified in 5.2.2, shall be unitized as specified in 5.2.4.1, except that the fiberboard caps shall be class domestic.

5.2.4.3 Commercial. Tool chests packed as specified in 5.2.3, shall be unitized with pallets and caps of the type, size and kind commonly used for the purpose and shall conform to the applicable carrier rules and regulations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T12:51Z
Check the source to verify that this is the current version before use.

5.3 Marking. In addition to any special marking required by the contractor, each unit package, intermediate and exterior container and unitized, load shall be marked in accordance with MIL-STD-129. When packaging and packing conforms to commercial practice, as specified in 5.1.2 and 5.2.3, marking shall be in accordance with MIL-STD-1188.

6. NOTES

6.1 Intended use. The tool chest covered by this specification is intended for use as permanent container for tool sets.

6.2 Ordering data.

6.2.1 Acquisition requirements. Acquisition documents should specify the following:

(a) Title, number and date of this specification.
(b) When first article is required (see 3.1).
(c) Level of preservation, packaging and packing required (see Section 5).

6.2.2 Data requirements. When this specification is used in an acquisition which incorporates a DD Form 1423, Contract Data Requirements List (CDRL), the data requirements identified below shall be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved CDRL incorporated into the contract. When the provisions of DAR 7-104.9(n)(2) are invoked and the DD Form 1423 is not used, the data specified below shall be delivered by the contractor in accordance with the contract or purchase order requirements. Deliverable data required by this specification is cited in the following paragraphs.

Paragraph No.	Data Requirements	Applicable DID No.	Options
4.5	First Article Inspection Procedure	DI-T-4901	-------
4.5	First Article Inspection Report	DI-T-4902	-------
4.7	Production/Acceptance Inspection Procedures	DI-T-4903	-------
4.7	Production Inspection Reports	DI-T-4904	-------

(Copies of DIDs required by contractors in connection with specific acquisition functions should be obtained from the Naval Publications and Forms Center or as directed by the contracting officer.)

6.3 Definitions. For the purpose of this specification, the following definitions apply:

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T12:51Z
Check the source to verify that this is the current version before use.

(a) Wood members. A part of the fundamental structure upon which the strength and rigidity of a container depends.

(b) Decay. The disintegration of wood due to the action of fungi.

(c) Check. A lengthwise separation of the wood, the greater part of which occurs across the rings of annual growth. Through checks extend through the full thickness of the member.

(d) Shake. A separation along the grain which occurs between the rings of annual growth.

(e) Knot, sound. A knot that is solid across the face and at least as hard as the surrounding wood, showing no indication of decay.

(f) Warp. Any variation from a true or plane surface. Warp includes bow, crook, cup, and twist, or any combination thereof.

(g) Grain, cross. Grain which is not parallel to the longitudinal axis of the piece. It may be either diagonal or spiral grain or a combination of the two.

(h) Moisture content. Weight of the water contained in wood, usually expressed as a percentage of the oven-dry weight of the wood.

6.4 First article. Any changes or deviations from the approved first article during production will be subject to the approval of the contracting officer. Approval of the first article will not relieve the supplier of his obligation to furnish tool chests conforming to this specification.

6.5 Changes from the previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Preparing Activity:
Navy - MC
Project No. 5140-N067

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T12:51Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use i submitting comments and suggestions for improvements. All users of military standardization documents are invited to provid suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, an mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, w too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE NAVY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12503 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

Commandant of the Marine Corps
Headquarters, US Marine Corps
Attn: Code LMA-1
Washington, DC 20380

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T12:51Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*:

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil/online/sdip/sdip.pdf 2026-02-18T12:51Z
Check the source to verify that this is the current version before use.