MIL-C-19482C
AMENDMENT 3

21 March 1972

SUPERSEDING
AMENDMENT 2
15 December 1971

MILITARY SPECIFICATION

CARRIERS, STORAGE BATTERY, HAND

This amendment forms a part of Military Specification MIL-C-19482C, dated 8 June 1970, and is approved for use by all Departments and Agencies of the Department of Defense.

Page 4

3.6.1, delete and substitute:

"3.6.1 Type I carrier. The type I carrier shall consist of a strap, with a battery post grip permanently held in place on each end of the strap. The battery post grips shall be disk or ring type, designed to hold the battery posts securely when under lifting tension, and shall have adequate clearance to release easily when relaxed. The overall length shall be the manufacturer's nominal standard nearest 12 inches for size 12, and 20 inches for size 20, as applicable, for use with storage batteries in accordance with table I."

Page 5

4.4.2, after table I, insert: "Type I carriers shall be tested with the heaviest and the lightest batteries having diagonally apposed terminals. The battery shall be lifted from the floor, utilizing the appropriate carrier, and pendulum swung not less than 5 strokes through an arc not less than 120°, centered on the vertical. After swinging, the battery shall be replaced on the floor, and relifted with a jerk at an angle of about 30° from vertical, in each of two different directions."

Custodians:

Army - GL
Navy - YD
Air Force - 84

Preparing activity:

Navy - YD

Project No. 5120-0759

User activity:

Army - ME

FSC 5120

☆U.S. GOVERNMENT PRINTING OFFICE: 1972-714-165/6456

Source: https://assist.dla.mil -- Downloaded: 202610-18T12:54Z
Check the source to verify that this is the current version before use.