INCH-POUND

MIL-L-19493C(SH)
AMENDMENT 1
5 April 1993

MILITARY SPECIFICATION

LAUNDRY PRESSING AND FINISHING EQUIPMENT, MODIFIED COMMERCIAL (SHIPBOARD)

This amendment forms part of MIL-L-19493C(SH), dated 9 April 1990, and is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

2.2: Add the following under: "AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)"

"B 200 - Standard Specification for Electrodeposited Coatings of Lead and Lead-Tin Alloys on Steel and Ferrous Alloys."

PAGE 4

2.2: Delete "1166-88" under "AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)" and substitute "F 1166".

PAGE 5

3.1, line 2: Delete "6.3" and substitute "6.5".

3.1.2, lines 2, 4 and 8: Delete "ASTM 1166" and substitute "ASTM F 1166".

PAGE 7

3.3.1: Add the following after the first sentence:

"Exposed steam hoses shall be shielded to prevent the operator or maintenance personnel from incidental contact that might result in bum accidents."

3.3.1, line 4: Delete "ASTM 1166" and substitute "ASTM F 1166".

DISTRIBUTION STATEMENT A Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T12:55Z
Check the source to verify that this is the current version before use.

3.3.5, lines 1 through 6: Delete “The laundry press base shall have four or six 5/8-inch bolt holes for anchoring the unit to the deck. Types I and II, classes C, and C-E, presses shall have six bolts 5/8-inch bolt holes and classes B, B-E, G, G-E, N, and N-E presses shall have four or six bolts 5/8-inch bolt holes. The press’s mounting configuration shall be in accordance with figure 1. Type III, classes A and B ironers shall have six bolt holes 3/4-inch. The ironer’s mounting configuration shall be in accordance with figures 2 or 3 as specified."

PAGE 9

3.3.23, line 1: Delete "workthrough" and substitute "workthrough"

3.3.16, third sentence: Delete,

PAGE 12

3.3.20.1, line 3: Delete “ASTM 1166-88” and substitute “ASTM F 1166”.

3.3.20.1.1, last line: Delete “ASTM 1166-88” and substitute “ASTM F 1166”.

PAGE 13

3.3.20.1.7, line 2: Delete “ASTM 1166" and substitute “ASTM F 1166".

3.3.20.1.9, line 3: Delete “ASTM 1166" and substitute “ASTM F 1166”.

3.3.20.1.11, lines 1 and 2: Delete “ASTM 1166" and substitute “ASTM F 1166”.

PAGE 16

Add as new paragraph 3.5.2.1.1.1:

"3.5.2.1.1.1 Head exhaust hood. A removable exhaust hood shall be connected to press head. Shape of hood shall conform to shape of head with 1 1/2-inch air space around perimeter. Hood shall be made of ASTM B 200, aluminum alloy, 1/16 inch thick. Hood shall be capable of exhausting 500 CFM via ship’s ventilation system. An exhaust duct opening shall be provided for exhausting air through a 6-inch diameter flexible duct. Hood shall be provided with removable maintenance access to grease fittings.”

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T12:55Z
Check the source to verify that this is the current version before use.

Add as new paragraph 3.5.2.1.1.2:

"3.5.2.1.1.2 Head shock absorber. A shock absorber shall be provided to permit checking of the head to a smooth, silent stop, but not to interfere with the rapid opening or closing of the head."

PAGE 17

3.5.2.1.8: Add the following after the sixth sentence:

"In case of an obstruction between the head and padded buck amounting to 3/4-inch or more, or if the safety control bar contacts an obstruction, the moving member shall not lock closed; and upon release of one or more of the closing buttons, the head shall release to the open position. In addition, a means shall be provided, independent of closing buttons, to immediately release head on down stroke should head come in contact with any obstruction of 3/4-inch or more. Presses supplied for shipboard use shall have the same basic operating characteristics and the same pressure between heads and bucks as those supplied for commercial use. Presses shall be pneumatically operated and shall operate on a minimum working air pressure of 65 psi gauge"

3.5.2.1.10: Delete in its entirety.

PAGE 18

Add as new paragraph 3.5.2.2.1.1:

"3.5.2.2.1.1 Head exhaust hood. A removable exhaust hood shall be connected to press head. Shape of hood shall conform to shape of head, with 1 l/2-inch air space around perimeter. Hood shall be made of ASTM B 200, aluminum alloy, 1/16-inch thick. Hood shall be capable of exhausting 500 CFM via ship's ventilation system. An exhaust duct opening shall be provided for exhausting air through a 6-inch diameter flexible duct. Hood shall be provided with removable maintenance access to grease fittings."

Add as new paragraph 3.5.2.2.1.2:

"3.5.2.2.1.2 Head shock absorber. A shock absorber shall be provided to permit checking of the head to a smooth, silent stop, but not to interfere with the rapid opening or closing of the head."

3.5.2.2.4: Delete and substitute:

"3.5.2.2.4 Pneumatic power application. Type II presses shall be pneumatically powered as specified for type I presses (see 3.5.2.1.8)."

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T12:55Z
Check the source to verify that this is the current version before use.

Add as new paragraph 3.5.2.2.5:

"3.5.2.2.5 Press controls. Type II presses shall be controlled as specified for type I presses (see 3.5.2.1.9)."

PAGE 19

3.5.2.3.6: Delete in its entirety.

PAGE 20

3.5.2.3.10: Delete in its entirety.

3.5.2.3.15, line 1: Delete "(see 6.2.1)" and substitute "(see 6.2)".

PAGE 21

3.5.2.3.16: Delete in its entirety.

3.6.1, lines 2 and 3: Delete ", with 600 pounds pressure between heads and bucks".

PAGE 25

4.3, line 1: Delete "(see 6.2.1)" and substitute "(see 6.2)".

4.4, line 2: Delete "(see 6.3)" and substitute "(see 3.1)".

PAGE 29

4.4.2.6a: Delete "(3.6.2.1.9)" and substitute "(3.5.2.1.9)".

4.4.2.6b: Delete "(3.6.2.1.5)" and substitute "(3.5.2.1.5)".

4.4.2.6c: Delete "(3.6.2.1.8)" and substitute "(3.5.2.1.8) and independent head release."

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T12:55Z
Check the source to verify that this is the current version before use.

PAGE 35

5.2, lines 3 and 4: Delete "(see 6.2.1)" and substitute "(see 6.2)".

6.2d: Delete "(see 3.6.2.3.15)" and substitute "(see 3.5.2.3.1.5)".

PAGE 36

6.3: Delete the following:

"3.5	DI-E-7031	Drawings, engineering and associated lists	-
4.5	DI-T-5329	Inspection and test reports	-
4.5	DI-T-4902	First article inspection report	- "

and substitute:

"4.5	DI-NDTI-80809	Test/inspection reports	----
4.5	DI-MISC-80678	Certification/data report	10.3.1 does not apply"

PAGE 36

Add as new paragraph 6.4.1:

"6.4.1 Technical manuals development. Technical manuals (including technical repair standards (TRS)) should be acquired under separate CLINs or subCLINs. Technical manual products (such as manuscript copy, preliminary copy, and reproducible copy) should be developed and delivered as specified in the Technical Manual Contract Requirements (TMCR) exhibit(s) to the contract. The TMCR is an exhibit or attachment to a contract specifying technical manual product development and delivery requirements, and/or management data development requirements. CDRLs and DID's should not be used for technical manual product acquisitions. Technical manual management data (such as plans and reports) should be acquired under a separate data CLIN, but delivery should continue to be specified on CDRLs and DID's. Technical manual quality assurance management data should be prepared and delivered as specified in the TMCR and contractor order."

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T12:55Z
Check the source to verify that this is the current version before use.

PAGE 38

Figure 1: Delete in its entirety.

PAGE 39

Figure 2: Delete in its entirety,

PAGE 40

Figure 3: Delete in its entirety.

Preparing activity:
Navy - SH
(Project 3510-N327)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T12:55Z
Check the source to verify that this is the current version before use.