MILITARY SPECIFICATION

CONTACTOR

This amendment forms a part of Military Specification MIL-C-22896A(OS) of 29 August 1968 and has been approved by the Naval Ordnance Systems Command, Department of the Navy

Page 1, paragraph 2.1, under FEDERAL: Delete "PPP-B-575" and "PPP-B-645" with associated titles.

Page 11, paragraph 4.4.8. Delete and substitute:
"4.4.8 Thermocouple bridge. Leads Northrup Model 8694 or equivalent. The instrument must be capable of indicating over a range from O to 400 degrees F with an accuracy of plus or minus two percent."

Page 11, paragraph 4.4.8.1. Delete and substitute:
"4.4.8.1 Sensing element. Copper Constantan Thermocouple with a response time no greater than two seconds when mounted. The thermocouple shall be capable of being electrically insulated from its mounting surface as specified in 4.5.4.7.

Page 13, paragraph 4.5.4.7. Delete and substitute:
"4.5.4.7 Temperature rise. Attach the thermocouple specified in 4.4.8.1 to one of the two main contact terminals, taking care to insulate the element electrically with a piece of 0.01 thick mica securely held in place with an epoxy resin. Connect the thermocouple lead to the thermocouple bridge specified in 4.4.8. With the contactor wired and the circuit adjusted as specified in 4.5.4.6, allow a current of 560 plus or minus 25 amperes to flow through the load and main contacts for 15 minutes. Read and record the temperature of the main contact terminals at the beginning, end, and at 2-minute intervals during the is-minute period. Compute the temperature rise above ambient (65 degrees F to 95 degrees F) for each reading taken. The temperature rise shall be in accordance with 3.3.8."

Page 21, Table II: Delete "PPP-B-575" and "PPP-B-645" with associated titles, and dimensions.

Page 22, paragraph 6.1. Delete "Torpedo Mk 45 Mod 0 and Mk 45 Mod 1" and substitute "Torpedo Mk 45 Mods 0, 1, and 2".

Preparing Activity
Navy - OS
Project No. 1355-N081

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:48Z
Check the source to verify that this is the current version before use.