MILITARY SPECIFICATION

CABLES, RADIO FREQUENCY, SEMIRIGID,

COAXIAL, SEMI-AIR-DIELECTRIC,

GENERAL SPECIFICATION FOR

This supplement forms a part of Military Specification MIL-C-22931, 10 February 1968, and is mandatory for use by all Departments and Agencies of the Department of Defense.

SPECIFICATION SHEETS

MIL-C-22931/9 - Cables, Radio Frequency, Semirigid, Coaxial, Semi-Air-Dielectric, .500 and .530 Inch Outside Diameter, 50 Ohms.
MIL-C-22931/10 - Cables, Radio Frequency, Semirigid, Coaxial, Semi-Air-Dielectric, .500 Inch Outside Diameter, 75 Ohms.
MIL-C-22931/11 - Cables, Radio Frequency, Semirigid, Coaxial, Semi-Air-Dielectric, .875 to 1.005 Inches Outside Diameter, 50 Ohms.
MIL-C-22931/12 - Cables, Radio Frequency, Semirigid, Coaxial, Semi-Air-Dielectric, .875 and 1.005 Inches Outside Diameter, 75 Ohms.
MIL-C-22931/13 - Cables, Radio Frequency, Semirigid, Coaxial, Semi-Air-Dielectric, 1.625 to 1.830 Inches Outside Diameter, 50 Ohms.
MIL-C-22931/14 - Cables, Radio Frequency, Semirigid, Coaxial, Semi-Air-Dielectric, 1.625 Inches Outside Diameter, 75 Ohms.
MIL-C-22931/15 - Cables, Radio Frequency, Semirigid, Coaxial, Semi-Air-Dielectric, 2.850 and 3.125 Inches Outside Diameter, 50 Ohms.
MIL-C-22931/16 - Cables, Radio Frequency, Semirigid, Coaxial, Semi-Air-Dielectric, 3.125 inches Outside Diameter, 75 Ohms.

Preparing activity:
Navy - EC

(Project 6145-0550)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:51Z
Check the source to verify that this is the current version before use.