MIL-R-22890(OS]
AMENDMENT 2
27 January 1987
SUPERSEDING
AMENDMENT 1
12 March 1973

MILITARY SPECIFICATION

RECTIFIER, ERROR METER ASSEMBLY

This **amendment forms a part of Mtlitary Specification MIL-R-22890Wep)* dated 9 January 1962, and is approved for use within the Naval Sea Systems Command, Department of the Navy, and is available** for use by all **Departments and** Agencies of the Department of Defense.

***** By this **amendment, basic specification MIL-R-22890(Wep) is** changed to **read M1L+-Z2890(OS), and throughout the specification "Bureau of Naval Weapons"' shall be changed to read** "Naval Sea Systems Command" and "BUWEpS" and **"NAVWEPS" shall be changed to read "NAVSEA".**

PAGE 1

* 2.1, Delete and substitute:

"2.1 Government documents.

2.1.1 Specifications and standards. The following **specifications are standards form a** part of **this specification to the extent specifed herein.** Unless otherwise specified the issues of these documents shall be those listed in the **issue of the Department of Defense Index of Specifications and Standards** (DODISS) and supplement thereto, cited in the solicitation."

*Delete: "MIL-E-5272 Environmental Testing, Aeronautical and Associated Equipment, General Specification for".

*Delete: "MIL-T-17113° **and its title and substitute MIL-S-901** Shock Tests, H.I. **(High Impact); Shipboard Machinery EQUIPMent And systems' Requirements** For".

PAGE 2

*** Under STANDARDS** add:

"FEDERAL

FED-STD-H28	Screw-Thread Standards For Federal Services"

DISTR1BUTION STATEMENT A Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:46Z
Check the source to verify that this is the current version before use.

PAGE 2

* Under STANDARDS, MILITARY add:

"MIL-STD-810	Environmental Test Methods and Engineering Guidelines

* 2.1.2 Other Government documents, drawings, and publications. The followlng other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation."

* Delete: "NAVORD OP *400"* and its title.

* *2.2,* Delete and substitute:

"2.2 Other publications. The following documents form a part of this specification to the **extent specified herein.** Unless otherwise specified, the issues of **the documents which are** DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. **Unless** otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation."

PAGE 3

* Delete:

"NATIONAL BUREAU OF STANDARDS PUBLICATION

Handbook H28 and all supplements thereto	Screw-Thread Standards for Federal Services

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington 25, DC)"

* Add: "2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained."

PAGE 4

* 3.2.7: Delete "Handbook H28° and substitute "FED-STD-H28"; two places.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:46Z
Check the source to verify that this is the current version before use.

* *3.2.8:* Delete **In its entinty.**

PAGE 6

*** 3.5.2:** Delete and substitute:

"*3.5.2* Shock, nonoperating condition. The error meter rectifier assembly shall withstand and Type C shock requirements specified in MIL-S-90l and thereafter shall show no damage and shall meet all the performance requirements and product charactertstics of this specification."

PAGE 7

*** 3.5.5,** third line: Delete "MIL-E-5272° and substitute "MIL-STD-810".

* 4.1, Delete and substitute:

"4.1A Responsibility for inspection. Unless otherwise specified in the **contract or purchase order, the contractor Is responsible** for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.lB Responsibility for compliance. All items must meet all requirements of sections 3 and .5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission **of** known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material."

* 4.1.1, line 2: Delete "by Government inspectors."

* 4.1.2, line 4: Delete "to the Government inspector."

PAGE 8

* 4.1.3, line **5:** Delete "will be as determined by the Government inspector and. "

*** 4.1.4, line 4:** Delete "by the Government inspector."

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:46Z
Check the source to verify that this is the current version before use.

* 4.2.1: Delete second sentence and substitute "Acceptance tests shall be performed by the manufacturer."

PAGE 10

* 4.5.2, Delete and substitute:

"4.5.2 Shock, nonoperating condition. The error meter rectifier assembly shall h subjected to the Type C shock tests specified in **MIL-S-901 and thereafter** shall show no damage and shall meet all the performance requirements and product characteristics of this specification."

* 4.5.4, second line: Delete "**MIL-E-5272°** and substitute "MIL-STD-81O".

PAGE 12

Delete "NOTICE" paragraph.

* The margins of this amendment are marked with asterisks to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were 'made. This was done as a convenience only **and** the Government assumes no liability whatsoever for **any Inaccuracies In these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the** last **previous amendment.**

Preparing activity:
Navy - OS
(Project 1290-N403)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T14:46Z
Check the source to verify that this is the current version before use.