MILITARY SPECIFICATION
IGNITOR, XENON LAMP
FOR
SEARCHLIGHT, INFRARED AN/TVS-3

1. SCOPE

1.1 This specification covers one type of ignitor for 10/15/20 Kilowatt (KW) short-arc xenon lamps conforming to MIL-L-55574 for use in searchlights.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATION

MILITARY

MIL-T-152	- Treatment, Moisture and Fungus-Resistant, of Communications, Electronic, and Associated Electrical Equipment
MIL-M-10304	- Meters, Electrical Indicating, Panel Ruggedized General Specification for
MIL-P-11268	- Parts, Materials and Processes Used in Electronic Communication Equipment

FSC 6230

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:36Z
Check the source to verify that this is the current version before use.

MIL-M-13231 - Marking of Electronic Items

MIL-W-16878 - Wire, Electrical, Insulated, High Temperature

MIL-E-17555 - Electronic and Electrical Equipment and Associated Repair Parts, Preparation for Delivery of

MIL-L-55574 - Lamp, Xenon, Short-Arc, 10/15/20 KW

STANDARDS

FEDERAL

FED-STD-595 - Color

MILITARY

MIL-STD-22 - Welded-Joint Design

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes

MIL-STD-171 - Finishing of Metal and Wood Surfaces

MIL-STD-810 - Environmental Test Methods for Aerospace and Ground Equipment

DRAWINGS

EC(NVE)

SC-D-599462 - Assembly, Ignitor and Voltage Booster

(Copies of specifications and standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. - The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:36Z
Check the source to verify that this is the current version before use.

AMERICAN STANDARDS ASSOCIATION

Electrical and Electronics Reference Designations ASA Y32.16-196[illegible]

Application for copies should be addressed to:

AMERICAN STANDARDS ASSOCIATION INC
10 East 40th Street
New York, New York 10016

AMERICAN WELDING SOCIETY

Standard Welding Symbols AWS A2.0-58

Application for copies should be addressed to:

AMERICAN WELDING SOCIETY
435 East 47th Street
New York, New York 10016

NATIONAL BUREAU OF STANDARDS

Handbook H-28

Application for copies should be addressed to:

NATIONAL BUREAU OF STANDARDS
Washington, D.C. 20036

3. REQUIREMENTS

3.1 Description. - The ignitor shall be in accordance with Drawing SC-D-599462 and as specified herein.

3.2 First Article Model. - The supplier shall furnish two ignitors within the time frame specified in the contract or purchase order to prove, prior to starting production, that his production methods will produce ignitors that comply with the requirements of this specification. Examination and tests shall be those specified herein. Any changes or deviations from the first article model shall be subject to the approval of the contracting officer. Approval of the first article model by the activity concerned shall not relieve the supplier of his obligation to furnish ignitors conforming to this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:36Z
Check the source to verify that this is the current version before use.

3.3 Initial Production. - Two ignitors selected from the first ten (10) ignitors produced from production tooling shall be examined and tested as specified in 4.4. to determine conformance to the requirements of this specification. Acceptance of initial production ignitors shall not establish the acceptability of the remainder of ignitors under contract in conflict with the acceptance levels specified in 4.4. These ignitors shall be fully representative of ignitors to be furnished under the contract.

3.4 Drawings. - The drawings forming a part of this specification are engineering design drawings. The supplier is responsible for preparing his own shop drawings. Where tolerances prescribed could cumulatively result in incorrect fits, the supplier shall provide tolerances within those prescribed on the drawings to insure correct fit, assembly and operation of the ignitor. No deviation from the prescribed dimensions or tolerances is permissible without prior approval of the contracting officer. In the event of conflict between the drawings and this specification, this specification shall govern.

3.5 Materials and Components. - Materials and components shall be as specified herein and as shown on the applicable drawings. Materials and components not specified shall be selected by the contractor, shall conform to MIL-P-11268 and shall be subject to all applicable provisions of this specification.

3.5.1 Wiring. - Unless otherwise specified, connections shall be made using AN or MS type waterproof connectors. Wiring, where exposed and subject to vibration shall be extra flexible and insulated with polytetra fluoroethylene (TFE).

3.6 Operation. - The ignitor shall ignite the 10/15/20 KW xenon lamp conforming to MIL-L-55574 within 2 seconds after the application of 115 volts ac plus or minus 10 V ac at a frequency of 400 hertz (Hz) plus or minus 25 Hz to its input terminals.

3.6.1 Temperature and Humidity. - The ignitor shall perform as specified herein with humidity uncontrolled, in any ambient temperature from minus 65 degrees F to plus 250 degrees F.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:36Z
Check the source to verify that this is the current version before use.

3.6.2 Thermal Shock. - The ignitor shall not be damaged by exposure to thermal shock at any temperature from minus 80 degrees F to plus 250 degrees F.

3.6.3 Altitude. - The ignitor shall perform as specified herein at any altitude from sea level to 10,000 feet above sea level.

3.7 Storage and Transit Conditions. -

3.7.1 Temperature and Humidity. - The ignitor shall not be damaged by storage in any temperature from minus 80 degrees F to plus 250 degrees F and at maximum relative humidities within that range.

3.7.2 Altitude. - The ignitor shall not be damaged by transportation in unpressurized aircraft at any altitude to 40,000 feet above sea level.

3.7.3 Mechanical Shock and Vibration . - The ignitor shall not be damaged when subjected to sustained shock and vibration would be encountered during transportation in military vehicles.

3.8 Electrical Characteristics

3.8.1 Ignition. - The ignitor shall deliver the following minimum values of electrical energy for ignition of the 10/15/29 KW xenon lamp:

a. Ignition pulse voltage not less than 45,000 volts.

b. Ignition pulse repetition rate not less than 1,600 per seconds.

c. Energy per ignition pulse not less than 0.1 watt seconds.

d. Ignition pulse energy not less than 160 watt seconds for 1 second duration.

e. An open circuit or boost voltage of not less than95 volts dc with energy of 0.5 watt seconds minimum.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:36Z
Check the source to verify that this is the current version before use.

3,8.2 Load Rating. - The ignitor shall carry, without damage a sustained electrical load through the power wiring of not less than 500 amperes after being subjected to an 800 ampere load for 1 minute.

3.8.3 Equivalent load. - The ignitor shall operate as specified herein when subjected to a load equal to the 20 KW xenon lamp with a resistance value equal to the lamp resistance between the electrodes and capacitance equal to the capacitance of the lamp.

3.9 Weight. - The ignitor (see 3.1) shall weight not more than 30 pounds excluding packaging for shipment.

3.10 Reliability. - The ignitor shall perform, as specified herein, without maintenance to ignite a 10/15/20 KW xenon lamp a minimum of 5000 times consecutively.

3.11 Treatment and Painting. - Unless otherwise specified the ignitor shall be given a protective finish in accordance with MIL-STD-171 , the color shall be lusterless black conforming to FED-STD-595, color no. 37038. Parts and components having a natural black lusterless finish with natural corrosion resistant qualities need not be treated and painted.

3.12 Fungus and Moisture Resistance. - The electrical circuitry, including all components and connections, shall be protected from the effects of moisture and fungus growth by an overall treatment conforming to MIL-T-152 Type I, with the following exceptions.

a. Components or circuit elements that are inherently fungus and moisture resistant or which are hermetically sealed need not be treated.

b. Components or circuit elements whose functions will be adversely affected by the varnish coating shall not be treated. When used, the varnish shall be applied by spray, brush, or a combination of both to give a minimum dry-film thickness of 1 mil to component or element surfaces previously cleaned and prepared so that the surfaces are free from all foreign matter which would interfere with the adherence or function of the varnish.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:36Z
Check the source to verify that this is the current version before use.

3.13 Identification and Information Plates and Stenciling. - The ignitor shall be identified and marked in accordance with MIL-M-13231 and the applicable drawings. All information and identification plates shall be photo-sensitive anodized aluminum and shall be permanently attached in accordance with the applicable drawings.

3.13.1 Connection Information. - Connection information shall be provided in accordance with the applicable drawings; shall be white legand on black background; and shall clearly identify all connections necessary for installation and operation of the ignitor.

3.13.2 Warning Plates. - Warning plates shall be affixed to warn of any condition which could cause damage to components of the ignitor or injury to operating personnel and shall be red blackground with black legend.

3.13.3 Electrical Component Location and Identification Markings. - The location of each electrical component shall be identified by stenciling on the supporting panel in a location adjacent to the component with symbols as indicated in the wiring diagrams and in accordance with Electrical and Electronics Reference Designations, ASA Y32.16-1965. Stenciling shall be in a color contrastinq to the background color for legibility.

3.13.4 Electrical Wiring Identification Marking. - Each individual electric conductor shall be identified by imprinting on the surface of its insulating jacket, the circuit identification number and the termination points. Wire conforming to MIL-W-16878/4 shall be color coded and identified by close fiting sleeve markers bearing the circuit identification number and termination points. Wire identification shall be a color contrasting to the background for legibility. The wire marking method selected shall not cause the insulation to be crushed or damaged so as to decrease the capacity or dielectric capability of the individual wires.

3.14 Technical publications. - Such technical publication as are specified shall be furnished (see 6.2)

3.15 Items Furnished with Ignitors. - No shipment of ignitors shall be made unless repair parts, maintenance tools, technical publications and operating supplies as are specified (see 6.2) are included with the shipment or unless approval for shipment without such items has been received.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:36Z
Check the source to verify that this is the current version before use.

3.16 Screw Threads. - Screw threads shall conform to the National Bureau of Standards Handbook H-28. Mating threaded aluminum surfaces shall be treated prior to assembly with a silicone lubricant capable of withstanding temperatures from minus 80 degrees F to plus 350 degrees F to prevent galling and seizure of the threads.

3.17 Welded Joint Design. - Welded joint designs shall conform to MIL-STD-22. Welding shall conform to Standard Welding Practices as prescribed by the American Welding Society.

3.18 Workmanship. - The ignition system shall be free from defects such as faulty soldering, crimping, wiring, welding and marking of parts and assemblies, or any other defects which may adversely impair the intended functions of the ignition system. All wiring shall be bundled into harnessess and supported by insulated cable clamps. Wiring shall be routed to avoid any sharp corners or possibility of damage from contact with high temperature surfaces, abrasion, or accidental severance.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for Inspection. - Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of Inspection. - Inspection shall be classified as follows:

a. First article model inspection (see 4.3).
b. Initial production inspection (see 4.4).
c. Quality conformance inspection (see 4.5).
d. Inspection comparison (see 4.7).
e. Inspection of preparation for delivery (see 4.8).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:36Z
Check the source to verify that this is the current version before use.

4.3 First Article Inspection

4.3.1 Examination. - Each searchlight shall be examined in accordance with Table I. One or more defects shall be cause for rejection.

TABLE I EXAMINATION

		REQUIREMENT PARAGRAPH
MAJOR		
101.	Absence of parts or components	3.5
102.	Materials or components not as specified	3.5
103.	Dimensions not as specified	3.4
MINOR		
201.	Identification markings not as specified	3.13
202.	Workmanship not as specified	3.18
203.	Treatment and painting not as specified	3.11, 3.12
204.	Weight not as specified	3.9
205.	Information plates not as specified	3.13

4.3.2 Tests. - Upon successful completion of the examination specified in 4.3.1 the first article model shall be subjected to the tests in Table II. Tests shall be conducted in the order listed. Failure of any test shall be cause for rejection.

TABLE II FIRST ARTICLE MODEL TEST SCHEDULE

TEST	TEST PARAGRAPH	REQUIREMENT PARAGRAPH
Electrical Characteristics	4.6.1	3.8
Performance	4.6.2	3.6
Mechanical Shock	4.6.3	3.7.3
Vibration	4.6.4	3.7.3
Low Temperature	4.6.5	3.7.1
Altitude	4.6.6	3.7.2
High Temperature	4.6.7	3.7.1
Humidity	4.6.8	3.7.1
Reliability	4.6.9	3.10

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:36Z
Check the source to verify that this is the current version before use.

4.4 Initial Production Inspection. - When specified (see 3.3) two initial production ignitors shall be selected at random by the Government from the first ten (10) ignitors being produced from production tooling, shall be examined as specified in Table I, and shall be tested as specified in Table II to determine conformance to the requirements of this specification. The inspection will be performed by the contractor under supervision of a representative of the contracting officer. Acceptance of the initial production ignitor shall not exclude the remaining ignitors from the quality conformance inspection and acceptance provisions specified in section 4.

4.4.1 Inspection failure. - Failure of an initial production ignitor to meet any requirement specified herein during and as a result of the examination and tests specified in 4.4 shall be cause for rejection of the initial production ignitor and shall be cause for refusal by the Government to continue acceptance of production ignitors until evidence has been provided by the supplier that corrective action has been taken to eliminate the deficiencies. Correction of such deficiencies shall be accomplished by the supplier at no cost to the Government on deficiencies found as a result of the initial production inspection will be considered prima facie evidence that all ignitors accepted prior to the completion of initial production inspection are similarly deficient unless evidence to the contrary is furnished by the supplier and such evidence is acceptable to the contracting officer.

4.5 Quality conformance inspection.

4.5.1 Examination. - Each ignitor shall be examined as specified in 4.3.1 Presence of one or more defects shall be cause for rejection.

4.5.2 Tests.

4.5.2.1 Group A. - Each ignitor shall be tested in accordance with Table III. Failure of any test shall be cause for rejection.

TABLE III GROUP "A" TEST SCHEDULE

TEST	TEST PARAGRAPH	REQUIREMENT PARAGRAPH
Performance	4.6.2.2	3.6

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:36Z
Check the source to verify that this is the current version before use.

4.5.2.2 Group B. - Group B tests shall be conducted on ignitors selected from units which have passed the examination and tests in 4.5.1 and 4.5.2. Sampling shall be in accordance with MIL-STD-105, AQL 2.5 percent defective, inspection level S-3. Tests shall be conducted in accordance with Table IV and may be performed in any sequence. Failure of any test shall be cause for rejection.

TABLE IV GROUP "B" TEST SCHEDULE

TEST	TEST PARAGRAPH	REQUIREMENT PARAGRAPH
Electrical Characteristics	4.6.1	3.8
Performance	4.6.2.1	3.6

4.5.2.3 Group C. - This inspection shall consist of the tests specified in Table V and shall be performed on sample units that have been subjected to and met Groups A and B inspection. Sample units shall be selected in accordance with 4.5.2.3.1.

4.5.2.3.1 Sampling for Inspection. - Two sample ignitors shall be selected at ramdom for all inspections in table V from each 100 ignitors produced or every sixty days, whichever occurs first. The first samples selected shall be at the start of the contract from the first quality conformance inspection production lot.

TABLE V GROUP "C" TEST SCHEDULE

TEST	TEST PARAGRAPH	REQUIREMENT PARAGRAPH
Shock	4.6.3	3.7.3
Vibration	4.6.4	3.7.3
Low Temperature	4.6.5	3.7.1
Humidity	4.6.8	3.7.1
Reliability	4.6.9	3.10

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:36Z
Check the source to verify that this is the current version before use.

4.5.2.3.2 Noncompliance. - The contractor shall immediately report in writing each group C failure occurrence, including details of the failure and characteristics affected. The contractor shall immediately investigate the cause of failure and further report the results of investigation and details of the proposed corrective action on (i) the process and materials, as applicable, and (ii) all units of product which were manufactured under the same conditions and which the Government considers subject to the same failure. Reports shall be forwarded to the responsible technical activity designated in the contract through the Quality Assurance Representative. After corrective action has been taken, additional sample units shall be subjected to group C inspection (all inspections, or the inspections which the sample failed, at the option of the Government) and groups A and B inspection may be reinstituted; however, final acceptance and shipment will be withheld until the group C reinspection results have shown that the corrective action was effective.

4.5.3 Reinspection of Conforming Group B and Group C Sample Units. - Unless otherwise specified, sample units which have been subjected to and passed both group B and group C inspection may be accepted on contract or order provided all damage is repaired and the sample units are resubjected to and pass Group A inspection.

4.6 Test Procedures. - Unless otherwise specified all tests shall be performed at plus 70 degrees F, plus or minus 5 degrees F, and all tests shall be conducted using a 20 KW xenon lamp conforming to MIL-L-55574 as the load or a load equivalent to the lamp in all electrical respects. Tests shall be conducted using an input voltage of 115 volts ac plus or minus 5 Volts ac at a frequency of 400 Hz plus or minus 25 Hz. All meters used during tests shall have been calibrated within 30 days prior to start of testing and thereafter as required but at intervals not to exceed 6 months. Tests shall be monitored by direct-reading laboratory type meters accurate within 1 percent and connected to indicate in the most accurate portion of their range. Voltage, current, and ambient temperatures during all testing shall be recorded using recording instruments accurate within 1.0 percent and with a damping factor not greater than 3 (as defined in MIL-M-10304).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:36Z
Check the source to verify that this is the current version before use.

4.6.1 Electrical Characteristics. - Connect the ignitor input to a source of 115 volts ac plus or minus 10 volts ac at a frequency of 400 Hz plus or minus 25 Hz and terminate the ignitor across a 20 KW xenon lamp. Energize the ignitor to ignite the lamp and monitor the ignition pulse. Terminate the ignitor across a load equivalent to the xenon lamp in accordance with 3.8.3 and again monitor the ignition pulse. With the ignitor terminated across the equivalent load, raise the load to 800 amperes for 30 seconds then gradually reduce it to 500 amperes over a 5 minute time span and maintain it at 500 amperes for 1 hour. Failure of the ignitor to perform as specified in 3.8 or failure to ignite the lamp shall constitute failure of this test.

4.6.2 Performance.

4.6.2.1 Performance with Lamp. - With the ignitor terminated across the lamp as in 4.6.1, ignite the lamp not less than 50 times within a 2 minute period. Failure of the ignitor to ignite the lamp within 2 seconds during any attempt shall constitute failure of this test.

4.6.2.2 Performance with equivalent load. - Connect the ignitor across an equivalent load in accordance with 4.6.1. Energize the ignitor not less than 50 times within 2 minutes and record the results of each attempt. Failure of the ignitor to simulate ignition of the lamp within 2 seconds during any attempt shall constitute failure of this test.

4.6.3 Mechanical shock. - Mount the ignition system on a rigid non-resonant fixture and fasten it to the fixture by the mounting points only. Subject the ignition system to 12 impact shocks. Six shocks shall be applied in a vertical plane at a force of 5 g with a duration of 12 milliseconds plus or minus 1 millisecond. After completion of the 12 shocks, test the ignition system in accordance with 4.6.2. Damage to the ignition system or failure of the performance test shall constitute failure of this test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:36Z
Check the source to verify that this is the current version before use.

4.6.4 Vibration. - Mount the ignition system on a vibration table. Every 30 minutes during vibration operate the ignition system, as specified in 4.6.2. During the test procedure, vibrate the ignition system in each of its three planes, at an amplitude of 0.03 inch plus or minus 10 percent and the frequency varying uniformly from 10 to 55 cps and return to 10 cps at a rate of 1 cps. Continue the vibration for not less than 90 minutes in each plane, and during this time note the frequency and magnitude of resonant points. Vibrate the ignition system for 15 minutes at each of the resonant frequencies noted. If no resonant frequencies are observed, vibrate the ignition system for 30 minutes at 55 cps and 0.06 inch total excursion. Any evidence of damage or failure of the system to operate shall constitute failure of this test.

4.6.5 Low Temperature. - The ignitor shall be subjected to the test specified as method 502.1 of MIL-STD-810. The operational test specified in 4.6.2 shall be performed at -65 degrees F. Any evidence of damage or failure to operate as specified shall constitute failure of this test.

4.6.6 Altitude. - The ignitor shall be subjected to the test specified as method 500.1 of MIL-STD-810 except the chamber pressure shall not exceed 40,000 feet altitude, and the operational test as specified in 4.6.2 shall be performed at 8,000 feet altitude. Any evidence of damage or failure to operate as specified shall constitute failure of this test.

4.6.7 High Temperature. - The ignitor shall be subjected to the test specified as method 501.1 of MIL-STD-810 except a temperature of 250 degrees F shall be maintained during storage exposure. The operational test specified in 4.6.2 shall be performed at 250 degrees F. Any evidence of damage or failure to operate as specified shall constitute failure of this test.

4.6.8 Humidity. - The ignitor shall be subjected to the test specified as method 507.1 of MIL-STD-810. Upon completion of the humidity cycling the test specified in 4.6.2 shall be performed. Any evidence of damage or failure to operate as specified shall constitute failure of this test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:36Z
Check the source to verify that this is the current version before use.

4.6.9 Reliability. - Connect the ignitor as specified in 4.6.2. Operate the ignition system for 5000 consecutive cycles of 1 minute each. Each cycle shall consist of 30 seconds on and 30 seconds off. Failure of the ignitor to operate as specified for the full 5000 cycles shall constitute failure of this test.

4.7 Inspection comparison. - The Government may select searchlights at any time during the contract production period and subject the searchlights to the examination specified in Table I and the tests specified in Table II. The inspection will be performed by the Government at a site selected by the Government. Searchlights shall be selected at random from those which have been accepted by the Government and will not include the previously inspected first article models.

4.7.1 Inspection failure. - Failure of any searchlight, when examined and tested as specified in 4.7 may be considered cause for refusal by the Government to continue acceptance of searchlights until objective evidence furnished by the supplier reveals that corrective action has been taken to eliminate the condition which caused the rejection.

4.8 Inspection of preparation for delivery.

4.8.1 Examination. - The packaging and packing shall be examined before the cover of the shipping container is attached, and the completed pack shall be examined after the cover is attached to assure compliance with the requirements of section 5 of this specification.

4.8.2 Examination before attachment of cover. - Prior to the attachment of the cover, each searchlight packed shall be examined for the defects shown in Table III. Presence of one or more defects shall be cause for rejection of the pack.

4.8.3 Examination after attachment of cover. - After attachment of the cover, samples selected in accordance with MIL-STD-105 shall be examined for the applicable defects listed in Table III. The unit or product shall be one completed pack ready for shipment. AQL shall be 2.5 percent defective.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:36Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Preservation, Packaging, Packing, and Marking. - Ignition systems shall be unit protected, packaged, packed and marked in accordance with MIL-E-17555, level A or C preservation and packaging as specified and level A. B. or C packing as specified (see 6.2).

6. NOTES

6.1 Intended Use. - The ignition system is intended for use in igniting a 20 KW, 45-volt DC, short-arc xenon lamp used in searchlight conforming to MIL-L-55574

6.2 Ordering Data. - Procurement documents should specify the following:

a. Title, number and date of this specification.

b. Time frame required for submission of first article model (see 3.2).

c. When initial production inspection is required.

d. Technical publications required (see 3.14).

e. Level of preservation and packaging and level of packing required (see 5.1).

6.3 Definitions.

6.3.1 Damage. - Damage is deformation, loosening, breakage, corrosion, or change of fit of any component or parts, or any condition resulting in noncompliance of any requirement in this purchase description.

6.3.2 Thermal Shock. - Thermal shock is the damaging physical force resulting from sudden changes of temperature.

6.3.3 "g" - "g" is the force which results from acceleration or deceleration of 32.17 feet per second per second.

CUSTODIAN:

ARMY - EL

USER ACTIVITIES:

ARMY - EL

PREPARING ACTIVITY:

ARMY - EL

Project 6230-A089

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:36Z
Check the source to verify that this is the current version before use.