INCH-POUND

MIL-P-70820 (AR)
28 February 1991

MILITARY SPECIFICATION

PRIMER, ELECTRIC, M128
METAL PARTS

This specification is approved for use within the U. S. Army Armament Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification contains requirements and provides quality assurance provisions for parts of Primer, Electric, M128.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards and handbooks. The following specifications, standards and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification for.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army ARDEC, ATTN: SMCAR-BAC-S, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1390

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-23T04:04Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-1169 - Packaging, Packing and Marking for Shipment of Inert Ammunition Components.

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from: Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings and publications. The following other Government documents, drawings and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS

ARMY

12910250 - Primer, Electric, M128.

(Copies of Government documents, drawings and publications required by the contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted shall be those listed in the issue of the DoDISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DoDISS are the issues of the documents cited in the solicitation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:04Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM-B 117	-	Salt Spray (Fog) Testing.
ASTM-B 602	-	Attribute Sampling of Electrodeposited Metallic Coatings and Related Finishes.
ASTM-B 633	-	Electrodeposited Coatings of Zinc on Iron and Steel.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187).

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Material. Materials shall be in accordance with applicable drawings and specifications.

3.2 Metal parts. Metal parts shall comply with all requirements specified on drawing 12910250 and in applicable specifications.

3.3 Hydrostatic test. The primer body tubing shall withstand the application of a minimum hydrostatic pressure without rupture or indication of flaws, as evidenced by leaks, and without permanent deformation beyond drawing requirements, when tested to a pressure of 10,800 psi. If the primer tubing procured for the bodies manufactured in accordance with this specification has been previously subjected to the hydrostatic test specified in this specification, a second hydrostatic test is not required.

3.4 Corrosion resistance. Coatings shall show neither corrosion products of zinc nor basis metal visible to the unaided eye at normal reading distance, when tested by exposure to salt spray in accordance with ASTM-B-633.

3.5 Workmanship. All parts shall be fabricated and finished in a thorough, workmanlike manner. They shall be free of burrs, chips, sharp edges, cracks, unblended radii, surface defects, dirt, grease, rust, corrosion products and other foreign matter. The cleaning method shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. All required markings shall be neat and sharply defined.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:04Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.2 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in this specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.3 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Inspection Method Reference" column in the tables starting with 4.6.3.1.

4.4 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.5).
b. Quality conformance inspection (see 4.6).

Source: https://assist.dla.mil -- Downloaded: 202610-23T04:04Z
Check the source to verify that this is the current version before use.

4.5 First article inspection.

4.5.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer. The first article sample shall consist of the following items in sample quantities as indicated:

Part Description	Drawings	Quantity
Head	9327339	25
Closing Plug	9327342	25
Retainer	8839509	25
Primer Body	12910251	25
Tip, Primer	12910249	25
Body Liner	12910248	25
Tip Liner	12910256	25

4.5.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.5.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 202610-23T04:04Z
Check the source to verify that this is the currentversion before use.

TABLE I - First article inspection.

CLASSIFICATION OF CHARACTERISTICS

MIL-P-70820 (AR)

PARAGRAPH	TITLE Metal Parts Components	SHEET 1 OF 1		DRAWING NUMBER See below NEXT HIGHER ASSEMBLY
CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Head (Dwg. 9327339) Examination for defects	25	3.2	4.6.3.1
	Closing plug (Dwg. 9327342) Examination for defects	25	3.2	4.6.3.2
	Retainer (Dwg. 8839509) Examination for defects	25	3.2	4.6.3.3
	Body (Dwg. 12910251) Examination for defects	25	3.2	4.6.3.4
	Tip (Dwg. 12910249) Examination for defects	25	3.2	4.6.3.5
	Body Liner (Dwg. 12910248) Examination for defects	25	3.1	4.6.3.6
	Tip Liner (Dwg. 12910256) Examination for defects	25	3.1	4.6.3.7

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:04Z
Check the source to verify that this is the current version before use.

4.6 Quality conformance inspection.

4.6.1 Lot formation. Lots shall comply with the lot formation provisions of MIL-A-48078.

4.6.2 Examination and tests.

4.6.2.1 Classification of characteristics. Quality conformance examinations and tests are specified in the following Classification of Characteristics paragraphs. The contractor's quality program or detailed inspection plan shall provide assurance of compliance of all characteristics with the applicable drawing and specification requirements utilizing as a minimum the conformance criteria specified herein. Unless otherwise specified herein, attributes sampling inspection shall be conducted in accordance with Table II below using Level I for major defects and Level II for minor defects. Samples shall be selected at random.

4.6.2.2 Alternative inspection provisions. Alternative inspection procedures, methods or equipment, such as statistical process control, tool control, other types of sampling procedures, etc., may be used by the contractor when they provide, as a minimum, the level of quality assurance required by the provisions specified herein. Prior to applying such alternative procedures, methods, or equipment, the contractor shall describe them in a written proposal submitted to the procuring contracting officer for evaluation and approval by the Government. (See 6.4.) When required, the contractor shall demonstrate that the effectiveness of the proposed alternative(s) is equal to or better than the specified quality assurance provisions herein. In cases of dispute as to whether the contractor's proposed alternative(s) provide equal assurance, the provisions of this specification shall apply. All approved alternative inspection provisions shall be specifically incorporated into the contractor's quality program or detailed inspection system, as applicable.

Source: https://assist.dla.mil -- Downloaded: 202610-23T04:04Z
Check the source to verify that this is the currentversion before use.

TABLE II. Sampling plan for quality conformance.
(Accept on zero defects)

Lot Size	Sample Size (Characteristic)	
	Major	Minor
2 to 8	*	*
9 to 150	32	13
151 to 500	32	30
501 to 1200	74	35
1201 to 3200	74	43
3201 to 10000	87	50
10001 to 35000	109	61

* 100% inspection
NOTE: If sample size equals or exceeds lot or batch size, do 100% inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-P-70820 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.6.3.1	Head, primer	1 OF 3	9327339
			NEXT HIGHER ASSEMBLY 9327345

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical				
1	Pitch diameter of large internal threads, max.	100%	3.2	Gage
2	Minor diameter of large internal threads, max.	100%	3.2	Gage
Major				
101	Pitch diameter of external threads, min.	Table II	3.2	Gage
102	Minor diameter of external threads, min.	Table II	3.2	Gage
103	True position of pitch diameter of large internal threads with pitch diameter of external threads	Table II	3.2	Gage
104	Pitch diameter of small internal threads, max.	Table II	3.2	Gage
105	Minor diameter of small internal threads, min.	Table II	3.2	Gage
106	True position of pitch diameter of small internal threads with diameter of large unthreaded cavity	Table II	3.2	Gage
107	Flange diameter	Table II	3.2	Gage
108	True position of flange diameter with pitch diameter of external threads	Table II	3.2	Gage
109	Flange thickness	Table II	3.2	Gage

NOTES:

AMSMC Form 1570b, 1 Jul 89

Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:04Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.6.3.1	Head, primer	2 OF 3	9327339
			NEXT HIGHER ASSEMBLY 9327345

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
110	Diameter of large unthreaded cavity	Table II	3.2	Gage
111	Diameter of small unthreaded cavity	Table II	3.2	Gage
112	True position of diameter of small unthreaded cavity with diameter of large unthreaded cavity	Table II	3.2	Gage
113	Protective coating missing or inadequate	Table II	3.2	Visual
114	Salt spray	4.6.4.2.1	3.5	4.7.2
Minor				
201	Pitch diameter of external threads, max.	Table II	3.2	Gage
202	Pitch diameter of large internal threads, min.	Table II	3.2	Gage
203	Pitch diameter of small internal threads, min.	Table II	3.2	Gage
204	Length, total	Table II	3.2	Gage
205	Length from flange to beginning of external threads	Table II	3.2	Gage
206	Length from flange to end of external threads	Table II	3.2	Gage
207	Depth of small unthreaded cavity	Table II	3.2	Gage
208	Diameter , forward end, of large threaded cavity	Table II	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:04Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.6.3.1	Head, primer	3 OF 3	9327339
			NEXT HIGHER ASSEMBLY 9327345

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
209	Outside diameter, forward	Table II	3.2	Gage
210	Depth of large threaded cavity	Table II	3.2	Gage
211	Minimum effective length of large internal thread	Table II	3.2	Gage
212	Depth from front face to rear of small threaded cavity	Table II	3.2	Gage
213	Countersink angle at the rear of small threaded cavity	Table II	3.2	Visual
214	Width of wrench slots (if applicable)	Table II	3.2	Gage
215	Depth of wrench slots (if applicable)	Table II	3.2	Gage
216	Distance between wrench slots (if applicable)	Table II	3.2	Gage
217	Depth of wrench holes (if applicable)	Table II	3.2	Gage
218	Diameter of wrench holes (if applicable)	Table II	3.2	Gage
219	Distance between wrench holes (if applicable)	Table II	3.2	Gage
220	Distance from center hole to wrench hole(s) (if applicable)	Table II	3.2	Gage
221	Chamfers missing or incorrect	Table II	3.2	Visual
222	Radii missing or incorrect	Table II	3.2	Visual
223	Surface finish incorrect	Table II	3.2	Visual
224	Workmanship	Table II	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.6.3.2	Plug, closing	1 OF 1	9327342
			NEXT HIGHER ASSEMBLY 9327346

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined.			
Major				
101	Pitch diameter, min.	Table II	3.2	Gage
102	Hole missing or obstructed	Table II	3.2	Gage
103	Major diameter, min.	Table II	3.2	Gage
104	Thread length of engagement	Table II	3.2	Gage
Minor				
201	Pitch diameter, max.	Table II	3.2	Gage
202	Diameter of hole, min.	Table II	3.2	Gage
203	Diameter of counterbore	Table II	3.2	Gage
204	Total length, max.	Table II	3.2	Gage
205	Length to shoulder, min.	Table II	3.2	Gage
206	Length of thread relief	Table II	3.2	Gage
207	Depth of slot	Table II	3.2	Gage
208	Width of slot	Table II	3.2	Gage
209	Workmanship	Table II	3.6	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.6.3.3	Retainer	1 OF 1	8839509
			NEXT HIGHER ASSEMBLY 9327346

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Pitch diameter, min.	Table II	3.2	Gage
102	Major diameter, min.	Table II	3.2	Gage
103	Diameter of hole, min.	Table II	3.2	Gage
Minor				
201	Thickness, min.	Table II	3.2	Gage
202	Slot missing	Table II	3.2	Visual
203	Surface finish improper	Table II	3.2	Visual
204	Pitch diameter, max.	Table II	3.2	Gage
205	Workmanship	Table II	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.6.3.4	Body	1 OF 2	12910251
			NEXT HIGHER ASSEMBLY 12910250

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical				
1	Hydrostatic test	100%	3.3	4.7.1
2	Crack or split (prior to plating)	100%	3.2	Gage
3	One or more flash holes missing	100%	3.2	Gage
Major				
101	Pitch diameter of external thread, min.	Table II	3.2	Gage
102	Major diameter of external thread, min.	Table II	3.2	Gage
103	Outside diameter	Table II	3.2	Gage
104	Wall thickness	Table II	3.2	Gage
105	Diameter of holes	Table II	3.2	Gage
106	Location of holes	Table II	3.2	Gage
107	Tip gage fails to pass through body	Table II	3.2	Gage
108	Salt spray	4.6.4.2.1	3.5	4.7.2
109	Pitch diameter of internal thread, max.	Table II	3.2	Gage
110	Minor diameter of internal thread, max.	Table II	3.2	Gage
111	Protective coating missing or inadequate	Table II	3.2	Visual
112	Flash hole variation, max. (a)	Table II	3.2	Gage

NOTES: (a) Two holes, minimum shall be checked in each row.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 2 OF 2	DRAWING NUMBER
4.6.3.4	Body		12910251
			NEXT HIGHER ASSEMBLY 12910250

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Minor				
201	Pitch diameter of external thread, max.	Table II	3.2	Gage
202	Length of internal thread	Table II	3.2	Gage
203	Total length	Table II	3.2	Gage
204	Pitch diameter of internal thread, max.	Table II	3.2	Gage
205	Minimum full external thread	Table II	3.2	Gage
206	Diameter of external thread pilot	Table II	3.2	Gage
207	Length of external thread pilot	Table II	3.2	Gage
208	True position of holes with outside diameter	Table II	3.2	Gage
209	True position of external thread with outside diameter	Table II	3.2	Gage
210	True position of internal thread with outside diameter	Table II	3.2	Gage
211	Surface finish	Table II	3.2	Gage
212	Workmanship	Table II	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.6.3.5	Tip	1 OF 1	12910249
			NEXT HIGHER ASSEMBLY 12910250

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical				
1	Flash holes missing	100%	3.2	Gage
Major				
101	Pitch diameter of thread, min.	Table II	3.2	Gage
102	Major diameter of thread, min.	Table II	3.2	Gage
Minor				
201	Pitch diameter of thread, max.	Table II	3.2	Gage
202	Thickness	Table II	3.2	Gage
203	Width of wrench slot	Table II	3.2	Gage
204	Depth of wrench slot	Table II	3.2	Gage
205	Chamfer(s) missing or inadequate	Table II	3.2	Visual
206	Surface finish	Table II	3.2	Visual
207	Workmanship	Table II	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:04Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.6.3.6	Body liner	1 OF 1	12910248
			NEXT HIGHER ASSEMBLY 12910250

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major	None defined			
Minor				
201	Length	Table II	3.1	Gage
202	Width	Table II	3.1	Gage
203	Thickness	Table II	3.1	Gage
204	Workmanship	Table II	3.6	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 . Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:04Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.6.3.7	Tip liner	1 OF 1	12910256
			NEXT HIGHER ASSEMBLY 12910250

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major	None defined			
Minor				
201	Diameter	Table II	3.1	Gage
202	Thickness	Table II	3.1	Gage
203	Workmanship	Table II	3.6	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:04Z
Check the source to verify that this is the current version before use.

4.6.4 Testing.

4.6.4.1 Hydrostatic test. This test shall be conducted 100 percent on body tubing either before or after cutting to length. Tubing that fails to comply with the requirements shall be removed from production.

4.6.4.2 Salt spray test.

4.6.4.2.1 Sampling. Random samples of the body and head shall be drawn for salt spray testing in accordance with the following table: (Ref. ASTM-B-602)

INSPECTION LOT SIZE	SAMPLE SIZE	ACCEPTANCE NO.	AQL %
2 - 25	2	0	2.5
26 - 1200	13	1	2.8
1201 - 35000	32	2	2.6
Over 35000	55	3	2.5

4.6.4.2.2 Acceptance criteria - individual sample. Coatings shall show neither Corrosion products of zinc nor basis metal corrosion products at the end of the test period. The appearance of corrosion products (except for white corrosion products at the edges of specimens) visible to the unaided eye at normal reading distance shall be cause for rejection of the sample. (REF. ASTM-B-633).

4.6.4.2.3 Acceptance criteria - entire lot. Rejection of any samples in excess of the acceptance number shall be cause for rejection of the lot.

4.7 Methods of inspection.

4.7.1 Hydrostatic test. Prior to machining, the primer body tubing shall be tested for not less than five seconds at the minimum hydrostatic pressure of 10,800 psi. Acceptable units shall be marked with an "H".

4.7.2 Salt spray. The body, head, tip, and body metal parts assembly, shall be tested in accordance with ASTM B-117, Salt Spray (Fog) Testing. The duration of the test shall be 96 hours.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:04Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging, packing and marking. The parts shall be packaged, packed and marked in accordance with MIL-STD-1169.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The M128 components in this specification are intended for use in the M128 Electric Primer.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number and date of the specification.

b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced. (See 2.1.)

6.3 Submission of inspection equipment designs for approval. See MIL-A-48078. Submit equipment designs as required to:

Commander
U.S. Army Armament Research, Development and Engineering Center
ATTN: AMSMC-QAT-I (D)
Picatinny Arsenal, NJ 07806-5000

This address will be specified on the Contract Data Requirements list in the contract.

6.4 Submission of firing records and ammunition data cards. In addition to the normal distribution of records, when the primer is procured by the Army Armament, Munitions and Chemical Command, one copy of all firing records and ammunition data cards shall be forwarded to:

Commander
U.S. Army Armament Research, Development and Engineering Center
ATTN: AMSMC-QAT-A (D)/SMCAR-CCH-P
Picatinny Arsenal, NJ 07806-5000

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:04Z
Check the source to verify that this is the current version before use.

6.5 Submission of alternative inspection provisions. Proposed alternative inspection provisions should be submitted by the contractor to the Procuring Contracting Officer for evaluation and approval by the technical activity responsible for preparation of this specification.

6.6 Subject term (key word) listing.

Ammunition
Tank
Cannon
Cartridge
Projectile
Primer

Custodian:
Army - AR

Preparing activity:
Army - AR

(Project 1390-A679)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:04Z
Check the source to verify that this is the current version before use.